

```

import numpy as np
import pandas as pd

# Load the pre_process_datasample.csv
df = pd.read_csv("pre_process_datasample.csv")
print("Original Dataset:")
print(df)

# Check dataset info
print("\nDataset Info:")
df.info()

# Get mode of Country column
print("\nMode of Country column:")
print(df.Country.mode())
print(df.Country.mode()[0])
print(type(df.Country.mode()))

# Fill missing values
df.Country.fillna(df.Country.mode()[0], inplace=True)
df.Age.fillna(df.Age.median(), inplace=True)
df.Salary.fillna(round(df.Salary.mean()), inplace=True)

print("\nAfter filling missing values:")
print(df)

# Create dummy variables for categorical data
print("\nDummy variables for Country:")
print(pd.get_dummies(df.Country))

# Create updated dataset with dummy variables
updated_dataset = pd.concat([pd.get_dummies(df.Country), df.iloc[:,
[1,2,3]]], axis=1)
print("\nUpdated dataset with dummy variables:")
print(updated_dataset)

# Check info again
print("\nFinal dataset info:")
df.info()

# Convert Purchased to numerical values
updated_dataset.Purchased.replace(['No', 'Yes'], [0, 1], inplace=True)
print("\nFinal updated dataset with numerical Purchased:")
print(updated_dataset)

```

Original Dataset:

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No

3	Spain	38.0	61000.0	No
4	Germany	40.0	NaN	Yes
5	France	35.0	58000.0	Yes
6	Spain	NaN	52000.0	No
7	France	48.0	79000.0	Yes
8	Germany	50.0	83000.0	No
9	France	37.0	67000.0	Yes

Dataset Info:

```
<class 'pandas.core.frame.DataFrame'>
```

RangeIndex: 10 entries, 0 to 9

Data columns (total 4 columns):

#	Column	Non-Null Count	Dtype
0	Country	10 non-null	object
1	Age	9 non-null	float64
2	Salary	9 non-null	float64
3	Purchased	10 non-null	object

dtypes: float64(2), object(2)

memory usage: 452.0+ bytes

Mode of Country column:

0 France

Name: Country, dtype: object

France

```
<class 'pandas.core.series.Series'>
```

After filling missing values:

	Country	Age	Salary	Purchased
0	France	44.0	72000.0	No
1	Spain	27.0	48000.0	Yes
2	Germany	30.0	54000.0	No
3	Spain	38.0	61000.0	No
4	Germany	40.0	63778.0	Yes
5	France	35.0	58000.0	Yes
6	Spain	38.0	52000.0	No
7	France	48.0	79000.0	Yes
8	Germany	50.0	83000.0	No
9	France	37.0	67000.0	Yes

Dummy variables for Country:

	France	Germany	Spain
0	True	False	False
1	False	False	True
2	False	True	False
3	False	False	True
4	False	True	False
5	True	False	False
6	False	False	True
7	True	False	False

8	False	True	False
9	True	False	False

Updated dataset with dummy variables:

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	No
1	False	False	True	27.0	48000.0	Yes
2	False	True	False	30.0	54000.0	No
3	False	False	True	38.0	61000.0	No
4	False	True	False	40.0	63778.0	Yes
5	True	False	False	35.0	58000.0	Yes
6	False	False	True	38.0	52000.0	No
7	True	False	False	48.0	79000.0	Yes
8	False	True	False	50.0	83000.0	No
9	True	False	False	37.0	67000.0	Yes

Final dataset info:

```
<class 'pandas.core.frame.DataFrame'>
```

RangeIndex: 10 entries, 0 to 9

Data columns (total 4 columns):

#	Column	Non-Null Count	Dtype
---	-----	-----	-----
0	Country	10 non-null	object
1	Age	10 non-null	float64
2	Salary	10 non-null	float64
3	Purchased	10 non-null	object

dtypes: float64(2), object(2)

memory usage: 452.0+ bytes

Final updated dataset with numerical Purchased:

	France	Germany	Spain	Age	Salary	Purchased
0	True	False	False	44.0	72000.0	0
1	False	False	True	27.0	48000.0	1
2	False	True	False	30.0	54000.0	0
3	False	False	True	38.0	61000.0	0
4	False	True	False	40.0	63778.0	1
5	True	False	False	35.0	58000.0	1
6	False	False	True	38.0	52000.0	0
7	True	False	False	48.0	79000.0	1
8	False	True	False	50.0	83000.0	0
9	True	False	False	37.0	67000.0	1

/tmp/ipykernel_20938/2843840289.py:20: FutureWarning: A value is trying to be set on a copy of a DataFrame or Series through chained assignment using an inplace method.

The behavior will change in pandas 3.0. This inplace method will never work because the intermediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try

using 'df.method({col: value}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation inplace on the original object.

```
df.Country.fillna(df.Country.mode()[0], inplace=True)
```

/tmp/ipykernel_20938/2843840289.py:21: FutureWarning: A value is trying to be set on a copy of a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the intermediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: value}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation inplace on the original object.

```
df.Age.fillna(df.Age.median(), inplace=True)
```

/tmp/ipykernel_20938/2843840289.py:22: FutureWarning: A value is trying to be set on a copy of a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the intermediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: value}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation inplace on the original object.

```
df.Salary.fillna(round(df.Salary.mean()), inplace=True)
```

/tmp/ipykernel_20938/2843840289.py:41: FutureWarning: A value is trying to be set on a copy of a DataFrame or Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never work because the intermediate object on which we are setting values always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try using 'df.method({col: value}, inplace=True)' or df[col] = df[col].method(value) instead, to perform the operation inplace on the original object.

```
updated_dataset.Purchased.replace(['No', 'Yes'], [0, 1],  
inplace=True)
```

/tmp/ipykernel_20938/2843840289.py:41: FutureWarning: Downcasting

behavior in `replace` is deprecated and will be removed in a future version. To retain the old behavior, explicitly call `result.infer_objects(copy=False)`. To opt-in to the future behavior, set `pd.set_option('future.no_silent_downcasting', True)`

```
updated_dataset.Purchased.replace(['No', 'Yes'], [0, 1],  
inplace=True)
```