

Exception Handling

Programming Foundation

Presented by
Nikhil Nair

Website
www.guvi.com

Objectives

- What you will learn today
 - Purpose of exceptions in programming
 - Checked vs Unchecked exceptions
 - Handling exceptions in Java
 - Custom Exceptions
- How this builds on previous lectures
 - Any methods or static methods may throw exceptions
 - Exceptions can be produced when performing arithmetic operations, user input is invalid, etc

common goal






Exceptions

Why exceptions exist


- Inputs, computations, or environment can fail at runtime
- Exceptions provide one structured path for handling failures
- Centralized handling keeps normal logic readable and testable
- Magic return values hide bugs and confuse control flow

When plans hit a bump, choose the next best step




Exception as a concept

- An exception is an object describing a specific problem
- Stack unwinding pops frames until a matching handler appears
- A handler is a catch block that decides action
- Errors mark serious conditions usually outside application control



Checked versus unchecked

- Checked exceptions require handling or declaration at compile time
- Unchecked exceptions occur without compiler enforcement and caller obligations
- Use checked when callers can realistically recover from failure
- Use unchecked for programmer mistakes and invalid API usage



When to use exceptions

- Use exceptions for rare, disruptive events beyond normal expectations
 - Examples: database down, corrupted input, invariant breach, configuration missing
- Prefer return-based validation for expected mistakes and routine branches
 - Examples: empty field, optional filter, retry prompt, missing optional data
- Throw when method contract fails after reasonable local recovery attempts
- Avoid exceptions for loop exits, boolean checks, predictable branches

```
public static boolean validAge(int age) { return age >= 0; }  
public static void requireNonNegative(int n) {  
    if (n < 0) throw new IllegalArgumentException("negative not allowed");  
}
```

Activity: classify failures

- Classify each scenario as checked or unchecked with a reason checked or unchecked with justification
- `Integer.parseInt("abc")`
 - unchecked
- `a[10]` when size three
 - unchecked
- `new FileInputStream("missing-file.txt")`
 - checked
- Exceptions that must be declared in the method signature
 - checked
- `obj.toString()` on null
 - unchecked

try and catch anatomy

- A try block encloses code that might throw an exception
- A catch block names the exception type and a variable
- Order multiple catches from specific types to broader base classes
- Continue after catch or finally, unless rethrow or fatal error

```
try {  
    int x = Integer.parseInt(s);  
    System.out.println(x);  
} catch (NumberFormatException e) {  
    System.out.println("invalid number: " + e.getMessage());  
}
```

Ordering and specificity

- Catch specific exception types before their broader superclasses
- Place broad catch blocks last to avoid unreachable handlers
- Handle distinct failure cases separately to keep recovery actions clear
- Avoid swallowing exceptions by logging context and rethrowing when needed

```
try { Integer.parseInt(s); }
catch (Exception e) { System.out.println("broad"); }
catch (NumberFormatException e) { System.out.println("specific"); } // unreachable
```

Finally semantics

- A finally block runs after matching catch or normal exit
- Finally executes even with thrown exceptions or early returns
- Use finally for essential cleanup like closing scanners (when reading files) or resources (closing a database connection)
- Avoid changing return values or throwing new exceptions from finally

```
static int f() {  
    try { return 1; }  
    finally { System.out.println("cleanup"); }  
}
```

Multi-catch and rethrow

- Multi-catch handles several exception types with identical recovery code
- Use it when messages and actions are truly the same
- Rethrow when this method cannot decide safe recovery behavior
- Prefer translating to domain exceptions for clearer contracts and callers

```
try { Integer.parseInt(s.trim()); }  
catch (NumberFormatException | NullPointerException e) {  
    throw new IllegalArgumentException("invalid number input", e);  
}
```

Handler side effects

- Choose handler action: recover now, translate, or rethrow
- Log only context needed to reproduce and debug failures
- Avoid empty catches that swallow errors and hide bugs
- Prefer specific messages and actions per distinct failure type

```
try { readConfig(); }
catch (IOException e) {
  System.err.println("config issue: " + e.getMessage());
  throw new IllegalStateException("required config missing", e);
}
```

Activity: try-catch-finally order

- Predict execution order across try, catch, finally, return
- Focus on first matching catch and guaranteed finally run

```
static int g(String s) {  
    try {  
        System.out.println("try");  
        Integer.parseInt(s);  
        return 10;  
    } catch (NumberFormatException e) {  
        System.out.println("catch");  
        return 20;  
    } finally {  
        System.out.println("finally");  
    }  
}  
// call: g("abc");
```

Activity: try-catch-finally order

```
static int h() {  
    try {  
        System.out.println("try");  
        return 1;  
    } finally {  
        System.out.println("finally");  
    }  
}  
// call: h();
```

```
static void k() {  
    try {  
        System.out.println("try");  
        throw new RuntimeException("x");  
    } catch (RuntimeException e) {  
        System.out.println("catch");  
        throw e;  
    } finally {  
        System.out.println("finally");  
    }  
}  
// call: k();
```

throw keyword purpose

- Use throw to signal a detected problem immediately
- Create specific exceptions with messages explaining context clearly
- Throw nearest to detection after minimal local checks
- Document thrown types so callers know their obligations

```
if (age < 0) {  
    throw new IllegalArgumentException("age must be nonnegative");  
}
```


throws and contracts

- throws declares checked exceptions a method may pass to callers
- Callers must handle those exceptions or declare them again
- Do not list unchecked exceptions in a throws clause
- Declare only types the caller truly needs to know

```
public static void enrollStudent(String s) throws Exception {
    int age = Integer.parseInt(s);    // unchecked if bad
    requireValidAge(age);             // checked, must handle or declare
}

public static void requireValidAge(int age) throws Exception {
    if (age < 0) throw new Exception("age cannot be negative");
}
```

Propagation and translation decisions

- Propagate in the middle layers; handle at boundaries; throw at source
- Translate = wrap low-level exception into clearer one, keep original cause
- Do not translate when caller needs the original exception type
- Preserve stack trace by rethrowing or passing the cause to the new exception

```

void runGate(String input) {
    try {
        int fare = parseFare(input);    // may translate (bad input)
        computeFare(fare);              // may propagate (checked failure)
        System.out.println("entry allowed");
    } catch (IllegalArgumentException e) { // translated unchecked
        System.out.println("invalid input: " + e.getMessage());
    } catch (Exception e) {             // propagated checked
        System.out.println("system error: " + e.getMessage());
    }
}

int parseFare(String s) {
    try { return Integer.parseInt(s.trim()); }
    catch (NumberFormatException e) {
        throw new IllegalArgumentException("fare must be a whole number", e); // translate
    }
}

void computeFare(int fare) throws Exception { // propagate
    if (fare <= 0) throw new Exception("fare rule misconfigured");
}
  
```

Activity: propagate or translate

- A) Input text is "29x" at gate keypad during entry. Assume input must be a number.
 - Translate to `IllegalArgumentException` with message "fare must be a whole number"
- B) Card balance is lower than fare when tapping gate.
 - Propagate `InsufficientBalanceException` to boundary for user-facing message
- C) Application startup fails to load required rules for fare from config.
 - Handle here by failing fast with clear error and halt startup

Custom exception roles

- Name domain rules with clear, specific custom exception types
- Separate detection sites from handling sites using those types
- Prefer one type per rule family, not per message variant
- Write actionable messages including failed value and expected constraint

```
public void debit(int bal, int amt) throws InsufficientBalanceException {
    if (amt > bal) throw new InsufficientBalanceException("amount " + amt + " exceeds " + bal);
}
```

Naming and hierarchy

- Choose checked when callers can reasonably recover in context
- Extend Exception for checked, RuntimeException for unchecked
- Use informative names like InsufficientBalance or InvalidPin
- Provide constructors for message and cause preservation

```
public class InsufficientBalanceException extends Exception {
    InsufficientBalanceException(String msg) { super(msg); }
    InsufficientBalanceException(String msg, Throwable cause) { super(msg, cause); }
}

public class InvalidPinException extends RuntimeException {
    InvalidPinException(String msg) { super(msg); }
}
```

Activity: design two exceptions

- Define two domain exceptions with name, type, and usage site
- Pick checked or unchecked based on caller recovery ability
- Write one actionable message with failed value or constraint
- A) Wallet debit fails when amount exceeds available balance.
 - `InsufficientBalanceException`; checked; thrown in debit step; message “amount 750 exceeds balance 500”
- B) PIN input contains letters instead of digits.
 - `InvalidPinException`; unchecked; thrown at PIN parse; message “PIN must be four digits 0-9”

Wrap up and next steps

- Recognize when to use, catch, throw, and declare exceptions
- Apply ordering, finally, and multi catch with clear intent
- Decide propagate versus translate based on caller responsibilities
- Design lean custom types with names, hierarchy, and messages



That's for today!
Any questions?