

HTML answer key

Alternative solutions are acceptable when they preserve valid HTML structure and satisfy the stated requirements.

Section A: Document structure and content hierarchy

Exercise 1: Complete the HTML document

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">

  <meta
    name="viewport"
    content="width=device-width, initial-scale=1.0"
  >

  <title>Community reading room</title>
</head>
<body>
  <h1>Community reading room</h1>

  <p>
    The reading room is open from
    9 AM to 6 PM.
  </p>
</body>
</html>
```

The `<head>` contains document information used by the browser. The heading and paragraph belong in `<body>` because they are visible page content.

Exercise 2: Separate document information from visible content

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">

  <meta
    name="viewport"
```

```

    content="width=device-width, initial-scale=1.0"
  >

  <title>Weekend learning centre</title>
</head>
<body>
  <h1>Weekend learning centre</h1>

  <p>
    Workshops begin at 10 AM.
  </p>
</body>
</html>

```

Answers:

1. The character encoding, viewport information, and browser-tab title belong in `<head>`.
2. The visible heading and paragraph belong in `<body>`.
3. `<head>` stores information about the document. A visible page header is created inside `<body>`, usually with a `<header>` element.

Exercise 3: Repair the nesting

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">

  <title>Workshop information</title>
</head>
<body>
  <main>
    <h1>Frontend workshop</h1>

    <p>
      Learn the foundations of web development.
    </p>

    <section>
      <h2>Topics</h2>

      <ul>
        <li>HTML</li>
        <li>CSS</li>
        <li>JavaScript</li>
      </ul>
    </section>
  </main>

```

```
</body>
</html>
```

The heading is not placed inside the paragraph. Each list item is closed, and the section is closed before the surrounding `<main>` element.

Exercise 4: Create a meaningful heading structure

```
<h1>Frontend foundations</h1>

<section>
  <h2>Course overview</h2>

  <p>
    This course introduces the main technologies
    used to build web pages.
  </p>
</section>

<section>
  <h2>Weekly schedule</h2>

  <article>
    <h3>Saturday session</h3>

    <p>
      Learn HTML structure and common elements.
    </p>
  </article>

  <article>
    <h3>Sunday session</h3>

    <p>
      Practise CSS styling and responsive design.
    </p>
  </article>
</section>
```

The heading levels describe the content hierarchy:

- `<h1>` is the page title.
- `<h2>` identifies the main page sections.
- `<h3>` identifies topics inside the schedule section.

Section B: Text, grouping, links, images, lists, and media

Exercise 5: Choose between `div` and `span`

```
<div>
  <p>
    Frontend development combines
    <span>HTML</span>,
    <span>CSS</span>,
    and
    <span>JavaScript</span>.
  </p>

  <p>
    Course status:
    <span>Enrolment open</span>
  </p>
</div>
```

Answers:

1. The `<div>` groups several complete elements into one larger block.
2. Each `<span>` marks a small part of text inside a paragraph without creating a new section.

Exercise 6: Complete a link and image

```
<a href="https://developer.mozilla.org/">
  Read the HTML documentation
</a>


```

Answers:

1. Without `href`, the `<a>` element has no navigation destination and does not behave as a normal link.
2. When the image path is incorrect, the image fails to load. The browser may display a broken-image indicator and the alternative text.
3. Alternative text should communicate the useful information or purpose of the image.

Exercise 7: Choose the correct type of list

Workshop topics

```
<h2>Workshop topics</h2>

<ul>
  <li>HTML structure</li>
  <li>CSS styling</li>
  <li>JavaScript basics</li>
</ul>
```

Registration steps

```
<h2>Registration steps</h2>

<ol>
  <li>Choose a workshop</li>
  <li>Complete the registration form</li>
  <li>Check the confirmation message</li>
</ol>
```

The topics use an unordered list because their sequence is not important.

The registration steps use an ordered list because the learner should complete them in the stated order.

Exercise 8: Add audio and video

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">

  <meta
    name="viewport"
    content="width=device-width, initial-scale=1.0"
  >

  <title>Workshop media</title>
</head>
<body>
  <h1>Workshop media</h1>

  <section>
    <h2>Audio introduction</h2>
```

```

<audio controls>
  <source
    src="./media/workshop-introduction.mp3"
    type="audio/mpeg"
  >

  Your browser does not support
  the audio element.
</audio>
</section>

<section>
  <h2>Video preview</h2>

  <video controls>
    <source
      src="./media/workshop-preview.mp4"
      type="video/mp4"
    >

    Your browser does not support
    the video element.
  </video>
</section>
</body>
</html>

```

The `controls` attribute displays the browser's playback controls.

The `<source>` element provides the file path and media type. The fallback text is available when the browser cannot use the media element.

Section C: Semantic HTML

Exercise 9: Replace generic containers where the role is clear

```

<body>
  <header>
    <h1>Community courses</h1>

    <p>
      Short courses for local learners.
    </p>
  </header>

  <nav>
    <a href="#courses">Courses</a>
    <a href="#contact">Contact</a>
  </nav>

```

```

<main>
  <section id="courses">
    <h2>Weekend courses</h2>

    <p>
      Choose from three beginner sessions.
    </p>
  </section>
</main>

<footer id="contact">
  <p>
    Contact the course team.
  </p>
</footer>
</body>

```

The semantic elements describe the role of each major area:

- `<header>` introduces the page.
- `<nav>` contains navigation links.
- `<main>` contains the primary content.
- `<section>` groups the weekend course content.
- `<footer>` contains the page's closing contact information.

Exercise 10: Use `section` and `article` for different roles

```

<section>
  <h2>Upcoming workshops</h2>

  <article>
    <h3>HTML foundations</h3>

    <p>Saturday, 10 AM</p>

    <p>
      Learn how to structure a web page.
    </p>
  </article>

  <article>
    <h3>Responsive CSS</h3>

    <p>Sunday, 10 AM</p>

    <p>
      Adapt layouts to different screen sizes.
    </p>
  </article>

```

```

    </p>
</article>

<article>
  <h3>JavaScript basics</h3>

  <p>Sunday, 2 PM</p>

  <p>
    Add behaviour to a web page.
  </p>
</article>
</section>

```

Answers:

1. The `<section>` groups several related workshop announcements under one heading.
2. Each `<article>` represents an independent workshop announcement that could be read or reused on its own.

Exercise 11: Improve a page that already renders

```

<body>
  <header>
    <h1>Learning centre</h1>
  </header>

  <nav>
    <a href="#about">About</a>
    <a href="#courses">Courses</a>
  </nav>

  <main>
    <section id="about">
      <h2>About the centre</h2>

      <p>
        The centre offers weekend classes.
      </p>
    </section>

    <section id="courses">
      <h2>Available courses</h2>

      <p>
        HTML, CSS, and JavaScript courses
        are available.
      </p>
    </section>
  </main>
</body>

```

```
    </section>
</main>

<footer>
  <p>Copyright 2026</p>
</footer>
</body>
```

The original page could display, but the revised structure identifies the page header, navigation, main content, sections, and footer.

Section D: Forms

Exercise 12: Connect a label to an input

```
<label for="email">
  Email address
</label>

<input
  id="email"
  name="email"
  type="email"
>

<label for="full-name">
  Full name
</label>

<input
  id="full-name"
  name="fullName"
  type="text"
>
```

The label's `for` value matches the input's `id`.

Clicking the label focuses the corresponding control.

The `name` identifies the field when form values are submitted.

Exercise 13: Choose the correct form control

Suitable choices:

Requirement	Control
Enter a full name on one line	Text
Enter an email address	Email
Write a longer question	
Choose one visible session	Radio buttons
Choose several topics	Checkboxes
Choose one city from a longer list	

Requirement 3: Longer question

```

<label for="question">
  Your question
</label>

<textarea
  id="question"
  name="question"
  rows="5"
></textarea>

```

Requirement 4: Choose one session

```

<fieldset>
  <legend>Preferred session</legend>

  <input
    id="session-morning"
    name="preferredSession"
    type="radio"
    value="morning"
  >

  <label for="session-morning">
    Morning
  </label>

  <input
    id="session-afternoon"
    name="preferredSession"
    type="radio"
    value="afternoon"
  >

  <label for="session-afternoon">
    Afternoon

```

```
</label>
</fieldset>
```

Requirement 6: Choose one city

```
<label for="city">
  City
</label>

<select
  id="city"
  name="city"
>
  <option value="">
    Choose a city
  </option>

  <option value="mysuru">
    Mysuru
  </option>

  <option value="bengaluru">
    Bengaluru
  </option>

  <option value="mangaluru">
    Mangaluru
  </option>
</select>
```

Exercise 14: Create one radio-button group

```
<fieldset>
  <legend>Preferred session</legend>

  <div>
    <input
      id="saturday-morning"
      name="preferredSession"
      type="radio"
      value="saturday-morning"
    >

    <label for="saturday-morning">
      Saturday morning
    </label>
  </div>
```

```

<div>
  <input
    id="saturday-afternoon"
    name="preferredSession"
    type="radio"
    value="saturday-afternoon"
  >

  <label for="saturday-afternoon">
    Saturday afternoon
  </label>
</div>

<div>
  <input
    id="sunday-morning"
    name="preferredSession"
    type="radio"
    value="sunday-morning"
  >

  <label for="sunday-morning">
    Sunday morning
  </label>
</div>
</fieldset>

```

All three radio buttons share the name `preferredSession`. The browser therefore treats them as one group and permits only one selected value at a time.

Exercise 15: Create independent checkboxes and a select menu

```

<section>
  <h2>Workshop preferences</h2>

  <fieldset>
    <legend>Topics of interest</legend>

    <div>
      <input
        id="topic-html"
        name="topics"
        type="checkbox"
        value="html"
      >

      <label for="topic-html">

```

```

        HTML
    </label>
</div>

<div>
    <input
        id="topic-css"
        name="topics"
        type="checkbox"
        value="css"
    >

    <label for="topic-css">
        CSS
    </label>
</div>

<div>
    <input
        id="topic-javascript"
        name="topics"
        type="checkbox"
        value="javascript"
    >

    <label for="topic-javascript">
        JavaScript
    </label>
</div>
</fieldset>

<label for="experience-level">
    Experience level
</label>

<select
    id="experience-level"
    name="experienceLevel"
>
    <option
        value=""
        selected
        disabled
    >
        Choose a level
    </option>

    <option value="beginner">
        Beginner
    </option>

```

```
<option value="intermediate">
  Intermediate
</option>
</select>
</section>
```

Checkboxes are suitable because participants may select more than one topic.

The select menu is suitable because the participant chooses one value from a longer or compact list.

Exercise 16: Repair a registration form

```
<form>
  <label for="participant-name">
    Full name
  </label>

  <input
    id="participant-name"
    name="fullName"
    type="text"
  >

  <label for="email">
    Email address
  </label>

  <input
    id="email"
    name="email"
    type="email"
  >

  <fieldset>
    <legend>Preferred session</legend>

    <input
      id="morning"
      name="preferredSession"
      type="radio"
      value="morning"
    >

    <label for="morning">
      Morning
    </label>

    <input
```

```

        id="afternoon"
        name="preferredSession"
        type="radio"
        value="afternoon"
    >

    <label for="afternoon">
        Afternoon
    </label>
</fieldset>

<label for="question">
    Your question
</label>

<textarea
    id="question"
    name="question"
    rows="5"
></textarea>

<button type="submit">
    Register
</button>
</form>

```

Corrections:

- The full-name label now matches the input ID.
- Every form control has a meaningful `name`.
- Both radio inputs share `name="preferredSession"`.
- The longer response uses a `<textarea>`.
- The submit button is inside the form.
- Every ID is unique.

Final exercise: Build a community workshop page

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">

    <meta
        name="viewport"
        content="width=device-width, initial-scale=1.0"
    >

```

```

    <title>Community web workshop</title>
</head>
<body>
    <header>
        <h1>Community web workshop</h1>

        <p>
            A beginner workshop covering the
            foundations of web development.
        </p>
    </header>

    <nav>
        <a href="#overview">
            Workshop overview
        </a>

        <a href="#sessions">
            Session schedule
        </a>

        <a href="#registration">
            Register
        </a>
    </nav>

    <main>
        <section id="overview">
            <h2>Workshop overview</h2>

            <p>
                The workshop introduces HTML, CSS,
                and JavaScript.
            </p>

            

            <h3>Topics covered</h3>

            <ul>
                <li>HTML</li>
                <li>CSS</li>
                <li>JavaScript</li>
            </ul>
        </section>

        <section id="sessions">
            <h2>Workshop sessions</h2>

```

```

<article>
  <h3>Morning session</h3>

  <p>Saturday, 10 AM</p>

  <p>
    HTML structure and semantic elements
  </p>
</article>

<article>
  <h3>Afternoon session</h3>

  <p>Saturday, 2 PM</p>

  <p>
    Forms, links, images, and media
  </p>
</article>
</section>

<section>
  <h2>Media preview</h2>

  <video controls>
    <source
      src="./media/workshop-preview.mp4"
      type="video/mp4"
    >

    Your browser does not support
    the video element.
  </video>
</section>

<section id="registration">
  <h2>Workshop registration</h2>

  <form>
    <div>
      <label for="full-name">
        Full name
      </label>

      <input
        id="full-name"
        name="fullName"
        type="text"
      >
    </div>
  </form>

```

```
<div>
  <label for="email">
    Email address
  </label>

  <input
    id="email"
    name="email"
    type="email"
  >
</div>

<fieldset>
  <legend>Preferred session</legend>

  <div>
    <input
      id="session-morning"
      name="preferredSession"
      type="radio"
      value="morning"
    >

    <label for="session-morning">
      Morning
    </label>
  </div>

  <div>
    <input
      id="session-afternoon"
      name="preferredSession"
      type="radio"
      value="afternoon"
    >

    <label for="session-afternoon">
      Afternoon
    </label>
  </div>
</fieldset>

<fieldset>
  <legend>Topics of interest</legend>

  <div>
    <input
      id="interest-html"
      name="topics"
      type="checkbox">
```

```

        value="html"
    >

    <label for="interest-html">
        HTML
    </label>
</div>

<div>
    <input
        id="interest-css"
        name="topics"
        type="checkbox"
        value="css"
    >

    <label for="interest-css">
        CSS
    </label>
</div>

<div>
    <input
        id="interest-javascript"
        name="topics"
        type="checkbox"
        value="javascript"
    >

    <label for="interest-javascript">
        JavaScript
    </label>
</div>
</fieldset>

<div>
    <label for="experience-level">
        Experience level
    </label>

    <select
        id="experience-level"
        name="experienceLevel"
    >
        <option
            value=""
            selected
            disabled
        >
            Choose a level
        </option>
    </select>
</div>

```

```

        <option value="beginner">
            Beginner
        </option>

        <option value="intermediate">
            Intermediate
        </option>
    </select>
</div>

<div>
    <label for="question">
        Optional question
    </label>

    <textarea
        id="question"
        name="question"
        rows="5"
    ></textarea>
</div>

<button type="submit">
    Register for the workshop
</button>
</form>
</section>
</main>

<footer>
    <p>
        Contact the community learning team
        for support.
    </p>
</footer>
</body>
</html>

```

Completion review

- The document contains one `<h1>`.
- All visible content is inside `<body>`.
- Every navigation destination matches an existing ID.
- Heading levels follow the page hierarchy.
- The image includes useful alternative text.
- The topics use an unordered list.
- Each session is an independent article.
- The video includes controls, a source type, and fallback text.
- Every form label matches a control ID.

- Radio buttons share one group name.
- Checkboxes allow multiple selections.
- The experience level uses a select menu.
- The longer question uses a textarea.
- The submit button is inside the form.
- All IDs are unique.