

HOW TO RUN

Start the server in order to run your application .

Create a data base in the phpMyAdmin with the following tables

about

`id` int(10) NOT NULL

`title` varchar(100) NOT NULL

`content` longtext NOT NULL

`image` varchar(300) NOT NULL

Insert the values in it.

admin

`aid` int(10) NOT NULL,

`auser` varchar(50) NOT NULL,

`aemail` varchar(50) NOT NULL,

`apass` varchar(50) NOT NULL,

`adob` date NOT NULL,

`aphone` varchar(15) NOT NULL

Insert the values into it.

city

cid int(50) NOT NULL,

`cname` varchar(100) NOT NULL,

`sid` int(50) NOT NULL

contact

```
`cid` int(50) NOT NULL,  
`name` varchar(100) NOT NULL,  
`email` varchar(100) NOT NULL,  
`phone` varchar(20) NOT NULL,  
`subject` varchar(100) NOT NULL,  
`message` varchar(250) NOT NULL
```

Feedback

```
`fid` int(50) NOT NULL,  
`uid` int(50) NOT NULL,  
`fdescription` varchar(300) NOT NULL,  
`status` int(1) NOT NULL,  
`date` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP
```

Insert values

property

```
`pid` int(50) NOT NULL,  
`title` varchar(200) NOT NULL,  
`pcontent` longtext NOT NULL,  
`type` varchar(100) NOT NULL,  
`bhk` varchar(50) NOT NULL,  
`stype` varchar(100) NOT NULL,  
`bedroom` int(50) NOT NULL,  
`bathroom` int(50) NOT NULL,
```

`balcony` int(50) NOT NULL,
`kitchen` int(50) NOT NULL,
`hall` int(50) NOT NULL,
`floor` varchar(50) NOT NULL,
`size` int(50) NOT NULL,
`price` int(50) NOT NULL,
`location` varchar(200) NOT NULL,
`city` varchar(100) NOT NULL,
`state` varchar(100) NOT NULL,
`pimage` varchar(300) NOT NULL,
`pimage1` varchar(300) NOT NULL,
`pimage2` varchar(300) NOT NULL,
`pimage3` varchar(300) NOT NULL,
`pimage4` varchar(300) NOT NULL,
`uid` int(50) NOT NULL,
`status` varchar(50) NOT NULL,
`mapimage` varchar(300) NOT NULL,
`topmapimage` varchar(300) NOT NULL,
`groundmapimage` varchar(300) NOT NULL,
`totalfloor` varchar(50) NOT NULL,
`date` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
`isFeatured` int(11) DEFAULT NULL

state

`sid` int(50) NOT NULL,

`sname` varchar(100) NOT NULL

user

`uid` int(50) NOT NULL,

`uname` varchar(100) NOT NULL,

`uemail` varchar(100) NOT NULL,

`uphone` varchar(20) NOT NULL,

`upass` varchar(50) NOT NULL,

`utype` varchar(50) NOT NULL,

`uimage` varchar(300) NOT NULL

Insert the values

Use [localhost/application_name](#) to run the application

Or

Use 127.0.0.1 to run your application.