Evidence of Performance

Airborne sound insulation of building components

Test Report No. 14-000251-PR01 (PB Z06-H01-04-en-01)



Basis

EN ISO 10140-1: 2010 +A1:2012 EN ISO 10140-2: 2010

EN ISO 717-1: 2013

Client **PRESS GLASS SA Nowa Wies**

Kopalniana 9 42-262 Poczesna Poland

Insulating glass unit

Type 33.1 TH1,1 Phon kl.1(B)1+12+FL 6+12+TH1,1 4 Ar

External Dimen-1,230 mm × 1,480 mm sions (W x H)

6LSG / 12 / 6 / 12 / 4 Construction

Argon Gas filling

40.0 kg/m² Area related mass

Special features

Weighted sound reduction index R_w Spectrum adaptation terms C and C_{tr}




 $R_w(C; C_{tr}) = 37 (-2; -6) \text{ dB}$

ift Rosenheim 23.05.2014

Dr. Joachim Hessinger, Dipl.-Phys. Head of Testing Department **Building Physics**

J. Keninger

Andreas Preuss, Dipl.-Ing. (FH) Head of Laboratory **Building Acoustics**



Instructions for use

This test report serves to demonstrate the airborne sound insulation of a building compo-

Applicable for Germany.

 R_w corresponds to $R_{w,P}$ for DIN 4109, Annex 1, Table 40

Validity

The data and results given relate solely to the tested and described specimen.

Testing the sound insulation does not allow any statement to be made on further characteristics of the present construction regarding performance and quality.

Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies. The cover sheet can be used as abstract.

Contents

The test report contains a total of 7 pages:

- 1 Object
- 2 Procedure
- 3 Detailed results
- 4 Instructions for use

Data sheet (1 page)



