Evidence of Performance

Airborne sound insulation of building elements

Test report 163 36489/Z1e

This is a translation of the test report 163 36489/Z1 of 22nd August 2008.



Client

Press Glas S.A. Nowa Wies Kopalniana 9

42-262 Poczesna Poland

Product	single pane glass
Designation	Float 12 mm
Size (w × h)	1230 mm × 1480 mm
Construction	12 mm Float
Area related weight	30 kg/m²
Special items	-/-
Opecial items	1

Basis

EN ISO 140-1:1997+A1:2004 EN 20140-3 :1995+A1:2004 EN ISO 717-1 : 1996+A1:2006

Representation



Informations for use

This test report may be used to validate the sound reduction of a building element.

Validity for germany:

 $R_{\mbox{\tiny W}}$ corresponds to $R_{\mbox{\tiny W,P}}$ for DIN 4109 Annex 1 table 40 a

Validity

The data and results given relate solely to the described, tested object.

Testing the acoustic properties does not allow any statement to be made on further characteristics of the present structure which could define performance and quality.

Notes on publication

The **ift** Guidance Sheet "Conditions and Guidance for the use of **ift** Test Documents" applies.

The cover sheet can be used as a summary.

Contents

This test report includes 6 pages

- 1 Test specimen
- 2 Test procedure
- 3 Test results
- 4 Instructions for use Data sheet (1 page)

Weighted sound reduction index R_{w} Spectrum adaptation terms C and C_{tr}



 $R_w (C; C_{tr}) = 35 (-1;-3) dB$

ift Rosenheim01. September 2008

Dr. Joachim Hessinger, Opl.-Phys. Head of test laboratory ift centre for acoustic

Bernd Saß, Dipl.-Ing. (FH) vice head of test laboratory ift centre for acoustic