

Лабораторная работа №6

СТУДЕНТ: САХНО

ГРУППА: НФИБД-02-23

Цель

Приобрести практические навыки по установке и конфигурированию системы управления базами данных на примере программного обеспечения MariaDB.

Задания

Установить необходимые для работы MariaDB пакеты (см. раздел 6.4.1).

Настроить в качестве кодировки символов по умолчанию utf8 в базах данных.

В базе данных MariaDB создать тестовую базу addressbook, содержащую таблицу city с полями name и city, т.е., например, для некоторого сотрудника указан город, в котором он работает.

Создать резервную копию базы данных addressbook и восстановите из неё данные.

Написать скрипт для Vagrant, фиксирующий действия по установке и настройке базы данных MariaDB во внутреннем окружении виртуальной машины server. Соответствующим образом внести изменения в Vagrantfile.

```
Rocky Linux 9 - BaseOS
Rocky Linux 9 - AppStream
Rocky Linux 9 - Extras
Dependencies resolved.
```

```
=====
Package                                         Architecture
=====
```

```
Installing:
```

```
 mariadb                                         x86_64
```

```
 mariadb-server                                x86_64
```

```
Installing dependencies:
```

```
 mariadb-common                                x86_64
```

```
 mariadb-connector-c                           x86_64
```

```
 mariadb-connector-c-config                    noarch
```

```
 mariadb-connector-c-devel                     x86_64
```

Задание №1

Computer	etc	my.cnf.d		Q			x
nt	Name		Size	Modified			
ed	auth_gssapi.cnf		42 bytes	12 Oct			
e	client.cnf		295 bytes	27 May 2022			
ments	enable_encryption.preset		763 bytes	10 Aug			
loads	mariadb-server.cnf		1.5 kB	12 Oct			
c	mysql-clients.cnf		232 bytes	10 Aug			
res	spider.cnf		120 bytes	10 Aug			
ns							
1							

Задание №1

```
NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MariaDB  
SERVERS IN PRODUCTION USE! PLEASE READ EACH STEP CAREFULLY!
```

```
In order to log into MariaDB to secure it, we'll need the current  
password for the root user. If you've just installed MariaDB, and  
haven't set the root password yet, you should just press enter here.
```

```
Enter current password for root (enter for none):  
OK, successfully used password, moving on...
```

```
Setting the root password or using the unix_socket ensures that nobody  
can log into the MariaDB root user without the proper authorisation.
```

```
You already have your root account protected, so you can safely answer 'n'.
```

```
Switch to unix_socket authentication [Y/n] n  
... skipping.
```

```
You already have your root account protected, so you can safely answer 'n'.
```

```
Change the root password? [Y/n] n  
... skipping.
```

```
By default, a MariaDB installation has an anonymous user, allowing anyone  
to log into MariaDB without having to have a user account created for
```

Задание №1

```
All done! If you've completed all of the above steps, your MariaDB
installation should now be secure.

Thanks for using MariaDB!
[root@vbox ~]# mysql -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 6
Server version: 10.5.29-MariaDB MariaDB Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> \h

General information about MariaDB can be found at
http://mariadb.org

List of all client commands:
Note that all text commands must be first on line and end with ';'
?      (\?) Synonym for 'help'.

```

Задание №2

```
MariaDB [(none)]> SHOW DATABASES;
```

```
+-----+  
| Database          |  
+-----+  
| information_schema |  
| mysql             |  
| performance_schema |  
+-----+
```

```
3 rows in set (0.001 sec)
```

```
MariaDB [(none)]> exit;
```

```
Bye
```

Задание №1


```
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 10
Server version: 10.5.22-MariaDB MariaDB Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.


Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> status
-----
mysql Ver 15.1 Distrib 10.5.22-MariaDB, for Linux (x86_64) using EditLine wrapper

Connection id:          10
Current database:
Current user:           root@localhost
SSL:                    Not in use
Current pager:          stdout
Using outfile:          ''
Using delimiter:        ;
Server:                 MariaDB
Server version:         10.5.22-MariaDB MariaDB Server
Protocol version:       10
Connection:             Localhost via UNIX socket
Server characterset:    latin1
Db characterset:        latin1
Client characterset:    utf8
Conn. characterset:     utf8
UNIX socket:            /var/lib/mysql/mysql.sock
Uptime:                 20 min 17 sec

Threads: 1  Questions: 19  Slow queries: 0  Opens: 20  Open tables: 13  Queries per second avg: 0.015
-----
```

Задание №2



A terminal window with a dark background. The top bar shows a file icon on the left and the text 'root@server:/etc/my.cnf.d' on the right. Below the bar, the text 'GNU nano 5.6.1' is on the left and 'utf8.cnf' is on the right. The main area contains the following text:

```
[client]
default-character-set = utf8
[mysqld]
character-set-server = utf8
```

Задание №2

```
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 3
Server version: 10.5.22-MariaDB MariaDB Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> status
-----
mysql  Ver 15.1 Distrib 10.5.22-MariaDB, for Linux (x86_64) using  EditLine wrapper

Connection id:          3
Current database:
Current user:           root@localhost
SSL:                    Not in use
Current pager:          stdout
Using outfile:          ''
Using delimiter:        ;
Server:                 MariaDB
Server version:         10.5.22-MariaDB MariaDB Server
Protocol version:       10
Connection:             Localhost via UNIX socket
Server characterset:    utf8
Db      characterset:    utf8
Client characterset:    utf8
Conn.  characterset:    utf8
UNIX socket:            /var/lib/mysql/mysql.sock
Uptime:                 27 sec

Threads: 1  Questions: 4  Slow queries: 0  Opens: 17  Open tables: 10  Queries per second avg: 0.148
-----
```

Задание №2

```
MariaDB [(none)]> CREATE DATABASE addressbook CHARACTER SET utf8 COLLATE utf8_general_ci;  
Query OK, 1 row affected (0.000 sec)  
  
MariaDB [(none)]> USE addressbook;  
Database changed  
MariaDB [addressbook]> SHOW TABLES;  
Empty set (0.000 sec)  
  
MariaDB [addressbook]> CREATE TABLE city(name VARCHAR(40), city VARCHAR(40));  
Query OK, 0 rows affected (0.066 sec)  
  
MariaDB [addressbook]> SHOW TABLES;  
+-----+  
| Tables_in_addressbook |  
+-----+  
| city                   |  
+-----+  
1 row in set (0.000 sec)
```

Задание №2

```
MariaDB [addressbook]> INSERT INTO city(name,city) VALUES ('Иванов','Москва');
Query OK, 1 row affected (0.016 sec)

MariaDB [addressbook]> INSERT INTO city(name,city) VALUES ('Петров','Сочи');
Query OK, 1 row affected (0.003 sec)

MariaDB [addressbook]> INSERT INTO city(name,city) VALUES ('Сидоров','Дубна');
Query OK, 1 row affected (0.010 sec)

MariaDB [addressbook]> SELECT * FROM city;
+-----+-----+
| name      | city    |
+-----+-----+
| Иванов     | Москва  |
| Петров     | Сочи    |
| Сидоров    | Дубна   |
+-----+-----+
3 rows in set (0.001 sec)

MariaDB [addressbook]> CREATE USER dmbelicheva@'%' IDENTIFIED BY '123456';
Query OK, 0 rows affected (0.027 sec)

MariaDB [addressbook]> GRANT SELECT,INSERT,UPDATE,DELETE ON addressbook.* TO dmbelicheva@'%';
Query OK, 0 rows affected (0.011 sec)
```

Задание №2

```
MariaDB [addressbook1]> CREATE USER nvsakhno@'%' IDENTIFIED BY 'qweRY1234!';  
Query OK, 0 rows affected (0,007 sec)
```

```
MariaDB [addressbook1]> GRANT SELECT,INSERT,UPDATE,DELETE ON addressbook.* TO nv  
sakhno@'%';  
Query OK, 0 rows affected (0,004 sec)
```

```
MariaDB [addressbook1]> FLUSH PRIVILEGES;  
Query OK, 0 rows affected (0,002 sec)
```

```
MariaDB [addressbook1]> 
```

Задание №2

```
root@vbox:~  
[root@vbox ~]# mkdir -p /var/backup  
[root@vbox ~]# mysqldump -u root -p addressbook1 > /var/backup/addressbook1.sql  
Enter password:  
[root@vbox ~]# mysqldump -u root -p addressbook1 | gzip > /var/backup/addressbook1.sql.gz  
Enter password:  
[root@vbox ~]# mysqldump -u root -p addressbook | gzip > $(date  
> +/var/backup/addressbook.%Y%m%d.%H%M%S.sql.gz)  
Enter password: -bash: +/var/backup/addressbook.%Y%m%d.%H%M%S.sql.gz: Нет такого  
файла или каталога  
-bash: $(date  
+/var/backup/addressbook.%Y%m%d.%H%M%S.sql.gz): неоднозначное перенаправление  
  
mysqldump: Got errno 32 on write  
[root@vbox ~]# mysqldump -u root -p addressbook | gzip > $(date  
+/var/backup/addressbook.%2025%02%11.%23%19%55.sql.gz)  
-bash: +/var/backup/addressbook.%2025%02%11.%23%19%55.sql.gz: Нет такого файла и  
ли каталога  
-bash: $(date  
+/var/backup/addressbook.%2025%02%11.%23%19%55.sql.gz): неоднозначное перенаправ  
ление  
Enter password:  
mysqldump: Got errno 32 on write  
[root@vbox ~]#
```

Задание №2

Вывод:

В процессе выполнения данной лабораторной работы я приобрел практические навыки по установке и конфигурированию системы управления базами данных на примере программного обеспечения MariaDB.