


Introduction to Machine Learning

Tuning: In a Nutshell





Learning goals

- Understand the main idea behind tuning,
- the untouched-test set principle,
- nested resampling,
- and pipelines





WHAT IS TUNING?

- Tuning is the process of selecting the best hyperparameters, denoted as λ , for a machine learning model
- Hyperparameters are the parameters of the learner (versus model parameters θ)
- Consider a guitar analogy: Hyperparameters are akin to the tuning pegs. Learning the best parameters $\hat{\theta}$ - playing the guitar - is a separate process that depends on tuning!



WHY TUNING MATTERS

- Just like a guitar won't perform well when out-of-tune, properly tuning a learner can drastically improve the resulting model performance
- Tuning helps find a balance between underfitting and overfitting





comparing AUCs of different values for hyperparameters *maxdepth*, *k*, *gamma*

HOW HARD COULD IT BE?

- Very difficult: There are lots of different configurations to choose from, known as the hyperparameter space, denoted by Λ (analogous to Θ)
- Black box: If one opts for a configuration $\lambda \in \Lambda$, how can its performance be measured (and compared)?

⇒ Well-thought-out **Black-Box Optimization Techniques** are needed!





exponential growth of Λ : for two discrete hyperparameters with each 10 possible values,
 $10 * 10 = 100$ configurations can be evaluated

UNTOUCHED-TEST-SET PRINCIPLE

We've found a $\lambda^* \in \tilde{\Lambda}$. How well does it perform?



- **Careful!** We cannot use the same data for both tuning and performance estimation, as this would lead to (optimistically) biased performance estimates!
- To obtain an unbiased \widehat{GE} , we need an **untouched** test set:



NESTED RESAMPLING

To decrease variance of the \widehat{GE} , **Nested Resampling** is used:

- Just like we can generalize holdout splitting to resampling, we can generalize the three-way split to nested resampling
- The key idea is to repeatedly perform a three-way split with an additional layer (as we first have to find a λ^*):



PIPELINES IN MACHINE LEARNING

Pipelines are like the assembly lines in machine learning. They automate the sequence of data processing and model building tasks.

Why Pipelines Matter:

- **Streamlined Workflow:** Automates the flow from data preprocessing to model training
- **Reproducibility:** Ensures that results can be reproduced consistently
- **Error Reduction:** Minimizes the chance of human errors in the model building process

