

MH4311 Cryptography

Lecture 12

Message Authentication Code

Wu Hongjun

Lecture Outline

- Classical ciphers
- Symmetric key encryption
- Hash function and Message Authentication Code
 - Birthday attack
 - Hash function
 - Message Authentication Code
 - CBC-MAC, CMAC
 - HMAC
- Public key encryption
- Digital signature
- Key establishment and management
- Introduction to other cryptographic topics

Recommended Reading

- CTP Section 4.4
- HAC Section 9.5
- NIST documents
 - CMAC: http://csrc.nist.gov/publications/nistpubs/800-38B/SP_800-38B.pdf
 - HMAC: <http://csrc.nist.gov/publications/fips/fips198/fips-198a.pdf>
- Wikipedia
 - Message Authentication Code
http://en.wikipedia.org/wiki/Message_authentication_code
 - CBC-MAC
<http://en.wikipedia.org/wiki/CBC-MAC>
 - CMAC
<http://en.wikipedia.org/wiki/CMAC>
 - HMAC
<http://en.wikipedia.org/wiki/HMAC>

Message Authentication

- Message Authentication: **check whether the received message was sent from the sender**
 - Message authentication implies data integrity
 - Data integrity: **whether there is unauthorized modification to the message**

Message Authentication

- Two approaches to authenticate message
 - Symmetric key approach:

Message Authentication Code

- Compress a message together with a secret key
 - The person who knows the secret key can verify the authenticity of the message
- Public key approach: **digital signature**

Message Authentication Code

- Message Authentication Code (MAC)
 - MAC is an algorithm that compresses a **secret key** and a message with arbitrary length into a fixed length output (we call this output as authentication tag)
 - Verification: After receiving a message together with the authentication tag, generate a new authentication tag from the message, and compare it with the tag being received

Note: Another frequently used MAC refers to Media Access Control address (MAC address). For example, each network card in a computer has a 48-bit unique identifier (MAC address).

Message Authentication Code

- Two security parameters
 - The size of secret key
 - Should be large enough to resist brute force attack
 - The size of authentication tag
 - For a strong MAC with n -bit authentication tag, the probability of modifying (or forging) a message without being detected is 2^{-n} .
 - The size of authentication tag should not be too small
 - Typical authentication tag sizes: 64 bits, 128 bits, 160 bits

Message Authentication Code

- Repeated trials
 - For a strong MAC with n -bit authentication tag, the probability of modifying (or forging) a message without being detected is 2^{-n} .
 - However, if there is no mechanism that stops repeated trials, the chance to forge a message successfully can become higher.
 - Example: with 1024 trials, the probability that one of the forged messages & their tags can pass the verification with probability about 2^{-n+10}

Message Authentication Code

- Security requirements on MAC algorithm

Requirement 1: The key should remain secret even if it has been used to generate many authentication tags

- Large key size to resist brute force attack
- MAC algorithm should resist other key recovery attacks

Requirement 2: Without knowing the secret key, any forged or modified message can pass verification with negligible probability


- An attacker may obtain the authentication tags of many messages, then try to forge some message (generate the authentication tag for a forged message without knowing the secret key)

MAC Constructions

- MAC algorithm based on block cipher
 - CBC-MAC
 - CMAC (NIST recommendation)
 -
- MAC algorithm based on hash function
 - HMAC (NIST standard)
- Dedicated MAC algorithm

CBC-MAC

- Construct MAC algorithm from block cipher in CBC mode



- Differences between CBC-MAC and CBC encryption
 - CBC-MAC
 - Authentication, fixed public IV (0), output is the authentication tag
 - CBC encryption:
 - Encryption, random public IV, output is the ciphertext

CBC-MAC



- CBC-MAC is insecure
 - Attack 1. Use the authentication tags of two messages. The authentication tag of a new message can be forged without knowing the secret key
 - Example: (diagram in the next slide)

$$\begin{array}{ll} M = m_0 \parallel m_1 & \text{CBC-MAC}(M) = t \\ M' = m'_0 \parallel m'_1 \parallel m'_2 & \text{CBC-MAC}(M') = t' \end{array}$$

The new message: $m_0 \parallel m_1 \parallel (m'_0 \oplus t) \parallel m'_1 \parallel m'_2$

The forged tag: t'

(diagram in next page)



CBC-MAC

- CBC-MAC is insecure
 - Attack 2. With message length being appended to message, message can still be forged
 - Example (diagram in the next page):

Let M'_1 represents M_1 with length padding




M'_2 represents M_2 with length padding (the length of M_1 is the same as that of M_2)

Let M'_3 represents M_3 with length padding,

$M'_3 = M'_1 // a_0 // a_1$, where each a_i represents one message block.

Suppose now an attacker knows that the authentication tags of M_1, M_2, M_3 are t_1, t_2, t_3 , then an attacker can generate the authentication tag of the following message without knowing the secret key :

$M'_4 = M'_2 // (a_0 \oplus t_1 \oplus t_2) // a_1$, and the authentication tag is t_3




CMAC (Cipher-based Message Authentication Code)


- CMAC is a NIST recommendation
- CMAC strengthens CBC-MAC
 - Use **an additional key (K_1 or K_2) for the last message block** to thwart the attacks on CBC-MAC
 - The last message block (to eliminate the ambiguity in the last block: full or partial, and how “partial”)
 - **K_1 is used if it is a full block**
 - **K_2 is used if it is partial block**
 - **Pad the partial block by bit ‘1’ followed by some zero bits**
 - Derive K_1 and K_2 from the secret key K
 - If the MAC size is less than the block size of block cipher, truncate some less significant bits

CMAC

- CMAC without considering truncation



No partial message block



with partial message block

CMAC

- Derive K_1 and K_2 from K
 - Let $W = E_K(0)$
 - Represent W as polynomial over GF(2)
 - If the block size of block cipher is 128 bits:
 - $K_1 = W \cdot x \mod (x^{128} + x^7 + x^2 + x + 1)$
 - $K_2 = K_1 \cdot x \mod (x^{128} + x^7 + x^2 + x + 1)$
 - If the block size of block cipher is 64 bits:
 - $K_1 = W \cdot x \mod (x^{64} + x^4 + x^3 + x + 1)$
 - $K_2 = K_1 \cdot x \mod (x^{64} + x^4 + x^3 + x + 1)$

CMAC

- *Security of CMAC
 - With $2^{n/2}$ authentication tags being generated from the same key, an attacker may generate the tag of a new message without knowing the secret key

- Example:

Find two messages $M = m_0 \parallel m_1 \parallel m_2 \parallel m_3 \parallel m_4$

$$M' = m'_0 \parallel m'_1 \parallel m_2 \parallel m_3 \parallel m_4$$

with the same tag t (birthday attack). Then

$$E_K(m_0) \oplus m_1 = E_K(m'_0) \oplus m'_1$$

Now an attacker requests for the MAC of

$$M'' = m_0 \parallel (m_1 \oplus x) \parallel y \quad (\text{for any } x \text{ and } y)$$

the attacker can forge the new message

$$M''' = m'_0 \parallel (m'_1 \oplus x) \parallel y$$

(the tag of M''' is the same as that of M'')

HMAC

- The Keyed-Hash Message Authentication Code (HMAC)
 - NIST standard (2002)
 - Construct a secure MAC from a strong hash function

HMAC

- How to construct a MAC algorithm from a strong hash function?
 - Method 1: key-prefix (**insecure**)
 - The key is prepended to the message, then hash
$$\text{MAC}_K(M) = \text{Hash}(K \parallel M)$$
(‘ \parallel ’ indicates concatenation)
 - Insecure
 - An attacker can extend the message and generate new tag of an extended message (such as MD5, SHA-1, SHA-256).
 - Details: Suppose that $(K \parallel M)$ after padding becomes $(K \parallel M \parallel p)$, and the attacker knows the tag value $\text{Hash}(K \parallel M \parallel p)$. Then an attacker can compute $\text{Hash}(K \parallel M \parallel p \parallel x)$ for an x due to the iterated nature of has function

HMAC

- How to construct a MAC algorithm from a strong hash function?
 - Method 2: Key-suffix (**insecure**)
 - A secret key is appended to the end of message, then hash
$$\text{MAC}_K(M) = \text{Hash}(M \parallel K)$$
 - Not strong
 - A MAC can be forged with $2^{n/2}$ hash function computations
 - Details:
 - » An attacker can apply birthday attack to find two messages M and M' (with the same length) satisfying $\text{Hash}(M) = \text{Hash}(M')$
 - » Then the attacker requests for the tag of M
 - » The attacker immediately knows the tag of M'
(The forgery is successful, since the people who know the secret key K has never generated the tag of M')

HMAC

- How to construct a MAC algorithm from a strong hash function?
 - Method 3: Key-prefix + key-suffix (envelope)
(not strong)
 - A secret key is used as both prefix and suffix, then hash
$$\text{MAC}_K(M) = \text{Hash}(K \parallel M \parallel K)$$
 - *Not strong (suppose n -bit key, and hash function with n -bit message digest)
 - The attacker requests the authentication tags of more than $2^{n/2}$ messages, then recovers the n -bit secret key
 - » Reason: depending on the message length, a secret key may be separated into two parts, and those two parts appear in two compression functions

HMAC

- How to construct a secure MAC algorithm from a strong hash function?
 - Method 3: key-prefix + key-suffix (envelope)
 - *Example: recovering 32 key bits
 - Suppose that the messages lengths are chosen so that after padding, the last block contains only $n-32$ key bits, i.e., the previous block contains the first 32 bits of the key
 - An attacker requests for the tags of about $2^{n/2+0.5}$ messages, with difference in the last message block (but the last padded block is the same).
 - » The attacker obtains two collisions $\text{MAC}(x) = \text{MAC}(x')$:
 - one collision happens before compressing the last padded block

i.e., $\text{hash}(K \parallel x \parallel K_{32}) = \text{hash}(K \parallel x' \parallel K_{32})$

HMAC

- How to construct a secure MAC algorithm from a strong hash function?
 - Method 3: key-prefix + key-suffix (envelope)
 - Example: recovering 32 key bits (cont.)
 - Then an attacker requests for tags of $\text{MAC}(x \parallel r \parallel y)$ and $\text{MAC}(x' \parallel r \parallel y)$, where r is a 32-bit number, and y is a fixed arbitrary message.
 - » For all the 2^{32} values of r , if any particular r satisfies that $\text{MAC}_k(x \parallel r \parallel y) = \text{MAC}_k(x' \parallel r \parallel y)$, then we know that this r is equal to the first 32 bits of the key with high chance.
 - Reason: if $\text{hash}(K \parallel x \parallel K_{32}) = \text{hash}(K \parallel x' \parallel K_{32})$, and if some $r = K_{32}$, then $\text{hash}(K \parallel x \parallel r) = \text{hash}(K \parallel x' \parallel r)$
 $\Rightarrow \text{hash}(K \parallel x \parallel r \parallel y \parallel K) = \text{hash}(K \parallel x' \parallel r \parallel y \parallel K)$,
i.e., $\text{MAC}_k(x \parallel r \parallel y) = \text{MAC}_k(x' \parallel r \parallel y)$

HMAC

- How to construct a MAC algorithm from a strong hash function?
 - Method 4: **HMAC** (NIST standard, FIPS 198a)
 - Suppose: key size is less than or equal to message block size
 - Append '0's to the end of key K so that the resulting K' is with one message block length
 - Example: 128-bit key, and 512-bit message block size, then 384 '0' bits are appended to the key
 - Let opad and ipad be two constants with one block size
 - opad = 0x5c5c5c5c5c5c5c
– ipad = 0x36363636363636
 - Compute the MAC as
$$\text{MAC}_K(M) = \text{Hash}((K' \oplus \text{opad}) \parallel \text{Hash}((K' \oplus \text{ipad}) \parallel M))$$

HMAC

More specifically, HMAC is computed by applying the hash function twice:

$$\text{temp} = \text{Hash}((K' \oplus \text{ipad}) \parallel M);$$
$$\text{MAC}_K(M) = \text{Hash}((K' \oplus \text{opad}) \parallel \text{temp});$$

Authentication and Encryption

Authentication and Encryption

- For secure communication,
 - Authentication is always necessary
 - Encryption may be optional
 - Depending on the sensitivity of the content
- In general, both authentication and encryption are needed for secure communication.

Authentication and Encryption

- If both symmetric key encryption and authentication are required
 - It is recommended to encrypt the message first, then authenticate the ciphertext (encrypt-then-authenticate)
 - If we compute the authentication tag from the plaintext, then encrypt the plaintext (authenticate-then-encrypt), the padding information in some cipher modes are not protected by authentication, then the encryption may become insecure. (For example, POODLE attack against the CBC encryption in TLS/SSL. In TLS/SSL, strong HMAC and strong AES-CBC are used, but the early versions are insecure.)

Authentication and Encryption

- In recent years, there is demand to combine authentication and encryption into a single algorithm for better security and efficiency
 - The combined algorithm is called authenticated-encryption algorithm
 - In the coming TLS 1.3, it is required that authenticated-encryption algorithms must be used
 - Currently, there is only one NIST recommendation on authenticated-encryption algorithm: AES-GCM (NIST SP 800-38D)
 - Research are needed on authentication-encryption algorithm

Authentication and Encryption

- Current research on authenticated-encryption algorithm
 - CAESAR competition (2014 to 2018)
(Competition on Authenticated Encryption: Security, Applicability, and Robustness)
 - 56 submissions received in March 2014
 - 7 finalists (selected in March 2018)
 - Winner(s) will be announced in 2018

Authentication and Encryption

- Coming research on authenticated-encryption algorithm
 - NIST lightweight crypto competition (2019 -- ?)
 - To design authenticated-encryption algorithms for resource constrained applications (low cost, low power, low energy, ...)

Summary

- Message Authentication Code
 - Compresses a secret key and a message into an authentication tag with fixed length
 - MAC based on block cipher
 - CBC-MAC
 - CMAC (NIST recommendation)
 - MAC based on hash function
 - HMAC (NIST standard)
- Authentication and encryption
 - Use encryption-then-authentication approach
 - Use the authenticated-encryption algorithms