

# Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

## Showing results for footer.jsx

### Checker Input

Show  source  outline  image report

Check by   Aucun fichier choisi

Uploaded files with .xhtml or .xht extensions are parsed using the XML parser.

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

### Message Filtering

1. **Warning** Consider adding a `lang` attribute to the `html` start tag to declare the language of this document.

From line 1, column 1; to line 1, column 26

```
import React from "react";
```

For further guidance, consult [Declaring the overall language of a page](#) and [Choosing language tags](#).

If the HTML checker has misidentified the language of this document, please [file an issue report](#) or [send e-mail to report the problem](#).

2. **Error** The character encoding was not declared. Proceeding using `windows-1252`.

3. **Error** Non-space characters found without seeing a doctype first. Expected

```
<!DOCTYPE html>.
```

From line 1, column 1; to line 1, column 26

```
import React from "react";
```

4. **Error** Element `head` is missing a required instance of child element `title`.

From line 1, column 1; to line 1, column 26

```
import React from "react";
```

Content model for element `head`:

If the document is [an iframe srcdoc document](#) or if title information is available from a higher-level protocol: Zero or more elements of [metadata content](#), of which no more than one is a [title](#)

element and no more than one is a [base](#) element.

Otherwise: One or more elements of [metadata content](#), of which exactly one is a [title](#) element and no more than one is a [base](#) element.

5. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 8, column 9; to line 8, column 35

```
<div className="container">
```

Attributes for element [div](#):

[Global attributes](#)

6. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 9, column 11; to line 9, column 42

```
<div className="row box-footer">
```

Attributes for element [div](#):

[Global attributes](#)

7. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 10, column 13; to line 10, column 60

```
<div className="col-12 col-md-6 col-lg-3 block">
```

Attributes for element [div](#):

[Global attributes](#)

8. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 17, column 15; to line 17, column 43

```
<div className="social-icon">
```

Attributes for element [div](#):

[Global attributes](#)

9. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 18, column 27

```
<Link to={"https://github
```

10. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 18, column 62

```
github-john-doe"}>
```

11. **Error** Attribute `to` not allowed on element `link` at this point.

From line 18, column 17; to line 18, column 64

```
<Link to={"https://github.com/github-john-doe"}></Link>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

12.

**Error** Element [link](#) is missing one or more of the following attributes: [href](#),

[itemprop](#), [property](#), [rel](#), [resource](#).

From line 18, column 17; to line 18, column 64

```
<Link to={"https://github.com/github-john-doe"}></Link>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetched](#) initiated by the element  
[sizes](#) — Sizes of the icons (for [rel="icon"](#))  
[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))  
[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))  
[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))  
[blocking](#) — Whether the element is [potentially render-blocking](#)  
[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))  
[disabled](#) — Whether the link is disabled  
[fetchpriority](#) — Sets the [priority](#) for [fetched](#) initiated by the element  
Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

13. **Error** A [link](#) element must have an [href](#) or [imagesrcset](#) attribute, or both.

From line 18, column 17; to line 18, column 64

```
<Link to={"https://github.com/github-john-doe"}>←
```

14. **Error** A [link](#) element must not appear as a descendant of a [body](#) element unless the [link](#) element has an [itemprop](#) attribute or has a [rel](#) attribute whose value contains [dns-prefetch](#), [modulepreload](#), [pingback](#), [preconnect](#), [prefetch](#), [preload](#), [prerender](#), or [stylesheet](#).

From line 18, column 17; to line 18, column 64

```
<Link to={"https://github.com/github-john-doe"}>←
```

15. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 21, column 37

```
style={{ color: "#000000" }}←
```

16. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 21, column 45

```
color: "#000000" }}←
```

17. **Warning** Attribute [color:](#) is not serializable as XML 1.0.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

18. **Warning** Attribute `"#000000"` is not serializable as XML 1.0.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

19. **Warning** Attribute `{}{}` is not serializable as XML 1.0.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

20. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

Attributes for element `i`:

[Global attributes](#)

21. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

Attributes for element `i`:

[Global attributes](#)

22. **Error** Attribute `"#000000"` not allowed on element `i` at this point.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

Attributes for element `i`:

[Global attributes](#)

23. **Error** Attribute `{}{}` not allowed on element `i` at this point.

From line 19, column 19; to line 22, column 19

```
<i↔          className="fa-brands fa-github"↔
  style={{ color: "#000000" }}↔          ></i>↔
```

Attributes for element `i`:

[Global attributes](#)24. **Error** Stray end tag `link`.

From line 23, column 17; to line 23, column 23

`</Link>↵`25. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 24, column 27

`<Link to={"https://twitte`26. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 24, column 64

`witter-john-doe"}>↵`27. **Error** Attribute `to` not allowed on element `link` at this point.

From line 24, column 17; to line 24, column 66

`<Link to={"https://twitter.com/twitter-john-doe"}>↵`Attributes for element `link`:[Global attributes](#)`href` — Address of the [hyperlink](#)`crossorigin` — How the element handles crossorigin requests`rel` — Relationship between the document containing the [hyperlink](#) and the destination resource`media` — Applicable media`integrity` — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)`hreflang` — Language of the linked resource`type` — Hint for the type of the referenced resource`referrerpolicy` — [Referrer policy](#) for [fetches](#) initiated by the element`sizes` — Sizes of the icons (for `rel="icon"`)`imagesrcset` — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)`imagesizes` — Image sizes for different page layouts (for `rel="preload"`)`as` — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)`blocking` — Whether the element is [potentially render-blocking](#)`color` — Color to use when customizing a site's icon (for `rel="mask-icon"`)`disabled` — Whether the link is disabled`fetchpriority` — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

28. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

From line 24, column 17; to line 24, column 66

```
<Link to={"https://twitter.com/twitter-john-doe"}>←
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for `rel="icon"`)

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

[imagesizes](#) — Image sizes for different page layouts (for `rel="preload"`)

[as](#) — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for `rel="mask-icon"`)

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

29. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 24, column 17; to line 24, column 66

```
<Link to={"https://twitter.com/twitter-john-doe"}>←
```

30. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 24, column 17; to line 24, column 66

```
<Link to={"https://twitter.com/twitter-john-doe"}></Link>
```

31. **Error** **Quote " " in attribute name. Probable cause: Matching quote missing somewhere earlier.**

At line 27, column 37

```
style={{ color: "#000000" }}<
```

32. **Error** **Quote " " in attribute name. Probable cause: Matching quote missing somewhere earlier.**

At line 27, column 45

```
color: "#000000" }}<
```

33. **Warning** **Attribute color: is not serializable as XML 1.0.**

From line 25, column 19; to line 28, column 19

```
<i< ..... className="fa-brands fa-x-twitter"<.....>
style={{ color: "#000000" }}< ..... ><
```

34. **Warning** **Attribute "#000000" is not serializable as XML 1.0.**

From line 25, column 19; to line 28, column 19

```
<i< ..... className="fa-brands fa-x-twitter"<.....>
style={{ color: "#000000" }}< ..... ><
```

35. **Warning** **Attribute {} is not serializable as XML 1.0.**

From line 25, column 19; to line 28, column 19

```
<i< ..... className="fa-brands fa-x-twitter"<.....>
style={{ color: "#000000" }}< ..... ><
```

36. **Error** **Attribute classname not allowed on element i at this point.**

From line 25, column 19; to line 28, column 19

```
<i< ..... className="fa-brands fa-x-twitter"<.....>
style={{ color: "#000000" }}< ..... ><
```

Attributes for element i:

[Global attributes](#)

37. **Error** **Attribute color: not allowed on element i at this point.**

From line 25, column 19; to line 28, column 19

```
<i< ..... className="fa-brands fa-x-twitter"<.....>
style={{ color: "#000000" }}< ..... ><
```

Attributes for element [i](#):

[Global attributes](#)

38. **Error** Attribute `"#000000"` not allowed on element [i](#) at this point.

From line 25, column 19; to line 28, column 19

```
<i class="fa-brands fa-x-twitter" style={{ color: "#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

39. **Error** Attribute `{}>` not allowed on element [i](#) at this point.

From line 25, column 19; to line 28, column 19

```
<i class="fa-brands fa-x-twitter" style={{ color: "#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

40. **Error** Stray end tag `link`.

From line 29, column 17; to line 29, column 23

```
</Link></
```

41. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 30, column 27

```
<Link to={"https://www.li
```

42. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 30, column 73

```
nkedin-john-doe"}></
```

43. **Error** Attribute `to` not allowed on element [link](#) at this point.

From line 30, column 17; to line 30, column 75

```
<Link to={"https://www.linkedin.com/in/linkedin-john-doe"}></
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media  
[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [[SRI](#)]  
[hreflang](#) — Language of the linked resource  
[type](#) — Hint for the type of the referenced resource  
[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element  
[sizes](#) — Sizes of the icons (for [rel="icon"](#))  
[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))  
[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))  
[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))  
[blocking](#) — Whether the element is [potentially render-blocking](#)  
[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))  
[disabled](#) — Whether the link is disabled  
[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element  
 Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

44. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

From line 30, column 17; to line 30, column 75

```
<Link to={"https://www.linkedin.com/in/linkedin-john-doe"}></Link>
```

Attributes for element [link](#):

[Global attributes](#)  
[href](#) — Address of the [hyperlink](#)  
[crossorigin](#) — How the element handles crossorigin requests  
[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource  
[media](#) — Applicable media  
[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [[SRI](#)]  
[hreflang](#) — Language of the linked resource  
[type](#) — Hint for the type of the referenced resource  
[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element  
[sizes](#) — Sizes of the icons (for [rel="icon"](#))  
[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))  
[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))  
[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))  
[blocking](#) — Whether the element is [potentially render-blocking](#)

color — Color to use when customizing a site's icon (for `rel="mask-icon"`)

disabled — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the `title` attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

45. **Error** A link element must have an href or imagesrcset attribute, or both.

From line 30, column 17; to line 30, column 75

```
<Link to={"https://www.linkedin.com/in/linkedin-john-doe"}>
```

46. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 30, column 17; to line 30, column 75

```
<Link to={"https://www.linkedin.com/in/linkedin-john-doe"}>
```

47. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 33, column 37

```
tyle={{ color: "#000000" }}←
```

48. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 33, column 45

```
color: "#000000" }}←
```

49. **Warning** Attribute color: is not serializable as XML 1.0.

From line 31, column 19; to line 34, column 19

```
    <i class="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

50. **Warning** Attribute "#000000" is not serializable as XML 1.0.

From line 31, column 19; to line 34, column 19

```
        <i style={{ color: "#000000" }} className="fa-brands fa-linkedin"></i>
```

51. **Warning** Attribute } } is not serializable as XML 1.0.

From line 31, column 19; to line 34, column 19

```
<i class="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

52. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 31, column 19; to line 34, column 19

```
<i className="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

53. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 31, column 19; to line 34, column 19

```
<i className="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

54. **Error** Attribute `"#000000"` not allowed on element `i` at this point.

From line 31, column 19; to line 34, column 19

```
<i className="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

55. **Error** Attribute `}}` not allowed on element `i` at this point.

From line 31, column 19; to line 34, column 19

```
<i className="fa-brands fa-linkedin" style={{ color: "#000000" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

56. **Error** Stray end tag `link`.

From line 35, column 17; to line 35, column 23

```
</Link>
```

57. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 38, column 13; to line 38, column 70

```
<div className="col-12 col-md-6 col-lg-3 block link-list">
```

Attributes for element [div](#):

[Global attributes](#)

58. **Error** `["]` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 40, column 25

```
<Link to={"/"}>←
```

59. **Error** `["]` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 40, column 27

```
<Link to={"/"}>←
```

60. **Error** Attribute `to` not allowed on element [link](#) at this point.

From line 40, column 15; to line 40, column 29

```
<Link to={"/"}>←
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

61. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

From line 40, column 15; to line 40, column 29

```
<Link to="/">
```

Attributes for element `link`:

#### [Global attributes](#)

[`href`](#) — Address of the [hyperlink](#)

[`crossorigin`](#) — How the element handles crossorigin requests

[`rel`](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[`media`](#) — Applicable media

[`integrity`](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[`hreflang`](#) — Language of the linked resource

[`type`](#) — Hint for the type of the referenced resource

[`referrerpolicy`](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[`sizes`](#) — Sizes of the icons (for `rel="icon"`)

[`imagesrcset`](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

[`imagesizes`](#) — Image sizes for different page layouts (for `rel="preload"`)

[`as`](#) — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

[`blocking`](#) — Whether the element is [potentially render-blocking](#)

[`color`](#) — Color to use when customizing a site's icon (for `rel="mask-icon"`)

[`disabled`](#) — Whether the link is disabled

[`fetchpriority`](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [`title`](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

62. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 40, column 15; to line 40, column 29

```
<Link to="/">
```

63. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 40, column 15; to line 40, column 29

```
<Link to="/">
```

64. **Error** Quote ["] in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 43, column 35

```
[tyle={{ color: "#0d6efd " }}]← ]
```

65. **Error** Quote ["] in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 43, column 44

```
[olor: "#0d6efd " }]← ]
```

66. **Warning** Attribute [color:] is not serializable as XML 1.0.

From line 41, column 17; to line 44, column 17

```
<i←                            className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd " }}]←                            ></i>← ]
```

67. **Warning** Attribute [#0d6efd] is not serializable as XML 1.0.

From line 41, column 17; to line 44, column 17

```
<i←                            className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd " }}]←                            ></i>← ]
```

68. **Warning** Attribute ["] is not serializable as XML 1.0.

From line 41, column 17; to line 44, column 17

```
<i←                            className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd " }}]←                            ></i>← ]
```

69. **Warning** Attribute [{}]} is not serializable as XML 1.0.

From line 41, column 17; to line 44, column 17

```
<i←                            className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd " }}]←                            ></i>← ]
```

70. **Error** Attribute [classname] not allowed on element [i] at this point.

From line 41, column 17; to line 44, column 17

```
[i←                            className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd " }}]←                            ></i>← ]
```

Attributes for element i:

[Global attributes](#)

71. **Error** Attribute [color:] not allowed on element [i] at this point.

From line 41, column 17; to line 44, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

72. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

From line 41, column 17; to line 44, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

73. **Error** Attribute `"` not allowed on element [i](#) at this point.

From line 41, column 17; to line 44, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

74. **Error** Attribute `{}>` not allowed on element [i](#) at this point.

From line 41, column 17; to line 44, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

75. **Error** Stray end tag [link](#).

From line 46, column 15; to line 46, column 21

```
</Link>
```

76. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 47, column 24

```
<a href="#apropos">
```

77. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 47, column 33

78. **Error** **Bad value** `{"#apropos"}` **for attribute** `href` **on element** `a`: **Illegal character in path segment:** `{` **is not allowed.**
- From line 47, column 15; to line 47, column 35
79. **Error** **Quote** `"` **in attribute name. Probable cause: Matching quote missing somewhere earlier.**
- At line 50, column 35
80. **Error** **Quote** `"` **in attribute name. Probable cause: Matching quote missing somewhere earlier.**
- At line 50, column 44
81. **Warning** **Attribute** `color:` **is not serializable as XML 1.0.**
- From line 48, column 17; to line 51, column 17
82. **Warning** **Attribute** `"#0d6efd` **is not serializable as XML 1.0.**
- From line 48, column 17; to line 51, column 17
83. **Warning** **Attribute** `"` **is not serializable as XML 1.0.**
- From line 48, column 17; to line 51, column 17
84. **Warning** **Attribute** `{}}}` **is not serializable as XML 1.0.**
- From line 48, column 17; to line 51, column 17
85. **Error** **Attribute** `classname` **not allowed on element** `i` **at this point.**

From line 48, column 17; to line 51, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

86. **Error** Attribute `color:` not allowed on element [i](#) at this point.

From line 48, column 17; to line 51, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

87. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

From line 48, column 17; to line 51, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

88. **Error** Attribute `"` not allowed on element [i](#) at this point.

From line 48, column 17; to line 51, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

89. **Error** Attribute `{}>` not allowed on element [i](#) at this point.

From line 48, column 17; to line 51, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

90. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 54, column 25

```
<Link to="/services"></Link>
```

91. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 54, column 35

```
to={"/services"}>...
```

92. **Error** Attribute `to` not allowed on element `link` at this point.

From line 54, column 15; to line 54, column 37

```
<Link to={"/services"}>...
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

93. **Error** Element `link` is missing one or more of the following attributes: `href`,

`itemprop`, `property`, `rel`, `resource`.

From line 54, column 15; to line 54, column 37

```
<Link to={"/services"}>...
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

94. **Error** A [link](#) element must have an [href](#) or [imagesrcset](#) attribute, or both.

From line 54, column 15; to line 54, column 37

```
<Link to={"/services"}>↔
```

95. **Error** A [link](#) element must not appear as a descendant of a [body](#) element unless the [link](#) element has an [itemprop](#) attribute or has a [rel](#) attribute whose value contains [dns-prefetch](#), [modulepreload](#), [pingback](#), [preconnect](#), [prefetch](#), [preload](#), [prerender](#), or [stylesheet](#).

From line 54, column 15; to line 54, column 37

```
<Link to={"/services"}>↔
```

96. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 57, column 35

```
tyle={{ color: "#0d6efd" }}↔
```

97. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 57, column 44

```
color: "#0d6efd" } } ↵
```

98. **Warning** Attribute `color:` is not serializable as XML 1.0.

From line 55, column 17; to line 58, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

99. **Warning** Attribute `"#0d6efd` is not serializable as XML 1.0.

From line 55, column 17; to line 58, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

100. **Warning** Attribute `[]` is not serializable as XML 1.0.

From line 55, column 17; to line 58, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

101. **Warning** Attribute `{} }`  is not serializable as XML 1.0.

From line 55, column 17; to line 58, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

102. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 55, column 17; to line 58, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

103. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 55, column 17; to line 58, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

104. **Error** Attribute `"#0d6efd` not allowed on element `i` at this point.

From line 55, column 17; to line 58, column 17

```
<i style={{ color: "#0d6efd " }}> className="fa-solid fa-chevron-right"</i>
```

Attributes for element [i](#):

[Global attributes](#)

105. **Error** Attribute `[]` not allowed on element [i](#) at this point.

From line 55, column 17; to line 58, column 17

```
<i style={{ color: "#0d6efd " }}> className="fa-solid fa-chevron-right"</i>
```

Attributes for element [i](#):

[Global attributes](#)

106. **Error** Attribute `{}>` not allowed on element [i](#) at this point.

From line 55, column 17; to line 58, column 17

```
<i style={{ color: "#0d6efd " }}> className="fa-solid fa-chevron-right"</i>
```

Attributes for element [i](#):

[Global attributes](#)

107. **Error** Stray end tag [link](#).

From line 60, column 15; to line 60, column 21

```
</Link>
```

108. **Error** `[]` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 61, column 25

```
<Link to={"/contact"}>
```

109. **Error** `[]` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 61, column 34

```
Link to={"/contact"}>
```

110. **Error** Attribute `to` not allowed on element [link](#) at this point.

From line 61, column 15; to line 61, column 36

```
<Link to={"/contact"}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests  
[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource  
[media](#) — Applicable media  
[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)  
[hreflang](#) — Language of the linked resource  
[type](#) — Hint for the type of the referenced resource  
[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element  
[sizes](#) — Sizes of the icons (for [rel="icon"](#))  
[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))  
[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))  
[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))  
[blocking](#) — Whether the element is [potentially render-blocking](#)  
[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))  
[disabled](#) — Whether the link is disabled  
[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element  
Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

111. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

From line 61, column 15; to line 61, column 36

```
<Link to={"/contact"}>←
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)  
[crossorigin](#) — How the element handles crossorigin requests  
[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource  
[media](#) — Applicable media  
[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)  
[hreflang](#) — Language of the linked resource  
[type](#) — Hint for the type of the referenced resource  
[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element  
[sizes](#) — Sizes of the icons (for [rel="icon"](#))  
[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))  
[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

as — Potential destination for a preload request (for rel="preload" and rel="modulepreload")  
blocking — Whether the element is potentially render-blocking  
color — Color to use when customizing a site's icon (for rel="mask-icon")  
disabled — Whether the link is disabled  
fetchpriority — Sets the priority for fetches initiated by the element  
Also, the title attribute has special semantics on this element: Title of the link; CSS style sheet set name

112. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 61, column 15; to line 61, column 36

```
<Link to={"/contact"}>←
```

113. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 61, column 15; to line 61, column 36

```
<Link to={"/contact"}>←
```

114. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 64, column 35

```
style={{ color: "#0d6efd" }}←
```

115. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 64, column 44

```
olor: "#0d6efd" }}←
```

116. **Warning** Attribute `color:` is not serializable as XML 1.0.

From line 62, column 17; to line 65, column 17

```
<i←                          className="fa-solid fa-chevron-right"←
style={{ color: "#0d6efd" }}←                                  >/i>←
```

117. **Warning** Attribute `#0d6efd` is not serializable as XML 1.0.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

118. **Warning** Attribute `[]` is not serializable as XML 1.0.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

119. **Warning** Attribute `{}[]` is not serializable as XML 1.0.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

120. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

121. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

122. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

123. **Error** Attribute `[]` not allowed on element `i` at this point.

From line 62, column 17; to line 65, column 17

```
<i style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

124. **Error** Attribute `[]{}` not allowed on element `link` at this point.

From line 62, column 17; to line 65, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

125. **Error** Stray end tag `link`.

From line 67, column 15; to line 67, column 21

```
</Link>
```

126. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 68, column 25

```
<Link to={"/mentions"}>
```

127. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 68, column 35

```
to={"/mentions"}>
```

128. **Error** Attribute `to` not allowed on element `link` at this point.

From line 68, column 15; to line 68, column 37

```
<Link to={"/mentions"}>
```

Attributes for element `link`:

[Global attributes](#)

`href` — Address of the [hyperlink](#)

`crossorigin` — How the element handles crossorigin requests

`rel` — Relationship between the document containing the [hyperlink](#) and the destination resource

`media` — Applicable media

`integrity` — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

`hreflang` — Language of the linked resource

`type` — Hint for the type of the referenced resource

`referrerpolicy` — [Referrer policy](#) for [fetches](#) initiated by the element

`sizes` — Sizes of the icons (for `rel="icon"`)

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetched](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

129. **Error** Element [link](#) is missing one or more of the following attributes: [href](#),

[itemprop](#), [property](#), [rel](#), [resource](#).

From line 68, column 15; to line 68, column 37

```
<Link to={"/mentions"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetched](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetched](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

130. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 68, column 15; to line 68, column 37

```
<Link to={"/mentions"}>
```

131. **Error** A `link` element must not appear as a descendant of a `body` element

unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 68, column 15; to line 68, column 37

```
<Link to={"/mentions"}>
```

132. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing

somewhere earlier.

At line 71, column 35

```
style={{ color: "#0d6efd" }}>
```

133. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing

somewhere earlier.

At line 71, column 44

```
olor: "#0d6efd" }}>
```

134. **Warning** Attribute `color:` is not serializable as XML 1.0.

From line 69, column 17; to line 72, column 17

```
<i>                          className="fa-solid fa-chevron-right">  
style={{ color: "#0d6efd" }}>                                  </i>
```

135. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

From line 69, column 17; to line 72, column 17

```
<i>                          className="fa-solid fa-chevron-right">  
style={{ color: "#0d6efd" }}>                                  </i>
```

136. **Warning** Attribute `[]` is not serializable as XML 1.0.

From line 69, column 17; to line 72, column 17

```
<i>                          className="fa-solid fa-chevron-right">  
style={{ color: "#0d6efd" }}>                                  </i>
```

137. **Warning** Attribute `{}0` is not serializable as XML 1.0.

From line 69, column 17; to line 72, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

138. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 69, column 17; to line 72, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

139. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 69, column 17; to line 72, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

140. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

From line 69, column 17; to line 72, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

141. **Error** Attribute `"` not allowed on element `i` at this point.

From line 69, column 17; to line 72, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

142. **Error** Attribute `}}` not allowed on element `i` at this point.

From line 69, column 17; to line 72, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

143. **Error** Stray end tag `link`.

From line 74, column 15; to line 74, column 21

```
</Link>←
```

144. **Error** Attribute `classname` not allowed on element `div` at this point.

From line 76, column 13; to line 76, column 70

```
<div className="col-12 col-md-6 col-lg-3 block link-list">←
```

Attributes for element `div`:

[Global attributes](#)

145. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 78, column 25

```
<Link to={"/realisations"}>←
```

146. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 78, column 39

```
{"/realisations"}>←
```

147. **Error** Attribute `to` not allowed on element `link` at this point.

From line 78, column 15; to line 78, column 41

```
<Link to={"/realisations"}>←
```

Attributes for element `link`:

[Global attributes](#)

`href` — Address of the [hyperlink](#)

`crossorigin` — How the element handles crossorigin requests

`rel` — Relationship between the document containing the [hyperlink](#) and the destination resource

`media` — Applicable media

`integrity` — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

`hreflang` — Language of the linked resource

`type` — Hint for the type of the referenced resource

`referrerpolicy` — [Referrer policy](#) for [fetches](#) initiated by the element

`sizes` — Sizes of the icons (for `rel="icon"`)

`imagesrcset` — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

`imagesizes` — Image sizes for different page layouts (for `rel="preload"`)

`as` — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

`blocking` — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

148. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

From line 78, column 15; to line 78, column 41

```
<Link to={"/realisations"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

149. **Error** A [link](#) element must have an [href](#) or [imagesrcset](#) attribute, or both.

From line 78, column 15; to line 78, column 41

```
<Link to={"/realisations"}>...
```

150. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 78, column 15; to line 78, column 41

```
<Link to={"/realisations"}>...
```

151. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 81, column 35

```
style={{ color: "#0d6efd" }}...
```

152. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 81, column 44

```
olor: "#0d6efd" }}...
```

153. **Warning** Attribute `color:` is not serializable as XML 1.0.

From line 79, column 17; to line 82, column 17

```
<i... className="fa-solid fa-chevron-right"... style={{ color: "#0d6efd" }}...></i>...
```

154. **Warning** Attribute `#0d6efd` is not serializable as XML 1.0.

From line 79, column 17; to line 82, column 17

```
<i... className="fa-solid fa-chevron-right"... style={{ color: "#0d6efd" }}...></i>...
```

155. **Warning** Attribute `"` is not serializable as XML 1.0.

From line 79, column 17; to line 82, column 17

```
<i... className="fa-solid fa-chevron-right"... style={{ color: "#0d6efd" }}...></i>...
```

156. **Warning** Attribute `}}` is not serializable as XML 1.0.

From line 79, column 17; to line 82, column 17

```
<i... className="fa-solid fa-chevron-right"... style={{ color: "#0d6efd" }}...></i>...
```

157. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 79, column 17; to line 82, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

158. **Error** Attribute `color:` not allowed on element [i](#) at this point.

From line 79, column 17; to line 82, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

159. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

From line 79, column 17; to line 82, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

160. **Error** Attribute `"` not allowed on element [i](#) at this point.

From line 79, column 17; to line 82, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

161. **Error** Attribute `}}` not allowed on element [i](#) at this point.

From line 79, column 17; to line 82, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

162. **Error** Stray end tag `link`.

From line 84, column 15; to line 84, column 21

```
</Link>
```

163. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 85, column 25

```
<Link to={"/realisations"}>
```

164. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 85, column 39

```
{"/realisations"}>←
```

165. **Error** Attribute `to` not allowed on element `link` at this point.

From line 85, column 15; to line 85, column 41

```
<Link to={"/realisations"}>←
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for `rel="icon"`)

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

[imagesizes](#) — Image sizes for different page layouts (for `rel="preload"`)

[as](#) — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for `rel="mask-icon"`)

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

166. **Error** Element `link` is missing one or more of the following attributes: `href`,

`itemprop`, `property`, `rel`, `resource`.

From line 85, column 15; to line 85, column 41

```
<Link to={"/realisations"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

167. **Error** A [link](#) element must have an [href](#) or [imagesrcset](#) attribute, or both.

From line 85, column 15; to line 85, column 41

```
<Link to={"/realisations"}>...
```

168. **Error** A [link](#) element must not appear as a descendant of a [body](#) element

unless the [link](#) element has an [itemprop](#) attribute or has a [rel](#) attribute

whose value contains [dns-prefetch](#), [modulepreload](#), [pingback](#), [preconnect](#), [prefetch](#), [preload](#), [prerender](#), or [stylesheet](#).

From line 85, column 15; to line 85, column 41

```
<Link to={"/realisations"}>...
```

169. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 88, column 35

```
style={{ color: "#0d6efd" }}←
```

170. **Error** **Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.**

At line 88, column 44

```
olor: "#0d6efd" }}←
```

171. **Warning** **Attribute [color:] is not serializable as XML 1.0.**

From line 86, column 17; to line 89, column 17

```
<i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                          >/i>←
```

172. **Warning** **Attribute ["#0d6efd] is not serializable as XML 1.0.**

From line 86, column 17; to line 89, column 17

```
<i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                  >/i>←
```

173. **Warning** **Attribute ["] is not serializable as XML 1.0.**

From line 86, column 17; to line 89, column 17

```
<i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                  >/i>←
```

174. **Warning** **Attribute [{}]} is not serializable as XML 1.0.**

From line 86, column 17; to line 89, column 17

```
<i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                  >/i>←
```

175. **Error** **Attribute [classname] not allowed on element [i] at this point.**

From line 86, column 17; to line 89, column 17

```
[  <i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                  >/i>←]
```

Attributes for element [i](#):

[Global attributes](#)

176. **Error** **Attribute [color:] not allowed on element [i] at this point.**

From line 86, column 17; to line 89, column 17

```
[  <i←                          className="fa-solid fa-chevron-right"←  
style={{ color: "#0d6efd" }}←                                  >/i>←]
```

Attributes for element [i](#):

[Global attributes](#)

177. **Error** Attribute "#0d6efd" not allowed on element [i](#) at this point.

From line 86, column 17; to line 89, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

178. **Error** Attribute "}" not allowed on element [i](#) at this point.

From line 86, column 17; to line 89, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

179. **Error** Attribute "}" not allowed on element [i](#) at this point.

From line 86, column 17; to line 89, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

180. **Error** Stray end tag [link](#).

From line 91, column 15; to line 91, column 21

```
</Link>
```

181. **Error** "[" in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 92, column 25

```
<Link to={"/realisations"}
```

182. **Error** "[" in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 92, column 39

```
{"/realisations"}>
```

183. **Error** Attribute "to" not allowed on element [link](#) at this point.

From line 92, column 15; to line 92, column 41

```
<Link to={"/realisations"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

184.

**Error** Element [link](#) is missing one or more of the following attributes: [href](#),

[itemprop](#), [property](#), [rel](#), [resource](#).

From line 92, column 15; to line 92, column 41

```
<Link to={"/realisations"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

referrerpolicy — Referrer policy for fetched initiated by the element  
sizes — Sizes of the icons (for rel="icon")  
imagesrcset — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for rel="preload")  
imagesizes — Image sizes for different page layouts (for rel="preload")  
as — Potential destination for a preload request (for rel="preload" and rel="modulepreload")  
blocking — Whether the element is potentially render-blocking  
color — Color to use when customizing a site's icon (for rel="mask-icon")  
disabled — Whether the link is disabled  
fetchpriority — Sets the priority for fetched initiated by the element  
Also, the title attribute has special semantics on this element: Title of the link; CSS style sheet set name

185. **Error** A link element must have an href or imagesrcset attribute, or both.

From line 92, column 15; to line 92, column 41

```
<Link to={"/realisations"}>...
```

186. **Error** A link element must not appear as a descendant of a body element unless the link element has an itemprop attribute or has a rel attribute whose value contains dns-prefetch, modulepreload, pingback, preconnect, prefetch, preload, prerender, or stylesheet.

From line 92, column 15; to line 92, column 41

```
<Link to={"/realisations"}>...
```

187. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 95, column 35

```
style={{ color: "#0d6efd" }}<...
```

188. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 95, column 44

```
olor: "#0d6efd" }}<...
```

189. **Warning** Attribute color: is not serializable as XML 1.0.

From line 93, column 17; to line 96, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

**190. Warning Attribute "#0d6efd" is not serializable as XML 1.0.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

**191. Warning Attribute "}" is not serializable as XML 1.0.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

**192. Warning Attribute "{}" is not serializable as XML 1.0.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

**193. Error Attribute "classname" not allowed on element i at this point.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element i:

[Global attributes](#)

**194. Error Attribute "color:" not allowed on element i at this point.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element i:

[Global attributes](#)

**195. Error Attribute "#0d6efd" not allowed on element i at this point.**

From line 93, column 17; to line 96, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element i:

[Global attributes](#)

**196. Error** Attribute `"` not allowed on element `i` at this point.

From line 93, column 17; to line 96, column 17

```
| <i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:[Global attributes](#)**197. Error** Attribute `}}` not allowed on element `i` at this point.

From line 93, column 17; to line 96, column 17

```
| <i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:[Global attributes](#)**198. Error** Stray end tag `link`.

From line 98, column 15; to line 98, column 21

```
| </Link>
```

**199. Error** Attribute `classname` not allowed on element `div` at this point.

From line 100, column 13; to line 100, column 70

```
| <div className="col-12 col-md-6 col-lg-3 block link-list">
```

Attributes for element `div`:[Global attributes](#)**200. Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 102, column 25

```
| <Link to={"/blog"}>
```

**201. Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 102, column 31

```
| Link to={"/blog"}>
```

**202. Error** Attribute `to` not allowed on element `link` at this point.

From line 102, column 15; to line 102, column 33

```
| <Link to={"/blog"}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

203. **Error** Element [link](#) is missing one or more of the following attributes: [href](#),

[itemprop](#), [property](#), [rel](#), [resource](#).

From line 102, column 15; to line 102, column 33

[<Link to={"/blog"}>](#)

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

204. **Error** A [link](#) element must have an [href](#) or [imagesrcset](#) attribute, or both.

From line 102, column 15; to line 102, column 33

```
<Link to={"/blog"}>↔
```

205. **Error** A [link](#) element must not appear as a descendant of a [body](#) element

unless the [link](#) element has an [itemprop](#) attribute or has a [rel](#) attribute whose value contains [dns-prefetch](#), [modulepreload](#), [pingback](#), [preconnect](#), [prefetch](#), [preload](#), [prerender](#), or [stylesheet](#).

From line 102, column 15; to line 102, column 33

```
<Link to={"/blog"}>↔
```

206. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 105, column 35

```
style={{ color: "#0d6efd " }}↔
```

207. **Error** Quote ["](#) in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 105, column 44

```
olor: "#0d6efd " }}↔
```

208. **Warning** Attribute [color:](#) is not serializable as XML 1.0.

From line 103, column 17; to line 106, column 17

```
<i↔                          className="fa-solid fa-chevron-right"↔
style={{ color: "#0d6efd " }}↔                                          >/i>↔
```

209. **Warning** Attribute ["#0d6efd](#) is not serializable as XML 1.0.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

210. **Warning** Attribute `[]` is not serializable as XML 1.0.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

211. **Warning** Attribute `{}()` is not serializable as XML 1.0.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

212. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

213. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

214. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

215. **Error** Attribute `[]` not allowed on element `i` at this point.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

216. **Error** Attribute `}}` not allowed on element [i](#) at this point.

From line 103, column 17; to line 106, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

217. **Error** Stray end tag [link](#).

From line 108, column 15; to line 108, column 21

```
</Link>
```

218. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 109, column 25

```
<Link to={"/blog"}>
```

219. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 109, column 31

```
Link to={"/blog"}>
```

220. **Error** Attribute `to` not allowed on element [link](#) at this point.

From line 109, column 15; to line 109, column 33

```
<Link to={"/blog"}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetched](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

221. **Error** Element [link](#) is missing one or more of the following attributes: [href](#),

[itemprop](#), [property](#), [rel](#), [resource](#).

From line 109, column 15; to line 109, column 33

```
<Link to={"/blog"}>...
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetched](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel="icon"](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel="preload"](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel="preload"](#))

[as](#) — [Potential destination](#) for a preload request (for [rel="preload"](#) and [rel="modulepreload"](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel="mask-icon"](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetched](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

222. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 109, column 15; to line 109, column 33

```
<Link to={"/blog"}>...
```

223. **Error** A `link` element must not appear as a descendant of a `body` element

unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 109, column 15; to line 109, column 33

```
<Link to={"/blog"}>...
```

224. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing

somewhere earlier.

At line 112, column 35

```
style={{ color: "#0d6efd" }}<...
```

225. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing

somewhere earlier.

At line 112, column 44

```
olor: "#0d6efd" }}<...
```

226. **Warning** Attribute `color:` is not serializable as XML 1.0.

From line 110, column 17; to line 113, column 17

```
<i>... class="fa-solid fa-chevron-right"<...>  
style={{ color: "#0d6efd" }}<... ></i>...
```

227. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

From line 110, column 17; to line 113, column 17

```
<i>... class="fa-solid fa-chevron-right"<...>  
style={{ color: "#0d6efd" }}<... ></i>...
```

228. **Warning** Attribute `[]` is not serializable as XML 1.0.

From line 110, column 17; to line 113, column 17

```
<i>... class="fa-solid fa-chevron-right"<...>  
style={{ color: "#0d6efd" }}<... ></i>...
```

229. **Warning** Attribute `{}()` is not serializable as XML 1.0.

From line 110, column 17; to line 113, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

230. **Error** Attribute `classname` not allowed on element `i` at this point.

From line 110, column 17; to line 113, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

231. **Error** Attribute `color:` not allowed on element `i` at this point.

From line 110, column 17; to line 113, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

232. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

From line 110, column 17; to line 113, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

233. **Error** Attribute `"` not allowed on element `i` at this point.

From line 110, column 17; to line 113, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

234. **Error** Attribute `}}` not allowed on element `i` at this point.

From line 110, column 17; to line 113, column 17

```
<i className="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element `i`:

[Global attributes](#)

235. **Error** Stray end tag `link`.

From line 115, column 15; to line 115, column 21

```
</Link>↔
```

236. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 116, column 25

```
<Link to={"/blog"}>↔
```

237. **Error** `"` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

At line 116, column 31

```
Link to={"/blog"}>↔
```

238. **Error** Attribute `to` not allowed on element `link` at this point.

From line 116, column 15; to line 116, column 33

```
<Link to={"/blog"}>↔
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for `rel="icon"`)

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

[imagesizes](#) — Image sizes for different page layouts (for `rel="preload"`)

[as](#) — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for `rel="mask-icon"`)

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

239. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

From line 116, column 15; to line 116, column 33

```
<Link to={"/blog"}>...
```

Attributes for element `link`:

#### [Global attributes](#)

[`href`](#) — Address of the [hyperlink](#)

[`crossorigin`](#) — How the element handles crossorigin requests

[`rel`](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[`media`](#) — Applicable media

[`integrity`](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[`hreflang`](#) — Language of the linked resource

[`type`](#) — Hint for the type of the referenced resource

[`referrerpolicy`](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[`sizes`](#) — Sizes of the icons (for `rel="icon"`)

[`imagesrcset`](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for `rel="preload"`)

[`imagesizes`](#) — Image sizes for different page layouts (for `rel="preload"`)

[`as`](#) — [Potential destination](#) for a preload request (for `rel="preload"` and `rel="modulepreload"`)

[`blocking`](#) — Whether the element is [potentially render-blocking](#)

[`color`](#) — Color to use when customizing a site's icon (for `rel="mask-icon"`)

[`disabled`](#) — Whether the link is disabled

[`fetchpriority`](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [`title`](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

240. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

From line 116, column 15; to line 116, column 33

```
<Link to={"/blog"}>...
```

241. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

From line 116, column 15; to line 116, column 33

```
<Link to={"/blog"}>...
```

242. **Error** Quote ["] in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 119, column 35

```
[tyle={{ color: "#0d6efd " }}]←
```

243. **Error** Quote ["] in attribute name. Probable cause: Matching quote missing somewhere earlier.

At line 119, column 44

```
[olor: "#0d6efd " }]←
```

244. **Warning** Attribute [color:] is not serializable as XML 1.0.

From line 117, column 17; to line 120, column 17

```
<i↔           className="fa-solid fa-chevron-right"↔  
style={{ color: "#0d6efd " }}]←             ></i>↔
```

245. **Warning** Attribute [#0d6efd] is not serializable as XML 1.0.

From line 117, column 17; to line 120, column 17

```
<i↔           className="fa-solid fa-chevron-right"↔  
style={{ color: "#0d6efd " }}]←             ></i>↔
```

246. **Warning** Attribute ["] is not serializable as XML 1.0.

From line 117, column 17; to line 120, column 17

```
<i↔           className="fa-solid fa-chevron-right"↔  
style={{ color: "#0d6efd " }}]←             ></i>↔
```

247. **Warning** Attribute [{}]} is not serializable as XML 1.0.

From line 117, column 17; to line 120, column 17

```
<i↔           className="fa-solid fa-chevron-right"↔  
style={{ color: "#0d6efd " }}]←             ></i>↔
```

248. **Error** Attribute [classname] not allowed on element i at this point.

From line 117, column 17; to line 120, column 17

```
<i↔           className="fa-solid fa-chevron-right"↔  
style={{ color: "#0d6efd " }}]←             ></i>↔
```

Attributes for element i:

[Global attributes](#)

249. **Error** Attribute [color:] not allowed on element i at this point.

From line 117, column 17; to line 120, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

250. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

From line 117, column 17; to line 120, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

251. **Error** Attribute `"` not allowed on element [i](#) at this point.

From line 117, column 17; to line 120, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

252. **Error** Attribute `{}>` not allowed on element [i](#) at this point.

From line 117, column 17; to line 120, column 17

```
<i class="fa-solid fa-chevron-right" style={{ color: "#0d6efd" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

253. **Error** Stray end tag `link`.

From line 122, column 15; to line 122, column 21

```
</Link>
```

254. **Error** Attribute `classname` not allowed on element [div](#) at this point.

From line 126, column 9; to line 126, column 35

```
><div className="copyright">&copy;
```

Attributes for element [div](#):

[Global attributes](#)

Document checking completed.

05/08/2024 17:13

Showing results for footer.jsx - Nu Html Checker

Used the HTML parser.

Total execution time 26 milliseconds.

---

[About this checker](#) • [Report an issue](#) • Version: 24.8.2