

# Model selection

## Lecture 1e

## Overview

- Model fitting
- Model selection

1

2

## Frequentist vs Bayesian

- Probabilistic Model  $p(y, x, w)$ 
  - **Frequentists:**  $w$  is a parameter that should be estimated by model fitting
  - **Bayesians:**  $w$  is a random variable that has a prior distribution  $p(w)$ 
    - How to set  $p(w)$ ??

Frequentists	vs.	Bayesian
Parameters fixed	Round 1	Data fixed
Data varies		Parameters Vary

**Example:** Linear regression, what are parameters here?

$$y \sim w_0 + \mathbf{w}x + e, e \sim N(0, \sigma^2)$$

$$y \sim N(w_0 + \mathbf{w}x, \sigma^2)$$

## An estimator

- $\hat{w} = \delta(D)$  (some function of your data) – an **estimator**
- Optimal parameter values? → there can be many ways to compute them (MLE, shrinkage...)
  - Compare Bayesian: given estimators  $w^1$  and  $w^2$ , we **can** compare them!  $p(w^1|D) > p(w^2|D)$
  - There is no easy way to compare estimators in frequentist tradition

**Example:** Linear regression


- Estimator 1:  $\mathbf{w} = (X^T X)^{-1} X^T Y$  (maximum likelihood)
- Estimator 2:  $\mathbf{w} = (0, \dots, 0, 1)$
- Which one is better?
  - A comparison strategy is needed!

3

4

## Overfitting

- Complex model can overfit your data



732A99/TDDE01

5

5

## Overfitting: solutions

- Observed:** Maximum likelihood can lead to overfitting.
- Solutions**
  - Selecting proper parameter values
    - Regularized risk minimization
  - Selecting proper model type, for ex. number of parameters
    - Houldout method
    - Cross-validation

732A99/TDDE01

6

6

## Model selection

- Given a model, choose the optimal parameter values
  - Decision theory
- Define loss  $L(Y, \hat{y})$ 
  - How much we loose in guessing true  $Y$  incorrectly
- If we know the true distribution  $p(y, x|w)$  then we choose  $\hat{y}$

$$\min_{\hat{y}} EL(y, \hat{y}) = \min_{\hat{y}} \int L(y, \hat{y}) p(y, x|w) dx dy$$

732A99/TDDE01


7

7

## Model selection

**Example:** Spam classification

- Loss for incorrect classifying mails and spams
  - $L_{12} = 100, L_{21} = 1$



732A99/TDDE01

8

8

## Loss functions

- How to define loss function?
  - No unique choice, often defined by application
  - **Normal practice:** Choose the loss related to minus loglikelihood

**Example:** Predicting the amount of the product at the storage:

$$L(Y, \hat{y}) = \begin{cases} 10 + \frac{\hat{y}}{Y}, & \hat{y} \geq Y \\ 1000, & \hat{y} < Y \end{cases}$$

**Example:** Compute loss function related to

- Normal distribution

Guess why such loss function was chosen

732A99/TDDE01

9

## Loss functions

- Classification problems
  - Common loss function  $L(Y, \hat{y}) = \begin{cases} 0, & Y = \hat{y} \\ 1, & Y \neq \hat{y} \end{cases}$
  - When minimizing the loss, equivalent to misclassification rate

732A99/TDDE01

10

## Model selection

- **Problem:** true model and true  $w$  are unknown  $\rightarrow$  can not compute expected loss!
- How to find an optimal model?
  - Consider what expected loss (**risk**) depends on  
 $R(Y, \hat{y}) = E[L(Y, \hat{y}(X, D))]$
- Random factors:
  - $D$  – **training set**
  - $Y, X$  – data to be predicted (**validation set**)

732A99/TDDE01

11

## Holdout method


- Simplify the risk estimation:
  - Fix  $D$  as a particular training set  $T$
  - Fix  $Y, X$  as a particular validation set  $V$
- Risk becomes (**empirical risk**)
 
$$\hat{R}(y, \hat{y}) = \frac{1}{|V|} \sum_{(X, Y) \in V} L(Y, \hat{y}(X, T))$$
  - Estimator is fit by Maximum Likelihood using training set
  - Risk estimated by using validation set
  - Model with minimum empirical risk is selected

732A99/TDDE01

12

## General model selection strategy

- Given data  $D = \{X_i, Y_i, i = 1 \dots n\}$



- When fitting data, Maximum Likelihood is usually used
- $\alpha_i$  can be different things:
  - Type of distribution
  - Number of variables in the model
  - Regularization parameter value
  - ...


732A99/TDDE01

13

13

## Holdout method

Divide into training, validation and test sets



- Choose proportions in some way


732A99/TDDE01

14

14

## Holdout method

- Given: training, validation, test sets and models to select between




732A99/TDDE01

15

15

## Holdout method

- Training set is to used for fitting models to the dataset by using maximum likelihood




732A99/TDDE01

16

16

## Holdout method

- Validation set is used to choose the best model (lowest risk)




732A99/TDDE01

17

17

## Holdout method

- Test set is used to test a performance on a new data




732A99/TDDE01

18

18

## Holdout method



732A99/TDDE01

19

19

## Holdout in R

- How to partition into train/test?
  - Use `set.seed(12345)` in the labs to get identical results

```
n=dim(data)[1]
set.seed(12345)
id=sample(1:n, floor(n*0.7))
train=data[id,]
test=data[-id,]
```

- How to partition into train/valid/test?

```
n=dim(data)[1]
set.seed(12345)
id=sample(1:n, floor(n*0.4))
train=data[id,]

id1=setdiff(1:n, id)
set.seed(12345)
id2=sample(id1, floor(n*0.3))
valid=data[id2,]

id3=setdiff(id1,id2)
test=data[id3,]
```

732A99/TDDE01

20

20

## Bias-variance tradeoff

- **Bias of an estimator**  $Bias(\hat{y}(x_0)) = E[\hat{y}(x_0) - f(x_0)]$ ,  $f(x_0)$  is expected response
  - If  $Bias(\hat{y}(x_0)) = 0$ , the estimator is **unbiased**
  - ML estimators are asymptotically unbiased if the model is enough complex
  - However, unbiasedness does not mean a good choice!


732A99/TDDE01

21

21

## Bias-variance tradeoff

- Assume loss is  $L(Y, \hat{y}) = (Y - \hat{y})^2$   
 $R(Y(x_0), \hat{y}(x_0)) = \sigma^2 + Bias^2(\hat{y}(x_0)) + Var(\hat{y}(x_0))$



When loss is not quadratic, no such nice formula exist

732A99/TDDE01

22

22

## Cross-validation

- Compared to holdout method:
  - Why do we use only some portion of data for training- can we use more (increase accuracy)?

**Cross-validation** (Estimates Err)

**K-fold cross-validation (rough scheme, show picture):**

1. Permute the observations randomly
2. Divide data-set in K roughly equally-sized subsets
3. Remove subset #i and fit the model using remaining data.
4. Predict the function values for subset #i using the fitted model.
5. Repeat steps 3-4 for different i
6. CV= squared difference between observed values and predicted values (another function is possible)

732A99/TDDE01

23

23

## Cross-validation

### Cross-validation



Note: if  $K=N$  then method is **leave-one-out** cross-validation.

$$K : \{1, \dots, N\} \mapsto \{1, \dots, K\}$$

**K-fold cross-validation:**  $CV =$

$$\frac{1}{N} \sum_{i=1}^N L(Y_i, \hat{y}^{-k(i)}(x_i))$$

What to do if N is not a multiple of K?

732A99/TDDE01

24

24

## Cross-validation vs Holdout

- Holdout is easy to do (a few model fits to each data)
- Cross validation is computationally demanding (many model fits)
- Holdout is applicable for large data
  - Otherwise, model selection performs poorly
- Cross validation is more suitable for smaller data

732A99/TDDE01

25

25

## Analytical methods

- Analytical expressions to select models
  - *AIC* (Akaike's information criterion)

**Idea:** Instead of  $R(Y, \hat{y}) = E[L(Y, \hat{y}(X, D))]$  consider **in-sample** risk (only  $Y$  in  $D$  is random):

$$R_{in}(Y, \hat{y}) = \frac{1}{N} \sum_{i=1}^N E_{Y_i} [L(Y_i, \hat{y}(X, D)) | D, X \in D]$$

732A99/TDDE01

26

26

## Analytical methods

- One can show that

$$R_{in}(Y, \hat{y}) \approx R_{train} + \frac{2}{N} \sum_i cov(\hat{y}_i, Y_i)$$

where  $R_{train} = \sum_{X_i, Y_i \in T} L(Y_i, \hat{y}_i)$

- Recall, **degrees of freedom**  $df(model) = \frac{1}{\sigma^2} \sum_i cov(\hat{y}_i, Y_i)$ 
  - When model is linear,  $df$  is the number of parameters.
- If loss is defined by minus two loglikelihood,
 
$$AIC \equiv -2loglik(D) + 2df(model)$$

732A99/TDDE01

27

27

## Model selection

**Example Computer Hardware Data Set** : performance measured for various processors and also

- Cycle time
- Memory
- Channels
- ...

Build model predicting performance



732A99/TDDE01

28


28

## Cross-validation

- Try models with different predictor sets

```
data=read.csv("machine.csv", header=F)
library(cvTools)
```

```
fit1=lm(V9~V3+V4+V5+V6+V7+V8, data=data)
fit2=lm(V9~V3+V4+V5+V6+V7, data=data)
fit3=lm(V9~V3+V4+V5+V6, data=data)
f1=cvFit(fit1, y=data$V9, data=data, K=10,
foldType="consecutive")
f2=cvFit(fit2, y=data$V9, data=data, K=10,
foldType="consecutive")
f3=cvFit(fit3, y=data$V9, data=data, K=10,
foldType="consecutive")
res=cvSelect(f1,f2,f3)
plot(res)
```



732A99/TDDE01

29