Activity and Sequence Specifications

10 October 2026 | playerP2

Activity A1 — Media playback

Start → Add files → Select file → Load file → Play. The user may Pause, Resume, Seek, change volume or Stop. If the file ends naturally, the selected repeat and shuffle modes determine the next action. Stop ends the flow without starting another item.

Activity A2 — Repeat and shuffle

Natural end → Repeat One? Replay current file. Otherwise select the next unplayed item. If no item remains: Repeat All? Start a new cycle; otherwise stop. Shuffle changes the order in which the next item is chosen.

Activity A3 — Full-screen controls

Enter full screen → Show video and floating controls → Wait for mouse input → Hide bar and cursor after inactivity → Show them again on movement. Esc, F or Exit Full Screen restores the normal view.

Sequence S1 — Play selected file

Step	Interaction
1	User selects a playlist item.
2	Main form retrieves the selected media path.
3	Main form sends a load request to libmpv.
4	libmpv reports playback and time information.
5	Main form updates the playlist selection and controls.

Sequence S2 — Advance at end of file

Step	Interaction
1	libmpv reports that the current file ended.
2	Application checks the end reason and active item.
3	Repeat and shuffle state determines the next item or Stop.
4	Application loads the selected item through libmpv.
5	The interface updates the active selection and playback state.

Diagram conventions

Use decision diamonds for mode checks in activity diagrams and lifelines for the user, main form, playback state and libmpv in sequence diagrams. Verify actual method names before labelling code-level messages.