Final Report: Video-Based People Counting (Project p29)

Computer Vision course project

Repository: https://github.com/NikolayTaran/cv_people_counting

Report date: 1 November 2026

1. Introduction / Brief Overview

The objective is to count people crossing a virtual line in both directions (IN and OUT) in video, including scenes with occlusion, dense crowds, and different camera viewpoints. The research question is: How reliably does a YOLO11 detector, ByteTrack-style multi-object tracker, and directional line counter transfer across these conditions, and do pedestrian fine-tuning or a two-detector ensemble improve counting enough to justify their tracking and computational costs?

We implemented an end-to-end pipeline: MOT17/MOT20 data loading and YOLO-format export; COCO-pretrained or pedestrian-fine-tuned YOLO11 person detection; custom two-stage ByteTrack association using an eight-dimensional Kalman filter, IoU cost, and Hungarian matching; bottom-centre track points with line hysteresis and cooldown; and evaluation of counting and tracking. MOT17-11 also uses camera-motion compensation. A second approach fuses detections from the fine-tuned and COCO-pretrained YOLO11s models before the same tracker and counter. The selected three-epoch checkpoint and both inference modes are available in the repository.

Detector training used the first 80% of MOT17-04 and MOT17-05: 1,510 images and 39,144 pedestrian boxes. The remaining 377 images and 11,397 boxes from those same two cameras formed chronological validation. Four additional sequences, MOT17-02, MOT20-01, MOT17-09, and MOT17-11, supplied 2,454 frames for configuration comparison. No frames from these four videos entered detector training. However, their scores influenced the choice of the three-epoch model and the ensemble.

> **All four-camera results in this report are preliminary post-selection comparisons, not an unbiased final test.**

2. Final Results

For each sequence, counting accuracy is CA = max(0, 1 - (|Pred_IN - GT_IN| + |Pred_OUT - GT_OUT|) / max(GT_IN + GT_OUT, 1)). Curve MAE is the mean absolute error of cumulative IN/OUT counts at 50-frame checkpoints. Ground-truth counting events are generated from annotated tracks with the same line geometry as predicted events. MOTA and IDF1 evaluate tracking. All aggregate metrics below are unweighted means over the same four comparison sequences; arrows indicate the preferred direction.

Tested approach	Mean CA ↑	Curve MAE ↓	MOTA ↑	IDF1 ↑
COCO YOLO11n	0.5501	2.5913	0.4361	0.4446
COCO YOLO11s	0.6222	1.9747	0.4352	0.4671
YOLO11s fine-tuned, 3 epochs	0.6548	1.7021	0.4113	0.4324
YOLO11s fine-tuned, 20 epochs	0.5794	2.1542	0.4080	0.4277
Two-detector ensemble	0.6654	1.7858	0.3989	0.4261

Scene-level CA shows why the aggregate ranking alone is insufficient:

Sequence and condition	COCO 11n	COCO 11s	3 epochs	20 epochs	Ensemble
MOT17-02, occlusion	0.4762	0.5238	0.5238	0.3810	0.5714
MOT20-01, dense crowd	0.3462	0.4231	0.3462	0.6154	0.5385
MOT17-09, low-angle view	0.7692	0.8462	0.9231	0.5385	0.7692
MOT17-11, moving view	0.6087	0.6957	0.8261	0.7826	0.7826

For the two approaches directly compared in matched runs, directional totals were as follows. These totals expose errors that a single average can hide.

Sequence	GT IN/OUT	3-epoch IN/OUT	Ensemble IN/OUT
MOT17-02	16 / 5	10 / 1	10 / 2
MOT20-01	21 / 5	7 / 2	10 / 6
MOT17-09	10 / 3	9 / 3	8 / 4
MOT17-11	11 / 12	9 / 10	7 / 11

3. Comparison

The three-epoch YOLO11s raises observed mean CA from 0.5501 for COCO YOLO11n to 0.6548 (+0.1047), while reducing Curve MAE to 1.7021. COCO YOLO11s is a stronger untrained detector than YOLO11n on these videos (CA 0.6222 versus 0.5501) and has the highest mean IDF1, 0.4671. The three-epoch checkpoint is best among single detectors for mean CA and for the two camera-view sequences, MOT17-09 and MOT17-11.

Longer fine-tuning is condition-dependent. The 20-epoch checkpoint improves validation mAP50-95 from 0.6781 to 0.7246 and achieves the best MOT20-01 CA, 0.6154, but its mean comparison CA is only 0.5794. On MOT17-09, CA falls from 0.9231 (three epochs) to 0.5385 (20 epochs). The two-camera training and validation distribution therefore does not predict the ranking on the other camera viewpoints. The result is consistent with view specialization, though these experiments do not isolate the exact mechanism.

The ensemble adds 0.0106 mean CA over the three-epoch single detector. It improves MOT20-01 by 0.1923 CA and MOT17-02 by 0.0476, but loses 0.1539 on MOT17-09 and 0.0435 on MOT17-11. Across the four videos, the ensemble reduces tracker misses from 26,801 to 23,491 and increases false positives from 5,812 to 9,076. Its mean MOTA falls from 0.4113 to 0.3989, and IDF1 falls from 0.4324 to 0.4261. Its Curve MAE also rises from 1.7021 to 1.7858. Thus a small improvement in final IN/OUT totals does not imply better track quality or more accurate counts throughout each video.

4. Runtime / Computational Measurements

The matched single-detector and ensemble runs processed the same 2,454 frames on an NVIDIA GeForce RTX 4060 Laptop GPU with video rendering disabled. The per-sequence wall times below are recorded in the run metadata, rather than estimated from rounded per-sequence FPS.

Sequence	Frames	Single detector, s	Ensemble, s	Single FPS	Ensemble FPS
MOT17-02	600	22.83	27.47	26.28	21.84
MOT20-01	429	16.40	20.21	26.16	21.23
MOT17-09	525	14.53	23.80	36.14	22.06
MOT17-11	900	71.66	93.14	12.56	9.66
Total / effective rate	2,454	125.42	164.62	19.57	14.91

The ensemble adds 39.20 seconds, approximately 31% of the single-detector time, for a 0.0106 gain in mean CA. The effective rate is about 19.6 versus 14.9 FPS over this particular mixture of sequences. MOT17-11 is substantially slower than the other scenes in both modes. These GPU, no-render timings are pipeline measurements, not a guaranteed deployment frame rate or isolated neural-network latency.

The Ultralytics training logs record a cumulative time value of 579.528 s at epoch 3 (about 9.7 minutes) and 3,031.73 s at epoch 20 (about 50.5 minutes). The 20-epoch run was interrupted by an OpenCV warpAffine error with Windows data-loader workers and resumed with workers=0; its logged value does not include the cost of the failed attempt. These figures are training-log measurements, not a controlled training-speed comparison.

5. Failure Analysis

The following are observed event-level discrepancies in the saved ensemble run, checked against counting events generated from ground-truth tracks. Nearby means within 12 frames of the cited event. Temporal proximity does not prove that two events belong to the same person; the causal explanations are hypotheses consistent with the logs and scenes, not verified annotations of every detector failure. The machine-readable audit is in reports/final_failure_cases.json. MOT ground-truth frames are 1-based and predicted frames are 0-based; the diagnostics align them before comparison.

Case (anchor)	Ground-truth events	Single detector	Ensemble
MOT20-01, GT frame 70	1 IN	No event	No event
MOT17-09, predicted frame 252	3 IN, 0 OUT	3 IN, 0 OUT	2 IN, 1 OUT
MOT17-11, GT frame 146	1 IN	No event	No event

The table counts events within the aligned 12-frame window around each cited frame. It describes local discrepancies, not person-level matches.

Case 1: missed IN under crowding (MOT20-01, frame 70). The ground-truth counter records an IN event for track 23 at frame 70. Neither the three-epoch single detector nor the ensemble produces a counting event within 12 frames. At scene level, the ensemble predicts 10 IN and 6 OUT versus 21 IN and 5 OUT in ground truth (CA 0.5385). The frame contains many overlapping pedestrians. At the crossing frame, the best saved ensemble track overlaps the ground-truth box by only 0.1135 IoU, below the 0.5 matching threshold. The missing event therefore coincides with a missing or poorly localized track. Occlusion could have disrupted detection or IoU-based association; because raw detector confidences were not saved, low confidence cannot be established for this person. The tracker has no appearance features to recover identity after a long overlap.

Case 2: spurious or directionally inconsistent OUT (MOT17-09, frame 252). The ensemble records an OUT for predicted track 58 at frame 252. The nearby ground-truth events at frames 242, 253, and 258 are all IN; there is no ground-truth OUT within 12 frames. The single-detector run records IN events near frames 243, 257, and 259 without this OUT. Across the video, ensemble totals are 8 IN / 4 OUT versus 10 IN / 3 OUT in ground truth, and CA falls from 0.9231 to 0.7692. Fusion increases false positives on this scene from 1,108 to 1,478. The saved box of track 58 best overlaps ground-truth person 11 at aligned GT frame 252 (IoU 0.8087), then person 12 at GT frame 254 (IoU 0.7721). Its foot point jumps from x=979.51 to x=946.33 across the manually placed line at x=960 as the OUT is emitted. This supports an apparent identity transfer between adjacent people, producing a false directional crossing. The saved tracker output cannot establish whether box fusion or association caused the transfer.




Figure 1. Track 58 changes its best-overlapping ground-truth person near the spurious OUT event on MOT17-09. Predicted frames are 0-based; aligned ground-truth frames are one greater.

Case 3: missed IN in a moving-camera view (MOT17-11, frame 146). Ground truth records an IN for track 77 at frame 146; neither approach emits a counting event within 12 frames. The ensemble finishes with 7 IN / 11 OUT versus 11 IN / 12 OUT in ground truth. Compared with the single detector, ensemble identity switches rise from 29 to 52 and false positives from 669 to 1,567 on this sequence. Camera-motion compensation is enabled, but the camera still moves and people overlap. At GT frame 146, the best saved ensemble track overlaps person 77 by only 0.1978 IoU, again below the 0.5 matching threshold. The immediate failure is a lack of a well-localized track at the line. Motion compensation, detection, and IoU-only association are possible contributors. The increased scene-level identity switches do not prove an ID switch for this specific person.

6. Discussion & Limitations

The implemented system counts directional crossings and yields its highest observed mean CA with the two-detector ensemble. Nevertheless, the gain over the three-epoch model is small and concentrated in crowded/occluded scenes; camera-view scenes, temporal count accuracy, tracking metrics, and runtime favor the single detector. The selected three-epoch YOLO11s remains the practical default in the repository. The ensemble is an optional experimental mode for density-sensitive use, not a validated universal upgrade.

The evaluation protocol limits every generalization claim. The four comparison sequences were excluded from detector training, but their scores were used to choose the three-epoch checkpoint and motivate and evaluate the ensemble. Reusing them to present the best observed CA as a final independent test would introduce selection bias. In addition, the 20% detector validation images are later frames from the same two training cameras, so validation mAP does not measure transfer to unseen views. The code calls the four-camera comparison split test; the terminology in this report reflects its actual role. A new camera-disjoint development set is needed for tuning, followed by a once-only evaluation on untouched cameras after all settings are frozen.

Other limits remain: the tracker has no ReID or appearance branch; line geometry and counting direction are manually specified for each camera; the dataset does not cover the planned aerial VisDrone experiment; and the runtime figures come from one laptop GPU and no-render runs. We have not measured end-to-end deployment latency with decoding, display, or multiple simultaneous streams. Per-event failure mechanisms are inferred from event logs and scene context rather than confirmed by manually annotated detector and association diagnostics. The relevant archived evidence is in reports/, while reproduction commands and code are in the repository.

7. Conclusion

The research question has a qualified answer. A YOLO11s detector fine-tuned for three epochs, followed by custom ByteTrack and a directional line counter, works across the four tested comparison scenes and achieves 0.6548 mean CA with the best Curve MAE (1.7021) among the five approaches. A two-detector ensemble reaches the highest observed mean CA, 0.6654, and substantially improves the crowded MOT20-01 scene, but worsens MOTA, IDF1, Curve MAE, and runtime and loses on two camera-view scenes. Longer fine-tuning improves validation mAP and the crowded scene but lowers mean comparison CA. Therefore, the operational pipeline and trained checkpoint are complete, but evidence of generalization is not: all reported CA values are preliminary post-selection comparisons until an untouched final test is performed.