

Ola Ride Booking Analysis

MySQL Queries | Database Setup, Data Import, Views & Validation

```
CREATE DATABASE ola;
USE ola;

CREATE TABLE bookings (
  `Date` DATE,
  `Time` TIME,
  Booking_ID VARCHAR(50),
  Booking_Status VARCHAR(50),
  Customer_ID VARCHAR(50),
  Vehicle_Type VARCHAR(50),
  Pickup_Location VARCHAR(100),
  Drop_Location VARCHAR(100),
  V_TAT INT NULL,
  C_TAT INT NULL,
  Canceled_Rides_by_Customer VARCHAR(100),
  Canceled_Rides_by_Driver VARCHAR(100),
  Incomplete_Rides VARCHAR(50),
  Incomplete_Rides_Reason VARCHAR(255),
  Booking_Value DECIMAL(10,2) NULL,
  Payment_Method VARCHAR(50),
  Ride_Distance DECIMAL(10,2) NULL,
  Driver_Ratings DECIMAL(3,2) NULL,
  Customer_Rating DECIMAL(3,2) NULL,
  `Vehicle Images` VARCHAR(255)
);

LOAD DATA LOCAL INFILE 'D:/Data Analytics Course/Project/Ola/Bookings.csv'
INTO TABLE bookings
FIELDS TERMINATED BY ','
ENCLOSED BY '"'
LINES TERMINATED BY '\n'
IGNORE 1 ROWS
(
  @DateTime,
  @Time,
  Booking_ID,
  Booking_Status,
  Customer_ID,
  Vehicle_Type,
  Pickup_Location,
  Drop_Location,
  @V_TAT,
  @C_TAT,
  Canceled_Rides_by_Customer,
  Canceled_Rides_by_Driver,
  Incomplete_Rides,
  Incomplete_Rides_Reason,
  @Booking_Value,
  Payment_Method,
  @Ride_Distance,
  @Driver_Ratings,
  @Customer_Rating,
  `Vehicle Images`
)
SET
  `Date` = CASE
    WHEN LOWER(TRIM(@DateTime)) = 'null' OR TRIM(@DateTime) = ''
    THEN NULL
    ELSE STR_TO_DATE(TRIM(@DateTime), '%d-%m-%Y %H:%i:%s')
  END,
  `Time` = CASE
    WHEN LOWER(TRIM(@Time)) = 'null' OR TRIM(@Time) = ''
    THEN NULL
    ELSE STR_TO_DATE(TRIM(@Time), '%H:%i:%s')
  END,
  V_TAT = NULLIF(NULLIF(TRIM(@V_TAT), ''), 'null'),
  C_TAT = NULLIF(NULLIF(TRIM(@C_TAT), ''), 'null'),
  Booking_Value = NULLIF(NULLIF(TRIM(@Booking_Value), ''), 'null'),
  Ride_Distance = NULLIF(NULLIF(TRIM(@Ride_Distance), ''), 'null'),
  Driver_Ratings = NULLIF(NULLIF(TRIM(@Driver_Ratings), ''), 'null'),
  Customer_Rating = NULLIF(NULLIF(TRIM(@Customer_Rating), ''), 'null');

CREATE VIEW Successful_Bookings AS
SELECT *
FROM bookings
```

```

WHERE Booking_Status = 'Success';

SELECT * FROM Successful_Bookings;

CREATE VIEW ride_distance_for_each_vehicle AS
SELECT Vehicle_Type, AVG(Ride_Distance) AS avg_distance
FROM bookings
GROUP BY Vehicle_Type;

SELECT * FROM ride_distance_for_each_vehicle;

CREATE VIEW canceled_rides_by_customers AS
SELECT COUNT(*) AS total_canceled_rides
FROM bookings
WHERE Booking_Status = 'Canceled by Customer';

SELECT * FROM canceled_rides_by_customers;

CREATE VIEW Top_5_Customers AS
SELECT Customer_ID, COUNT(Booking_ID) AS total_rides
FROM bookings
GROUP BY Customer_ID
ORDER BY total_rides DESC
LIMIT 5;

SELECT * FROM Top_5_Customers;

CREATE VIEW Canceled_Rides_by_Driver AS
SELECT COUNT(*) AS driver_cancellations_for_personal_car_issues
FROM bookings
WHERE Canceled_Rides_by_Driver = 'Personal & Car related issue';

SELECT * FROM Canceled_Rides_by_Driver;

CREATE VIEW MAX_MIN_Driver_Rating AS
SELECT
    MAX(Driver_Ratings) AS max_rating,
    MIN(Driver_Ratings) AS min_rating
FROM bookings
WHERE Vehicle_Type = 'Prime Sedan';

SELECT * FROM MAX_MIN_Driver_Rating;

CREATE VIEW UPI_Payment AS
SELECT *
FROM bookings
WHERE Payment_Method = 'UPI';

SELECT * FROM UPI_Payment;

CREATE VIEW AVG_Customer_Rating AS
SELECT Vehicle_Type, AVG(Customer_Rating) AS avg_customer_rating
FROM bookings
GROUP BY Vehicle_Type;

SELECT * FROM AVG_Customer_Rating;

CREATE VIEW total_successful_ride_value AS
SELECT SUM(Booking_Value) AS total_successful_ride_value
FROM bookings
WHERE Booking_Status = 'Success';

SELECT * FROM total_successful_ride_value;

CREATE VIEW Incomplete_Rides_Reason AS
SELECT Booking_ID, Incomplete_Rides_Reason
FROM bookings
WHERE Incomplete_Rides = 'Yes';

SELECT * FROM Incomplete_Rides_Reason;

SELECT COUNT(*) AS total_rows,
    COUNT(DISTINCT Booking_ID) AS unique_booking_ids
FROM bookings;

```