

Global alignment of the LHCb SciFi Tracker and Vertex Locator

Nils Breer, Biljana Mitreska, Sophie Hollitt, Johannes Albrecht

04.03.2024

DPG Conference, Karlsruhe


What is Alignment and why do we need it?



- Top: ideal detector, bottom: physical detector
- Surveys are used to find the rotation and position of each detector component
- → Starting positions for software alignment
- Building tracks accurately requires positions in reconstruction to be as similar as possible to real positions

Importance of alignments

- Alignment is part of the LHCb trigger system
- Physics performance tied to alignment performance
- with optimal alignment:
 - → remove systematic biases for asymmetry measurements
 - Best possible mass resolution




Alignment: track fits with the Kalman Filter

$$r_i = m_i - h_i(x, \alpha)$$

measurement m track model h


$$\chi^2 = r^T V^{-1} r$$

covariance matrix V




- Starting positions: positions from laser scans of detector objects (survey)
- Alignment: χ^2 minimization of track residuals
- Add measurements one-by-one to fit
- Prediction of next measurement → minimize residuals → redo until track complete
- Why Kalman Filter?
 - easily models material interactions as well as multiple scattering


LHCb upgraded with the SciFi



- 3 stations: T1, T2, T3
- 4 layers per station: X1, U, V, X2
- Replaces former IT and OT to cope with the increased instantaneous luminosity



The Scintillating Fibre Tracker



- Front two stations have 5 modules per side
- Back station has 6 modules on each side
- U, V layers have a $\mp 5^\circ$ stereo angle respectively
- → Used for determining y-position of tracks by comparing hitposition at different angles

Global alignment and motivation

Global alignment

- alignment of the velo and the scifi simultaneously
- Motivation for global alignment
 - understanding the interplay between tracking systems
 - rotations inside the VELO → weak modes inside SciFi (VELO twisting)

Configuration

First Longmodules then Halfmodules TxRxRz

Full VELO RxRz + VELO halves TxTyTz

VELO halves TxTyTz

CFrames to be able to absorb for the average movement

lagrange constraint in T2


VELO global rotation

rotation R_z leading to shifts in x and y

half alignment sensitive to x shift



global movement in y

can not be corrected for by half alignment





Comparison of SciFi only to global alignment

- zig-zag pattern still unknown origin
→ correlated with Tz shifting showing similar trend
- small improvement in comparison to SciFi only
→ layer movement has still issues from VELO rotation present in SciFi



Comparison of SciFi only to global alignment



Issues and possible solutions


- zig-zag pattern of stereo layers in Tx difficult to fix
→ similar pattern in Tz → cannot fix one without the other
- global VELO Rx might be overthrown by survey constraints acting on Rx → Rx not being picked up in the alignment
- Testing different survey uncertainties to study the impact on global VELO rotation
- Testing different settings in the alignment on stereo layers in Tx
make sure VELO Rx is being picked up in the alignment

Summary

- global alignment improving the position of the T-stations
- still unknown phenomena (zig-zag pattern, offset T2 position)
- survey constraints might counteract the global VELO Rx
- A lot more tests to do until data taking which look promising
- **Thank you for your attention!**

The survey: what is it and the different types

- Measure distance of some points on the detector with a laser



- Layer survey: find corners of layers
- Module survey: reflective stickers, calculate module plane
- Compare survey to simulation