Classical ML vs. Deep Learning for CVD Classification on NHANES 2011–2018: Experimental Results

All numbers below come from the scripts in this folder (run order `00` → `06`) and are reproducible with seed 42. Tables are in `results/tables/` (CSV and Markdown) and figures in `figures/` (300-dpi PNG and vector PDF). **7 models are compared: 4 classical ML (LR, RF, SVM, XGBoost) and 3 deep learning (MLP, ResNet, FT-Transformer).**

1. What was done (Methodology section material)

Data. Four NHANES cycles: 2011–2012 (G), 2013–2014 (H), 2015–2016 (I) and 2017–2018 (J), downloaded from the CDC. Files used: DEMO, BPX, BMX, MCQ, TCHOL, HDL, GHB, BIOPRO, SMQ and DIQ. BPQ was used only for the supplementary medication check. Every variable name was checked to exist with identical coding in all four cycles. 2019–2020 was excluded because COVID-19 interrupted its data collection.

Population. Adults aged ≥ 20 who completed the examination (RIDSTATR = 2) and had a determinable outcome.

Cycle	Participants	Examined adults ≥20	Outcome determined	CVD cases
2011–2012	9,756	5,319	5,302	550
2013–2014	10,175	5,588	5,572	574
2015–2016	9,971	5,474	5,448	598
2017–2018	9,254	5,265	5,230	647
Total	39,156	21,646	**21,552**	**2,369**

Outcome. CVD = 1 if the participant reported ever being told by a doctor they had congestive heart failure (MCQ160B), coronary heart disease (MCQ160C), angina (MCQ160D), heart attack (MCQ160E) or stroke (MCQ160F). CVD = 0 if "no" to all five. Anyone else was excluded (n = 94). Prevalence: 11.0% unweighted, 8.9% survey-weighted (MEC weight divided by 4).

Features (20). Age, sex, race/ethnicity (4 indicators; reference non-Hispanic White), income-to-poverty ratio, education, systolic and diastolic BP (mean of up to 3 readings), pulse rate, BMI, waist circumference, total cholesterol, HDL cholesterol, HbA1c, serum creatinine, uric acid, smoking status and diagnosed diabetes. Medication variables were **excluded** from the inputs, because treatment often follows a CVD diagnosis and would leak the label. The most missing feature was income-to-poverty ratio (9.8%).

Split and preprocessing. Stratified 80/20 split: training n = 17,241 (1,895 cases) and test n = 4,311 (474 cases). Median imputation and standardisation were fitted inside each pipeline on training folds only.

Models and tuning (5-fold stratified CV on the training set, objective ROC-AUC):

Model	Family	Search space	Selected
Logistic Regression (L2)	Classical	C in {1e-3 … 100}	C = 0.01
Random Forest (500 trees)	Classical	depth × min leaf × max_features (18 configurations)	depth 12, leaf 20, sqrt
SVM (RBF, Platt probabilities)	Classical	C × γ × class_weight (32 configurations)	C = 10, γ = 0.001, balanced
XGBoost	Classical	40-iteration random search (7 hyperparameters)	502 trees, depth 5, lr 0.0113
MLP	Deep	5 architectures × dropout × weight decay × lr (60 configurations)	64-32, dropout 0.5, wd 0.01, lr 1e-3
Tabular ResNet	Deep	width {64,128,256} × blocks {1,2,4} × dropout {0.1,0.3,0.5} × wd (54 configurations)	width 64, 4 blocks, dropout 0.5, wd 0.01
FT-Transformer	Deep	width {64,128} × blocks {2,3} × lr {1e-4,3e-4} (8 configurations)	width 64, 2 blocks, 8 heads, lr 3e-4

All three deep models (PyTorch) share one training loop: AdamW optimiser, binary cross-entropy loss, batch size 256, and early stopping on a 15% validation split (patience 15).

- **MLP:** Linear–BatchNorm–ReLU–Dropout blocks; 3,649 parameters.

- **ResNet** (Gorishniy et al., 2021): residual blocks of BN–Linear–ReLU–Dropout–Linear; 68,353 parameters.
- **FT-Transformer** (Gorishniy et al., 2021): a feature tokenizer, a [CLS] token, pre-norm Transformer blocks with multi-head self-attention and ReGLU feed-forward layers; 69,589 parameters.

For ResNet and FT-Transformer, the best configurations sit on a plateau: the top 8 ResNet configurations lie within 0.0016 CV-AUC of each other, and all 8 FT-Transformer configurations within 0.003. Both gaps are well below the CV standard deviation (about 0.006–0.009), so extending the grids would not change the results.

Decision threshold. For each model, the threshold maximising F1 on out-of-fold training predictions. The test set was never used for any choice.

Metrics. ROC-AUC (1,000-sample bootstrap 95% CI), PR-AUC, precision, recall, specificity, F1, Brier score, ECE (10 quantile bins), calibration slope and intercept, pairwise DeLong tests, survey-weighted test AUC, and tuning, fit, inference and SHAP time.

SHAP. The same model-agnostic method for all 7 models: permutation SHAP on the predicted probability, with 300 test rows, 50 background rows and 164 evaluations per row. Validated against exact TreeSHAP for XGBoost: ranking Spearman ρ = **0.989**.

Stability.

1. **Across models:** pairwise Spearman correlation of mean |SHAP|, top-5 Jaccard, and Kendall's W overall and within each family.
2. **Within each model:** 5 bootstrap refits of the training set, compared pairwise.

Ablation. Leave one feature group out (8 groups), retrain with the tuned settings, and average ΔAUC over 5 random splits. **Robustness:** full-model AUC over the same 5 splits. **Temporal validation:** train on 2011–2016 (n = 16,322), test on 2017–2018 (n = 5,230).

Compute. All tuning, final models and reported timings use the CPU. To save time, FT-Transformer's ablation, temporal and bootstrap refits ran on a GPU (RTX 3050). These analyses compare refits of the same model with each other, so the device is consistent within every comparison.

2. Results

Table 1: Survey-weighted characteristics (`table1_characteristics.md`)

CVD cases were older (65.0 vs 46.1 years), more often had diagnosed diabetes (33.0% vs 8.3%), and were more often former smokers (38.0% vs 23.1%). Notably, they had **lower** total cholesterol (177.5 vs 193.0 mg/dL) and lower diastolic BP (67.8 vs 71.3 mmHg); see §3.

Table 2: Test-set performance (n = 4,311; 474 cases)

Model	Family	CV AUC (SD)	Test AUC [95% CI]	PR-AUC	Precision	Recall	Specificity	F1	Brier	ECE	Cal. slope
Logistic Regression	Classical	0.846 (0.009)	0.839 [0.821–0.855]	0.392	0.383	0.561	0.888	0.455	0.080	0.010	1.04
Random Forest	Classical	0.847 (0.003)	0.839 [0.821–0.856]	0.407	0.361	0.586	0.872	0.447	0.080	0.010	1.16
SVM (RBF)	Classical	0.849 (0.007)	0.839 [0.821–0.854]	0.396	0.362	0.584	0.873	0.447	0.080	0.007	0.97
XGBoost	Classical	0.850 (0.005)	**0.848 [0.829–0.863]**	0.418	0.373	0.572	0.881	0.451	**0.078**	0.009	1.04
MLP	Deep	0.849 (0.007)	0.842 [0.825–0.858]	0.398	0.390	0.523	0.899	0.447	0.080	0.018	0.91
ResNet	Deep	0.849 (0.009)	0.837 [0.819–0.855]	0.402	0.377	0.527	0.892	0.439	0.080	0.021	0.87
FT-Transformer	Deep	0.850 (0.007)	0.843 [0.825–0.859]	**0.419**	0.371	0.586	0.877	0.455	0.079	0.012	0.99

Pairwise DeLong p-values (`table_delong_pairwise.md`):

	LR	RF	SVM	XGB	MLP	ResNet	FTT
LR	–	0.944	0.876	**0.005**	0.321	0.675	0.169

	LR	RF	SVM	XGB	MLP	ResNet	FTT
RF	0.944	–	1.000	**0.001**	0.460	0.643	0.239
SVM	0.876	1.000	–	**0.002**	0.274	0.547	0.161
XGB	**0.005**	**0.001**	**0.002**	–	0.064	**0.002**	0.075
MLP	0.321	0.460	0.274	0.064	–	**0.031**	0.682
ResNet	0.675	0.643	0.547	**0.002**	**0.031**	–	0.075
FTT	0.169	0.239	0.161	0.075	0.682	0.075	–

- The 7 models span only **0.011 AUC** (0.837–0.848).
- XGBoost had the highest AUC. **After Holm correction for the 21 pairwise comparisons** (`results/delong_pairwise_corrected.csv`), it remained significantly better than RF (adjusted p = 0.012), ResNet (0.036) and SVM (0.040). Its advantage over LR (unadjusted p = 0.005) did not survive correction (adjusted p = 0.095). It was not significantly better than the MLP or FT-Transformer (unadjusted p = 0.064 and 0.075; adjusted 1.000).
- **No deep model was significantly better than any classical model,** with or without correction. Wherever a deep model's AUC was higher than a classical model's (MLP and FT-Transformer vs LR, RF and SVM), unadjusted p ≥ 0.161.
- The MLP vs ResNet difference (unadjusted p = 0.031) did not survive correction (adjusted p = 0.525).
- All models were well calibrated (ECE ≤ 0.021). FT-Transformer had the slope closest to 1 (0.99). ResNet (0.87) and MLP (0.91) were slightly over-confident, and RF (1.16) slightly under-confident.
- Survey-weighted test AUC: 0.851–0.862, with XGBoost again highest.

Repeated splits (5 seeds, `repeated_split_auc.md`**):** mean AUC LR 0.842 ± 0.002, RF 0.841 ± 0.004, SVM 0.843 ± 0.003, **XGB 0.846 ± 0.004**, MLP 0.844 ± 0.003, ResNet 0.841 ± 0.005, FTT 0.845 ± 0.003. XGBoost is highest with FT-Transformer a close second, and all differences are within about one SD.

Temporal validation (train 2011–2016 → test 2017–2018, `temporal_validation.md`**):** AUC LR 0.838, RF 0.837, SVM 0.838, XGB 0.838, MLP 0.839, ResNet 0.840, FTT 0.837; Brier 0.088–0.089 for all. All 7 models converge to 0.837–0.840, so XGBoost's held-out advantage disappears.

Computational efficiency (`table_efficiency.md`)

Model	Parameters	Tuning (s)	Final fit (s)	Inference (ms / 1k rows)	SHAP, 300 rows (s)
LR	21	5	0.05	1.1	10
RF	500 trees	271	1.5	24.8	120
SVM	–	224	47.4	828	1,615
XGB	502 trees	49	0.6	2.9	10
MLP	3,649	352	9.0	1.2	5
ResNet	68,353	913	22.3	8.8	198
FT-Transformer	69,589	**5,779**	**275.6**	351	1,300

These are wall-clock times on a 12-core CPU, with tuning run in parallel. FT-Transformer took 119× longer to tune than XGBoost and about 445× longer to fit (5,000× longer than LR), with no significant accuracy gain.

Figure 2 / Table 3: SHAP importance and stability

- **Age was the #1 feature for all 7 models.** Total cholesterol, smoking, diagnosed diabetes and income-to-poverty ratio complete the top 5 for LR, SVM and all three deep models. RF and XGB bring serum creatinine into the top 5.
- Overall concordance across all 7 models: **Kendall's W = 0.752.**
- **The deep models agree with each other more closely than the classical models do:** Kendall's W = **0.921** among the 3 deep models vs **0.742** among the 4 classical models. The mean pairwise Spearman ρ is 0.882 within the deep family, 0.657 within the classical family and 0.694 between families.
- **Agreement reflects the shape of the decision function, not the classical/deep label.** The tree ensembles agree tightly with each other (RF–XGB ρ = 0.941) and less with everything else. The smooth-function models form a second cluster: ResNet–FTT 0.935, SVM–MLP 0.886, MLP–ResNet 0.863, MLP–FTT 0.848, LR–MLP

0.743. The pairs least in agreement mix trees with smooth models (LR–RF 0.474).

- **Within-model stability (bootstrap refits):** RF ρ = 0.973, XGB 0.921, LR 0.846, MLP 0.805, ResNet 0.804, FTT 0.761, SVM 0.732.
- Tree models give the most stable full rankings.
- MLP and SVM keep a perfectly stable top 5 (Jaccard 1.00).
- FT-Transformer is the least stable (top-5 Jaccard 0.61).
- Tree models give more weight to continuous laboratory and physiological measures (creatinine, HbA1c, systolic BP). The smooth models give more weight to demographics and smoking.

Figure 4 / Table 4: Leave-one-group-out ablation (ΔAUC, mean ± SD over 5 splits)

- **Removing demographics** caused the largest drop for every model (−0.037 to −0.063), largest for LR (−0.063).
- Lipid, glycaemic, socioeconomic, renal/metabolic and smoking groups each cost 0.001–0.007 AUC.
- **Anthropometric and blood-pressure groups contributed almost nothing** (|ΔAUC| ≤ 0.003 for every model). ResNet's small positive values (+0.003 ± 0.003 and +0.002 ± 0.001) are within noise.
- The ordering of groups is nearly identical across all 7 models, which agrees with SHAP at the group level.

Figures




Figure 1. (a) ROC curves on the held-out test set (n = 4,311), AUC in the legend. (b) Calibration by decile of predicted risk.




Figure 2. Mean |SHAP| per model, scaled to each model's top feature; numbers are within-model ranks.




Figure 3. SHAP beeswarm for XGBoost (best model). Each dot is one test participant; grey dots are missing values.




Figure 4. Change in test AUC (× 100) when each feature group is removed, mean of 5 random splits.

3. Discussion points (non-causal)

1. **Deep learning gave no measurable advantage.** Neither the MLP nor the two architectures designed for tabular data (ResNet and FT-Transformer) significantly outperformed any classical model. This is consistent with benchmarks showing that tree ensembles match or beat deep models on medium-sized tabular data. Under temporal validation, all 7 models converge to an AUC of about 0.84.
2. **Simplicity is competitive.** LR came within 0.009 AUC of the best model, was well calibrated, and was more than 5,000× cheaper to train than FT-Transformer.
3. **Attribution agreement depends on the shape of the decision function.** Models with similar AUC distribute credit differently. Tree ensembles form one cluster and smooth-function models (LR, SVM and all three deep models) another. The three deep models explain their predictions almost identically (W = 0.92). SHAP from a single model gives an incomplete picture.
4. **Reverse causation from treatment (important caveat).** In every model, SHAP shows *higher* total cholesterol associated with *lower* predicted CVD probability. This is explained by treatment after diagnosis (`06_medication_check.py`): weighted statin use was 58.0% among CVD cases vs 14.2% among non-cases, and among statin users mean cholesterol was 166.4 mg/dL (CVD) vs 183.0 (no CVD). Similarly, 62.8% of cases vs 20.1% of non-cases take BP medication, which likely explains why blood pressure added almost no AUC. Because the outcome is **prevalent, self-reported** CVD measured cross-sectionally, the models partly learn markers of *having been diagnosed and treated*, not *risk of developing* CVD. The attributions describe predictive association only.
5. **Limitations.**

- The outcome is cross-sectional and self-reported (recall bias; prevalent, not incident).
- Age is top-coded at 80.
- Survey weights were used for descriptive statistics and a weighted-AUC check, not in model training.
- Permutation SHAP is approximate (validated at ρ = 0.989 against exact TreeSHAP).
- Some selected deep-learning hyperparameters lie at the edges of their grids, but the CV surfaces are flat there (see Methodology).
- FT-Transformer refits for ablation and stability ran on a GPU.

4. Results-based abstract (about 190 words)

Cardiovascular disease (CVD) is a leading cause of death, yet it remains unclear whether deep learning improves CVD classification over classical machine learning on structured clinical data. Using four cycles of the U.S. National Health and Nutrition Examination Survey (NHANES 2011–2018; n = 21,552 adults, 2,369 with CVD), we compared four classical models (Logistic Regression, Random Forest, Support Vector Machine, XGBoost) with three deep learning models (multilayer perceptron, tabular ResNet, FT-Transformer) using 20 demographic, clinical and laboratory features. Models were evaluated for discrimination (ROC-AUC, PR-AUC, DeLong test), calibration (Brier score, expected calibration error) and computational cost, and interpreted with SHAP. All models performed similarly (ROC-AUC 0.837–0.848). XGBoost achieved the highest AUC, and no deep learning model significantly outperformed any classical model, although the FT-Transformer required 119 times longer tuning than XGBoost. Age was the most influential feature for every model. Feature rankings were broadly concordant (Kendall's W = 0.75) but clustered by the shape of the decision function, with the deep models agreeing closely with each other (W = 0.92). Inverse attributions for cholesterol reflected treatment after diagnosis, indicating association rather than causation. For structured health survey data, deep learning offered no measurable advantage over classical machine learning.

5. Files

Script	Purpose
`00_download_nhanes.py`	Download the NHANES files from the CDC
`01_build_dataset.py`	Merge and harmonise 4 cycles → `data/nhanes_cvd_2011_2018.csv`, `data/cohort_flow.csv`

Script	Purpose
`common.py`	Features, pipelines, PyTorch MLP/ResNet/FT-Transformer, metrics, DeLong test, bootstrap
`02_train_evaluate.py`	Tuning, OOF thresholds, test metrics, pairwise DeLong → `results/`, `models/`
`03_shap_stability.py`	SHAP for 7 models, TreeSHAP check, cross-model and within-model stability
`04_ablation_robustness.py`	Group ablation, repeated splits, temporal validation
`05_figures_tables.py`	Figures 1–4 and all tables
`06_medication_check.py`	Supplementary statin / BP-medication check

Figures: `fig1_roc_calibration` (ROC and calibration), `fig2_shap_importance_heatmap`, `fig3_shap_beeswarm_XGB`, `fig4_ablation`.

References for the paper (IEEE style)

Numbered in the order they would first be cited (Introduction → Related Work → Methodology → Discussion), as IEEE requires. Each entry was checked against Crossref or the publisher/PubMed Central page in October 2026. DOIs are given wherever one exists. Entries marked † are conference/JMLR papers that have no DOI; they were checked against the proceedings or journal page.

A 6-page IEEE paper usually has 20–30 references. The **core set** (*) is 25 entries and fits about 0.9 page. The rest are optional extras.

A. Introduction: CVD burden and clinical risk scores

* [1] C. W. Tsao, A. W. Aday, Z. I. Almarzooq, *et al.*, "Heart disease and stroke statistics—2023 update: A report from the American Heart Association," *Circulation*, vol. 147, no. 8, pp. e93–e621, 2023, doi: 10.1161/CIR.0000000000001123.

* [2] G. A. Roth, G. A. Mensah, C. O. Johnson, *et al.*, "Global burden of cardiovascular diseases and risk factors, 1990–2019: Update from the GBD 2019 study," *J. Am. Coll. Cardiol.*, vol. 76, no. 25, pp. 2982–3021, 2020, doi: 10.1016/j.jacc.2020.11.010.

* [3] R. B. D'Agostino Sr., R. S. Vasan, M. J. Pencina, *et al.*, "General cardiovascular risk profile for use in primary care: The Framingham Heart Study," *Circulation*, vol. 117, no. 6, pp. 743–753, 2008, doi: 10.1161/CIRCULATIONAHA.107.699579.

* [4] D. C. Goff Jr., D. M. Lloyd-Jones, G. Bennett, *et al.*, "2013 ACC/AHA guideline on the assessment of cardiovascular risk: A report of the American College of Cardiology/American Heart Association Task Force on Practice Guidelines," *Circulation*, vol. 129, no. 25, suppl. 2, pp. S49–S73, 2014, doi: 10.1161/01.cir.0000437741.48606.98.

[5] J. Hippisley-Cox, C. Coupland, and P. Brindle, "Development and validation of QRISK3 risk prediction algorithms to estimate future risk of cardiovascular disease: Prospective cohort study," *BMJ*, vol. 357, p. j2099, 2017, doi: 10.1136/bmj.j2099.

B. Related Work: machine learning for CVD

* [6] S. F. Weng, J. Reps, J. Kai, J. M. Garibaldi, and N. Qureshi, "Can machine-learning improve cardiovascular risk prediction using routine clinical data?," *PLoS ONE*, vol. 12, no. 4, p. e0174944, 2017, doi: 10.1371/journal.pone.0174944.

* [7] A. M. Alaa, T. Bolton, E. Di Angelantonio, J. H. F. Rudd, and M. van der Schaar, "Cardiovascular disease risk prediction using automated machine learning: A prospective study of 423,604 UK Biobank participants," *PLoS ONE*, vol. 14, no. 5, p. e0213653, 2019, doi: 10.1371/journal.pone.0213653.

* [8] B. Ambale-Venkatesh, X. Yang, C. O. Wu, *et al.*, "Cardiovascular event prediction by machine learning: The Multi-Ethnic Study of Atherosclerosis," *Circ. Res.*, vol. 121, no. 9, pp. 1092–1101, 2017, doi: 10.1161/CIRCRESAHA.117.311312.

* [9] C. Krittanawong, H. U. H. Virk, S. Bangalore, *et al.*, "Machine learning prediction in cardiovascular diseases: A meta-analysis," *Sci. Rep.*, vol. 10, no. 1, p. 16057, 2020, doi: 10.1038/s41598-020-72685-1.

[10] S. Mohan, C. Thirumalai, and G. Srivastava, "Effective heart disease prediction using hybrid machine learning techniques," *IEEE Access*, vol. 7, pp. 81542–81554, 2019, doi: 10.1109/ACCESS.2019.2923707.

NHANES-based studies (closest to this paper)

* [11] A. Dinh, S. Miertschin, A. Young, and S. D. Mohanty, "A data-driven approach to predicting diabetes and cardiovascular disease with machine learning," *BMC Med. Inform. Decis. Mak.*, vol. 19, no. 1, p. 211, 2019, doi: 10.1186/s12911-019-0918-5.

* [12] A. Martin-Morales, M. Yamamoto, M. Inoue, T. Vu, R. Dawadi, and M. Araki, "Predicting cardiovascular disease mortality: Leveraging machine learning for comprehensive assessment of health and nutrition variables," *Nutrients*, vol. 15, no. 18, p. 3937, 2023, doi: 10.3390/nu15183937.

* [13] M. Ahiduzzaman and M. N. Hasan, "Interpretable machine learning for cardiovascular risk prediction: Insights from NHANES dietary and health data," *PLoS ONE*, vol. 20, no. 11, p. e0335915, 2025, doi: 10.1371/journal.pone.0335915.

Classical ML vs. deep learning on tabular / clinical data

* [14] E. Christodoulou, J. Ma, G. S. Collins, E. W. Steyerberg, J. Y. Verbakel, and B. Van Calster, "A systematic review shows no performance benefit of machine learning over logistic regression for clinical prediction models," *J. Clin. Epidemiol.*, vol. 110, pp. 12–22, 2019, doi: 10.1016/j.jclinepi.2019.02.004.

* [15] L. Grinsztajn, E. Oyallon, and G. Varoquaux, "Why do tree-based models still outperform deep learning on typical tabular data?," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 35, 2022, pp. 507–520.

* [16] R. Shwartz-Ziv and A. Armon, "Tabular data: Deep learning is not all you need," *Inf. Fusion*, vol. 81, pp. 84–90, 2022, doi: 10.1016/j.inffus.2021.11.011.

[17] V. Borisov, T. Leemann, K. Seßler, J. Haug, M. Pawelczyk, and G. Kasneci, "Deep neural networks and tabular data: A survey," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 35, no. 6, pp. 7499–7519, 2024, doi: 10.1109/TNNLS.2022.3229161.

Explainability in healthcare

* [18] C. Rudin, "Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead," *Nat. Mach. Intell.*, vol. 1, no. 5, pp. 206–215, 2019, doi: 10.1038/s42256-019-0048-x.

[19] G. Stiglic, P. Kocbek, N. Fijacko, M. Zitnik, K. Verbert, and L. Cilar, "Interpretability of machine learning-based prediction models in healthcare," *WIREs Data Min. Knowl. Discov.*, vol. 10, no. 5, p. e1379, 2020, doi: 10.1002/widm.1379.

* [20] S. Krishna, T. Han, A. Gu, S. Wu, S. Jabbari, and H. Lakkaraju, "The disagreement problem in explainable machine learning: A practitioner's perspective," *Trans. Mach. Learn. Res.*, 2024. [Online]. Available: arXiv:2202.01602 †

C. Methodology: data, models, tools

* [21] Centers for Disease Control and Prevention, National Center for Health Statistics, "National Health and Nutrition Examination Survey data, 2011–2018," Hyattsville, MD, USA: U.S. Dept. of Health and Human Services. [Online]. Available: https://wwwn.cdc.gov/nchs/nhanes/

* [22] C. L. Johnson, R. Paulose-Ram, C. L. Ogden, *et al.*, "National Health and Nutrition Examination Survey: Analytic guidelines, 1999–2010," *Vital Health Stat. 2*, no. 161, pp. 1–24, 2013. (Source for combining cycles and dividing the weights by the number of cycles.)

* [23] L. Breiman, "Random forests," *Mach. Learn.*, vol. 45, no. 1, pp. 5–32, 2001, doi: 10.1023/A:1010933404324.

* [24] C. Cortes and V. Vapnik, "Support-vector networks," *Mach. Learn.*, vol. 20, no. 3, pp. 273–297, 1995, doi: 10.1007/BF00994018.

[25] J. C. Platt, "Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods," in *Advances in Large Margin Classifiers*, A. J. Smola *et al.*, Eds. Cambridge, MA, USA: MIT Press, 1999, pp. 61–74. †

* [26] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2016, pp. 785–794, doi: 10.1145/2939672.2939785.

* [45] Y. Gorishniy, I. Rubachev, V. Khrulkov, and A. Babenko, "Revisiting deep learning models for tabular data," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 34, 2021, pp. 18932–18943. † (Source of the ResNet and FT-Transformer models; numbered 45 because it was added last)

[27] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: A simple way to prevent neural networks from overfitting," *J. Mach. Learn. Res.*, vol. 15, no. 56, pp. 1929–1958, 2014. †

[28] S. Ioffe and C. Szegedy, "Batch normalization: Accelerating deep network training by reducing internal covariate shift," in *Proc. 32nd Int. Conf. Mach. Learn. (ICML)*, PMLR vol. 37, 2015, pp. 448–456. †

[29] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019. † (AdamW optimiser)

[30] J. Bergstra and Y. Bengio, "Random search for hyper-parameter optimization," *J. Mach. Learn. Res.*, vol. 13, pp. 281–305, 2012. † (XGBoost random search)

* [31] F. Pedregosa, G. Varoquaux, A. Gramfort, *et al.*, "Scikit-learn: Machine learning in Python," *J. Mach. Learn. Res.*, vol. 12, pp. 2825–2830, 2011. †

[32] A. Paszke, S. Gross, F. Massa, *et al.*, "PyTorch: An imperative style, high-performance deep learning library," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 32, 2019, pp. 8024–8035. †

Evaluation metrics and statistics

* [33] E. R. DeLong, D. M. DeLong, and D. L. Clarke-Pearson, "Comparing the areas under two or more correlated receiver operating characteristic curves: A nonparametric approach," *Biometrics*, vol. 44, no. 3, pp. 837–845, 1988, doi: 10.2307/2531595.

[34] X. Sun and W. Xu, "Fast implementation of DeLong's algorithm for comparing the areas under correlated receiver operating characteristic curves," *IEEE Signal Process. Lett.*, vol. 21, no. 11, pp. 1389–1393, 2014, doi: 10.1109/LSP.2014.2337313. (The DeLong implementation used in the code)

[35] T. Saito and M. Rehmsmeier, "The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets," *PLoS ONE*, vol. 10, no. 3, p. e0118432, 2015, doi: 10.1371/journal.pone.0118432. (Justifies reporting PR-AUC at 11% prevalence)

[36] G. W. Brier, "Verification of forecasts expressed in terms of probability," *Mon. Weather Rev.*, vol. 78, no. 1, pp. 1–3, 1950, doi: 10.1175/1520-0493(1950)078<0001:VOFEIT>2.0.CO;2.

[37] M. P. Naeini, G. Cooper, and M. Hauskrecht, "Obtaining well calibrated probabilities using Bayesian binning," in *Proc. AAAI Conf. Artif. Intell.*, vol. 29, no. 1, 2015, doi: 10.1609/aaai.v29i1.9602. (ECE)

* [38] B. Van Calster, D. J. McLernon, M. van Smeden, L. Wynants, and E. W. Steyerberg, "Calibration: The Achilles heel of predictive analytics," *BMC Med.*, vol. 17, no. 1, p. 230, 2019, doi: 10.1186/s12916-019-1466-7. (Calibration slope and intercept)

SHAP and stability

* [39] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017, pp. 4765–4774. †

* [40] S. M. Lundberg, G. Erion, H. Chen, *et al.*, "From local explanations to global understanding with explainable AI for trees," *Nat. Mach. Intell.*, vol. 2, no. 1, pp. 56–67, 2020, doi: 10.1038/s42256-019-0138-9. (TreeSHAP, used for the validation check)

[41] M. G. Kendall and B. Babington Smith, "The problem of m rankings," *Ann. Math. Statist.*, vol. 10, no. 3, pp. 275–287, 1939, doi: 10.1214/aoms/1177732186. (Kendall's W)

[42] G. Hooker, L. Mentch, and S. Zhou, "Unrestricted permutation forces extrapolation: Variable importance requires at least one more model, or there is no free variable importance," *Stat. Comput.*, vol. 31, no. 6, p. 82, 2021, doi: 10.1007/s11222-021-10057-z. (Limitation of permutation-based attributions with correlated features)

D. Discussion: reporting standards

* [43] G. S. Collins, K. G. M. Moons, P. Dhiman, *et al.*, "TRIPOD+AI statement: Updated guidance for reporting clinical prediction models that use regression or machine learning methods," *BMJ*, vol. 385, p. e078378, 2024, doi: 10.1136/bmj-2023-078378.

[44] E. W. Steyerberg and Y. Vergouwe, "Towards better clinical prediction models: Seven steps for development and an ABCD for validation," *Eur. Heart J.*, vol. 35, no. 29, pp. 1925–1931, 2014, doi: 10.1093/eurheartj/ehu207.

> Cite TRIPOD+AI [43], not the 2015 TRIPOD statement. TRIPOD+AI officially replaces it, and reviewers check this.

Related Work summary table (for Section II)

Your outline asks Related Work to compare 5–8 studies and say what they did not evaluate. This table does that.

Study	Data	Models	Explainability	What it did not do (gap this paper fills)
Weng *et al.* 2017 [6]	UK CPRD, 378k patients	LR, RF, GBM, NN vs ACC/AHA score	none	No SHAP; no calibration comparison; no attribution agreement across models
Ambale-Venkatesh *et al.* 2017 [8]	MESA, 6.8k	Random survival forest vs Cox	variable importance from one model	One model family; no deep learning comparison
Alaa *et al.* 2019 [7]	UK Biobank, 423k	AutoML ensemble vs Framingham	AutoML variable ranking	No head-to-head classical vs MLP; no explanation stability analysis
Dinh *et al.* 2019 [11]	NHANES 1999–2014	LR, SVM, RF, gradient boosting, ensemble	feature importance	No MLP; no calibration analysis; no cross-model attribution agreement
Krittanawong *et al.* 2020 [9]	meta-analysis	many	n/a	Pooled AUCs only; heterogeneous outcomes and no shared evaluation
Martin-Morales *et al.* 2023 [12]	NHANES 2003–2012, CVD death	LR, SVM, RF, XGB, LightGBM	SHAP	No deep learning; no attribution agreement across models; undersampled data
Ahiduzzaman & Hasan 2025 [13]	NHANES 2017–2023	LR, RF, SVM, XGB, LightGBM	SHAP + LIME	No MLP; no attribution stability across or within models
Christodoulou *et al.* 2019 [14]	systematic review, 71 studies	ML vs LR	n/a	Shows ML ≈ LR in clinical data; motivates this comparison

Gap statement you can use: previous NHANES CVD studies compared classical models or reported SHAP for one model. None (a) compared classical models with a tuned MLP under the same pipeline, (b) measured whether SHAP attributions agree across model families and stay stable across refits, or (c) checked calibration and temporal validity together.

Where to cite what

- **Intro, paragraph 1 (burden):** [1], [2]
- **Intro (risk scores, nonlinearity):** [3], [4], [5]
- **Intro (DL not guaranteed better on tabular data):** [14]–[16]
- **Intro (explainability, attribution ≠ causation):** [18], [39]
- **Methods, data:** [21], [22]
- **Methods, models:** LR + [31]; RF [23]; SVM [24], [25]; XGB [26]; MLP [27]–[29], [32]; tuning [30], [31]
- **Methods, metrics:** [33]–[38]
- **Methods, SHAP:** [39], [40]; Kendall's W [41]
- **Discussion (performance parity):** [14]–[17]
- **Discussion (family-dependent attributions):** [20], [42]
- **Discussion (calibration and reporting):** [38], [43], [44]