

where the transaction log record can be used to recover all the committed data up to the point of the crash.

6) When does checkpoint occur in DBMS?

A checkpoint is like a snapshot of the DBMS state. Using checkpoints, the DBMS can reduce the amount of work to be done during a restart in the event of subsequent crashes. Checkpoints are used for the recovery of the database after the system crash. Checkpoints are used in the log-based recovery system. When due to a system crash we need to restart the system then at that point we use checkpoints. So that, we don't have to perform the transactions from the very starting.

7) What do you mean by transparent DBMS?

The transparent DBMS is a type of DBMS which keeps its physical structure hidden from users. Physical structure or physical storage structure implies to the memory manager of the DBMS, and it describes how the data stored on disk.

8) What are the unary operations in Relational Algebra?

PROJECTION and SELECTION are the unary operations in relational algebra. Unary operations are those operations which use single operands. Unary operations are SELECTION, PROJECTION, and RENAME.

As in SELECTION relational operators are used for example - =, <=, >=, etc.

9) What is RDBMS?

RDBMS stands for Relational Database Management Systems. It is used to maintain the data records and indices in tables. RDBMS is the form of DBMS which uses the structure to identify and access data concerning the other piece of data in the database. RDBMS is the system that enables you to perform different operations such as- update, insert, delete, manipulate and administer a