

Main chapter ko section-by-section simplify kar raha hoon, saath mein confusing points jaise var/let/const, equality, modules aur classes ko practical examples se clear karunga. #

Chapter 2: Surveying JS — Complete Hinglish Explanation

Is chapter ka goal JavaScript ki har syntax detail sikhana nahi hai. Yeh chapter JavaScript ke important areas ka **overview** deta hai, taaki tum language ki nature samajhkar confidently programs likhna start kar sako.

Author ka main message hai:

JavaScript seekhne ka best tareeka hai JavaScript code likhna, examples ko modify karna aur unke behavior ko observe karna.

Yeh chapter kaafi dense hai, isliye ise ek baar jaldi-jaldi padhne ke bajay sections mein divide karke practice karna better hoga.

1. Each File Is a Program

Normally kisi web application mein multiple JavaScript files hoti hain:

```
1 header.js
2 login.js
3 products.js
4 cart.js
5 payment.js
```

Hume application ek single program lagti hai, lekin JavaScript ke perspective se:

Har standalone .js file apna alag program hoti hai.

Yeh important kyun hai?

Maan lo application mein teen files load ho rahi hain:

Agar products.js mein error aa jaye, toh zaroori nahi ki header.js aur cart.js process hi na hon. Har file ko JavaScript separately parse aur execute kar sakti hai.

Lekin practical application mein files ek-doesre par depend kar sakti hain. Isliye ek file fail hone par poori application ka kuch part broken ho sakta hai.

Files milkar ek application kaise banati hain?

Traditional standalone JavaScript files **global scope** ke through state aur functions share kar sakti hain.

Example:

```
1 // user.js
2 var currentUser = "Ruth";

1 // greeting.js
2 console.log(`Hello, ${currentUser}`);
```

Agar files correct order mein load hui hain, toh greeting.js, user.js ke global variable ko access kar sakti hai.

Problem yeh hai ki bahut saari files global scope use karenge toh variable-name collision ho sakta hai.

```
1 // file-1.js
2 var user = "Ruth";
3
4 // file-2.js
5 var user = "Kyle";
```

Dono same global variable ko affect kar sakti hain.

Build tools kya karte hain?

Kayi projects build tools use karke multiple files ko combine karke ek final file bana dete hain:

```
1 file1.js + file2.js + file3.js
2           ↓
3           bundle.js
```

JavaScript ke liye ab bundle.js ek single program hoga.

ES Modules

ES6 ke baad JavaScript mein native modules aaye.

Agar file ko import ke through ya is tarah load kiya jaye:

toh woh file normal global-script ke bajay **module** treat hoti hai.

Har module bhi ek separate mini-program ki tarah hota hai, lekin modules import aur export ke through cooperate karte hain.

```
1 // math.js
2 export function add(a, b) {
3     return a + b;
4 }

1 // main.js
2 import { add } from "./math.js";
3
4 console.log(add(2, 3));
```

Main takeaway

Chahе tum:

- normal script files use karo,
- bundled files use karo,
- ya ES modules use karo,

har source file ko ek **small independent program** samjho jo baaki programs ke saath cooperate kar sakta hai.

2. Values

Program mein information ki sabse basic unit ko **value** kehte hain.

Values program ka data aur state represent karti hain.

JavaScript mein values do major categories mein aati hain:

1. **Primitive values**
 2. **Object values**
-

2.1 Primitive Values

Primitive values basic, non-object values hoti hain.

Chapter mein following primitive types discuss kiye gaye hain:

- string
 - number
 - boolean
 - undefined
 - null
 - symbol
 - bigint
-

String

String characters ka ordered collection hoti hai, jo usually text represent karti hai.

```
1 "My name is Kyle."
```

Yeh ek **string literal** hai.

String likhne ke teen common methods hain:

```
1 "Hello"
2 'Hello'
3 `Hello`
```

Double quotes aur single quotes mein mostly stylistic difference hai.

```
1 const firstName = "Kyle";
```

Important hai ki project mein ek consistent style follow ki jaye.

Template Literals and Interpolation

Backticks ka special purpose hota hai.

```
1 const firstName = "Kyle";
2
3 console.log(`My name is ${firstName}.`);
```

Output:

```
1 My name is Kyle.
```

`${...}` ke andar JavaScript expression evaluate hoti hai. Isse **interpolation** kehte hain.

Normal quotes mein interpolation nahi hoti:

```
1 console.log("My name is ${firstName}.");
```

Output literally yahi hoga:

```
1 My name is ${firstName}.
```

Author ki recommendation

- Normal strings ke liye ' ya " use karo.
- Jab interpolation chahiye tab backticks use karo.

Example:

```
1 const message = "Welcome";
2 const personalizedMessage = `Welcome, ${firstName}`;
```

Boolean

Boolean ke sirf do values hoti hain:

```
1 true
2 false
```

Boolean mostly decisions aur conditions mein use hota hai.

```
1 let isLoggedIn = true;
2
3 if (isLoggedIn) {
4     console.log("Welcome!");
5 }
```

Chapter ka example:

```
1 while (false) {
2     console.log("Hello");
3 }
```

Loop ek baar bhi run nahi hoga, kyunki condition shuru se false hai.

Agar condition permanently true ho:

```
1 while (true) {
2     console.log("Hello");
3 }
```

toh infinite loop ban sakta hai.

Number

JavaScript mein regular numeric values ka type number hota hai.

```
1 42
2 3.141592
3 -10
```

PI ke liye manually approximate value likhne ke bajay predefined value use ki ja sakti hai:

```
1 Math.PI
```

Numbers commonly use hote hain:

- calculations mein
 - counters mein
 - loop iterations mein
 - array positions access karne mein
-

Array Indexing

JavaScript arrays **zero-indexed** hoti hain.

```
1 const names = ["Frank", "Kyle", "Peter"];
```

Positions:

```
1 "Frank" → index 0
2 "Kyle" → index 1
3 "Peter" → index 2
```

Isliye:

```
1 console.log(names[1]);
```

Output:

```
1 Kyle
```

Second element ka index 1 hota hai, 2 nahi.

BigInt

bigint bahut bade integers store karne ke liye use hota hai, especially jab value regular number ki reliably supported integer range se bahar ho.

Chapter mein iska sirf introductory mention hai.

null and undefined

Dono generally value ki absence ya emptiness indicate karte hain.

```
1 let selectedUser = undefined;
2 let response = null;
```

Inke beech historical aur technical differences hain, lekin chapter ka author recommend karta hai ki possible ho toh emptiness ke liye primarily undefined use karo.

Example:

```
1 while (value !== undefined) {
2     console.log("Still got something!");
3 }
```

Yahan !== coercive comparison hai. Is particular comparison mein null aur undefined dono empty values ki tarah match ho jate hain.

```
1 null !== undefined; // false
2 undefined !== undefined; // false
```

Matlab loop tab rukega jab value, null ya undefined ho.

Symbol

Symbol ek special primitive value hai jo unique aur unguessable hoti hai.

```
1 const secretKey = Symbol("meaning of life");
```

Symbol ko object key ki tarah use kiya ja sakta hai:

```
1 const guide = {  
2     42  
3 };  
4  
5 console.log(guide[secretKey]);
```

Symbols normal application code mein frequently nahi dikhte. Yeh libraries, frameworks aur low-level mechanisms mein zyada mil sakte hain.

3. Arrays and Objects

Primitive ke alawa doosri main value category **object** hai.

Arrays

Array ordered collection hoti hai:

```
1 var names = ["Frank", "Kyle", "Peter", "Susan"];
```

Array ki length:

```
1 names.length;  
2 // 4
```

Elements access karna:

```
1 names[0];  
2 // "Frank"  
3  
4 names[1];  
5 // "Kyle"
```

Array kisi bhi type ki values hold kar sakti hai:

```
1 const values = [  
2     "Ruth",  
3     25,  
4     true,  
5     { city: "Delhi" },  
6     [1, 2, 3]  
7 ];
```

Ismein primitives, objects aur nested arrays sab ho sakte hain.

Objects

Object unordered, keyed collection hota hai.

```
1 var person = {  
2     first: "Kyle",  
3     last: "Simpson",  
4     age: 39,  
5     specialties: ["JS", "Table Tennis"]  
6 };
```

Object mein value numeric position ke bajay property name se access hoti hai.

Dot notation

```
1 person.first
```

Bracket notation

```
1 person["first"]
```

Dono "Kyle" return karenge.

Bracket notation tab especially useful hai jab key dynamic ho:

```
1 const propertyName = "first";  
2  
3 console.log(person[propertyName]);
```

4. Checking Value Types with typeof

typeof operator kisi value ka built-in type identify karne mein help karta hai.

```
1 typeof 42;  
2 // "number"  
3  
4 typeof "abc";  
5 // "string"  
6  
7 typeof true;  
8 // "boolean"  
9  
10 typeof undefined;  
11 // "undefined"
```

Objects ke saath:

```
1  typeof { a: 1 };
2  // "object"
3
4  typeof [1, 2, 3];
5  // "object"
```

Array object ka special subtype hai, isliye typeof array ko "array" nahi batata.

Functions:

```
1  typeof function hello() {};
2  // "function"
```

Function technically special object-type value hai, lekin typeof uske liye "function" return karta hai.

Famous typeof null bug

```
1  typeof null;
2  // "object"
```

Expected "null" lag sakta hai, lekin result "object" aata hai. Yeh JavaScript ka purana historical behavior hai.

Isliye null check karne ke liye direct comparison better hai:

```
1  value === null
```

Array check karne ke liye:

```
1  Array.isArray(value)
```

5. Coercion

Ek type ki value ko doosre type mein convert karne ko **coercion** kehte hain.

Example:

```
1  Number("42");
2  // 42
```

Yahan string "42" number 42 mein convert hui.

Coercion explicit bhi ho sakti hai:

```
1  String(42);
2  Number("42");
3  Boolean(1);
```

Aur kuch operators coercion implicitly bhi kar sakte hain:

```
1 42 == "42";  
2 // true
```

Is comparison se pehle string numeric value mein convert hoti hai.

6. Declaring and Using Variables

Variable ko ek container samajh sakte ho jo kisi value ko hold karta hai.

JavaScript mein three major declaration keywords hain:

```
1 var  
2 let  
3 const
```

6.1 var

```
1 var myName = "Kyle";  
2 var age;
```

First line variable declare karke initial value assign karti hai.

Second line variable declare karti hai, lekin initial value nahi deti. Initially age ki value undefined hogi.

var normally **function-scoped** hota hai, block-scoped nahi.

```
1 if (true) {  
2     var message = "Hello";  
3 }  
4  
5 console.log(message);  
6 // "Hello"
```

if ka block close hone ke baad bhi message available hai.

6.2 let

let block-scoped hota hai.

```
1 if (true) {  
2     let age = 39;  
3     console.log(age);  
4 }
```

```
5
6 console.log(age);
7 // ReferenceError
```

age sirf { ... } block ke andar accessible hai.

Block scope ka benefit

Block scope variables ki access ko limited rakhta hai. Isse:

- accidental naming conflicts reduce hote hain
 - variable ka purpose clear hota hai
 - unexpected modification ka risk kam hota hai
-

var vs let

Example:

```
1 var adult = true;
2
3 if (adult) {
4     var myName = "Kyle";
5     let age = 39;
6 }
7
8 console.log(myName);
9 // "Kyle"
10
11 console.log(age);
12 // Error
```

Reason:

- myName var se declared hai, isliye if block tak limited nahi hai.
- age let se declared hai, isliye block ke bahar available nahi hai.

Author ka view yeh hai ki var ko completely ban karna zaroori nahi. Agar code mein intentionally wider function scope communicate karna ho, toh var meaningful ho sakta hai.

6.3 const

const bhi let ki tarah block-scoped hai, lekin:

1. Declaration ke time value deni hoti hai.
2. Baad mein variable ko reassign nahi kar sakte.

```
1  const myBirthday = true;
2
3  myBirthday = false;
4  // Error
```

const ka matlab completely unchangeable nahi hai

Yeh bahut important point hai.

```
1  const actors = [
2      "Morgan Freeman",
3      "Jennifer Aniston"
4  ];
```

Array ko mutate karna allowed hai:

```
1  actors[2] = "Tom Cruise";
```

Lekin variable ko new array dena allowed nahi:

```
1  actors = [];
2  // Error
```

Reassignment aur mutation ka difference

Reassignment:

Variable ko completely different value dena:

```
1  actors = [];
```

Mutation:

Existing object ya array ke andar change karna:

```
1  actors.push("Tom Cruise");
```

const reassignment rokta hai, mutation nahi.

Author confusion avoid karne ke liye const ko primarily primitive values ke saath use karne ki recommendation deta hai.

7. Variables Declare Karne Wali Doosri Syntax

Variables sirf var, let aur const se declare nahi hote.

Function Name and Parameters

```
1 function hello(myName) {  
2     console.log(`Hello, ${myName}.`);  
3 }
```

Yahan:

- hello outer scope mein identifier hai.
- myName function ke andar local identifier hai.

myName function ke bahar available nahi hai.

catch Parameter

```
1 try {  
2     someError();  
3 }  
4 catch (err) {  
5     console.log(err);  
6 }
```

err sirf catch block ke andar available hai. Yeh block-scoped variable ki tarah behave karta hai.

8. Functions

JavaScript mein function ko ek **procedure** samajh sakte ho:

- statements ka collection
 - multiple times invoke ho sakta hai
 - input receive kar sakta hai
 - output return kar sakta hai
-

Function Declaration

```
1 function awesomeFunction(coolThings) {  
2     return amazingStuff;  
3 }
```

Yeh function declaration hai.

Function declaration aur uske name ka association code execution se pehle compile phase mein establish ho jata hai.

Isliye declaration se pehle call bhi possible hoti hai:

```
1 greet();
2
3 function greet() {
4     console.log("Hello");
5 }
```

Function Expression

```
1 var awesomeFunction = function(coolThings) {
2     return amazingStuff;
3 };
```

Yahan anonymous function value ko variable mein assign kiya gaya hai.

Function expression ka variable ke saath association tab hota hai jab execution is assignment statement tak pahunchti hai.

```
1 greet();
2 // Error ki possibility
3
4 var greet = function() {
5     console.log("Hello");
6 };
```

Yeh function declaration jaisa behavior nahi deta.

Functions Are Values

JavaScript mein functions values hoti hain.

Isliye functions ko:

- variables mein store kar sakte ho
- objects mein rakh sakte ho
- arrays mein rakh sakte ho
- doosre functions ko argument ke roop mein pass kar sakte ho
- function se return kar sakte ho

```
1 const sayHello = function() {
2     console.log("Hello");
3 }
```

```
3 };
```

Function ek special object subtype hai.

Yahi capability JavaScript mein functional programming patterns possible banati hai.

Parameters and Arguments

```
1 function greeting(myName) {  
2     console.log(`Hello, ${myName}!`);  
3 }  
4  
5 greeting("Kyle");
```

Yahan:

- myName **parameter** hai.
- "Kyle" **argument** hai.

Parameter function definition mein local variable hota hai. Argument function call ke time pass ki jane wali actual value hoti hai.

Returning Values

```
1 function greeting(myName) {  
2     return `Hello, ${myName}!`;  
3 }  
4  
5 var message = greeting("Kyle");  
6 console.log(message);
```

Function return ke through ek value return karti hai.

Technically function ek time par single value return karti hai. Multiple pieces of information return karne hain toh unhe object ya array mein wrap kar sakte ho:

```
1 function getUser() {  
2     return {  
3         name: "Kyle",  
4         age: 39  
5     };  
6 }
```

Functions as Object Methods

```
1  var whatToSay = {  
2    greeting() {  
3      console.log("Hello!");  
4    },  
5  
6    question() {  
7      console.log("What's your name?");  
8    },  
9  
10   answer() {  
11     console.log("My name is Kyle.");  
12   }  
13 };
```

Object ke andar stored function ko generally **method** kehte hain.

Method call:

```
1  whatToSay.greeting();
```

9. Comparisons

Programs ko decisions lene ke liye values compare karni padti hain.

JavaScript mein comparison ke major forms hain:

- strict equality: ===
 - coercive equality: ==
 - relational comparisons: <, >, <=, >=
-

10. Strict Equality: ===

Common explanation hoti hai:

=== value aur type dono check karta hai.

Chapter is explanation ko incomplete maanta hai. Better explanation hai:

=== comparison ke dauraan type coercion allow nahi karta.

Examples:

```
1 3 === 3.0;
2 // true
3
4 "yes" === "yes";
5 // true
6
7 42 === "42";
8 // false
9
10 true === 1;
11 // false
12
13 null === undefined;
14 // false
```

3 aur 3.0 JavaScript mein same numeric value hain, isliye result true hai.

42 aur "42" ka type different hai. === conversion nahi karta, isliye result false hai.

NaN and -0

=== ke do special surprising cases hain.

```
1 NaN === NaN;
2 // false
```

NaN, khud ke saath bhi equal nahi hota.

Reliable check:

```
1 Number.isNaN(value);
```

Ya:

```
1 Object.is(value, NaN);
```

Second case:

```
1 0 === -0;
2 // true
```

JavaScript mein 0 aur -0 technically distinguishable values hain, lekin === unhe equal batata hai.

Difference detect karne ke liye:

```
1 Object.is(0, -0);
2 // false
```

Object.is() NaN ko bhi correctly recognize karta hai:

```
1 Object.is(NaN, NaN);
2 // true
```

11. Object Equality Means Identity Equality

Primitive values ke comparison mein actual value compare hoti hai:

```
1 42 === 42;
2 // true
```

Lekin objects aur arrays ke case mein reference identity compare hoti hai.



```
1 [1, 2, 3] === [1, 2, 3];
2 // false
```

Dono arrays ke contents same hain, lekin dono separately created arrays hain. Dono ka reference different hai.

Same object reference ho toh result true aayega:

```
1 var x = [1, 2, 3];
2 var y = x;
3
4 y === x;
5 // true
```

Yahan y mein array ki copy nahi bani. x aur y same array ko reference karte hain.

```
1 x 
2  —> same array
3 y 
```

Lekin:

```
1 y === [1, 2, 3];
2 // false
```

Right side par ek new array create hui hai.

Structural equality

Agar objects ke actual content compare kiye jayen, use structural equality keh sakte hain.

JavaScript ka === objects ke liye structural equality perform nahi karta.

```
1 const user1 = { name: "Kyle" };
2 const user2 = { name: "Kyle" };
3
4 user1 === user2;
```

```
5 // false
```

Content compare karne ke liye custom logic likhna padta hai.

12. Coercive Equality: ==

== ko usually “loose equality” kaha jata hai, lekin author ise **coercive equality** kehna more accurate maanta hai.

Important rule:

Agar dono values ka type same hai, toh == aur === generally same comparison karte hain.

```
1 42 == 42;  
2 // true  
3  
4 42 === 42;  
5 // true
```

Difference tab aata hai jab types different hon.

```
1 42 == "42";  
2 // true
```

== type conversion allow karta hai. String "42" number 42 mein convert hoti hai aur phir comparison hota hai.

```
1 1 == true;  
2 // true
```

true numeric comparison mein 1 ban jata hai.

Confusing corner cases

```
1 "" == 0;  
2 // true  
3  
4 0 == false;  
5 // true
```

Isi tarah ke cases ki wajah se == confusing lagta hai.

Author ka view hai ki coercion ko blindly avoid karne ke bajay uske rules properly samajhne chahiye.

13. Relational Comparisons

Operators:

```
1 <
2 >
3 <=
4 >=
```

Agar compared values ke types different hon, toh relational operators coercion kar sakte hain.

```
1 var arr = ["1", "10", "100", "1000"];
2
3 for (
4     let i = 0;
5     i < arr.length && arr[i] < 500;
6     i++
7 ) {
8     console.log(arr[i]);
9 }
```

arr[i] string hai aur 500 number hai. Comparison ke waqt strings numbers mein convert hongy:

```
1 "1" < 500
2 // 1 < 500 → true
3
4 "10" < 500
5 // 10 < 500 → true
6
7 "100" < 500
8 // 100 < 500 → true
9
10 "1000" < 500
11 // 1000 < 500 → false
```

Isliye loop three times execute hoga.

Jab dono values strings hon

Agar comparison ke dono operands strings hain, toh alphabetical ya dictionary-like comparison hota hai.

```
1 var x = "10";
```

```
2 var y = "9";
3
4 x < y;
5 // true
```

Numeric perspective se 10, 9 se bada hai. Lekin yahan strings compare ho rahi hain.

Character comparison mein "1", "9" se pehle aata hai. Isliye "10" < "9" result true hai.

Numeric comparison chahiye toh explicit conversion useful hai:

```
1 Number(x) < Number(y);
2 // false
```

Main lesson

Relational comparisons use karte time operands ke types ko clearly samjho.

14. How We Organize JavaScript Code

Chapter JavaScript code organize karne ke do major patterns discuss karta hai:

1. Classes
2. Modules

Dono ka broad goal similar hai:

Related data aur us data par kaam karne wale behavior ko logical unit mein group karna.

Ek program classes aur modules dono use kar sakta hai.

15. Classes

Class ek custom data structure ka blueprint hoti hai.

Class khud concrete value nahi hoti. Usse usable object banane ke liye instantiate karna padta hai.

```
1 class Page {
2     constructor(text) {
3         this.text = text;
4     }
5
6     print() {
```

```
7     console.log(this.text);
8   }
9 }
```

Page class define karti hai ki har page object ke paas:

- text data hoga
- print() behavior hoga

Instance:

```
1 const page = new Page("Hello");
```

Yahan new class ka instance create karta hai.

constructor

constructor instance creation ke time automatically execute hota hai.

```
1 constructor(text) {
2   this.text = text;
3 }
```

this.text current instance ki property hai.

Notebook Example

```
1 class Notebook {
2   constructor() {
3     this.pages = [];
4   }
5
6   addPage(text) {
7     const page = new Page(text);
8     this.pages.push(page);
9   }
10
11   print() {
12     for (const page of this.pages) {
13       page.print();
14     }
15   }
16 }
```

Notebook ke paas:

Data

```
1 this.pages
```

Yeh Page instances ki array hai.

Behavior

```
1 addPage()  
2 print()
```

Use:

```
1 const notes = new Notebook();  
2  
3 notes.addPage("Arithmetic");  
4 notes.addPage("Trigonometry");  
5  
6 notes.print();
```

Classes data aur behavior ko ek organized unit mein package karti hain.

16. Class Inheritance

Inheritance ka matlab hai ek class doosri class ki capabilities ko extend kare.

Parent class:

```
1 class Publication {  
2     constructor(title, author, pubDate) {  
3         this.title = title;  
4         this.author = author;  
5         this.pubDate = pubDate;  
6     }  
7  
8     print() {  
9         console.log(this.title);  
10        console.log(this.author);  
11        console.log(this.pubDate);  
12    }  
13 }
```

Child class:

```
1 class Book extends Publication {  
2     constructor(details) {  
3         super(  

```

```
4         details.title,  
5         details.author,  
6         details.pubDate  
7     );  
8  
9     this.publisher = details.publisher;  
10    this.ISBN = details.ISBN;  
11 }  
12 }
```

extends

```
1 class Book extends Publication
```

Iska matlab Book, Publication se capabilities inherit karti hai.

super()

Child constructor mein:

```
1 super(title, author, pubDate);
```

parent class ka constructor call karta hai.

Isse common initialization parent class handle karti hai.

Method overriding

Parent ke paas print() method ho sakta hai aur child bhi apna print() define kar sakta hai.

```
1 class Book extends Publication {  
2     print() {  
3         super.print();  
4         console.log(this.publisher);  
5         console.log(this.ISBN);  
6     }  
7 }
```

Child ka print() parent ke print() ko override karta hai.

Lekin child parent version ko call bhi kar sakta hai:

```
1 super.print();
```

Polymorphism

Book aur BlogPost, dono ke paas print() method ho sakta hai, lekin dono ka implementation different ho sakta hai.

```
1 book.print();
2 blogPost.print();
```

Same method name different object types par different appropriate behavior perform karta hai. Is concept ko **polymorphism** kehte hain.

17. Modules

Modules ka goal bhi related data aur behavior ko group karna hai, lekin unka implementation classes se different hota hai.

Chapter do kinds explain karta hai:

1. Classic modules
 2. ES modules
-

18. Classic Modules

Classic module generally ek outer function hota hai jo:

1. Internal private data create karta hai.
2. Internal functions define karta hai.
3. Public methods ka object return karta hai.

Example:

```
1 function Publication(title, author, pubDate) {
2     function printDetails() {
3         console.log(title);
4         console.log(author);
5         console.log(pubDate);
6     }
7
8     var publicAPI = {
9         print() {
10             printDetails();
11         }
12     }
13 }
```

```
12     };  
13  
14     return publicAPI;  
15 }
```

Use:

```
1  const publication = Publication(  
2    "You Don't Know JS",  
3    "Kyle Simpson",  
4    "June 2014"  
5  );  
6  
7  publication.print();
```

Publication() ko new ke bina normal function ki tarah call kiya gaya.

Module Factory

Aisa function har call par module ka new instance create karta hai, isliye ise **module factory** kaha ja sakta hai.

```
1  const firstPublication = Publication(...);  
2  const secondPublication = Publication(...);
```

Dono ke paas independent internal data hoga.

Private and Public Members

Function ke andar ka data directly available nahi hai:

```
1  title  
2  author  
3  pubDate
```

Yeh private state ki tarah behave karta hai.

Return kiya gaya object public API hai:

```
1  {  
2    print() { ... }  
3  }
```

Consumer sirf exposed functions access kar sakta hai:

```
1  publication.print();
```

Classes vs Classic Modules

Class style

Data aur methods instance object par store hote hain:

```
1  this.title
2  this.print()
```

Module style

Data aur functions surrounding scope mein identifiers ke form mein available hote hain:

```
1  title
2  printDetails()
```

Public API

Class mein instance properties aur methods generally public hoti hain.

Classic module mein tum explicitly decide karte ho ki return object mein kya expose karna hai. Jo return nahi kiya gaya, woh private rehta hai.

AMD, UMD and CommonJS

Chapter mention karta hai ki classic module pattern ke multiple variations exist karti hain:

- AMD
- UMD
- CommonJS

Inka exact format different ho sakta hai, lekin basic purpose same hai:

- code ko modules mein divide karna
 - private internal implementation rakhna
 - selected public functionality expose karna
 - modules ko cooperate karwana
-

19. ES Modules

ES Modules ko ESM bhi kaha jata hai. Yeh JavaScript ka native module system hai jo ES6 mein introduce hua.

Iske core concepts hain:

```
1 export
2 import
```

One File, One Module

ES module ke liye wrapping factory function necessary nahi hota.

File khud module boundary hoti hai.

```
1 publication.js → one module
2 blogpost.js    → one module
3 main.js        → one module
```

Export

Kisi function ya variable ko module ke bahar public banana ho toh export use hota hai.

```
1 // publication.js
2
3 function printDetails(title, author) {
4     console.log(title, author);
5 }
6
7 export function create(title, author) {
8     return {
9         print() {
10             printDetails(title, author);
11         }
12     };
13 }
```

create() exported hai, isliye doosri files access kar sakti hain.

printDetails() exported nahi hai, isliye woh module ke andar hidden hai.

Import

```
1 import { create } from "../publication.js";
```

Ab imported create() function current module mein use kiya ja sakta hai.

Import Rename Karna

```
1 import {  
2     create as createPublication  
3 } from "./publication.js";
```

Original exported name create hai, lekin current file mein use createPublication naam se karenge.

Isse readability improve ho sakti hai.

```
1 const article = createPublication(  
2     "Learning JS",  
3     "Kyle"  
4 );
```

20. ES Modules Are Singletons

Classic module factory har call par new instance create kar sakti hai.

```
1 const one = Publication(...);  
2 const two = Publication(...);
```

Lekin ES module ko baar-baar instantiate nahi kiya jata.

Jab module first time import hota hai, uska ek instance create/evaluate hota hai. Baaki imports usi module instance ka reference receive karte hain.

Isi sense mein ES modules **singletons** ki tarah behave karte hain.

```
1 import { sharedState } from "./store.js";
```

Different files se import karne par sab same module-level state access kar sakti hain.

Multiple Instances Chahiye Toh?

ES module ke andar factory function export kar sakte ho:

```
1 export function createUser(name) {  
2     return {  
3         getName() {  
4             return name;  
5         }  
6     };  
7 }
```

Ab factory ko multiple times call karke multiple independent objects bana sakte ho:

```
1 const user1 = createUser("Ruth");
2 const user2 = createUser("Kyle");
```

Matlab:

- ES module khud single instance hai.
- Exported factory multiple instances create kar sakti hai.

Alternative ke roop mein module se class export ki ja sakti hai, lekin chapter ka author ESM ke andar classic module-style factory approach ko prefer karta hai.

21. Classes and Modules Ka Conceptual Difference

Class

Class blueprint define karti hai.

```
1 class User {
2     constructor(name) {
3         this.name = name;
4     }
5 }
6
7 const user1 = new User("Ruth");
8 const user2 = new User("Kyle");
```

Har new se new instance banta hai.

Classic module factory

Function new encapsulated object create karti hai:

```
1 function User(name) {
2     return {
3         getName() {
4             return name;
5         }
6     };
7 }
8
9 const user1 = User("Ruth");
10 const user2 = User("Kyle");
```

ES module

File ek module hoti hai aur uske exported members public API form karte hain:

```
1  export function getUser() {  
2      // ...  
3  }
```

Module directly multiple instances nahi deta, jab tak tum factory ya class export na karo.

22. Complete Chapter Ka Mental Model

Is poore chapter ko is flow mein samjho:

```
1  JavaScript Application  
2      |  
3      ├── Multiple files  
4          ├── Standalone scripts  
5          └── ES modules  
6      |  
7      ├── Values  
8          ├── Primitives  
9          └── Objects  
10     |  
11     ├── Variables  
12         ├── var  
13         ├── let  
14         └── const  
15     |  
16     ├── Functions  
17         ├── Inputs  
18         ├── Output  
19         └── Values themselves  
20     |  
21     ├── Comparisons  
22         ├── ===  
23         ├── ==  
24         └── <, >, <=, >=  
25     |  
26     └── Code organization  
27         ├── Classes
```

28	Classic modules
29	ES modules

23. Most Important Points to Remember

Programs and files

- Har standalone JavaScript file ko separate program samjho.
- Multiple files global scope ya module imports ke through cooperate kar sakti hain.
- ES module mein one file generally one module hoti hai.

Values

- Values primitive ya object hoti hain.
- Arrays aur functions special objects hain.
- `typeof null` unexpectedly "object" deta hai.
- `typeof []` bhi "object" deta hai.

Variables

- `var` function-scoped hota hai.
- `let` block-scoped hota hai.
- `const` block-scoped hota hai aur reassign nahi ho sakta.
- `const` object ko immutable nahi banata.

Functions

- Functions values hoti hain.
- Parameter definition mein hota hai.
- Argument function call mein pass hota hai.
- Function ek value return kar sakti hai.
- Multiple results ko object ya array mein return kiya ja sakta hai.

Equality

- `===` coercion allow nahi karta.
- `==` mismatched types par coercion kar sakta hai.
- `NaN === NaN` false hota hai.
- `0 === -0` true hota hai.
- Objects content se nahi, reference identity se compare hote hain.

Organization

- Classes data aur behavior ko instances mein organize karti hain.

- Inheritance child class ko parent behavior extend karne deti hai.
 - Classic modules private state aur explicit public API offer karte hain.
 - ES modules import aur export use karte hain.
 - ES module ka ek shared instance hota hai.
 - Multiple instances ke liye factory function ya class export ki ja sakti hai.
-

24. Is Chapter Ko Practically Kaise Padho

Chapter ka intention sirf definitions yaad karwana nahi hai. Har section ke baad chhota program likhna useful hoga.

Suggested practice order:

1. String interpolation ka example banao.
2. Array aur object create karke values access karo.
3. Same variable ko var aur let ke saath block mein test karo.
4. const array ko mutate aur reassign karke difference dekho.
5. Function declaration aur function expression compare karo.
6. ===, == aur Object.is() examples console mein run karo.
7. Do similar-looking arrays ko compare karo.
8. Simple class banao.
9. Wahi functionality factory module se banao.
10. Do files ke beech export aur import practice karo.

Chapter ka final message yahi hai ki agar ek read mein sab clear nahi hua toh woh normal hai. Yeh chapter JavaScript ke wide surface area ka survey hai. Aage ke chapters in concepts ko deeper level par explain karenge, lekin usse pehle values, variables, functions, comparisons, classes aur modules ka basic mental model strong hona chahiye.

Chapter mein diya gaya external link

- [For and against let](#)

Explanation approach

Maine chapter ko original sequence mein simplify kiya hai, confusing concepts ke beech direct comparisons diye hain, aur author ki recommendations ko language ke actual behavior se alag rakhne ki koshish ki hai. Isse tumhe chapter dobara padhte waqt har section ka context aur purpose easily samajh aayega.