

React — Today's Interview Notes

Components • Props • Multiple Props • Objects as Props • Tailwind CSS

1. React Components

Definition: A component is a reusable building block of a React application that returns JSX and represents part of the UI.

Create → Import → Use

```
function Card() {  
  return <h2>My Card</h2>  
}  
  
export default Card  
  
<Card />
```

<Card /> means render/use the Card component here. Card is your own React component, not a built-in HTML tag.

2. Props ■

Definition: Props are read-only data passed from a parent component to a child component. They make components reusable and dynamic.

```
Parent: <Card username="Mani bhai" />  
  
function Card(props) {  
  console.log(props)  
  return <h1>{props.username}</h1>  
}
```

3. Props Are an Object

When you pass username="Mani bhai", the child receives:

```
props = {  
  username: "Mani bhai"  
}
```

Use **props.username** to get the value.

4. The Mistake You Made

You initially wrote **function Card(username)**. That parameter receives the whole props object, not just the username string.

Correct beginner version: **function Card(props)**

Then use **props.username**.

5. Multiple Props

```
<Card  
  username="Mani bhai"  
  btnText="click me"  
/>
```

The child receives an object containing both values. Access them with **props.username** and **props.btnText**.

6. Same Component, Different Data ■

```
<Card username="Mani bhai" btnText="click me" />  
<Card username="Nilmani" btnText="Buy Now" />
```

One Card component can display different data. This is a major reason props are useful.

7. Passing an Object as a Prop

```
const myobj = {
  username: "Nilmani",
  age: 23
}

<Card someobj={myobj} />
```

Inside Card: **props.someobj.username** or **props.someobj.age**.

8. Props Flow

Parent (App) → sends props → Child (Card) → receives props → uses props.username

9. Tailwind CSS ■

Definition: Tailwind CSS is a utility-first CSS framework that lets you style elements using predefined utility classes directly in JSX.

```
<h1 className="p-4 text-black bg-green-400 rounded-xl">TAILWIND TEST</h1>
```

Class	Meaning
p-4	padding
mt-4	margin-top
bg-green-400	background color
text-black	text color
rounded-xl	rounded corners
w-96	width
flex	Flexbox
flex-col	column direction
justify-between	space between items
font-bold	bold text
font-mono	monospace font

10. Tailwind + Normal CSS

Tailwind goes in **className**; React inline CSS goes in **style={{ ... }}**. Both can be used together.

```
<div className="flex p-4 rounded-xl"
  style={{ border: '1px solid' }}
>
```

11. Interview Q&A;

Q: What are props?

A: Props are read-only data passed from a parent component to a child component. They help make components reusable and dynamic.

Q: How do you pass props?

A: `<Card username="Nilmani" />`

Q: How do you receive props?

A: `function Card(props) { return <h1>{props.username}</h1> }`

Q: Can a component receive multiple props?

A: Yes. Example: `<Card username="Nilmani" btnText="Buy Now" />`

Q: Why use props?

A: They let a parent pass data to a child and let the same component be reused with different data.

Q: What is Tailwind CSS?

A: A utility-first CSS framework that provides predefined utility classes for styling.

12. 30-Second Interview Summary

In React, I can create reusable components and pass data between them using props. Props are received as an object in the child component, for example `props.username`. I can pass multiple props and reuse the same component with different data. Tailwind CSS lets me style elements with utility classes directly in JSX.