

Agent Wiki: A Local-First Evidence-Closed Markdown Wiki for LLM Agents

Zijun Chu

<https://github.com/NimaChu/agent-wiki>

Technical Report, July 2026

Abstract

Large language model (LLM) agents increasingly perform long-running reading, coding, and maintenance tasks, but their durable knowledge often remains trapped in chat transcripts, proprietary note systems, vector databases, or ad hoc project memories. This report introduces Agent Wiki, a local-first, Markdown-native knowledge substrate designed for coding agents and human users who want source-grounded, inspectable, and low-cost long-term knowledge management. Agent Wiki separates immutable or lightly edited raw evidence from agent-synthesized wiki pages, uses Obsidian-compatible links as a computable knowledge graph, and defines a “processed” closure condition that is checked by local linting tools: a raw source is processed only when its primary wiki targets resolve, the wiki layer links back to the raw evidence, and follow-up flags are closed. The system also treats images as evidence by mirroring remote images, building image inventories, and allowing selected visuals to be promoted into wiki answers. A read-only dashboard exposes global and local graph views, evidence drill-downs, and health indicators such as broken links, orphaned wiki pages, stale sources, and processed-gate failures. A case study on an Autodesk FlexSim documentation corpus produced 1,097 raw source notes, 93 durable wiki pages, and 5,261 graph edges, with zero unresolved links, zero orphaned wiki pages, and zero processed-gate violations under the included lint checks. Agent Wiki does not replace retrieval-augmented generation; instead, it offers a file-native, auditable staging layer from which retrieval, dashboards, and agent workflows can later be built.

1 Introduction

LLM agents are now capable of reading documentation, summarizing long sources, editing code, and maintaining project-local context across multi-step workflows. Yet durable agent knowledge remains awkward. Many practical systems fall into one of three patterns: transient chat history, human-authored note vaults, or retrieval-augmented generation (RAG) stacks backed by a database or vector index. Each pattern is useful, but each leaves a gap for independent developers and small teams who want a private, inspectable, source-grounded knowledge base that agents can maintain without requiring a hosted service, a custom database, or a heavy retrieval pipeline.

Agent Wiki addresses this gap with a deliberately simple design: files first, Markdown first, and evidence first. The system is a repository layout, command line interface, and optional dashboard for maintaining a local knowledge base in which raw captures and durable wiki pages are separate layers. Raw notes preserve bibliographic metadata, capture details, snapshots, content hashes, images, and processing status. Wiki pages distill durable knowledge units such as concepts, entities, APIs, workflows, comparisons, and recurring questions. Claims in wiki pages link back to raw evidence using ordinary wiki links. Local scripts scan the vault, resolve links, build graph statistics, surface maintenance queues, and enforce a strict processed-source closure rule.

The guiding premise is that agent memory should be inspectable before it is intelligent. Instead of beginning with embeddings or opaque hidden state, Agent Wiki creates a substrate that humans and agents can both read, edit, diff, lint, and version. This makes it possible to separate capture from synthesis, review agent-maintained knowledge with ordinary developer tools, and preserve the option to add retrieval or automation later.

This report makes four contributions:

1. It describes a local-first architecture for agent-maintained knowledge bases that separates raw evidence from synthesized wiki knowledge.

2. It defines an evidence-closure invariant for processed sources and implements local linting checks for unresolved links, orphaned wiki pages, missing source links, and processed-gate failures.
3. It introduces an image-evidence workflow for mirroring, indexing, and promoting visual source material into answer-ready wiki pages.
4. It reports an initial case study over a large technical documentation corpus, demonstrating that the approach scales to more than one thousand raw source notes while preserving graph health under local checks.

2 Design Goals

Agent Wiki was designed around constraints that appear frequently in real personal and small-team agent workflows.

Local ownership. The user should own the source captures, synthesized pages, images, snapshots, and maintenance state as local files. A user should be able to inspect the knowledge base with a text editor, search it with command line tools, and keep private knowledge out of public code repositories.

Agent-native operation. The repository should be legible to coding agents. The project includes workspace rules, templates, and root npm scripts so that agents can capture sources, maintain the vault, repair links, and answer from the wiki without depending on globally installed skills or a particular editor.

Evidence before synthesis. Raw source material should remain available after synthesis. The wiki layer is not a replacement for source evidence; it is a compiled layer of durable knowledge units whose claims point back to raw notes.

Low operational cost. The system should work without a hosted database, paid subscription, required embedding service, or always-on dashboard. Visualization is generated and opened only when requested.

Auditable maintenance. Agent-maintained knowledge needs health checks. Broken links, orphaned pages, unprocessed sources, follow-up flags, and weakly connected pages should be computable from local files.

3 System Overview

Agent Wiki is organized as a self-contained repository with the following major directories:

Directory	Role
<code>raw/</code>	source notes, snapshots, evidence metadata, image inventories
<code>wiki/</code>	durable synthesized knowledge pages
<code>templates/</code>	reusable raw and wiki page templates
<code>scripts/</code>	local command line workflows for capture, lint, search, repair
<code>tools/wiki-dashboard/</code>	optional read-only graph dashboard

The main command line entry point is `scripts/karpathy-wiki.mjs`, exposed through root npm scripts. The core commands are: `wiki:status`, `wiki:lint`, `wiki:garden`, `wiki:repair-links`, `wiki:search`, `wiki:capture`, `wiki:images`, `dashboard`, and `dashboard:open`.

3.1 Raw Evidence Layer

The raw layer is the factual source layer. A raw note stores metadata such as title, author, publication date, source URL, capture date, source type, snapshot path, content hash, capture method, source quality, tags, related wiki targets, and processing status. The body preserves captured content, explicit images, extracted claims, candidate wiki links, and processing notes.

Raw notes are intentionally not treated as disposable summaries. They are the evidence ledger from which multiple wiki pages can be synthesized. A single source may update many durable concepts, and a single wiki concept may cite many raw notes.

3.2 Wiki Layer

The wiki layer is the compiled knowledge layer. It favors one durable knowledge unit per page: a concept, entity, method, API, workflow, comparison, or recurring question. Pages use Obsidian-compatible links such as `[[Page Name]]` or `[[Page Name|label]]`. Frontmatter may include typed relation hints from a small supported vocabulary: `supports`, `challenges`, `related_to`, `applies_to`, `company_of`, and `product_of`.

This design borrows from evergreen-note practices, especially the preference for atomic, linked, evolving notes [3]. The difference is that Agent Wiki makes the maintenance procedure executable by agents and auditable by local scripts.

3.3 Graph and Resolver

The scanner walks Markdown files under `raw/`, `wiki/`, `templates/`, and archives. It parses simple YAML frontmatter, extracts body links and frontmatter links, resolves targets by id, title, basename, and alias, and emits nodes, edges, unresolved links, typed relations, invalid relations, incoming counts, and outgoing counts.

The resolver deliberately uses ordinary Markdown and wiki-link conventions rather than a hidden database. The graph is therefore a derived artifact, not the source of truth. If a generated JSON file is deleted, it can be rebuilt from the Markdown vault.

4 Evidence Closure

The central maintenance invariant in Agent Wiki is evidence closure. A raw note with status `processed` should satisfy three conditions:

1. It has at least one related wiki target.
2. Each related target resolves to an existing page.
3. At least one resolved wiki target links back to the raw note.

In addition, explicit follow-up flags prevent a source from being treated as complete. The lint workflow reports processed-source issues such as `missing-related`, `unresolved-related`, `missing-wiki-backlink`, and `explicit-followup`. This turns a normally subjective maintenance action—“this source has been processed”—into a local, reviewable property.

Evidence closure is modest but important. It does not prove that every claim is correct or that the synthesis is complete. It does, however, prevent a common failure mode in agent-maintained knowledge bases: raw material is summarized, marked done, and later becomes unreachable from the synthesized knowledge layer.

5 Image Evidence

Many useful sources are visual: documentation screenshots, UI states, architecture diagrams, charts, workflows, and configuration examples. Agent Wiki therefore treats images as evidence rather than decoration.

The image workflow scans raw notes and selected snapshots for Markdown image syntax and HTML `img` tags, resolves relative URLs, deduplicates images, mirrors remote images into `raw/assets/<source-note>/`, writes an `image-index.json`, records local paths, content types,

byte counts, and download errors, and updates the raw note’s **Images** section with a preview table. Agents are instructed to promote only the most useful visual evidence into wiki pages, keeping exhaustive inventories in raw notes.

This mechanism supports grounded answers that include local images when a visual state is material to the answer. It also avoids a common degradation in web captures: links to remote images rot or become difficult to associate with their source context.

6 Dashboard

The dashboard is a read-only visualization surface. Its graph generator scans **raw/** and **wiki/**, excludes navigation and maintenance files, and writes **public/wiki-graph.json**. The frontend displays global and local graph browsing, a wiki-only knowledge view by default, evidence drill-down for a wiki page and its directly linked raw sources, search, group and status filters, selected-node links and backlinks, tags, raw/wiki/link counts, and health indicators for inbox, follow-up, stale, broken-link, and processed-gate queues.

The dashboard does not write to the vault. This read-only constraint keeps the Markdown repository as the source of truth and lets visualization remain an on-demand artifact rather than a runtime dependency.

7 Implementation

Agent Wiki is implemented with Node.js scripts and a Vite/React dashboard. The repository is intentionally small. In the inspected version, the root scripts directory contains roughly 94 KB of JavaScript source, and the dashboard source contains a React graph surface plus CSS. No database server is required.

Table 1 summarizes the primary command line workflows.

Command	Purpose
<code>npm run wiki:status</code>	report vault graph and queue statistics
<code>npm run wiki:lint</code>	validate unresolved links, source closure, and metadata
<code>npm run wiki:garden</code>	show maintenance queues and weakly connected pages
<code>npm run wiki:repair-links</code>	assist with link repair
<code>npm run wiki:search - "query"</code>	search across titles, tags, aliases, and excerpts
<code>npm run wiki:capture</code>	create a raw source note with metadata and snapshots
<code>npm run wiki:images</code>	extract, mirror, and index image evidence
<code>npm run dashboard:open</code>	refresh graph, start local frontend, open browser

Table 1: Primary local workflows exposed as npm scripts.

8 Case Study: FlexSim Documentation Vault

To evaluate the system as a practical maintenance substrate, Agent Wiki was used to ingest and synthesize a large technical documentation corpus for Autodesk FlexSim. The vault health commands were run on July 7, 2026. Table 2 shows the resulting graph statistics.

The case study suggests that a file-native approach can remain mechanically healthy over a documentation-scale corpus. The strongest result is not the node count alone, but the absence of unresolved links, orphaned wiki pages, and processed-gate violations after agent-assisted maintenance. These metrics show that the raw evidence layer and wiki synthesis layer can be kept connected by local checks.

9 Relationship to RAG and Agent Memory

RAG combines parametric language models with external non-parametric memory to improve knowledge-intensive generation [1]. Agent Wiki is complementary to RAG rather than a replacement for it. RAG

Metric	Value
Total nodes	1,201
Graph edges	5,261
Raw source notes	1,097
Wiki pages	93
Inbox raw sources	0
Processed raw sources	1,096
Needs follow-up	0
Stale sources	0
Unresolved links	0
Invalid relation hints	0
Orphaned wiki pages	0
Processed-source issues	0

Table 2: Vault health for the FlexSim case study. Metrics are produced by the included local status and lint commands.

typically optimizes retrieval at answer time; Agent Wiki optimizes source preservation, synthesis, inspection, and maintenance before retrieval. A clean Agent Wiki vault can later serve as a high-quality corpus for embeddings, search, or retrieval pipelines.

Agent memory systems such as MemGPT study how LLMs can manage context beyond a fixed context window using memory tiers and control flow [2]. Agent Wiki focuses on the external substrate that an agent can maintain: ordinary files, explicit evidence links, and local health checks. It does not assume that the LLM owns or hides the memory representation.

Personal AI systems such as Khoj provide search and chat over user documents and support Markdown, PDFs, and note tools [5]. Obsidian provides a widely used local Markdown note environment with links and graph visualization [4]. Agent Wiki is narrower and more procedural: it packages a vault layout, agent instructions, capture templates, evidence-closure rules, image evidence handling, and lintable maintenance workflows specifically for agent-maintained knowledge bases.

10 Limitations

Agent Wiki currently emphasizes auditable structure over semantic automation. The search command is lightweight and does not rank with embeddings. The system does not automatically prove that wiki claims faithfully summarize raw sources; it only makes source links and maintenance state inspectable. The YAML parser is purposefully simple and may not support every frontmatter convention used by larger static-site or note-taking ecosystems. The dashboard is read-only and local. Finally, the case study is a single-developer, single-corpus deployment; future work should evaluate multi-user workflows, cross-agent consistency, and answer quality compared with chat-only and RAG-first baselines.

11 Future Work

Several extensions follow naturally from the current design. First, the vault could expose a stable Model Context Protocol server so agents can query graph state and source evidence through structured APIs while preserving Markdown as the source of truth. Second, the system could add optional embedding indexes that are built from the wiki layer, the raw layer, or both, allowing retrieval to be compared against graph-guided search. Third, evidence closure could be extended from page-level links to claim-level citations. Fourth, image evidence could be augmented with OCR, diagram captions, and visual similarity search. Fifth, dashboard interactions could create suggested maintenance actions while keeping write operations explicit and reviewable.

12 Conclusion

Agent Wiki demonstrates that a useful LLM-agent memory substrate can begin as a local Markdown repository rather than a hosted service or vector database. By separating raw evidence from synthesized

wiki knowledge, enforcing a processed closure rule, indexing images as evidence, and deriving graph health from plain files, the system offers a pragmatic bridge between personal knowledge management, source-grounded agent answers, and future retrieval pipelines. The initial FlexSim case study shows that the approach can support more than one thousand raw sources while preserving link and evidence health under local lint checks. The broader claim is simple: before agent knowledge becomes more automated, it should become more inspectable.

Availability

The Agent Wiki source code is available at <https://github.com/NimaChu/agent-wiki>. The current report describes the repository state inspected on July 7, 2026.

References

- [1] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Kuttler, Mike Lewis, Wen-tau Yih, Tim Rocktaschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, 2020. <https://arxiv.org/abs/2005.11401>.
- [2] Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. arXiv:2310.08560, 2023. <https://arxiv.org/abs/2310.08560>.
- [3] Andy Matuschak. Evergreen notes. <https://notes.andymatuschak.org/>.
- [4] Obsidian. Obsidian: Sharpen your thinking. <https://obsidian.md/>.
- [5] Khoj AI. Khoj documentation. <https://docs.khoj.dev/>.
- [6] Google. NotebookLM. <https://notebooklm.google/>.