

Javascript interview questions and answers

1.What is JavaScript, and how does it differ from Java?

JavaScript is a high-level, dynamic, and versatile programming language primarily used for front-end web development. It allows developers to create interactive and dynamic content on websites, handle user input, and perform various tasks within a web browser. JavaScript is often referred to as the "language of the web."

Java, on the other hand, is a completely different programming language. While both JavaScript and Java have "Java" in their names, they are not related. Java is a general-purpose, object-oriented programming language that can be used for a wide range of applications, including web development, mobile app development, and desktop software. Unlike JavaScript, Java requires a separate runtime environment (Java Virtual Machine) for execution and is typically used for server-side applications or Android app development.

2.Explain the difference between "null" and "undefined" in JavaScript.

null is a value in JavaScript that represents the intentional absence of any object value or a variable that has been explicitly set to have no value. It is a deliberate assignment and indicates that a variable or object does not point to any valid memory or object.

undefined is a value in JavaScript that indicates a variable has been declared but has not been assigned any value. It also represents the default value of function parameters that are not provided. It essentially means that a variable exists in the current scope but hasn't been given a meaningful value.

3.How do you declare variables in JavaScript using "var," "let," and "const"? What are the differences between them?

var: Variables declared with var are function-scoped, meaning they are only accessible within the function in which they are defined or globally if declared outside of any function. They are also hoisted, which means the declaration is moved to the top of the function or global scope during execution. var variables can be redeclared within the same scope.

let: Variables declared with let are block-scoped, which means they are limited to the block (enclosed by curly braces) where they are defined. They are not hoisted and cannot be redeclared within the same scope.

const: Variables declared with const are also block-scoped and cannot be reassigned once a value is assigned to them. Like let, const variables are not hoisted, and they also cannot be redeclared within the same scope.

4.What is the purpose of the "this" keyword in JavaScript, and how does its value change in different contexts?

The this keyword in JavaScript refers to the current execution context, which can vary depending on how and where a function is called. The value of this is determined by the function's invocation context:

5.What are callbacks in JavaScript? How do they work, and why are they important?

Callbacks in JavaScript are functions that are passed as arguments to other functions and are executed after the completion of some asynchronous operation or task. They are essential for managing asynchronous operations like handling user input, making network requests, or reading files.

6.What is the purpose of the Document Object Model (DOM) in web development, and how do you manipulate it using JavaScript?

The Document Object Model (DOM) is a programming interface provided by web browsers that allows JavaScript to interact with and manipulate web page content. It represents the structure of an HTML or XML document as a tree of objects, where each element, attribute, and piece of text is a node in the tree.

JavaScript can manipulate the DOM to dynamically update, create, or delete elements, change text and attributes, and respond to user interactions. Some common DOM manipulation methods include getElementById, querySelector, createElement, appendChild, and many more.

The DOM is essential for creating interactive and dynamic web pages by allowing JavaScript to access and modify the content and structure of a webpage in real-time.

7.What are the differences between setTimeout and setInterval in JavaScript?

setTimeout: This function is used to execute a specified function or code block after a specified time delay (in milliseconds). It only runs once. You provide a function as the first argument and the delay as the second argument.

setInterval: This function is used to repeatedly execute a specified function or code block at a specified time interval (in milliseconds) until it is cleared with clearInterval. It continues running at the specified interval until explicitly stopped.

|

8.What are the differences between confirm, prompt, and alert in JavaScript?

alert: It displays a simple dialog box with a message and an "OK" button. It's used to show a message to the user and does not take any input.

confirm: It displays a dialog box with a message, an "OK" button, and a "Cancel" button. It's typically used when you want the user to confirm or cancel an action.

prompt: It displays a dialog box with a message, an input field for the user to enter data, and "OK" and "Cancel" buttons. It's used when you need to get input from the user.

9.what is synchronous and asynchronous function.

Synchronous Function:

- Executes sequentially and blocks the program's execution until it completes.
- The program waits for it to finish before proceeding to the next task.
- Examples include basic arithmetic operations and simple function calls.
-

Asynchronous Function:

- Doesn't block the program's execution while running.
- Allows the program to continue working on other tasks.
- Typically involves tasks that may take time to complete, such as making network requests, reading files, or handling user input.
- Uses callbacks, promises, or async/await to handle the completion of the asynchronous operation.
- Examples include fetching data from a server or responding to user interactions.

10.Describe the differences between "function expressions" and "function declarations."

Function Declaration:

- Declared with the function keyword followed by a name.

- Hoisted to the top of their containing scope, so they can be called before the actual declaration.

Function Expression:

- Define functions as values assigned to variables.
- Not hoisted, and they can only be called after they are assigned.

. 11.What are arrow functions in JavaScript, and how do they differ from regular functions?

- Arrow functions are a concise way to define functions in JavaScript.
- They differ from regular functions in how they handle the this keyword, as arrow functions do not have their own this binding.
- Arrow functions are defined using the => syntax.
- They are often used for short, simple functions.

12.What is the difference between "==" and "===" in JavaScript?

== is the equality operator and performs type coercion. It compares values after converting them to a common type.

=== is the strict equality operator and does not perform type coercion. It compares values without type conversion

13.What is an event in JavaScript, and how do you handle events in the browser using JavaScript?

- An event in JavaScript represents something that happens in the browser, such as a user clicking a button or a page finishing loading.
- You can handle events by attaching event listeners to DOM elements using methods like addEventListener.
- Event listeners specify a function to execute when a specific event occurs.

14.What is a loop, and how do you use "for" and "while" loops in JavaScript to iterate over data?

- A loop is a control structure that allows you to repeat a block of code until a certain condition is met.
- The for loop is used when you know the number of iterations in advance. It has three parts: initialization, condition, and iteration.
- The while loop is used when the number of iterations is not known in advance, and it continues as long as a specified condition is true.

15.What is an object in JavaScript, and how do you create and work with objects and their properties?

- An object in JavaScript is a collection of key-value pairs where keys are strings (or symbols in ES6) that act as property names.
- Objects can represent complex data structures and are used to group related data and behavior.
- Objects are created using curly braces {} and properties are accessed using dot notation or bracket notation.

- example

```
const person = {
  name: "John",
  age: 30,
  sayHello: function() {
    console.log(`Hello, my name is ${this.name}.`);
  }
};
```

16.What is a data type in JavaScript? Can you name some primitive data types in JavaScript?

In JavaScript, a data type defines the kind of data that a variable can hold. Some primitive data types in JavaScript include numbers, strings, booleans, null, undefined.

17.What are arrays in JavaScript, and how do you create and manipulate them?

- Arrays are data structures in JavaScript used to store and manipulate collections of data.

- You create an array using square brackets [], and elements are separated by commas.
- You can access array elements by their index, and you can add, remove, or modify elements using various array methods like push, pop, splice, etc.

18.. Explain what JSON is, and how do you parse JSON data in JavaScript?

- JSON (JavaScript Object Notation):
- JSON is a lightweight data interchange format often used for data exchange between a server and a web application.
- It's a text-based format that represents data as key-value pairs, similar to JavaScript objects.
- You can parse JSON data in JavaScript using JSON.parse() to convert a JSON string into a JavaScript object.

19.What is the ternary (conditional) operator in JavaScript, and how is it used to create concise conditional statements?

- The ternary operator ? is a concise way to write conditional (if-else) statements in JavaScript.
- It takes a condition, and if the condition is true, it returns one value; otherwise, it returns another value.
- Example: condition ? trueValue : falseValue

20.. What is the Document Object Model (DOM), and how do you interact with it using JavaScript?

- Document Object Model (DOM):
- The DOM is a programming interface provided by browsers to interact with web page content.
- You can use JavaScript to manipulate and modify the structure and content of web pages by selecting and modifying DOM elements.
- Common DOM methods include getElementById, querySelector, appendChild, and more.

21.Advantages and disadvantages of Javascript.

Advantages:

- Widely supported in web browsers, making it essential for web development.
- Versatile language used for both front-end and back-end development (Node.js).

- Supports asynchronous programming for responsive web applications.
- Has a vast ecosystem of libraries and frameworks.

Disadvantages:

- Can be a source of security vulnerabilities if not used carefully.
- Differences in browser implementations can lead to compatibility issues.
- Single-threaded nature can cause performance bottlenecks in CPU-intensive tasks.
- Lack of strong typing can lead to runtime errors that are harder to catch.