



SHARABATI

Fabric Specification

Denim

Date:	17.07.2022	Status:	Canceled
Code:	DRS503330	Quality Control :	4 Point System
Type:	Denim Stretch	Weave:	Fancy
Fabric Name:	COSTA /W OCEAN	Finishing:	CK + H.S
Composition:	97.5CO + 2.5EA	Color:	Ocean Blue /7.5
Shade Control:	Stone wash 45min		

Physical Properties		Actual	Unit	Tolerance		Standards	Remarks
Weight		9.25	oz/y²	±5%		ASTM D3776 (2020)	Unwashed
Weight Washed		9.75	oz/y²	±5%		ASTM D3776 (2020)	Washed AATCC 135-2004(3x60HL)
Total Average Width		160	cm	-		ASTM D3774-18 (2024)	Unwashed
		63	inch	-			
Minimum Cuttable Width		155	cm	-		ASTM D3774-18 (2024)	Unwashed
		61	inch	-			
Shrinkage Warp		2.5	%	min. 0	max. 4	AATCC 135 (2004)	Washed (3x60HL)
Shrinkage Weft		11	%	±2		AATCC 135 (2004)	Washed (3x60HL)
Movement		0	%	±3		AATCC 179 (2004)	Washed (3x60HL)
Tear Warp	ELMENDORF	5890	g	min. 3820		ASTM D1424 (2021)	Washed (3x60HL)
		13	lbf	min. 8.45			
Tear Weft	ELMENDORF	3850	g	min. 2500		ASTM D1424 (2021)	Washed (3x60HL)
		8.5	lbf	min. 5.525			
Tensile Strength Warp		81640	g	min. 53060		ASTM D5034 (2021)	Washed (3x60HL)
		180	lbf	min. 117			
Tensile Strength Weft		36280	g	min. 23580		ASTM D5034 (2021)	Washed (3x60HL)
		80	lbf	min. 52			
Stiffness		0.6	KGF	±0.2		ASTM D4032 (2012)	Unwashed
Elasticity		30	%	min. 26	max. 34	ASTM D3107 (4lb)- Modified	Washed AATCC 135-2004(3x60HL)
Growth		6	%			ASTM D3107 (4lb)- Modified	Washed AATCC 135-2004(3x60HL)
Abrasion Resistance	MARTINDALE		rub/s	-		ISO 12947-2 (1998)	Max 20.000 Rubs or 2 Thread Breaks
Seam Slippage Warp			mm			ISO 13936-2 (120N)	Washed
Seam Slippage Weft			mm				
Pilling Tendency	MARTINDALE		-			ISO 12945-2 (2000)	Washed
pH		6	-	min. 4.5	max. 7.5	ISO 3071: (2020)	
Crocking Dry (Rubbing)		4	-			ISO 105-X12 (2001)	Unwashed
Crocking Wet		2	-			ISO 105-X12 (2001)	Unwashed

Care Instructions

Wash	Iron	Chlorinate	Dry clean	Temporal Dry

Notes :

- The roll length is measured by calibrated inspection with machines tolerance ± 1% : ISO 3933:1976.
- Please inspect before cutting, no claims acceptable after cutting.
- Please note that heavy washing recipes (stone washes, heavy brushing-scrapping, and use of bleach or similar chemicals) may cause problems, Therefore the customer should do the washing trials before bulk production.
- Please be informed that we cannot accept any claim after six Months from invoice issuing date.

