



OFFICE  
Huzur Mahallesi Cendere Caddesi  
No: 114 B Blok Kat:26 No:377  
Skyland Sariyer Istanbul Turkey  
PostCode: 34396  
P. +90 212 465 80 99 | Ext  
F. +90 212 465 82 32

MILL  
Public Free Zone  
Damietta, EGYPT  
P: +20 (57) 229 23 30 Pbx  
F: +20 (57) 229 2331 Pbx

## FABRIC SPECIFICATION

ARTICLE NAME : KARDIYA BLACK OD BLACK

PRD NO : 99469

SAMPLE NAME : D291-F STR OD BLACK

COLOR: : NERO

DATE: 28.2.2023

| CONSTRUCTION |                         | QUALITY CONTROL        |                    |
|--------------|-------------------------|------------------------|--------------------|
| WEAVE        | 3/1 RHT                 | QUALITY CONTROL SYSTEM | 4 POINT SYSTEM     |
| COMPOSITION  | %80CO %1EL %11CLY %8EME | SHADE CONTROL SYSTEM   | 555                |
| NOTE         |                         | SHADE CONTROL RECIPE   | ENZYME WASH 10 MIN |

| PHYSICAL                    | Test Method      | units             | MIN          | AVG          | MAX          | REMARKS    |
|-----------------------------|------------------|-------------------|--------------|--------------|--------------|------------|
| WEIGHT                      | ASTM D3776       | gr/m2<br>ouns/yd2 | 298<br>8.79  | 313<br>9.25  | 329<br>9.70  | RAW FABRIC |
| WEIGHT                      | ASTM D3776       | gr/m2<br>ouns/yd2 | 346<br>10.20 | 364<br>10.75 | 383<br>11.30 | 1*90 HL    |
| USABLE WIDTH                |                  | cm                | 140          |              |              | RAW FABRIC |
| SHRINKAGE Warp              | ISO 6330         | %                 | 0            |              | -4           | 1*90 HL    |
| SHRINKAGE Weft              | ISO 6330         | %                 | -13          |              | -17          | 1*90 HL    |
| SKEW MOVEMENT               | LS&CO Method 2   | %                 | -3           |              | 3            | 1*90 HL    |
| TEAR STRENGTH Warp          | ASTM D1424       | gr                | 4000         |              |              | 1*90 HL    |
| TEAR STRENGTH Weft          | ASTM D1424       | gr                | 2800         |              |              | 1*90 HL    |
| TENSILE STRENGTH Warp       | ASTM D5034       | kg                | 55           |              |              | 1*90 HL    |
| TENSILE STRENGTH Weft       | ASTM D5034       | kg                | 30           |              |              | 1*90 HL    |
| STIFFNESS                   | ASTM D4032       | kg                |              | N/A          |              | RAW FABRIC |
| WARP ELONGATION             | ASTM D3107       | %                 |              | N/A          |              | RAW FABRIC |
| WARP ELASTICITY             | ASTM D3107       | %                 |              | N/A          |              | 1*90 HL    |
| WEFT ELASTICITY             | ASTM D3107       | %                 | 38           |              | 46           | 1*90 HL    |
| WARP GROWTH                 | ASTM D3107       | %                 |              | N/A          |              | 1*90 HL    |
| WEFT GROWTH                 | ASTM D3107       | %                 |              |              | 7            | 1*90 HL    |
| SEAM SLIPPAGE (Warp x Weft) | ASTM D1683       | kg                |              | N/A          |              | 1*90 HL    |
| pH                          | ISO 3071/Morapex | Value             | 4.5          |              | 7.5          | RAW FABRIC |

| COLOUR FASTNESS | Test Method | units  | MIN | AVG | MAX | REMARKS    |
|-----------------|-------------|--------|-----|-----|-----|------------|
| CROCKING Dry    | AATCC 8     | rating | 3   |     |     | RAW FABRIC |
| CROCKING Wet    | AATCC 8     | rating | 1.5 |     |     | RAW FABRIC |

| VISUAL                              | Test Method | units    | MIN | AVG | MAX | REMARKS |
|-------------------------------------|-------------|----------|-----|-----|-----|---------|
| Dp/100m2                            |             | dP       |     | 14  | 20  |         |
| Major Defects/100m                  |             | #defects |     |     | 5   |         |
| Piece Length                        |             | MT       | 15  |     |     |         |
| Roll Length                         |             | MT       | 30  |     |     |         |
| #Piece / Roll                       |             | pcs      |     |     | 3   |         |
| Max SHADE(for 0<>5000 mt shipments) |             | Value    |     |     | 4   |         |
| Max SHADE(for 5000<>10000mt shipm   |             | Value    |     |     | 6   |         |
| Max SHADE(for 10000< mt shipments)  |             | Value    |     |     | 8   |         |

| Care Instructions                                                                                                                                 | Certifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fabric:<br><br>Garment:<br><br>Inside-out; Wash&Dry Separately |          |