

CONCISE DESCRIPTION OF RELEVANCE: THIRD-PARTY SUBMISSION UNDER 37 CFR § 1.290

U.S. Application No. 19/318,450 (Publication No. US 2026/0070232 A1)

Document 3: U.S. Patent No. 2,379,596 (“Document 3”)

First Named Inventor: James W Seamans

Issue Date: July 3, 1945

Title: Magnetic lifting device

This document discloses a magnetic lifting device for manipulating metal plates, which includes a horseshoe magnet with spaced magnetic legs, non-magnetic clips attached to the magnet legs, and a pusher bar for aligning workpieces, where magnetic contact can be broken by a rocking movement. Its potential relevance to the claims of the above-identified application is set forth below.

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 1: “a number of pole shoes attached to the housing, wherein each pole shoe has a workpiece contact surface and is designed to guide a magnetic field portion of the magnet to the workpiece contact surface”	The reference discloses non-magnetic clips H that are insulated as at H from the bases 12 of the magnet legs 8 and 9, and are preferably made of brass, aluminum, or similar non-magnetic material. “Clips H] are insulated as at H from the bases 12 of the magnet legs 8 and 9 I The clips are preferably made of brass, aluminum, or similar non-magnetic material.” • Paragraph [0019]
Claim 6 (the first projection and the second projection are adjacent to one another)	The reference discloses a horseshoe magnet 'I having spaced magnetic legs 8 and 9. “a horseshoe magnet 'I, having spaced magnetic legs 8 and 9.” • Paragraph [0019]
Claim 7 (The magnetic gripper (10) according to claim 1, wherein the magnetic gripper (10) has a positioning device (56) for positioning the ferromagnetic workpiece (72) on the workpiece ...)	The reference discloses a pusher bar 12 that is adjustably secured at one end as at M to the handle 5, and has the body thereof extending at an angle to the handle. “As disclosed to advantage in the drawing, the numeral 12 indicates a pusher bar that is adjustably secured at one end as at M to the handle 5, and has the body thereof extending at an angle to the handle ...” • Paragraph [0020]
Claim 9 (The magnetic gripper according to claim 1, wherein the magnet is displaceable electrically, pneumatically, or mechanically between the gripping position and the release position)	The reference discloses that a movement of the device in the direction of the arrow of will effect a breaking of the magnetic contact occasioned by a rocking of the clips. “After the plates have been suitably aligned, as disclosed in Fig. 3, a movement of the device in the direction of the arrow of Fig. 3 will effect a breaking of the magnetic contact occasioned by a rocking of the ...” • Paragraph [0022]

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 14 (A magnetic gripper system, the magnetic gripper system comprising)	The reference discloses a device or apparatus for manipulating metal plate, which is a hand operated implement for pulling together sheet metal plates, iron, angles, and beams to be tack welded. “This invention relates to a device or apparatus for manipulating metal plate and has particular reference to a hand operated implement for pulling together sheet metal plates, iron, angles, and beams to be tack welded.” • Paragraph [0009] • Paragraph [0019]