

CONCISE DESCRIPTION OF RELEVANCE: THIRD-PARTY SUBMISSION UNDER 37 CFR § 1.290

U.S. Application No. 19/318,450 (Publication No. US 2026/0070232 A1)

Document 8: GB 874600 A (“Document 8”)

First Named Inventor: Joseph Crawford Williamson

Publication Date: August 10, 1961

Title: Improvements in or relating to magnetic chucks and similar holding devices

This document discloses a magnetic chuck or holding device for gripping a workpiece, which includes a magnetic assembly that moves between an "ON" (gripping) and "OFF" (release) position, and pole-pieces that provide holding effort and cooperate with the magnetic assembly to guide the magnetic field. Its potential relevance to the claims of the above-identified application is set forth below.

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 1: “A magnetic gripper for gripping a ferromagnetic workpiece, said magnetic gripper comprising”	The reference discloses a magnetic chuck or holding device for gripping a workpiece. “A magnetic chuck or holding device in which the holding effort is provided at the edges 4A, 4F, 4C, 4D of at least one pair of plate pole-pieces 2A, 2B, Figs. 1 and 3, cooperating with an assembly of permanent ...” • Abstract
Claim 1: “a magnet which is arranged in the housing and which is displaceable along a displacement direction between a gripping position for gripping the ferromagnetic workpiece and a release position for releasing the ferromagnetic workpiece”	The reference describes a magnetic assembly 1A, 1B that moves between an "ON" position (gripping) and an "OFF" position (release). “provision for relative movement of the pole pieces 2A, 2B and the magnetic assembly 1A, 1B, between an " ON " position (Fig. 1) in which each pole-piece is in surface contiguity with an area of magnetic material of one ...” • Abstract
Claim 1: “a number of pole shoes attached to the housing, wherein each pole shoe has a workpiece contact surface and is designed to guide a magnetic field portion of the magnet to the workpiece contact surface”	The reference describes plate pole-pieces 2A, 2B that provide holding effort and cooperate with a magnetic assembly to guide a magnetic field portion. “A magnetic chuck or holding device in which the holding effort is provided at the edges 4A, 4F, 4C, 4D of at least one pair of plate pole-pieces 2A, 2B, Figs. 1 and 3, cooperating with an assembly of permanent ...” • Abstract

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 3 (The magnetic gripper according to claim 1, wherein each pole shoe has an active structure for directing the magnetic field portion)	The reference describes plate pole-pieces 2A, 2B that provide holding effort and cooperate with a magnetic assembly, which implies directing a magnetic field portion. “A magnetic chuck or holding device in which the holding effort is provided at the edges 4A, 4F, 4C, 4D of at least one pair of plate pole-pieces 2A, 2B, Figs. 1 and 3, cooperating with an assembly of permanent ...” • Abstract
Claim 7 (The magnetic gripper (10) according to claim 1, wherein the magnetic gripper (10) has a positioning device (56) for positioning the ferromagnetic workpiece (72) on the workpiece ...)	The reference discloses a non-magnetic ring 55 and a rim 44 that enables the device to hold itself against a permeable mass and carry a dial. “A non-magnetic ring 55 surrounds the magnet plates 43A, 43B, the rim 44 enabling the device when turned to the " ON " position, to hold itself against a permeable mass, e.g. a surface plate, and to carry a dial ...” • Abstract
Claim 8 (The magnetic gripper according to claim 1, wherein the number of pole shoes includes a first pole shoe and a second pole shoe)	The reference describes at least one pair of plate pole-pieces 2A, 2B, which function as a first and second pole shoe. “A magnetic chuck or holding device in which the holding effort is provided at the edges 4A, 4F, 4C, 4D of at least one pair of plate pole-pieces 2A, 2B, Figs. 1 and 3 ...” • Abstract
Claim 9 (The magnetic gripper according to claim 1, wherein the magnet is displaceable electrically, pneumatically, or mechanically between the gripping position and the release position)	The reference describes magnet plates 21A, 21B that are rotatable by a lever-operated mechanism, which corresponds to mechanical displacement between the gripping and release positions. “The magnet plates 21A, 21B are rotatable in unison by a lever-operated cross-shaft and bevel pinion and quadrant, the shafts 20 being geared together.” • Abstract
Claim 14 (wherein, in a gripping state, the magnet is in the gripping position, and the ferromagnetic workpiece is pressed against each workpiece contact surface by means of a magnetic ...)	The reference discloses that a permeable workpiece is held when the magnetic assembly is in the "ON" position, indicating that the workpiece is pressed against the pole-pieces by a magnetic force. “A permeable work-piece is held when completing the circuit across the pole-pieces with the magnetic assembly is in the "ON" position ...” • Abstract