

CONCISE DESCRIPTION OF RELEVANCE: THIRD-PARTY SUBMISSION UNDER 37 CFR § 1.290

U.S. Application No. 19/318,450 (Publication No. US 2026/0070232 A1)

Document 7: JP 2007301640 A (“Document 7”)

First Named Inventor: Takeshi Ide

Publication Date: November 22, 2007

Title: Faceplate for magnetic chuck

This document discloses a faceplate for a magnetic chuck that releasably attracts a magnetic material such as a workpiece, featuring first and second pole shoes and spacers, and a magnetic flux generation source that can be switched between an excited and non-excited state. Its potential relevance to the claims of the above-identified application is set forth below.

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 1: “A magnetic gripper for gripping a ferromagnetic workpiece, said magnetic gripper comprising”	The reference discloses a magnetic chuck that releasably attracts a magnetic material such as a workpiece. “The present invention relates to a face plate for a magnetic chuck that releasably attracts a magnetic material such as a workpiece.” • Paragraph [0004]
Claim 1: “a magnet which is arranged in the housing and which is displaceable along a displacement direction between a gripping position for gripping the ferromagnetic workpiece and a release position for releasing the ferromagnetic workpiece”	The reference discloses a magnetic flux generation source including an electromagnet device with an iron core and an exciting coil, and a permanent magnet device with fixed and movable magnets. “The magnetic flux generation source includes an electromagnet device including an iron core and an exciting coil wound around the iron core, a permanent magnet device including a plurality of fixed permanent magnets and a plurality of movable magnets, and ...” • Paragraph [0071]
Claim 1: “a number of pole shoes attached to the housing, wherein each pole shoe has a workpiece contact surface and is designed to guide a magnetic field portion of the magnet to the workpiece contact surface”	The first and second magnetic pole pieces 20 and 22 and the spacer 24 jointly form a work surface for attracting the magnetic material. “The first and second magnetic pole pieces 20 and 22 and the spacer 24 jointly form a work surface for attracting the magnetic material on the side opposite to the main body 12.” • Paragraph [0090]

Claim language (US 2026/0070232 A1)	Relevant disclosure of this document
Claim 2 (The magnetic gripper according to claim 1, wherein the housing extends along a longitudinal axis)	The housing 18 is manufactured in the shape of a narrow box that is long in the longitudinal direction (first direction) of the main body 12. “The housing 18 is manufactured in the shape of a narrow box that is long in the longitudinal direction (first direction) of the main body 12.” • Paragraph [0061]
Claim 8 (The magnetic gripper according to claim 1, wherein the number of pole shoes includes a first pole shoe and a second pole shoe)	The faceplate includes a plurality of first pole shoes and a plurality of second pole shoes. “This faceplate includes a plurality of first pole shoes disposed at some interval apart in a first direction and being long in a second direction crossing with the first direction, a plurality of second pole shoes each disposed between the ...” • Abstract • Paragraph [0164]
Claim 9 (The magnetic gripper according to claim 1, wherein the magnet is displaceable electrically, pneumatically, or mechanically between the gripping position and the release position)	When the supply of current to the exciting coil 20 is stopped, the work surface is brought into a non-excited state, and the attracted magnetic body is released. “When the supply of current to the exciting coil 20 is stopped, the work surface is brought into a non-excited state, and the attracted magnetic body is released.” • Paragraph [0168]
Claim 14 (wherein, in a release state, the magnet is in the release position and the ferromagnetic workpiece is not pressed, by means of a magnetic force, against each workpiece contact ...)	When the supply of current to the exciting coil 20 is stopped, the work surface is brought into a non-excited state, and the attracted magnetic body is released. “When the supply of current to the exciting coil 20 is stopped, the work surface is brought into a non-excited state, and the attracted magnetic body is released.” • Paragraph [0168] • Paragraph [0004]
Claim 16 (The magnetic gripper according to claim 1, wherein the receptacle is in the form of a groove)	The face plate 14 is provided with a plurality of first grooves having a predetermined depth dimension. “In the example shown in the drawing, the face plate 14 is provided with a plurality of first grooves having a predetermined depth dimension and a constant pitch from the upper surface side of the plate body having a predetermined ...” • Paragraph [0113]