# HOTEL CHAIN MANAGEMENT SYSTEM



## MYSQL QUERIES ON NORMALIZATION PROJECT

GROUP 16

Nimra Ashraf & Noor Fatima 110829 & 110830 MORNING

Submitted to:

Mam Sehrish Khan

11/05/2025

#### TABLE OF CONTENTS

- 1. DESCRIPTION
- 2. ENTITY RELATIONSHIP DIAGRAM
- 3. RELATIONAL SCHEMA
- 4. SQL QUERIES
  - ♣ SHOW DATABASES
  - ♣ CREATING DATABASE &

TABLES

- DESCRIBE TABLES
- ♣ SELECT
- INSERT INTO
- ALTER TABLES
- ♣ TABLE UPDATION
- - ARITHMETIC OPERATIONS
  - ♣ RELATIONAL OPERATIONS
- ♣ AGGREGATE FUNCTIONS
  - · ORDER BY CLAUSE
- ♣ GROUP BY CLAUSE

- \* TABLE ALIAS
  - WHERE CLAUSE
- # DISTINCT COMMAND
- ♣ BETWEEN COMMAND
- 4 COUNT
- AND & OR
- IN.
- 4 LIKE
- ♣ IS NULL & IS NOT NULL
- 4 DELETE
- ♣ DROP.
- ♣ TRUNCATE
  - ♣ GRANT
- ♣ PRIVILEGE
- 5. NORMALIZATION TABLES
- 6. PRACTICAL IMPLEMENTATION OF QUERIES

#### **DESCRIPTION**


SQL stands for structure query language. It is a widely used, open source relational database management system.

A hotel chain management system provides a centralized platform for managing multiple hotel properties within a chain. This database would store information about different hotels, including room details, staff managing, reservations, guest records pricing information etc.

#### Pros:

- Scalability
- Reliability
- Cost effectiveness
- Flexibility

## ENTITY RELATIONSHIP DIAGRAM



### ⇒ RELATIONAL SCHEMA

- 1.hotel\_branch (h\_id, h\_name, h\_address, staff\_id)
- 2.staff (s id, s name, s address, s role)
- 3.room\_booking (R\_id, R\_no, check\_in\_date, check\_out\_date, weekend\_pricing, holiday pricing, early bird offers, s\_id)
- 4. customer (c id, c name, c address, r id)
- 5.loyalty\_points (points\_id, upgrade\_points, service\_points, cus\_id)
- feedback (f\_id, f\_type, comment, customer\_id)
- 7.pre\_order (order\_id, meal, taxi\_service, cust\_id)
- 8. task (t\_id, type, s\_id)

### **SQL QUERIES**

#### Show DATABASES

Show all databases and tables placed in a database MySQL use the following command:

- ⇒ show databases;
- ⇒ show tables;

#### CREATE DATABASE & TABLES

Create a new database or table.

- ⇒ create database;
- ⇒ create table table\_name (attribute datatype (size), ...);

#### USING DATABASE

Use a database already saved in MySQL.

⇒ use database database\_name;

#### DESCRIBE TABLES

To see the constraints we have assigned to tables, DESCRIBE keyword is used.

⇒ DESCRIBE table\_name;

#### SELECT

Used to retrieve rows selected from one or more tables.

- ⇒ Select \* from table\_name;
- ⇒ Select attribute1\_name from table\_name where attribute2 name='--';

#### INSERT INTO

Insert values in tables.

⇒ INSERT INTO table\_name values ('attribute' datatype (value), ....);

#### ALTER TABLES

Used for many purposes such as:

- 1.To rename a column of a table
- ⇒ ALTER table table\_name RENAME COLUMN column\_name from existing\_name to new\_name;
- 2. To add a new column in a table
- ⇒ ALTER table table\_name ADD column datatype (size);

#### 3.To make an attribute foreign key

⇒ ALTER table table\_name ADD column\_name

FOREIGN KEY REFERENCES

referencetable name (P.K);

#### TABLE UPDATION

To reset the values of attributes in a table.

⇒ Update table\_name set attribute='value' WHERE attribute\_PK='target-value';

#### TABLE CONTRAINTS

There are two constraints for tables, Primary key and Foreign key.

#### Primary Key:

The attribute of a table on which all the other attributes of that depend.

#### Foreign Key:

When Primary key of a table is used in another table, it becomes Foreign key.

⇒ ALTER table table\_name ADD FOREIGN KEY (key\_name) REFERENCES reference\_table (P.K);

#### Arithmetic Operations

Arithmetic operations include operators such as +, -, \*,

/ etc. to perform addition, subtraction, multiplication
and division of two attributes.

⇒ select attribute operator value from table;

#### Logical / Relational Operations

Logical operations include operators such as >, <, <=, >=, !=, == etc. to relate any two attributes of a table.

⇒ select attribute1 from table\_name where attribute2 relational operator value;

#### Aggregation Functions

Aggregate functions include avg, max, min etc. operations.

⇒ select aggregate\_function (attribute) from table;

#### ORDER BY

ORDER BY keyword is used to sort the values of

tables in ascending or descending order. By default ascending order is set. Otherwise for sorting the records in descending order DESC order is used. For ascending ASC and descending DESC is used.

Syntaxes of above two orders are:

- ⇒ select \* from table ORDER BY attribute DESC;
- ⇒ select \* from table ORDER BY attribute ASC;

#### GROUP BY

GROUP BY clause is very important used to group rows from a table based on the values of one or more column. It is used with aggregate functions like AVG, MAX, MIN, SUM and COUNT to perform calculations on grouped data. Also we can perform operations on group within the group.

#### Syntax:

⇒ select aggreagate\_function (attribute) from table GROUP BY attributes;

#### AS

The AS keyword in MySQL is used to assign an alias to a table or column, making it easier to reference or improving readability. It allows for temporary renaming with a query, which can simplify complex queries and result sets.

#### Where

This clause is used to filter records. It is used to extract only those records that fulfill a specified condition.

#### DISTINCT

The DISTINCT keyword in MySQL is used to remove duplicate records from the results of a SELECT query. It ensures that the query returns only unique values in the specified columns.

#### Syntax:

⇒ select DISTINCT attribute from table;

#### BETWEEN

The BETWEEN clause is used to show the values/
contents of the table between a given limit. It filter the
result set within a specified range.

#### Syntax:

⇒ select column\_name from table where column\_name BETWEEN value1 AND value2;

#### Count & Count(\*)

Used to count the number of rows in a table. This function counts all rows regardless of whether they contain NULL values.

#### Syntax:

- ⇒ select count (\*) attribute\_name from table;
- ⇒ select count (attribute name) from table;

#### HAVING

The HAVING clause is similar to the WHERE clause but is specifically applied after grouping and aggregation, allowing you to filter on the results of aggregate functions like COUNT, SUM, AVG, and others.

#### Syntax:

⇒ select aggreagate\_function (attribute) from table GROUP BY attributes HAVING count (attribute) >1;

#### AND & OR

The AND & OR operators are used to filter records based on more than one conditions:

- The AND operator displays a record if all the conditions separated by AND are true.
- The AND operator displays a record if any of the conditions separated by AND are true.

#### IN

The IN operator allows you to specify multiple values in a where clause. It is a shorthand for multiple OR conditions.

⇒ SELECT attribute\_name(s) FROM table\_name

WHERE attribute\_name IN (value1, value2, ...);

#### LIKE

The LIKE operator is used in a WHERE clause to search for a specified pattern in a column.

#### Syntax:

- ⇒ SELECT column1...FROM table\_name
  WHERE columnN LIKE pattern;
- The percent sign (%) represents zero, one, or multiple characters
- The underscore sign (\_) represents one, single character

#### IS NULL & IS NOT NULL

These keywords are used for checking that the values of attributes checked are **NULL** or not.

#### Syntax:

⇒ select attribute\_name from table where attribute IS NULL; ⇒ select attribute\_name from table where attribute IS NOT NULL;

#### **JOINS**

Joins allows to retrieve related data from multiple tables in a single query, avoiding the need for different separate queries. There are multiple types of joins such as inner, right, left etc.

#### Syntax:

⇒ Select column\_list from table1 JOIN table2 ON table1.
column = table1;

#### INNER JOIN:

The joins in which both the tables have matching values in them are called inner join.

#### Left Join:

This join return all rows from the left table and matching rows in right table.

#### Cross join:

A cross join is type of join that return cartesian product of rows from the tables in the join.

#### Equi join:

It is join operation in sql that combines two table based on a matching column between them.

#### Right Join:

This join return all rows from right table and matching rows from left table.

#### VIEWS

A MySQL view is a predefined select query that operates on existing data without duplicating it. A view acts as a virtual table.

#### Syntax:

⇒ create or replace VIEW view\_name AS select column1, column2 from table\_name where condition;

#### DELETE

DELETE statement is used to delete rows in a table.

It deletes a specific row using where clause.

#### Syntax:

⇒ delete from table where column\_name= 'value';

#### DROP

DROP statement is used to delete the whole table along with table structure, attribute and indexes.

#### Syntax:

⇒ drop table table name;

#### TRUNCATE

The truncate statement is used to delete all data in the table not the whole table.

#### Syntax:

⇒ truncate table name;

#### Sub Query

Subqueries are also known as inner queries or nested queries. It is embedded inside another query and acts as input or output for that query.

#### Syntax:

⇒ Select column1, column2... from table where column operator (select column from another\_table where condition); column1, column2, ...: The columns you want to retrieve.

#### GRANT

Grant is a statement used to assign privileges to user accounts, allowing them to perform specific actions on database projects.

#### **PRIVILEGES**

Privileges are the rights or permissions assigned to users that determine what actions they can perform on the database.

### NORMALIZATION TABLES



#### CREATE DATABASE HOTEL\_CHAIN

#### **CREATE Hotel\_Branch Table**



#### INSERTING VALUES IN HOTEL\_BRANCH



#### 3 NF OF HOTEL\_BRANCH



#### CREATE STAFF TABLE



#### INSERTING VALUES IN STAFF

C.H. C. Name C. antifesti C. Celli C. III	model reception during the terrorial		illiena (0.		Political Communic Committee Committ
1 have selection manager 10 have selection manager 10	내	1,160	1,1111900		111411455
1 mai jann feannis 1		Status	Selitare	temper	10 12 13 13

#### 3RD NORMAL FORM OF STAFF

```
resign in lect colors, confront in

resign in lect colors, confront in

resign in lect colors, colors, color from mark

resign in least colors colors

butter include colors

resign in least colors

resign in least (1 to sec)
```

#### ADD s\_id COLUMN IN HOTEL BRANCH TABLE



#### CHANGE COLUMN NAME (FROM s\_id TO staff\_id)

MI) ACH BIS OK S SAMBLE SAMBLE	talle oro de ron of second solicates: 1		10.0	-0041/894-192	10 XD-11
FIET	TO I	H	Keg	octailt	totra
i di Lidon	int Variate (35) Canceller (35) fart	各点的	PAI	発展を	

#### MAKE staff\_id FOREIGN KEY

```
The state of the s
```

#### INSERTING VALUES IN FOREIGN KEY

```
mostly thomato word struck set staff the 1' where H ide 1990;

Surry in 1 row affection (C.D. suc)

White Protection i Charges: 1 Workings 0

White Protection is Charges: 1 Workings 0

Where H ide 1990;

Surry in 1 row affection (C.D. suc)

Surry in 1 row affection (C.D. suc)
```

#### SELECT FROM HOTEL BRANCH

#### CREATE ROOM\_BOOKING TABLE

		too 1, (1) 1 (1)	overs) e Valieta Di seci	ers avi
-	-	30	tefill):	Entru
素材料的內容	医原性 医原生	7	SPEEFE	
	15世 年世世世	Tiple   Holl Tiple   Holl Fig. Ma Fig. Ma Fi	150 m 151 m	Tak i kulli sej i kefault

## MODIFY CHECK\_IN & CHECK\_OUT DATES

#### DESCRIBE ROOM\_BOOKING

riielid	CE SIL MY MINIT	tatra
reschi dividuality dividuality dividuality of chip wilday of chip wilday of chip wilday of chip wilday of chip		

## MODIFY EARLY\_BIRD\_OFFERS & INSERTING VALUES

```
egaph with table has been possing and process and interfere various (20);

Congress of the constant of (0.00 pec)

Congress of the constant of
```

#### SELECT FROM ROOM\_BOOKING

roceid	0.000	ded_in_date	check contidate	Meet the Total east	roi loay_arteing	
N	302	205-01-35	2025-01-25	E00	5000	474
	504	205-37-34	5225-02-05	736	8003	304
	501	205-37-34	2025-02-08	836	12005	305

#### ADD STAFF\_ID FOREIGN KEY IN ROOM BOOKING

ecoren: I Dapi ent					
(April ) Distribut (Doc	Pref (still				
Field	Type:	141	199	Defanit	Estra
name to ripo sheek incluses sheek out data waxand infiling out lot his orders traffical orders traffical	715 715 912 912 715 970 970 970 970 970 970 970 970 970 970	<b>多数是用的强烈者</b>	美	<b>美景角音角音</b>	

#### INSERT VALUES IN FOREIGN KEY

```
#### in this complection set STATE_DEA'S where now the 'United States of the Complete State
```

#### SELECT FROM ROOM\_BOOKING

tu ji	1.16	141 141	संग्री भूक व्यक्त	melend of stop	heilder pricing	early simplifiers	群群边
2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2	製器は	2525-01-05 2525-02-04 2525-07-04	765-24-15 2025-22-00 2025-22-00	9025 7003 5001	9010 8010 12010	(3 17 10	-0.00


#### 3 NF OF ROOM\_BOOKING

d)+	54 (450) - unios H. act. c. co. and lan	Correcting, her star.	it mandant	firs fra location (in;	
78	emanupricing	he ide pricing	saly_linkeffen		
提送車	230 250 250 250	9000 8000 12000	400- 100: 100:		

## MAKE ROOM\_ID FOREIGN KEY IN STAFF TABLE

may'e Altik Hery St. I Mileta II Mileta IISCK			60	DOM:	militir)
rtsM	iv.	MIT	69	intuits	inthi.
5 1 1 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	int merchanicho merchanicho merchanicho merchanicho met	agge	fitt fez		
i ruun (in ser rysit):-	00.00 Ser3				

#### CREATE CUSTOMER TABLE



#### ADD MISING C\_ADDRESS COLUMN IN CUSTOMER TABLE

	ns Affected ipricator: LL autwe	12 *11n	E)		
rield	Type:	ugij	ciy	mfait	EXXII
C.W C.Carl F.Sif C.Milhista	fit wrom(15) int wrote(30)	A1 41 A1	ш	11.11. 16.11. 16.11. 16.11.	

#### **INSERTING VALUES**

```
Arrent 2007 Sept (minute values) (U 'see' 12' throughout') (See 'see') (minute values) (minute
```

#### MAKE r\_id FOREIGN KEY IN CUSTOMER TABLE

```
number with table contract on contact on C_dd) nationals now_backing from _00;

party on 3 year affected (0.12 dec)

produced to be blooder; if secology to

produced to contact

produced to the blooder; if secology to

produced to the blooder; if secology to

produced to the blooder; if secology to

produced to the blooder; if secology to the blooder; if secology
```

#### CREATE LOYALTY POINTS TABLE

egio preme nab dre de, 2 cans : egio manem D	ferre	4 41	nts (co rolln)s	int_id 10(10) PkDMAT KEY, service_points DAT(E), upprade_points IsT(E),tus_jd DAT(E)): (U.C4 ist)
rieli	Tyse.		TE)	Setroit Extre
print_id dervice_prints upprace_prints cot_it	HEEK	のはない	HEE	MCT MCT MCT

#### MAKE cus\_id FOREIGN KEY



#### INSERTING VALUES & DESCRIBE

```
Approximation of the contraction of a contract of a contract of the contract o
```

#### CREATE FEEDBACK TABLE


ab reichs	E ferduce;			
al:	Tess	will	XZV.	Estra
fa jo fa type common controver_to	im varcus(20) varcus(30) int	· · · · · · · · · · · · · · · · · · ·	HI	

#### MAKE customer\_id FOREIGN KEY IN FEEDBACK TABLE

```
most) distry just feedback vilues 1001 compliment breat four light;

most) most into feedback vilues 1001 compliment land mostles into the affected to 00 and the compliment land mostles into the affected to 00 and the compliment land mostles into the affected to 00 and the compliment land mostles into the affected to 00 and the compliment land mostles into the affected to 00 and the complete comp
```

#### INSERTING VALUES



#### CREATE PRE ORDER TABLE

and describe	oferen in Padra	AO JUNE	:- NY (%)	145/	
rield	Typt	4.1	te:	befruit:	抽面
order Jd wedd God Jan vicina God Jan vicina	int string(40) arthor(10) int	5世田田田	批		

#### MADE cus\_id FOREIGN KEY

```
nagh affit talle Promer 45 forms 63 four 16 636 astronom anne (2.14);
gara coll majorimore (0.13 m)
scordi d'Implicatori I Vandaşa II
nerther strengt diego
  Field
                                      H.
                                                     tefralt litte
                     "YH!
                                              liv
  ofter 1d
                     ht
                                      10
                                                      瞡
                     etither (4)
egiter (10)
                                      15
                                                     MOL
                                                     WX
  SHI JUNIORS
                                      啦
                                              w.
  CUS_10
                      ĦΪ
                                      153
                                                     搬送
  ena in het El 160 jan
```

#### INSERTING VALUES IN ORDER

```
windly these throughout animal(sec.) beachfact, year, 1982();

public these throughout animal(sec.) beachfact, year, 1982();

public these throughout animal(sec.) beachfact, year, 1982();

public throughout animal animal animal section of the sec.

public throughout animal animal animal section of the sec.

public throughout animal animal animal animal section of the sec.

public throughout animal animal
```

#### CREATE TASK TABLE

#### ADD st\_id FOREIGN KEY AND DESCRIBE IT

#### INSERTING VALUES IN TASK


```
Anny Death | 1907 that anterir not , the same of the common of the commo
```

## PRACTICAL IMPLEMENTATION OF MYSQL QUERIES

#### ARITHMETIC & LOGICAL OPERATIONS ON LOYALTY POINTS TABLE

## LOGICAL OPERATIONS ADDING ph\_no COLUMN IN CUSTOMER






 $\mu$  . The contraction is the contraction of the contraction  $\lambda$ 

### ORDER BY CLAUSE ON CUSTOMER



# GIVING TWO h\_ids SAME NAME



# DISTINCT CLAUSE AND ADDING SALARY COLUMN IN STAFF TABLE


```
From street 14-00 common plants of the common process of the common plants of the common plan
```

# BETWEEN, HAVING AND IN CLAUSES

```
The state of the s
```


```
| The content of the
```

# ARITHMETIC OPERATIONS ON STAFF




# COUNT & COUNT(\*)







### LIKE CLAUSE ON CUSTOMER

# JOINS



# INNER JOIN






# **EQUIJOIN**




# LEFT JOIN



# RIGHT JOIN

# CROSS JOIN





### **DELETE ROW4 FROM STAFF**

		Third		31111	Ca Profession susceptions facts ("Solid Joseff" beind Joseph 1987 - D. California	
and I know	1,410,000	Litela	1277	subseq		
			J	782		
-	5 (4 (4))					
of the same	mierm	K nashiru Danis	-	7		
alla select o						
SE 12.00	CAMPIE	spele :		-149		
				100		

### DROP

# TRUNCATE

### SUBQUERY

```
The to see the second s
```


#### LOWEST SALARY PRINTED


```
The trace of the control of the cont
```

#### MIN SALARY USING GROUP BY FROM S-ID PRINTED

```
the state of the s
```

#### GRANT





#### PRIVILEGES

```
The state of the s
```

