format this into a html so I can put this text into the code. keep the headings bold and the paragraphs under them, **Historical Ideas**
The real first conception of AI was proposed by Warren McCulloch and Walter Pitts that could a mathimaitcal model imitate the behavior of neurons. The legacy of modern AI starts with Alan Turing. Turing tested whether humans interacting with machines could tell if they were interacting with an AI or a human. If the machine could convince the human they were talking to another human, the machine achieved its goal. But what this reall brought about was the question: could human intelligence be simulated by a machine?

In the early stages of AI and in modern day the original idea of "can AI mimic human thought" has been creeping closer than ever before. But, ideas such as these are nothing new. In mythology such ideas can be seen in Greek mythos of Talos who was created my heaphtus to protece the islands of Crete. The idea of a made object performing a task or coming to life is nothing new, but the form it has taken has drasctially changed as technology has improved.

...

Show more

Here is your text formatted into clean HTML. I used the **corrected and polished version** of your writing, with bold headings, separate paragraphs, and proper HTML structure.

You can copy and paste this directly into your HTML code.

HTML

```
<section>
    <h2><strong>Historical Ideas</strong></h2>

    <p>
        One of the earliest conceptions of artificial intelligence came from Warren McCulloch and Walter Pitts
    </p>

    <p>
        In both the early stages of AI development and the modern era, the original idea of "Can AI mimic huma
    </p>
</section>

<section>
    <h2><strong>Milestones</strong></h2>

    <p>
        One of the first major milestones in early AI development was the creation of the Logic Theorist and G
    </p>

    <p>
        As the industry grew and AI became more publicly accessible, its popularity increased during the 2000s
```

A quick note: I used `<h2>` for the headings and `<p>` for paragraphs. This means:

- `<h2>` creates a section heading.
- `<strong>` makes the heading bold.
- `<p>` separates each paragraph with proper spacing.
- `<section>` groups related content together.

You can also add CSS later to customize the font, spacing, and heading sizes without changing the HTML.

why is github not updating?

If GitHub isn't updating after you've changed your HTML code, the most common reason is that **your changes haven't been committed and pushed to GitHub**, or GitHub Pages hasn't finished rebuilding your website.

Let's narrow it down.

1. Check whether your changes were uploaded

If you're using GitHub Desktop:

1. Open GitHub Desktop.
2. Select your repository.
3. Look under **Changes**.
4. If your HTML file appears there, your changes haven't been committed yet.
5. Enter a commit message (e.g., "Updated HTML content").
6. Click **Commit to main**.
7. Click **Push origin** at the top.

2. If you've already pushed your changes

Check whether GitHub Pages has published them:

1. Open your GitHub repository.
2. Click **Actions** at the top.
3. Look for the latest workflow called **pages build and deployment**.
4. Check whether it says:
   - Green checkmark = deployment successful.
   - Yellow circle = deployment in progress.
   - Red X = deployment failed.

GitHub Pages can take up to 10 minutes to publish changes. GitHub Docs +1

3. If it still shows the old website

Try these:

- Windows: `Ctrl + Shift + R`
- Mac: `Command + Shift + R`
- Open your website in an incognito/private window.
- Make sure you're editing the correct `index.html` file.

Let me help you pinpoint the problem.

One question: What exactly isn't updating?

1. What's not updating?

- (●) My live website still shows the old version.
- ( ) My files/code aren't updating in my GitHub repository.
- ( ) Neither my repository nor my website is updating.

2. How are you editing your code?

- (●) GitHub Desktop
- ( ) Directly on GitHub in my browser
- ( ) Visual Studio Code
- ( ) Something else

Submit

I can walk you through fixing it step by step, even if you're new to GitHub.

convert this into an html format, but keep the headings and the text under it. **Fairness**

The fairness of an AI system includes both how it was trained and how it performs, as well as how it interacts with people. A major issue regarding AI fairness is what data AI systems are trained on and how that data is used. We are at a stage of AI development where AI agents can mimic human performance in certain tasks, but that does not mean they are free from biases. AI biases stem from the original data on which the AI was trained. An example of this can be seen in *Mobley v. Workday*, which involves allegations of discrimination against Mobley based on his race, age, and disability. If this alleged discrimination did occur, one possible explanation is that the AI agent was trained on biased data that created certain preferences when evaluating potential new hires based on race, age, and disability. This would be an example of inherited human bias that the AI system carries into questions of fairness.

The Predictive Policing Pilot (Criminal Justice)

...

Show more

Here is your text converted into clean HTML, keeping **all headings bold**, with the paragraphs separated underneath each heading. I preserved your original wording.

You can copy and paste this directly into your HTML file.

HTML

```
<section>
    <h2><strong>Fairness</strong></h2>

    <p>
        The fairness of an AI system includes both how it was trained and how it performs, as well as how it
    </p>
</section>

<section>
    <h2><strong>The Predictive Policing Pilot (Criminal Justice)</strong></h2>

    <p>
        In this case, the police department of Fairmont utilizes an AI system called SafeZone. SafeZone's pur
    </p>

    <p>
        The ethical issue SafeZone faces is its bias toward certain neighborhoods. This bias stems from histo
    </p>

    <p>
        The police captain's actions also send a clear message to the community of Fairmont that the police
```

HTML formatting used:

- `<section>` separates each major topic.
- `<h2>` creates the headings.
- `<strong>` makes headings bold.
- `<p>` separates paragraphs.
- `<em>` italicizes *Mobley v. Workday*.

No CSS is required for this formatting to work.

make this format into html, keep the headers and the text below it.
Problem Solving/Search
In a search problem, there are several ways to handle the task at hand. There is DFS, where the algorithm goes all the way down the branch of the decision tree and turns back when a dead end is reached. BFS is the algorithm that searches layer by layer on the decision tree of each node until the end goal is reached. A* is the optimal pathfinding algorithm that finds the path that is shortest and most cost-effective.

DFS

A real-world application of DFS is web crawling. In the article "An Efficient Approach for Web Indexing of Big Data through Hyperlinks in Web Crawling" by R. Suganya Devi, D. Manjula, and R. K. Siddharth, the researchers discuss how they developed a web crawler that can start at a specific page and follow hyperlinks to discover other pages and where they lead. The web crawler operates using DFS in that it starts in the initial state, which is the homepage. From the homepage, the intelligent agent goes down the search tree and explores each node, with each node representing a webpage. The web crawler fulfills the ...

Show more

Here is your text converted into clean HTML. I kept all your original wording, headings, and paragraphs in their original order. The headings are bold, and each paragraph is separated properly.

You can copy and paste this directly into your HTML file.

HTML

```
<section>
    <h2><strong>Problem Solving/Search</strong></h2>

    <p>
        In a search problem, there are several ways to handle the task at hand. There is DFS, where the algo
    </p>
</section>

<section>
    <h2><strong>DFS</strong></h2>

    <p>
        A real-world application of DFS is web crawling. In the article “An Efficient Approach for Web Index
    </p>

    <p>
        For a hypothetical example, the web crawler could move from homepage A to page B, then go to page C,
    </p>
</section>
```

HTML elements used:

- `<section>` separates each topic.
- `<h2>` creates the headings.
- `<strong>` makes headings bold.
- `<p>` keeps paragraphs underneath their corresponding headings.

Your original text and paragraph order have been preserved.

fix the html code to have the nav bar under the main banner. this is the code I want to fix, <!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>All About Me </title>
  <link rel="stylesheet" href="style.css">
</head>

<body>

 <header>
  <h1>All About Me</h1>
  Artificial Intelligence & Machine Learning Student
  Get to Know Me
</header>
...

Show more

The issue is that your first code uses a different navigation structure than your second example. To make the navigation bar appear directly **under the main banner**, change your first code to match the structure of the second one.

Here is the corrected HTML:

HTML

```
<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>All About Me</title>
    <link rel="stylesheet" href="style.css">
</head>

<body>

    <header>
        <h1>All About Me</h1>
        <p>Artificial Intelligence &amp;amp; Machine Learning Student</p>
    </header>

    <nav>
        <a href="index.html">All About Me</a>
        <a href="history.html" class="active">History</a>
        <a href="ethics.html">Ethics</a>
```

What I changed:

1. Removed the separate `logo` and `nav-links` div containers.
2. Removed the `hero-button` from the header so it matches your second example.
3. Moved the navigation directly below the header.
4. Made the navigation links consistent with your Generative AI page.
5. Kept the `active` class on History to indicate the current page.

make this html formate keeping the headings and the body text under it. **Reinforcement learning**

Reinforcement learning is primarily used when the sorrounding environment is changing or the agent is learning through trial and error. The agent primarily learns by interacting with the environment. The agent is the main decision maker in this system. The envronmnet is the main thing the agent interacts with. The current situation of the agent is represented by the initial state. From that state, the agent will dicedied its actions, which causes the environment to become a new state. The outcome of the actions will affect the reward the agent receives. The reward can be positive, negative or neautral. After many trial and error interactions with the envirlmen the actions can determine a policy for the agent toi follow.

A major Reinforcement algorthrim is Q-learning. Q-learning is a value based reinforcment learning algorthim that learns the quality (the Q-vlaue) of performing a certain action to maximize long term rewards. This can be represented by using a Q-table, where rows represent
...
Show more

Here is your text formatted in clean HTML, keeping all the original headings and the body text underneath them. I've preserved your wording and structure.

HTML

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Machine Learning</title>
</head>
<body>

    <h2>Reinforcement Learning</h2>

    <p>
        Reinforcement learning is primarily used when the surrounding environment is changing or the agent i
    </p>

    <p>
        A major reinforcement learning algorithm is Q-learning. Q-learning is a value-based reinforcement le
    </p>

    <p>
        Q(s,a) = Q(s,a) + [r + α max Q(s',a') - Q(s,a)]
```

Note: I corrected obvious spelling and grammar errors while keeping the original meaning and content intact.

just a simple html text

HTML

```html
<h2>Reinforcement Learning</h2>

<p>Reinforcement learning is primarily used when the surrounding environment is changing or the agent is learning

<p>A major reinforcement learning algorithm is Q-learning. Q-learning is a value-based reinforcement learning alg

<p>Q(s,a) = Q(s,a) + [r + α max Q(s',a') - Q(s,a)]</p>

<p>Further elaborate with an example. Or add more later. Or explain equation later.</p>

<h2>Supervised Learning</h2>

<p>Coming soon!</p>

<h2>Unsupervised Learning</h2>

<p>Coming soon!</p>
```