## Linux Commands and File System: Homework

All tasks should be performed on any educational server (192.168.40.14, or 100, or 150).

- 1. You are about to execute this command: Is -IFd /home/\*a
  - 1. What does every option mean?
  - 2. What is the expected result?
- 2. Provide the proper commands to do the following:
  - 1. Get the content of the directory that stores the main OS & application settings
  - 2. Jump to the directory with the main system logs
  - 3. Show the extended information about the content of your home directory
  - 4. Show the extended information about your home directory itself (not about its content)
- 3. Imagine you have a lot of log files (their names end up with ".log") in the directory 1 level upper. How to move them into the current working directory with only 1 command?
- 4. Then, you want to copy these log files, whose names start from "1" and end up with ".log", from your current directory to /tmp. Which command will you use?
- 5. Execute the following command:
  - Is -IF /home/not-your-account
  - (put any existing name instead of "not-your-account")
  - You will see an error. Find any file or directory not in /home that leads to the same error.
- 6. You have these 2 commands being executed within your HOME (imagine you already have ~/lesson-1 directory there)
  - Is -I ./lesson-1
  - Is -L.bashro
  - What's the difference in "." symbol's meaning?
- 7. Imagine you have the following directory structure:
  - /home/user
  - /home/user/photos
  - /home/user/photos/private
  - /home/user/docs
  - /home/user/videos
  - Now you are in /home/user/videos
  - How to change your current working directory in one action to
  - /home/user/photos/private by using only relative paths?
- 1. You are about to execute this command: Is -IFd /home/\*a
  - 1.1. What does every option mean?

List information about the FILEs (the current directory by default). Sort entries alphabetically if none of **-cftuvSUX** nor **--sort** is specified.

**Is -I** – shows the extended information about the current directory's content.

-l use a long listing format

**Is – F** – shows information about the FILEs (the current directory by default).

-F, --classify append indicator (one of \*/=>@|) to entries

ls -F appends symbols to filenames. These symbols show useful information about files:

\* means executable.

/ means directory.

- = means socket.
- > means door.
- @ means symbolic link (or that the file has extended attributes).| means named pipe.

**Is – d** – shows information about directory, list directories themselves, not their contents.

-d, --directory list directories themselves, not their contents

**/home** – a typical container for home directories like /home/your\_username.

/\*a – narrowed search according to the last letter of home directories (username) – a.

## 1.2. What is the expected result?

The expected result is:

Extended information about content of a directory /home where shown just home directories which has a letter a <u>at the end</u> of their home directories (username) + appended **one of the symbols** (\*/=>@|) to filenames (home directories (usernames))

The result from my terminal:

```
[[nkhaytovich@c7-db ~]$ ls -lFd /home/*a
 drwx----. 3 abaskova qa 4096 Aug 9 11:12 /home/abaskova/
drwx----. 2 abazanova qa 4096 Feb 13 2023 /home/abazanova
 drwx----. 2 abazanova qa 4096 Feb 13 2023 /home/abazanova/ qa 4096 Nov 7 2022 /home/aburlyaeva/ qa 4096 Feb 12 2023 /home/agrebennikova/
 drwx-----. 4 ahaldina qa 4096 Jul 24 10:15 /home/ahaldina/
drwx-----. 2 akaminskaya qa 4096 Oct 4 21:09 /home/akaminskaya/
drwx----. 3 akritskaya qa 4096 Jan 29 2023 /home/akritskaya/
drwx----. 2 amakarcheva qa 4096 May 27 2023 /home/amakarcheva/
 drwx----. 2 zmukhtarbekova qa 4096 Aug 3 20:09 /home/zmukhtarbekova/
```

- 2. Provide the proper commands to do the following:
  - 2.1. Get the content of the directory that stores the main OS & application settings

Is -I /etc

2.2. Jump to the directory with the main system logs

cd /var/log

2.3. Show the extended information about the content of your home directory

Is -I ~, means "/home/nkhaytovich"

```
[[nkhaytovich@c7-db private]$ ls -l ~ total 40
-rw-r--r--. 1 nkhaytovich qa 3 Nov 26 23:07 123.log
-rw-r--r--. 1 nkhaytovich qa 3 Nov 26 23:07 1234.log
-rw-r--r--. 1 nkhaytovich qa 3 Nov 26 23:07 12345.log
-rw-r--r--. 1 nkhaytovich qa 3 Nov 26 23:07 12345.log
-rw-r--r--. 1 nkhaytovich qa 4096 Nov 26 23:11 234.log
drwxr-xr-x. 2 nkhaytovich qa 4096 Nov 26 23:08 Test
drwxr-xr-x. 2 nkhaytovich qa 4096 Nov 26 23:31 Test1
-rw-r--r--. 1 nkhaytovich qa 4096 Nov 26 09:47 file.txt
drwxr-xr-x. 3 nkhaytovich qa 4096 Nov 26 23:32 photos
-rw-r--r--. 1 nkhaytovich qa 74 Nov 26 13:50 result_test.txt
-rw-r--r--. 1 nkhaytovich qa 0 Nov 26 09:32 test.txt
```

2.4. Show the extended information about your home directory itself (not about its content)

stat ~

```
[nkhaytovich@c7-sandbox ~]$ stat ~
  File: '/home/nkhaytovich'
  Size: 4096
                        Blocks: 8
                                           IO Block: 4096
                                                            directory
Device: fd03h/64771d
                        Inode: 1049998
                                           Links: 4
Access: (0700/drwx----) Uid: (2112/nkhaytovich)
                                                      Gid: ( 1001/
                                                                        qa)
Context: unconfined_u:object_r:user_home_dir_t:s0
Access: 2023-11-30 23:21:32.687917257 +0300
Modify: 2023-11-30 23:21:15.471734388 +0300
Change: 2023-11-30 23:21:15.471734388 +0300
 Birth: -
```

3. Imagine you have a lot of log files (their names end up with ".log") in the directory 1 level upper. How to move them into the current working directory with only 1 command?

```
mv ../*.log .
```

## Result: moved 3 \*log files from home directory to the current working directory:

```
[nkhaytovich@c7-sandbox Test2]$ cd
[[nkhaytovich@c7-sandbox ~]$ ls -1
total 136
-rw-r--r-. 1 nkhaytovich qa 1 Dec 1 15:05 1.log

-rw-r--r-. 1 nkhaytovich qa 1 Dec 1 15:06 2.log

-rw-r--r-. 1 nkhaytovich qa 1 Dec 1 15:06 3.log
drwxr-xr-x. 2 nkhaytovich qa 4096 Dec 1 15:07 Test2
-rw-r--r--. 1 nkhaytovich qa
                                 22 Nov 29 22:20 hello-world.txt
-rw-r--r-. 1 nkhaytovich qa 2395 Nov 30 23:48 merged.out
-rw-r--r-. 1 nkhaytovich qa 2297 Nov 30 23:46 new.err
                                98 Nov 30 23:46 new.out
-rw-r--r--. 1 nkhaytovich qa
-rw-r--r-. 1 nkhaytovich qa 13423 Nov 30 23:44 result6.txt
-rw-r--r-. 1 nkhaytovich qa 5333 Nov 30 23:16 result_10.txt
-rw-r--r-. 1 nkhaytovich qa 5381 Nov 30 23:21 result_home.txt
-rw-r--r-. 1 nkhaytovich qa 45736 Nov 30 22:45 result_of_3.txt
-rw-r--r-. 1 nkhaytovich qa 8984 Nov 29 23:43 resultfile.txt
-rw-r--r-. 1 nkhaytovich qa 22 Nov 29 23:31 reversed1_hello-world.txt -rw-r--r-. 1 nkhaytovich qa 22 Nov 29 22:58 reversed2_hello_world.txt
                                22 Nov 29 22:45 reversed_hello-world.txt
-rw-r--r-. 1 nkhaytovich qa
[nkhaytovich@c7-sandbox ~]$ cd ~/Test2
[nkhaytovich@c7-sandbox Test2]$ 1s -1
total 0
[nkhaytovich@c7-sandbox Test2]$ mv ../*.log .
[nkhaytovich@c7-sandbox Test2]$ 1s -1
total 12
-rw-r--r--. 1 nkhaytovich qa 1 Dec 1 15:05 1.log
-rw-r--r-. 1 nkhaytovich qa 1 Dec 1 15:06 2.log
 -rw-r--r-. 1 nkhaytovich qa 1 Dec 1 15:06 3.log
[nkhaytovich@c7-sandbox Test2]$ cd
[nkhaytovich@c7-sandbox ~]$ 1s -1
total 124
drwxr-xr-x. 2 nkhaytovich qa 4096 Dec 1 15:11 Test2
-rw-r--r-. 1 nkhaytovich qa 22 Nov 29 22:20 hello-world.txt
-rw-r--r-. 1 nkhaytovich ga 2395 Nov 30 23:48 merged.out
-rw-r--r-. 1 nkhaytovich qa 2297 Nov 30 23:46 new.err
-rw-r--r-. 1 nkhaytovich qa 98 Nov 30 23:46 new.out
-rw-r--r-. 1 nkhaytovich qa 13423 Nov 30 23:44 result6.txt
-rw-r--r-. 1 nkhaytovich qa 5333 Nov 30 23:16 result_10.txt
-rw-r--r-. 1 nkhaytovich qa 5381 Nov 30 23:21 result_home.txt
-rw-r--r-. 1 nkhaytovich qa 45736 Nov 30 22:45 result_of_3.txt
-rw-r--r-. 1 nkhaytovich qa 8984 Nov 29 23:43 resultfile.txt
-rw-r--r-. 1 nkhaytovich qa 22 Nov 29 23:31 reversed1_hello-world.txt
-rw-r--r-. 1 nkhaytovich qa 22 Nov 29 22:58 reversed2_hello_world.txt 22 Nov 29 22:45 reversed_hello-world.txt
```

4. Then, you want to copy these log files, whose names start from "1" and end up with ".log", from your current directory to /tmp. Which command will you use?

```
cp 1*.log /tmp
```

cp 1\*.log ~/Test1 - checked in my terminal how it works

5. Execute the following command:

Is -IF /home/not-your-account (put any existing name instead of "not-your-account")
You will see an error. Find any file or directory not in /home that leads to the same error.

Is -IF /home/abaskova

ls: cannot open directory /home/abaskova: Permission denied

## Is -IF /lost+found

Is: cannot open directory /lost+found: Permission denied

6. You have these 2 commands being executed within your HOME (imagine you already have ~/lesson-1 directory there)

ls -l ./lesson-1

Is -I .bashrc

What's the difference in "." symbol's meaning?

ls -l ./lesson-1 – "." means **current directory** – command shows the extended information about directory's 1 level lower content

Is -I .bashrc – "." means file extension a part of the filename.

7. Imagine you have the following directory structure:

/home/user

/home/user/photos

/home/user/photos/private

/home/user/docs

/home/user/videos

Now you are in /home/user/videos

How to change your current working directory in one action to

/home/user/photos/private by using only relative paths?

cd ../photos/private