

26. Remove Duplicates from Sorted Array

Easy Topics Companies Hint

Given an integer array `nums` sorted in **non-decreasing order**, remove the duplicates **in-place** such that each unique element appears only **once**. The **relative order** of the elements should be kept the **same**.

Consider the number of *unique elements* in `nums` to be `k`. After removing duplicates, return the number of unique elements `k`.

The first `k` elements of `nums` should contain the unique numbers in **sorted order**. The remaining elements beyond index `k - 1` can be ignored.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int[] expectedNums = [...]; // The expected answer with correct length

int k = removeDuplicates(nums); // Calls your implementation

assert k == expectedNums.length;
for (int i = 0; i < k; i++) {
    assert nums[i] == expectedNums[i];
}
```

If all assertions pass, then your solution will be **accepted**.

```
| }
```

If all assertions pass, then your solution will be **accepted**.

Example 1:

Input: `nums = [1,1,2]`

Output: `2, nums = [1,2,_]`

Explanation: Your function should return `k = 2`, with the first two elements of `nums` being 1 and 2 respectively. It does not matter what you leave beyond the returned `k` (hence they are underscores).

Example 2:

Input: `nums = [0,0,1,1,1,2,2,3,4]`

Output: `5, nums = [0,1,2,3,4,_,_,_,_]`

Explanation: Your function should return `k = 5`, with the first five elements of `nums` being 0, 1, 2, 3, and 4 respectively. It does not matter what you leave beyond the returned `k` (hence they are underscores).

Constraints:

- `1 <= nums.length <= 3 * 104`
- `-100 <= nums[i] <= 100`
- `nums` is sorted in **non-decreasing order**.

</> Code

C   Auto

    

```
1 int removeDuplicates(int* nums, int numsSize) {
2     if (numsSize == 0)
3         return 0;
4
5     int k = 1; // index for unique elements
6
7     for (int i = 1; i < numsSize; i++) {
8         if (nums[i] != nums[k - 1]) {
9             nums[k] = nums[i];
10            k++;
11        }
12    }
13
14    return k;
15 }
16
```

☒ Testcase  Test Result

Accepted Runtime: 0 ms

☒ Case 1

☒ Case 2

Input

nums =
[1,1,2]

Output

[1,2]

Expected

[1,2]

 [Contribute a testcase](#)