

/*WAP to simulate the working of a circular queue of integers using an array. Provide the following operations: Insert, Delete & Display The program should print appropriate messages for queue empty and queue overflow conditions*/

```
#include <stdio.h>

#define MAX 5

int queue[MAX];

int front = -1, rear = -1;

void insert(int value)
{
    if ((front == 0 && rear == MAX - 1) || (front == (rear + 1) % MAX))
    {
        printf("Queue Overflow! Cannot insert %d\n", value);
    }
    else
    {
        if (front == -1)
        {
            front = 0;
            rear = 0;
        }
        else
        {
            rear = (rear + 1) % MAX;
        }
        queue[rear] = value;
        printf("%d inserted into the queue.\n", value);
    }
}
```

```

}
}
void delete()
{
if (front == -1)
{
printf("Queue Underflow! Queue is empty.\n");
}
else
{
printf("Deleted element: %d\n", queue[front]);
if (front == rear)
{
front = -1;
rear = -1;
}
else
{
front = (front + 1) % MAX;
}
}
}
void display(){
if (front == -1)
{

```

```
printf("Queue is empty.\n");
}
else
{
printf("Queue elements: ");
int i = front;
while (1)
{
printf("%d ", queue[i]);
if (i == rear)
break;
i = (i + 1) % MAX;
}
printf("\n");
}
}

int main()
{
int choice, value;
while (1)
{
printf("\nCircular Queue Operations:\n");
printf("1. Insert\n");
printf("2. Delete\n");
printf("3. Display\n");printf("4. Exit\n");
```

```
printf("Enter your choice: ");
scanf("%d", &choice);
switch (choice)
{
case 1:
printf("Enter value to insert: ");
scanf("%d", &value);
insert(value);
break;
case 2:
delete();
break;
case 3:
display();
break;
case 4:
printf("Exiting program.\n");
return 0;
default:
printf("Invalid choice! Please try again.\n");
}
}
return 0;
}
```

Output:-



