



20.55 Writing the Specified Bit of Word Label

SET_BIT_OF_INT(_E)

FX5S **FX5UJ** **FX5U** **FX5UC**

These functions writes the specified bit of the word label.

Ladder diagram		Structured text	FBD/LD
[Without EN/ENO] 	[With EN/ENO] 	[Without EN/ENO] d:=SET_BIT_OF_INT(s,n); [With EN/ENO] d:=SET_BIT_OF_INT_E(EN,ENO,s,n);	Not supported

Setting data

■Descriptions, types, and data types

Argument	Description	Type	Data type
EN	Execution condition (TRUE: Execution, FALSE: Stop)	Input variable	BOOL
s	Input	Input variable	BOOL
n	Only a constant 0 to 15 can be specified.	Input variable	INT
ENO	Output status (TRUE: Normal, FALSE: Abnormal)	Output variable	BOOL
d(SET_BIT_OF_INT(_E))	Output	Output variable	ANY16

Processing details

■Operation processing

- These functions write the BOOL value specified by (s) in the (n)th bit of (d).

■Operation result

1. Function without EN/ENO

The operation processing is executed. The operation output value is output from (d).

2. Function with EN/ENO

The following table lists the execution conditions and operation results.

Execution condition	Operation result	
EN	ENO	(d)
TRUE (Executes operation)	TRUE	Operation output value
FALSE (Stops operation)	FALSE ^{*1}	Indefinite value

^{*1} When FALSE is output from ENO, data output from (d) is undefined. In that case, modify a program so that the data output from (d) is not used.

Operation error

There is no operation error.