



# Attributed Graph Alignment



Ning Zhang <sup>\*</sup>   Weina Wang <sup>†</sup>   Lele Wang <sup>\*</sup>

<sup>\*</sup>University of British Columbia   <sup>†</sup>Carnegie Mellon University


International Symposium on Information Theory (ISIT)  
June 2021

# Social network de-anonymization









**Other applications:** computer vision, biological network analysis, natural language processing...



- **Information-theoretic limit:**

Pedarsani and Grossglauser (2011), Cullina and Kiyavash (2016), Cullina and Kiyavash (2017), Wu et al. (2021)

- **Efficient algorithms:**

- ▶ **Convex optimization:** Lyzinski et al. (2015);
- ▶ **Spectral method:** Nassar et al. (2018), Feizi et al. (2019), Fan et al. (2020) etc. ;
- ▶ **Belief propagation:** Onaran and Villar (2020)
- ▶ **Others:** Barak et al. (2019)

# What if graph structure is not enough?





Ning Zhang

## Intro



Studies ECE at **University of British Columbia**



Studied Physics Major at Nankai University, China



Lives in **Vancouver, British Columbia**



From **Shijiazhuang Shi, Hebei, China**



Joined February 2017


Edit Details



Hiking



Badminton





**Ning Zhang**


Information theory; MASc@UBC;  
Vancouver



# We do know more ...



# Attributes as vertices




How much **benefit** can **vertex attributes** bring?

# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$


► For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .



# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$


► For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .



# Model: attributed Erdős–Rényi graph pair


- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$

► For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .



# Model: attributed Erdős–Rényi graph pair


- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$ 
  - ▶ For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .
  - ▶ For  $e \in \mathcal{E}_a$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{q}$ , where  $\mathbf{q} = (q_{11}, q_{10}, q_{01}, q_{00})$ .



# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$


- ▶ For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .
- ▶ For  $e \in \mathcal{E}_a$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{q}$ , where  $\mathbf{q} = (q_{11}, q_{10}, q_{01}, q_{00})$ .



# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$


- ▶ For  $e \in \mathcal{E}_u$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{p}$ , where  $\mathbf{p} = (p_{11}, p_{10}, p_{01}, p_{00})$ .
- ▶ For  $e \in \mathcal{E}_a$ ,  $(\mathbb{1}\{e \in E_1\}, \mathbb{1}\{e \in E_2\}) \stackrel{\text{i.i.d.}}{\sim} \mathbf{q}$ , where  $\mathbf{q} = (q_{11}, q_{10}, q_{01}, q_{00})$ .






# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$
- **Anonymization:** Obtain  $G'_2$  by applying random  $\Pi^*$  on user vertex set



# Model: attributed Erdős–Rényi graph pair


- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$
- **Anonymization:** Obtain  $G'_2$  by applying random  $\Pi^*$  on user vertex set



# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$
- **Anonymization:** Obtain  $G'_2$  by applying random  $\Pi^*$  on user vertex set
- **Exact alignment:** Recover  $\hat{\pi}(G_1, G'_2)$  s.t.

$$\lim_{n \rightarrow \infty} \mathbb{P}(\hat{\pi}(G_1, G'_2) = \Pi^*) = 1$$



# Model: attributed Erdős–Rényi graph pair

- $(G_1, G_2) \sim \mathcal{G}(n, \mathbf{p}; m, \mathbf{q})$
- **Anonymization:** Obtain  $G'_2$  by applying random  $\Pi^*$  on user vertex set
- **Exact alignment:** Recover  $\hat{\pi}(G_1, G'_2)$  s.t.

$$\lim_{n \rightarrow \infty} \mathbb{P}(\hat{\pi}(G_1, G'_2) = \Pi^*) = 1$$

- **Our goal:** characterize the information-theoretic limit

## Achievability

Conditions on  $(n, \mathbf{p}, m, \mathbf{q})$  to achieve exact alignment;

## Converse

Conditions on  $(n, \mathbf{p}, m, \mathbf{q})$  s.t. exact alignment is not possible.


# Main results

## Achievability (simplified)

- $m = \Omega((\log n)^3)$ :  $np_{11} + mq_{11} - \log n \rightarrow \infty$
- $m = o((\log n)^3)$ :  
 $np_{11} + mq_{11} - O(mq_{11}^{3/2}) - \log n \rightarrow \infty$

## Converse


$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$



# Main results


## Achievability (simplified)

- $m = \Omega((\log n)^3)$ :  $np_{11} + mq_{11} - \log n \rightarrow \infty$
- $m = o((\log n)^3)$ :  
 $np_{11} + mq_{11} - O(mq_{11}^{3/2}) - \log n \rightarrow \infty$




## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$




# Recover the Erdős–Rényi graph alignment

## 1. Erdős–Rényi graph alignment ( $q_{00} = 1$ ) Cullina and Kiyavash (2017)




(a)  $m = \Omega((\log n)^3)$




(b)  $m = o((\log n)^3)$

# Recover the Erdős–Rényi graph alignment

## 1. Erdős–Rényi graph alignment ( $q_{00} = 1$ ) Cullina and Kiyavash (2017)



(a)  $m = \Omega((\log n)^3)$




(b)  $m = o((\log n)^3)$




# Improve the bipartite graph alignment

## 2. Bipartite graph alignment ( $p_{00} = 1$ ) Dai et al. (2019)




(a)  $m = \Omega((\log n)^3)$




(b)  $m = o((\log n)^3)$

# Improve the seeded graph alignment

## 3. Seeded graph alignment ( $p = q$ ) Yartseva and Grossglauser (2013)



(a)  $m = \Omega((\log n)^3)$



(b)  $m = o((\log n)^3)$

# Proof of achievability (sketch)

## Achievability

- $m = \Omega((\log n)^3)$ :  $np_{11} + mq_{11} - \log n \rightarrow \infty$
- $m = o((\log n)^3)$ :  $np_{11} + mq_{11} - O(mq_{11}^{3/2}) - \log n \rightarrow \infty$

### Key ideas:

- MAP estimator (see Lemma1)

## Achievability

- $m = \Omega((\log n)^3)$ :  $np_{11} + mq_{11} - \log n \rightarrow \infty$
- $m = o((\log n)^3)$ :  $np_{11} + mq_{11} - O(mq_{11}^{3/2}) - \log n \rightarrow \infty$

## Key ideas:

- MAP estimator (see Lemma1)
- Upper bound error probability of MAP (Cullina and Kiyavash (2017)):
  - ▶ Orbit decomposition
  - ▶ Generating functions

# Proof of converse (sketch)

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$



# Proof of converse (sketch)

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$




# Proof of converse (sketch)

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$
- $|\text{Aut}| \geq |\text{Aut}_{\text{iso}}|$




# Proof of converse (sketch)

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$
- $|\text{Aut}| \geq |\text{Aut}_{\text{ind}}| \geq |\text{Aut}_{\text{iso}}|$






# Proof of converse (sketch)

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$
- $|\text{Aut}| \geq |\text{Aut}_{\text{ind}}| \geq |\text{Aut}_{\text{iso}}|$



$$\begin{aligned} |\text{Aut}_{\text{iso}}| &= 0 \\ |\text{Aut}_{\text{ind}}| &= 1 \end{aligned}$$

## Converse

$$np_{11} + mq_{11} - \log n \rightarrow -\infty$$

### Key ideas:

- $P(\hat{\pi}_{\text{MAP}}(G_1, G'_2) = \Pi^*) \leq \frac{1}{|\text{Aut}(G_1 \wedge G_2)|}$
- $|\text{Aut}| \geq |\text{Aut}_{\text{ind}}| \geq |\text{Aut}_{\text{iso}}|$
- Use the second moment method to show that w.h.p.  $|\text{Aut}(G_1 \wedge G_2)| \geq 2$   
In particular, we show  $\# \text{ indistinguishable vertex pair} > 0$ .

- Propose attributed Erdős–Rényi graph pair model
- Characterize the information-theoretic limits
- Unify existing models for graph alignment

- B. Barak, C.-N. Chou, Z. Lei, T. Schramm, and Y. Sheng. (nearly) efficient algorithms for the graph matching problem on correlated random graphs. In *Advances in Neural Information Processing Systems*. Curran Associates, Inc., 2019.
- D. Cullina and N. Kiyavash. Improved achievability and converse bounds for Erdős-Rényi graph matching. *ACM SIGMETRICS Perform. Evaluation Rev.*, 44(1):63–72, 2016. doi: 10.1145/2964791.2901460.
- D. Cullina and N. Kiyavash. Exact alignment recovery for correlated Erdős-Rényi graphs. *arXiv:1711.06783 [cs.IT]*, 2017.
- O. E. Dai, D. Cullina, N. Kiyavash, and M. Grossglauser. Analysis of a canonical labeling algorithm for the alignment of correlated erdos-rényi graphs. *Proc. ACM Meas. Anal. Comput. Syst.*, 3(2), June 2019. doi: 10.1145/3341617.3326151.
- Z. Fan, C. Mao, Y. Wu, and J. Xu. Spectral graph matching and regularized quadratic relaxations: Algorithm and theory. In *International Conference on Machine Learning*, pages 2985–2995. PMLR, 2020.

## Selected references (cont.)

- S. Feizi, G. Quon, M. Recamonde-Mendoza, M. Medard, M. Kellis, and A. Jadbabaie. Spectral alignment of graphs. *IEEE Transactions on Network Science and Engineering*, 7(3):1182–1197, 2019.
- V. Lyzinski, D. E. Fishkind, M. Fiori, J. T. Vogelstein, C. E. Priebe, and G. Sapiro. Graph matching: Relax at your own risk. *IEEE transactions on pattern analysis and machine intelligence*, 38(1):60–73, 2015.
- H. Nassar, N. Veldt, S. Mohammadi, A. Grama, and D. F. Gleich. Low rank spectral network alignment. In *Proceedings of the 2018 World Wide Web Conference*, pages 619–628, 2018.
- E. Onaran and S. Villar. Efficient belief propagation for graph matching. In *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 9060–9064, 2020. doi: 10.1109/ICASSP40776.2020.9053147.
- P. Pedarsani and M. Grossglauser. On the privacy of anonymized networks. In *Proc. Ann. ACM SIGKDD Conf. Knowledge Discovery and Data Mining (KDD)*, pages 1235–1243, 2011. doi: 10.1145/2020408.2020596.
- Y. Wu, J. Xu, and S. H. Yu. Settling the sharp reconstruction thresholds of random graph matching, 2021.

## Selected references (cont.)

- L. Yartseva and M. Grossglauser. On the performance of percolation graph matching. In *Proceedings of the first ACM conference on Online social networks*, pages 119–130, 2013.