IPECC | Side Channel Analysis

Collection of scripts to perform a complete side-channel analysis flow on IPECC electromagnetic (EM) traces, based on the open-source library SCALib, related to the research paper **IPECC: an Open-Source Side-Channel Resistant ECC Hardware Accelerator**, published in the journal TCHES 2027 issue 1.

Datasets available via:

`ASCAD IPECC`

Contents

- Requirements
- Quickstart
- Setup
- Datasets Details
- Dataset Access
    - Dataset Download
    - Dataset Decompression
    - Dataset Concatenation
- Usage
- Features
- Demonstration

Requirements

Native Installation

To run the provided scripts, you need a computer running Linux (tested with Debian X / Ubuntu 24.04 LTS and 26.04 LTS) or MacOS (tested with MacOS TAHOE 26.6.2) and Python version >= 3.13. Furthermore, you need to install the following packages: To run the provided scripts, you need a computer running Linux (tested with Debian X / Ubuntu 24.04 LTS and 26.04 LTS) or MacOS (tested with MacOS TAHOE 26.6.2) and Python version >= 3.13. Furthermore, you need to install the following packages:

Linux

```
sudo apt install git python3 pip wget
```

MacOS

```
brew install git python3 wget hdf5
```

Docker

If you would like to test the scripts using Docker, ensure you have `wget` (to download the datasets) and Docker installed and running (by following Docker official documentation).

Quickstart

If you wish to directly test the scripts, you can achieve that using the following. Otherwise, if you wish to dig deeper into the details of this work, please take a look at the following sections.

> [!NOTE] You need at least 140GB of free disk space. More generally, if you download, decompress and run the SCA flow on n subsets of one dataset, you will need at least $n \times 70GB$ of free disk space.

Native way

The script `test_all_scripts_level3-1.sh` is an all-in-one script which installs the required dependencies, downloads the two first subsets of the dataset corresponding to Level 3.1, and runs the SCA scripts using them directly. All you need is to run the following shell commands:

Linux

```
git clone https://github.com/NinjaLabFr/evaluation-SCA-IPECC
cd evaluation-SCA-IPECC
bash test_all_scripts_level3-1.sh
```

MacOS

```
git clone https://github.com/NinjaLabFr/evaluation-SCA-IPECC
cd evaluation-SCA-IPECC
zsh test_all_scripts_level3-1.sh
```

Docker

Linux

```
git clone https://github.com/NinjaLabFr/evaluation-SCA-IPECC
cd evaluation-SCA-IPECC
bash test_all_scripts_level3-1_docker.sh
```

MacOS

```
git clone https://github.com/NinjaLabFr/evaluation-SCA-IPECC
cd evaluation-SCA-IPECC
zsh test_all_scripts_level3-1_docker.sh
```

Setup

You will need to install the required Python libraries, namely `ECUtils`, `H5Py`, `Jupyter`, `NumPy`, `Matplotlib` and `SCALib`.

Linux & macOS

```
python3 -m venv IPECCenv && source IPECCenv/bin/activate
pip install -r requirements.txt
```

Otherwise, if you prefer using Docker, refer to this section.

Datasets Details

We provide 11 datasets, each one containing 900 EM traces of scalar multiplication computed over the elliptic curve FRP256v1. In the table below, we detail the security configurations of the 11 datasets showcasing the different countermeasures enabled for each dataset. Each line of the table corresponds to one of the 11 configurations / datasets.

A cell with a green checkmark (✅) conveys that the corresponding countermeasure is activated for the considered configuration / dataset. The ❌ indicates that the countermeasure is disabled by default.

Level/Countermeasure	XY Shuffling	Shift Register	Memory Shuffling
Level 1.0		❌	
Level 1.1	✅	❌	
Level 1.3	✅	❌	✅
Level 2.0			
Level 2.1	✅		
Level 2.2	✅	✅	
Level 2.3	✅	✅	✅
Level 3.0			
Level 3.1	✅		
Level 3.2	✅	✅	
Level 3.3	✅	✅	✅

Each provided dataset contains information about the setup, and for each scalar multiplication:

- the corresponding X affine coordinate value of a random point P,
- the corresponding Y affine coordinate value of a random point P,
- the corresponding k scalar value of $k.P$,
- the corresponding ϕ value,
- the corresponding scalar multiplication EM trace,

The content is detailed in the notebook `1_dataset_presentation.ipynb`.

Dataset Access

As each of the 11 datasets contains 900 traces of length 150 million samples stored as `int16`, one dataset has a size of ~270GB. To facilitate their download, each one is split in 9 subsets encompassing 100 traces (with their corresponding inputs). You can execute the SCA flow on one or several subsets of one dataset.

Dataset Download

You can test the scripts against (one of) the datasets available via this link.

To download a specific dataset subset, you can use the bash oneliner :

```
# (replace `X` , `Y` and `N` in the dataset name)
wget https://anssi.s3.sbg.io.cloud.ovh.net/ipecc/ipecc_level_<X>-
<Y>_part_<N>.tar.zst
```

For example, to download the first subset of the dataset Level 1.0 (only the first 100 inputs and traces of that dataset), you can use the following bash command:

```
wget https://anssi.s3.sbg.io.cloud.ovh.net/ipecc/ipecc_level_1-
0_part_0.tar.zst
```

To download all the subsets of one or several dataset(s), you can use the following bash commands:

```
# download the 9 subsets of Level 1.0 dataset at once:
wget https://anssi.s3.sbg.io.cloud.ovh.net/ipecc/ipecc_level_1-
0_part_{0..8}.tar.zst

# download the 9 subsets of each of the three level 1 datasets at once:
wget https://anssi.s3.sbg.io.cloud.ovh.net/ipecc/ipecc_level_1-
{0,1,3}_part_{0..8}.tar.zst

# download the 9 subsets of each of the four levels 2 and 3 datasets at
once:
wget https://anssi.s3.sbg.io.cloud.ovh.net/ipecc/ipecc_level_{2,3}-
{0..3}_part_{0..8}.tar.zst
```

Datasets Decompression

Once the dataset(s) downloaded, extract the content using the following (replace `X` , `Y` and `N` in the dataset name with the part which you downloaded):

- Linux

```
tar -I zstd -xf ipecc_level_X-Y_part_N.tar.zst

# To decompress several datasets at once
printf "%s " ipecc_level_X-Y_part_{M,N}.tar.zst | xargs -n 1 tar -I zstd -
xf
```

(`-xf` extracts the archive file, `-I` selects the compression method but might not be supported on MacOS)

- MacOS

```
tar -xf ipecc_level_X-Y_part_N.tar.zst

# To decompress several datasets at once
printf "%s " ipecc_level_X-Y_part_{M,N}.tar.zst | xargs -n 1 tar -xf
```

> **Note for MacOS users :** If `zstd` format is not recognized on your machine when decompressing, you can install it using `brew install zstd`

The dataset is an archive of type `.tar.zstd` (compressed with the zstd tool) with a unique `ipecc_level_<X>-<Y>_part_<N>.h5` file inside.

Datasets Subsets Concatenation

If you wish to use several subsets of the same dataset, you can concatenate them into one virtual dataset which you can use as argument in the following steps:

```
python3 link_datasets.py ipecc_level_1-0_part_0.h5 ipecc_level_1-
0_part_1.h5 ... [-o out.h5]
```

Usage

Native Usage

The script `sca-flow.sh` runs an example flow of the scripts. You can use the command

```
bash sca-flow.sh <dataset> <dataset-directory>
```

On a standard laptop, this script will run a couple of minutes before ending (using the provided parameters).

If you want to customize the parameters, the section Demonstration encompasses a complete example of usage for each script.

Docker Usage

If you wish to use Docker, upon downloading (and concatenating) the datasets, please run the following command (and replace `<absolute-path-of-dataset-directory>` and `<dataset-name>` with the absolute path of the local dataset directory and the dataset filename respectively):

```
 docker build -t ipecc . && docker run  -v <absolute-path-of-dataset-
directory>:/datasets ipecc  /datasets/<dataset-name> /datasets/
```

Notebooks

You can also refer to the two following notebooks:

- `1_dataset_presentation.ipynb` presenting the dataset structure and content,
- `2_template_attack_on_kappas.ipynb` which is a verbose version of `sca-flow.sh`.

Just launch from the virtual environment

```
jupyter notebook
```

and select the notebook in the opened browser.

Features

The scripts are based on SCALib.

1. `compute_kappas.py` computes:

   > $\kappa = (k >> 1) \oplus \phi$
   >
   > $\kappa' = (k >> 1) \oplus (\phi << 1)$

   -->

   $$\kappa \leftarrow (k \gg 1) \oplus \phi$$
   $$\kappa' \leftarrow (k \gg 1) \oplus (\phi \ll 1)$$

2. `splitting.py`:

   - splits the EM traces into the scalar multiplication iteration subtraces,
   - adds the corresponding inputs,
   - filter misaligned subtraces (optional),
   - saves the results in an HDF5 file.

3. `compute_snr.py` performs leakage assessment over the subtraces using SNR.

4. `template_attack.py` performs a template attack on the subtraces.

- `plot_traces.py` can be used to plot EM traces of any `.h5` file.

Demonstration

In this demonstration, we will create a directory `test_level3-1` in which we move our dataset and which will contain all the operations outputs.

Step 1: Generating κ and κ'
The first step is to generate the inputs κ and κ' that are used instead of k in the scalar multiplication (which implement the anti-ADPA countermeasure).

```
python3 compute_kappas.py -d test_level3-1/ipecc_level_3-1_part_0.h5 -t
test_level3-1

    ┌──────────────────────────────────────────────┐
    │         Compute kappa and kappa'             │
    └──────────────────────────────────────────────┘

Successfully processed 100 entries.
```

This will generate two new files `inputs_kappa.npy` and `inputs_kappaP.npy` in the directory `test_level3-1`.

Step 2: Splitting & Resynchronization

Given the fact that all our inputs are ready now, we split each scalar multiplication trace into 254 subtraces corresponding to the 254 iterations of each scalar multiplication, discard the first and last due to some specificities of these iterations and apply an additional filtering step for subtraces that are not aligned enough.

```
python3 splitting.py -d test_level3-1/ipecc_level_3-1_part_0.h5 -t
test_level3-1 -r

    ┌──────────────────────────────────────────────┐
    │              Split and Resync                │
    └──────────────────────────────────────────────┘

Writing patterns
Writing patterns 14131/14131
```


This generates a file in the `test_level3-1` directory (option `-t`), named `subtraces.h5`, which corresponds to the sub-traces of the scalar multiplication iterations and their corresponding inputs.

At the end of the script execution, you can notice the final subtraces number.

If you want to visualize the traces that you resynchronized (or any traces from the dataset or processed data), you can use the script `plot_traces.py`. For instance, to view the resynchronized sub-traces from the second to the sixth (5 traces starting from offset 1), we can perform the following :

```
python3 plot_traces.py -f test_level3-1/subtraces.h5 -n 5 -o 1
```

This will create the PNG file `traces` in the local directory with the corresponding plot.



Step 3: Leakage Assessment using SNR

At this step, we will perform leakage assessment on each on the input bits.

```
python3 compute_snr.py -d test_level3-1/subtraces.h5 -o data


    ┌──────────────────────────────────────────────┐
    │              SNR based on SCALib             │
    └──────────────────────────────────────────────┘

Traces shape: (14131, 510000)
Inputs shape: (14131,)
Will process 14131 traces starting from index 0.
Processing subtraces 14000:14131

Max SNR for :
    scalar: 0.0013
    phi: 0.0013
    kappa: 0.0138
    kappa_prime: 0.0150

global max is for kappa_prime with 0.0150
2nd global max is for kappa with 0.0138
```

We will obtain a saved PNG corresponding to the SNR results. E.g. :



Step 4: Template Attack using LDA

Finally, given the SNR results, we perform a template attack on the inputs that display high SNR results.

1. We divide our dataset into two subsets : 80% dedicated to building the templates (training) and 20% to perform the predictions (testing).
2. Using the first subset, and based on the threshold that we set, we select Points Of Interest (PoIs) and perform a template attack (LDA).
3. Finally, using these results, we predict the inputs of the testing subset, and compute our success rate (as the accuracy of the prediction)

```
python3 template-attack.py -d test_level3-1/subtraces.h5 -i kappa_prime -t
0.0009

    ┌──────────────────────────────────────────────┐
    │       Template attacks using SCALib          │
    └──────────────────────────────────────────────┘


1. Perform SNR (to select POIs)
Traces shape: (14131, 510000)
Inputs shape: (14131,)
Will process 11305 traces starting from index 0.
Processing subtraces 11000:11305
POIs: 4018


2. Build templates
Processing subtraces 11000:11305

3. Predict
Processing subtraces 13305:14131
Success rate: 86.91
```