

# Example Documentation

2026-05-18

Example using *UML* and *Emoji*.

emoji:bear[5x]

```
@startuml
    Class01 <|-- Class02
    Class03 *-- Class04
    Class05 o-- Class06
    Class07 .. Class08
    Class09 -- Class10
@enduml
```

```
// File: app.js
const User = ({
  username: 'c1source'
});
```



Figure 1. Image from directory

Include code from examples

```
# elixirc1.github.io
IO.inspect("Hello Elixir")
```

```
Table users {
  id integer
  username varchar
  role varchar
  created_at timestamp
}

Table posts {
  id integer [primary key]
  title varchar
  body text [note: 'Content of the post']
  user_id integer
```

```

status post_status
created_at timestamp
}

Enum post_status {
  draft
  published
  private [note: 'visible via URL only']
}

Ref: posts.user_id > users.id // many-to-one

```

```

{
  "$schema": "https://vega.github.io/schema/vega-lite/v3.json",
  "description": "A simple bar chart with embedded data.",
  "data": {
    "values": [
      {"a": "A", "b": 28}, {"a": "B", "b": 55}, {"a": "C", "b": 43},
      {"a": "D", "b": 91}, {"a": "E", "b": 81}, {"a": "F", "b": 53},
      {"a": "G", "b": 19}, {"a": "H", "b": 87}, {"a": "I", "b": 52}
    ]
  },
  "mark": "bar",
  "encoding": {
    "x": {"field": "a", "type": "ordinal"},
    "y": {"field": "b", "type": "quantitative"}
  }
}

```

# Asciimath using explicit block and macro names

## Configuration

- The `:stem:` attribute in the document header specifies *latexmath* or *mathjax*.
- In these examples, use of *asciimath* is signaled using the explicit ‘asciimath’ block and macro name notation. Note that *asciimath* is not compatible with PDF output.

## Examples

### Stem block

```

\ b e g \in \left \{ a l i g \neq d \right \} a_{11} x_1 + a_{12} x_2 + \ \cdots +

```

$$a_{1\ m} x_m \& = b_1 \backslash a_{21} x_1 + a_{22} x_2 + \backslash \cdots + a_{2\ m} x_m \& = \\ b_2 \backslash \& \backslash \vdots \backslash a_{n\ 1} x_1 + a_{n\ 2} x_2 + \backslash \cdots + a_{n\ m} \\ x_m \& = b_n \backslash \text{e n d} \left\{ \text{a l i g} \text{ \neq d} \right\}$$

## Mathjax block

```
\begin{cases}
2x_1 + x_2 = 15 \\
x_1 + 3x_2 = 20
\end{cases}
```

## Asciimath block

A matrix followed by some square roots can be written as

```
\left [ \begin{matrix} \text{ i n d e x : : : a \& b \\ c \& d } \end{matrix} \right ] \left (
\begin{matrix} n \\ k \end{matrix} \right ) \sqrt{4} = 2 \sqrt{9} = 3
```

## Inline in a paragraph

Some text might suddenly need to show some matrix calculations, such as  $[[a,b],[c,d]]((n),(k))$ .

## Inline, using attribute substitution

If you are not interested in exciting formulae such as  $[[a,b],[c,d]]((n),(k))$ , perhaps you would find the more mundane  $\text{sqrt}(4) = 2$  or even  $\text{sqrt}(9) = 3$  more to your taste.

## Lists

- A matrix can be written as  $[[a,b],[c,d]]((n),(k))$ .
  - A square root looks like  $\text{sqrt}(4) = 2$
- Another square root looks like  $\text{sqrt}(9) = 3$

## Section headings

**A matrix can be written as**  
 $[[a,b],[c,d]]((n),(k))$ .

**A square root looks like**  $\text{sqrt}(4) = 2$ .

Another square root looks like  $\text{sqrt}(9) = 3$ .

## Tables

Table 1. Math Table

|                                                       |                                               |                                                        |
|-------------------------------------------------------|-----------------------------------------------|--------------------------------------------------------|
| Header matrix:<br>[[a,b],[c,d]]((n),(k))              | Header square root: $\text{sqrt}(4) = 2$      | Header square root: $\text{sqrt}(9) = 3$               |
| A matrix can be written as<br>[[a,b],[c,d]]((n),(k)). | A square root looks like $\text{sqrt}(4) = 2$ | Another square root looks like<br>$\text{sqrt}(9) = 3$ |
| Footer matrix:<br>[[a,b],[c,d]]((n),(k))              | Footer square root: $\text{sqrt}(4) = 2$      | Footer square root: $\text{sqrt}(9) = 3$               |