Chapter IV

Mandatory part

Program Name	`libft.a`
Files to Submit	`Makefile, libft.h, ft_*.c`
Makefile	`NAME, all, clean, fclean, re`
External Function	`Detailed below`
Libft authorized	`n/a`
Description	`Create your own library: a collection of functions that will be a useful tool for your curriculum.`

IV.1 Technical considerations

- Declaring global variables is strictly forbidden.
- If you need helper functions to break down a more complex function, define them as `static` functions to restrict their scope to the appropriate file.
- All files must be placed at the root of your repository.
- Submitting unused files is not allowed.
- Every `.c` file must compile with the following flags: `-Wall -Wextra -Werror`.
- You must use the `ar` command to create your library. The use of `libtool` is strictly forbidden.
- Your `libft.a` must be created at the root of your repository.

IV.2 Part 1 - Libc functions

To begin, you must reimplement a set of functions from the `libc`. Your version will have the same prototypes and behaviors as the originals, adhering strictly to their definitions in the `man` page. The only difference will be their names, which must start with the '`ft_`' prefix. For example, `strlen` becomes `ft_strlen`.

> Some of the function prototypes you need to reimplement use the 'restrict' qualifier. This keyword is part of the C99 standard. Therefore, it is forbidden to include it in your own prototypes and to compile your code with the -std=c99 flag.

You must write your own functions that implement the following originals. They must not rely on any external functions.

> For the character classification functions (isalpha, isdigit, isalnum, isascii, isprint), the return value must be:
>
> - 1 if the character matches the tested class
> - 0 if the character does not match

- `isalpha`
- `isdigit`
- `isalnum`
- `isascii`
- `isprint`
- `strlen`
- `memset`
- `bzero`
- `memcpy`
- `memmove`
- `strlcpy`
- `strlcat`
- `toupper`
- `tolower`
- `strchr`
- `strrchr`
- `strncmp`
- `memchr`
- `memcmp`
- `strnstr`
- `atoi`

In order to implement the two following functions, you will use `malloc()`:

- `calloc`
- `strdup`

> Depending on your current operating system, the 'calloc' function's behavior may differ from its man page description. You must follow this rule: If nmemb or size is 0, then calloc() returns a unique pointer value that can be successfully passed to free().

Some functions that you must reimplement, such as strlcpy, strlcat, and bzero, are not included by default in the GNU C Library (glibc). To test them against the system standard, you may need to include <bsd/string.h> and compile with the -lbsd flag.

This behaviour is specific to glibc systems. If you are curious, take the opportunity to explore the differences between glibc and BSD libc.

IV.3 Part 2 - Additional functions

In this second part, you must develop a set of functions that are either not included in the `libc`, or exist in a different form.

Some of the functions from Part 1 may be useful for implementing the functions below.

Function Name	ft_substr
Prototype	char *ft_substr(char const *s, unsigned int start, size_t len);
Files to Submit	-
Parameters	s: The original string from which to create the substring. start: The starting index of the substring within 's'. len: The maximum length of the substring.
Return Value	The substring. NULL if the allocation fails.
External Function	malloc
Description	Allocates memory (using malloc(3)) and returns a substring from the string 's'. The substring starts at index 'start' and has a maximum length of 'len'.

Function Name	ft_strjoin
Prototype	char *ft_strjoin(char const *s1, char const *s2);
Files to Submit	-
Parameters	s1: The prefix string. s2: The suffix string.
Return Value	The new string. NULL if the allocation fails.
External Function	malloc
Description	Allocates memory (using malloc(3)) and returns a new string, which is the result of concatenating 's1' and 's2'.

Function Name	ft_strtrim
Prototype	char *ft_strtrim(char const *s1, char const *set);
Files to Submit	-
Parameters	s1: The string to be trimmed. set: The string containing the set of characters to be removed.
Return Value	The trimmed string. NULL if the allocation fails.
External Function	malloc
Description	Allocates memory (using malloc(3)) and returns a copy of 's1' with characters from 'set' removed from the beginning and the end.

Function Name	ft_split
Prototype	char **ft_split(char const *s, char c);
Files to Submit	-
Parameters	s: The string to be split. c: The delimiter character.
Return Value	The array of new strings resulting from the split. NULL if any allocation fails. The returned structure will be released using: 1) free() on each string in the array; 2) free() the array itself.
External Function	malloc, free
Description	Allocates memory (using malloc(3)) and returns an array of strings obtained by splitting 's' using the character 'c' as a delimiter. Each string in the returned array is allocated independently. The array of pointers itself is also allocated dynamically. The returned array must be NULL terminated.

Function Name	ft_itoa
Prototype	char *ft_itoa(int n);
Files to Submit	-
Parameters	n: The integer to convert.
Return Value	The string representing the integer. NULL if the allocation fails.
External Function	malloc
Description	Allocates memory (using malloc(3)) and returns a string representing the integer received as an argument. Negative numbers must be handled.

Function Name	ft_strmapi
Prototype	char *ft_strmapi(char const *s, char (*f)(unsigned int, char));
Files to Submit	-
Parameters	s: The string to iterate over. f: The function to apply to each character.
Return Value	The string created from the successive applications of 'f'. Returns NULL if the allocation fails.
External Function	malloc
Description	Applies the function f to each character of the string s, passing its index as the first argument and the character itself as the second. A new string is created (using malloc(3)) to store the results from the successive applications of f.

Function Name	ft_striteri
Prototype	void ft_striteri(char *s, void (*f)(unsigned int, char*));
Files to Submit	-
Parameters	s: The string to iterate over. f: The function to apply to each character.
Return Value	None
External Function	None
Description	Applies the function 'f' to each character of the string passed as argument, passing its index as the first argument. Each character is passed by address to 'f' so it can be modified if necessary.

Function Name	ft_putchar_fd
Prototype	void ft_putchar_fd(char c, int fd);
Files to Submit	-
Parameters	c: The character to output. fd: The file descriptor on which to write.
Return Value	None
External Function	write
Description	Outputs the character 'c' to the specified file descriptor.

Function Name	ft_putstr_fd
Prototype	void ft_putstr_fd(char *s, int fd);
Files to Submit	-
Parameters	s: The string to output. fd: The file descriptor on which to write.
Return Value	None
External Function	write
Description	Outputs the string 's' to the specified file descriptor.

Function Name	ft_putendl_fd
Prototype	void ft_putendl_fd(char *s, int fd);
Files to Submit	-
Parameters	s: The string to output. fd: The file descriptor on which to write.
Return Value	None
External Function	write
Description	Outputs the string 's' to the specified file descriptor followed by a newline.

Function Name	ft_putnbr_fd
Prototype	void ft_putnbr_fd(int n, int fd);
Files to Submit	-
Parameters	n: The integer to output. fd: The file descriptor on which to write.
Return Value	None
External Function	write
Description	Outputs the integer 'n' to the specified file descriptor.

IV.4 Part 3 - linked list

Memory and string manipulation functions are useful. But you will soon discover that manipulating lists is even more useful.

In this third part, you have to implement functions using a structure to manipulate linked list. To do so, add the following structure declaration to your `libft.h` file:

```
typedef struct      s_list
{
  void              *content;
  struct s_list     *next;
}                   t_list;
```

The members of the `t_list` struct are:

- `content`: The data contained in the node.
  Using `void *` allows you to store any type of data.
- `next`: The address of the next node, or `NULL` if the current node is the last one.

Implement the following functions in order to easily use your lists:

Function Name	`ft_lstnew`
Prototype	`t_list *ft_lstnew(void *content);`
Files to Submit	-
Parameters	content: The content to store in the new node.
Return Value	A pointer to the new node
External Function	malloc
Description	Allocates memory (using malloc(3)) and returns a new node. The 'content' member variable is initialized with the given parameter 'content'. The variable 'next' is initialized to NULL.

Function Name	`ft_lstadd_front`
Prototype	`void ft_lstadd_front(t_list **lst, t_list *new);`
Files to Submit	-
Parameters	lst: The address of a pointer to the first node of a list. new: The address of a pointer to the node to be added.
Return Value	None
External Function	None
Description	Adds the node 'new' at the beginning of the list.

Function Name	ft_lstsize
Prototype	int ft_lstsize(t_list *lst);
Files to Submit	-
Parameters	lst: The beginning of the list.
Return Value	The length of the list
External Function	None
Description	Counts the number of nodes in the list.

Function Name	ft_lstlast
Prototype	t_list *ft_lstlast(t_list *lst);
Files to Submit	-
Parameters	lst: The beginning of the list.
Return Value	Last node of the list
External Function	None
Description	Returns the last node of the list.

Function Name	ft_lstadd_back
Prototype	void ft_lstadd_back(t_list **lst, t_list *new);
Files to Submit	-
Parameters	lst: The address of a pointer to the first node of a list. new: The address of a pointer to the node to be added.
Return Value	None
External Function	None
Description	Adds the node 'new' at the end of the list.

Function Name	ft_lstdelone
Prototype	void ft_lstdelone(t_list *lst, void (*del)(void *));
Files to Submit	-
Parameters	lst: The node to free. del: The address of the function used to delete the content.
Return Value	None
External Function	free
Description	Takes a node as parameter and frees its content using the function 'del'. Free the node itself but does NOT free the next node.

Function Name	ft_lstclear
Prototype	void ft_lstclear(t_list **lst, void (*del)(void *));
Files to Submit	-
Parameters	lst: The address of a pointer to a node. del: The address of the function used to delete the content of the node.
Return Value	None
External Function	free
Description	Deletes and frees the given node and all its successors, using the function 'del' and free(3). Finally, set the pointer to the list to NULL.

Function Name	ft_lstiter
Prototype	void ft_lstiter(t_list *lst, void (*f)(void *));
Files to Submit	-
Parameters	lst: The address of a pointer to a node. f: The address of the function to apply to each node's content.
Return Value	None
External Function	None
Description	Iterates through the list 'lst' and applies the function 'f' to the content of each node.

Function Name	ft_lstmap
Prototype	t_list *ft_lstmap(t_list *lst, void *(*f)(void *), void (*del)(void *));
Files to Submit	-
Parameters	lst: The address of a pointer to a node. f: The address of the function applied to each node's content. del: The address of the function used to delete a node's content if needed.
Return Value	The new list. NULL if the allocation fails.
External Function	malloc, free
Description	Iterates through the list 'lst', applies the function 'f' to each node's content, and creates a new list resulting of the successive applications of the function 'f'. The 'del' function is used to delete the content of a node if needed.

Chapter V

Readme Requirements

A `README.md` file must be provided at the root of your Git repository. Its purpose is to allow anyone unfamiliar with the project (peers, staff, recruiters, etc.) to quickly understand what the project is about, how to run it, and where to find more information on the topic.
The `README.md` must include at least:

- The very first line must be italicized and read: *This project has been created as part of the 42 curriculum by <login1>[, <login2>[, <login3>[...]]].*
- A "**Description**" section that clearly presents the project, including its goal and a brief overview.
- An "**Instructions**" section containing any relevant information about compilation, installation, and/or execution.
- A "**Resources**" section listing classic references related to the topic (documentation, articles, tutorials, etc.), as well as a description of how AI was used — specifying for which tasks and which parts of the project.

➠ **Additional sections may be required depending on the project** (e.g., usage examples, feature list, technical choices, etc.).

Any required additions will be explicitly listed below.

- A detailed description of the library created for this project must also be included.

`English is recommended; alternatively, you may use the main language of your campus.`