ii) done :> used to mark the end

```
  GNU nano 8.7.1                                upper.sh
#!/bin/bash
for file in "$@"
do
if [ -f "$file" ]
then
    mv "$file" "$(echo "$file" | tr '[:lower:]' '[:upper:]')"
    echo "File name changed to uppercase"
else
    echo "File does not exist"
fi
done
```

[Read 11 lines]

^F Where Is ^K Cut ^T Execute

Command is used to move or rename file or directories.

name file name to uppercase

to mark the end of for loop

```
vboxuser@Nipun:~$ echo "hello" | tr '[:lower:]' '[:upper:]'
HELLO
vboxuser@Nipun:~$ nano upper.sh
vboxuser@Nipun:~$ . upper.sh file.txt user.txt
File name changed to uppercase
File does not exist
vboxuser@Nipun:~$ ls
CIVIL       Eng          MIET    Music      Templates  combined.txt  mithu        user.txt
CSE         FILE.TXT     MIET.   Of         Videos     countries.txt mydata.txt
Desktop     Inst.        Miet    Pictures   and        filee.txt     names.txt
Documents   LAW          Miet    Public     aryan      filenew.txt   snap
Downloads   MANAGEMENT   Modal   Tech       check.sh   miet          upper.sh
vboxuser@Nipun:~$
```