

SOP: Formation of LOCJSON and LOCJSONSEQ

This SOP explains how to create the LOCJSON and LOCJSONSEQ values used for extracting job details from a JSON response.

Rules for Creating LOCJSON

Step 1: Enter the List (Tree)

If all job records are present inside a list/array, first enter that list using [XX].

Example:

[XX]result

Step 2: Enter the Dictionary

If a required field is inside a nested dictionary/object, first enter the dictionary and then specify the field using [X].

Examples:

location,city[X]

location,state[X]

Meaning of Separators

Separator	Purpose
[X]	Used after specifying a dictionary and its field. It indicates that the field belongs to a nested dictionary/object.
[XX]	Used to enter the parent list (tree) that contains all job objects before extracting the fields.

Example JSON

```
{
  "result": [
    {
      "id": "112",
      "jobOpeningName": "Customer Success Manager",
      "location": {
        "city": "Santa Clara",
        "state": "California"
      }
    }
  ]
}
```

```
]
}
```

Final Configuration

```
"LOCJSON": "location,city|X|location,state|X|jobOpeningName|X|id|X|id|XX|result",
"LOCJSONSEQ": "LOCATION,LOCATION,JOBTITLE,JOBID,JOBLINK"
```

Field Mapping

LOCJSON Entry	Extracts
location,city	City from the location dictionary
location,state	State from the location dictionary
jobOpeningName	Job Title
id	Job ID
id	Job Link
XX result	Enter the result list containing all job records