Soft Flexible Robotic Manipulators

Seminar Report

2025

by

Niraj Niraula

(24M1723)

Under the supervision of

Prof. Anirban Guha



Department of Mechanical Engineering

Indian Institute of Technology, Bombay

April, 2025

Contents

Introduction 5
1.1 Motivation 5
1.2 Problem definition 6
Literature Review 7
2.1 Choice of Soft Robots over Conventional Rigid Robots 7
2.1.1 Safe Human-Robot Interaction 7
2.1.2 Adoptability and Flexibility 8
2.1.3 Bio inspired Locomotion and Dexterity 8
2.1.4 Delicate Object Handling 9
2.1.5 Resilience and Durability in Uncertain Environments 9
2.1.6 Lower Cost and Simpler Design 10
2.1.7 Built-In Environmental Compliance 10
2.2 Materials and Fabrication Techniques 10
2.2.1 Silicone Elastomers 10
2.2.2 Hydrogels and Smart Materials 11
2.2.3 3D Printing and Additive Manufacturing 11
2.2.4 Molding and Casting 11
2.3 Different drive modes according to actuation method 12
2.3.1 Fluid-driven mode: 12
2.3.2 Cable-driven mode 13
2.3.4 Electro active polymer (EAP) -driven mode 14
2.3.5 Shape memory materials-driven mode 15
2.3.6 Electromagnetic-driven mode 15
2.3.7 Hybrid drive Mode 15
2.4 Modeling and Control 16
2.4.1 Kinematic Modeling 16
2.4.2 Dynamic Modeling 16
2.4.3 Finite Element Modeling (FEM) 17
2.4.4. Data-Driven and Machine Learning Models 17
2.4.5 Control Strategies 17
2.5 Sensing Technology 18
2.5.1. Tactile Sensing 18
2.5.2. Proprioception 19
2.5.3. Vision Systems 19
2.5.4. Force and Pressure Sensing 19

2.5.5. Strain and Deformation Sensing 20
2.5.6. Environmental Sensing 20
2.5.7. Sensor Integration and Fusion 21
2.6 Challenges and Limitations in Soft Robotic Manipulators 21
2.6.1 Material Limitations 21
2.6.2 Actuation Challenges 22
2.6.3 Control Complexity 22
2.6.4 Sensing Challenges 23
2.6.5 Durability and Longevity 23
2.6.6 Cost and Scalability 24
2.7 Future Directions in Soft Robotic Manipulators 24
2.7.1 Advanced Materials Development 24
2.7.2 Actuation Innovation 25
2.7.3. Integration with Artificial Intelligence (AI) and Machine Learning (ML) 26
2.7.4. Bio inspired Designs 26
2.7.5 Hybrid Soft-Rigid Robots 27
2.7.6 Integration into Industry and Medicine 27
3.1 Conclusion 28
3.2 Further Work 28
References 29

List of figures

Figure 1 soft robot showing flexibility by fruit grasping [5] 8
Figure 2 Caterpillar inspired robots [5] 9
Figure 3 soft robot performing handshake [6] 9
Figure 4 Honeycomb network based soft manipulator [14] 12
Figure 5 pneumatic muscles driven soft robot [14] 12
Figure 7 Tendon driven soft griper [15] 13
Figure 6 soft griper grasping object of different shape [15] 13
Figure 8 Soft Manipulator Driven by Dielectric elastomers [16] 14

Chapter 1

Introduction

Robots have advanced quickly over the past few years and now serve multiple industries. Robots now serve as essential tools to enhance efficiency, precision and safety across diverse fields including manufacturing logistics healthcare and home environments. Industrial robots specialize in executing repetitive functions including welding, assembling, and packaging operations with exceptional speed and precision. Traditional robots typically consist of rigid materials and operate in structured settings. Increasing demand for safe human-compatible robots with complex task capabilities has led to development in adaptable and safer robotic systems. The emergence of flexible soft manipulators represents a new category of robots constructed from bendable materials.

Soft manipulators which emulate the flexibility of natural structures such as octopus arms, elephant trunks, and human fingers can stretch and adapt to various shapes. Soft manipulators have the ability to move freely which enables safe interactions with humans and delicate items unlike their rigid robot counterparts. Soft manipulators provide essential functionality in environments that demand delicate handling processes like medical surgery or food processing and extend to use cases such as agriculture and underwater exploration. Soft manipulators have numerous benefits but they also encounter multiple difficulties. The flexible nature of soft manipulators prevents traditional robot design methods from being effective while their unpredictable movements make them hard to control. Researchers conduct active investigations into the behavior of soft manipulators while developing advanced control systems and seeking new materials that combine strength with flexibility. The report examines flexible soft manipulators by detailing their design principles, materials used, operational mechanics, and practical applications in various environments.

1.1 Motivation

The concept of using soft and compliant materials in robotics is thrilling and critical in today's world. Traditional rigid robots, as strong and precise as they are, are handicapped when it comes to operating in uncertain environments or handling soft and delicate objects. They are also less safe when operating near humans, restricting their application in most critical applications. Soft manipulators with flexibility offer a solution to the aforementioned challenges. Their ability to bend, twist, and conform to different shapes renders them appropriate for applications that require gentle contact, flexibility, and protection. Nature-inspired robots have the potential to revolutionize industries such as minimally invasive surgery, human-robot interaction, agriculture, and underwater exploration.

Driving this research is the growing interest in soft robotics and its potential to complete the gaps left by traditional systems. Having the knowledge on how to design, control, and use soft manipulators can lead to more efficient and safer robotic interventions in real-world applications. This research project will explore the unique characteristics and potential of soft manipulators and assist in developing this new discipline.

1.2 Problem definition

Traditional robotic manipulators tend to consist of rigid components and joints, limiting them to working in structured or hard environments. The robots can be ineffective in operations involving safe human contact, flexibility, or holding soft or irregularly-shaped objects. Soft flexible manipulators, on the other hand, are a potential solution. Made of soft materials, they can bend, twist, and deform to different shapes and are flexible and safer. It is hard, however, to study them since they are non-linear and highly deformable. Designing them, modeling them, and controlling them involve different considerations from rigid robots.

The problem addressed in this study is to understand the working mechanisms, structure, materials, and control methods of soft flexible stationary manipulators. They are stationary robots that do not move but can move their body or arm using soft actuators. The objective is to have a clear understanding of how such a system would work, its advantages and disadvantages, and how it can be utilized in practical applications.

Chapter 2

Literature Review

Soft flexible manipulators design has grown immensely over the past decade due to the need for flexible and safer robotic systems. Soft manipulators are different from rigid manipulators in that they are capable of bending, twisting, and stretching and are therefore perfect for use where flexibility and safety are critical.

There are some articles that have highlighted the materials employed for soft manipulators. These can be silicone rubber, elastomers, and other kinds of polymers that are readily deformable. These enable the manipulator to glide effortlessly and to fit object shapes. Some articles have also attempted the use of fabric or sheet materials in providing strength and control. In terms of actuation mechanisms, researchers have examined numerous ways of how to drive soft manipulators. The most commonly used are:

- Pneumatic actuators- which operate using air pressure to produce motion. [1]
- Cable-driven systems- where strings or tendons are utilized to pull the soft body to produce motion. [2]
- Shape memory alloys (SMA) and electro active polymers, which change form upon heating or electrical stimulation. [3]

For stationary soft manipulators, the majority of the research is on stationary applications, like robotic arms mounted on a base. They are applied in medical settings, pick-and-place operations, or accurate lab tests, where the base remains stationary and only the arm must move in flexible manner. Researchers have explored various control strategies, including model-based control, machine learning, and sensor-based feedback systems, to control the intricate motion of soft bodies.

One of the major challenges to have been identified in the literature is the challenge of modeling and controlling soft robots due to their nonlinear and continuous deformation. The rigid-body model cannot be applied, and therefore new mathematical and simulation techniques are being formulated. Although numerous advances have been made, there is much work to be done to further develop control precision, material life, and real-world applications. The review included here suggests the field is advancing extremely fast but still has numerous areas for ongoing research most notably to make soft manipulators more efficient, and more usable for applications in everyday life.

2.1 Choice of Soft Robots over Conventional Rigid Robots

2.1.1 Safe Human-Robot Interaction

One of the biggest advantages of soft robots is their inherent safety during physical interaction with humans. Traditional rigid robots can be dangerous in close-contact environments because

of their hard components and high-force movements. In contrast, soft robots are made of compliant materials like silicone or elastomers, which reduce the risk of injury even when accidental contact occurs. This makes them ideal for collaborative robots in healthcare, domestic assistance, and elderly care. [4]

2.1.2 Adoptability and Flexibility

Soft robots can bend, stretch, and deform in ways that rigid robots cannot. This allows them to navigate tight or cluttered environments, conform to complex surfaces, and handle objects of various shapes and sizes with ease. For example, a soft gripper can gently grasp fruits, wires, or oddly shaped items without needing complex control systems. [5]




Figure 1 soft robot showing flexibility by fruit grasping [5]

2.1.3 Bio inspired Locomotion and Dexterity

Many soft robots are inspired by biological organisms such as octopuses, worms, snake and fish. This bio inspiration allows them to replicate natural movements like crawling, swimming, or slithering, which are difficult for rigid-body robots to achieve. This type of locomotion is useful in search-and-rescue operations, medical procedures, and underwater exploration.




Figure 2 Caterpillar inspired robots [5]

2.1.4 Delicate Object Handling

Soft manipulators can handle fragile items, such as biological tissues, fruits, or glassware, without damaging them. The gentle grip and distributed force of soft actuators reduce the need for complex sensors and control algorithms typically required in rigid robotic grippers.



Figure 3 soft robot performing handshake [6]

2.1.5 Resilience and Durability in Uncertain Environments

Soft robots can absorb shocks, withstand deformation, and continue operating in uncertain or rough environments where rigid robots might fail or get damaged. This makes them suitable for disaster response or navigation through rubble, pipelines, or narrow crevices. Some of the created soft robot walks through fire or gets run over by a car and still works! This makes them ideal for search-and-rescue missions in collapsed buildings. [7]

2.1.6 Lower Cost and Simpler Design

Soft robots often skip expensive motors, gears, or metal parts. Instead, they can be 3D-printed or molded in one piece, cutting production time and costs. A soft gripper might cost $50 to 3D-print, while a rigid robotic arm with similar functions could cost thousands. Some of the study note that simpler designs make soft robots accessible for small businesses or labs. [8]

2.1.7 Built-In Environmental Compliance

Soft robots don't need advanced sensors or computers to adapt to their surroundings. Their bodies naturally conform to surfaces or objects, like a soft glove molding to a hand. A soft robot exploring a rocky terrain can adjust its shape to climb over obstacles without needing a camera or AI. Some research call this "embodied intelligence," where the robot's body does the thinking. [9]

These traits make soft robots uniquely suited for tasks where safety, adaptability, and cost matter most like healthcare, disaster response, or environmental monitoring. While rigid robots excel in factories (e.g., car assembly), soft robots fill gaps in human-centered, unpredictable, or delicate applications.

2.2 Materials and Fabrication Techniques

The effectiveness and versatility of soft robotic manipulators depend heavily on the selection of appropriate materials and the fabrication methods used to construct them. These systems are built from materials that exhibit high flexibility, stretchability, and resilience, allowing for continuous deformation and safe interaction with humans and unstructured environments. The field of soft robotics leverages innovations in material science and advanced manufacturing to develop manipulators tailored for specific tasks and functionalities.

2.2.1 Silicone Elastomers

Silicone elastomers are among the most widely used materials in soft robotics due to their excellent **mechanical flexibility**, **chemical stability**, and **biocompatibility**. Materials like **Ecoflex**, **Dragon Skin**, and **PDMS (Polydimethylsiloxane)** offer high elasticity, tear resistance, and consistent performance under deformation. These silicones can stretch several times their original length without breaking and return to their initial shape, making them ideal for actuators, grippers, and joints.

Silicone elastomers are also easy to mold and can be cast into complex geometries with embedded components such as sensors or channels for pneumatic actuation. They can

withstand a range of temperatures and maintain their properties over time, which is essential for long-term robotic applications. In biomedical soft robotics, their biocompatibility makes them suitable for wearable devices and internal use. [10]

2.2.2 Hydrogels and Smart Materials

Hydrogels are polymeric networks that can retain large amounts of water, giving them a soft, jelly-like consistency similar to biological tissue. These materials are increasingly used in soft robotics for applications requiring **biointegration**, **biodegradability**, or **stimuli-responsiveness**. Hydrogels can swell or contract in response to changes in temperature, pH, or light, enabling actuation and shape change without external hardware.

In addition to hydrogels, other **smart materials** like **shape memory polymers (SMPs)** and **electroactive polymers (EAPs)** are also gaining traction. These materials change shape or stiffness when stimulated by heat, electricity, or magnetic fields, offering compact, embedded actuation without traditional pneumatic or hydraulic systems. While their force output is generally lower, their silent operation and simple structure are valuable in miniaturized or wearable robots.[11]

2.2.3 3D Printing and Additive Manufacturing

3D printing has revolutionized the fabrication of soft robotic components by enabling rapid prototyping and the creation of complex, multi-material structures. Techniques such as **fused deposition modeling (FDM)**, **stereolithography (SLA)**, and **polyjet printing** allow for the fabrication of soft parts with fine detail, internal channels, and variable stiffness within a single part.

One major advantage of additive manufacturing is its ability to fabricate **monolithic designs**, eliminating the need for manual assembly and reducing the chance of leakage or delamination in actuators. Researchers have developed customized printers capable of printing elastomers and hydrogels, expanding the material palette for soft robotics. Multi-material 3D printing also allows the integration of conductive inks, sensors, and structural supports, paving the way for soft robots with embedded functionality.

Despite its promise, challenges remain, such as ensuring strong interlayer bonding in highly stretchable materials and achieving high-speed production for commercial use. Nonetheless, 3D printing continues to push the boundaries of what is possible in soft manipulator design and functionality.[12]

2.2.4 Molding and Casting

Traditional **molding and casting techniques** remain essential for the fabrication of soft robotic components, especially when high precision and repeatability are required. This method involves pouring a liquid elastomer into a pre-made mold and curing it to form a solid yet

flexible part. Molds can be made using CNC-machined metal, 3D-printed plastic, or even silicone itself for over-molding applications.

Molding is particularly effective for creating **pneumatic actuators**, where internal channels and chambers need to be precisely shaped to achieve desired motion patterns. Multi-step molding processes can be used to embed sensors, reinforce structures, or produce composite designs with varying stiffness. Casting also allows for **custom geometries** tailored to specific tasks or anatomical shapes in medical applications.

While molding offers high quality and uniformity, it is labor-intensive and less suited for rapid iteration compared to additive manufacturing. However, it remains a reliable and scalable approach for producing soft robotic components, particularly in research labs and low-volume production settings.[13]

2.3 Different drive modes according to actuation method

2.3.1 Fluid-driven mode:

The soft manipulator with the fluid-driven mode makes spatial movement by controlling the gas or liquid pressure in the multicavity structure. According to this definition, the fluid-driven mode can be divided into gas-driven mode and liquid-driven mode. The gas-driven mode is light and pollution-free, which is widely used at present; the 2 | CHEN ET AL. liquid-driven mode has a high response frequency due to the incompressibility of the liquid (Yan et al., 2018). The difficulty of the fluid-driven mode lies in the design and the pressure control of the multicavity structure. Currently, a one of research works about this drive mode have been done and reported in the literatures. The typical design cases are shown in Figures.




Figure 5 pneumatic muscles driven soft robot [14]




Figure 4 Honeycomb network based soft manipulator [14]

Chen et al. (Hao et al., 2021; Jiang et al., 2016, 2017; You et al., 2017) designed a soft manipulator based on Honeycomb Pneumatic Networks (HPN), as shown in Figure 5. The soft manipulator was demonstrated to have a stable control performance due to structure support of the honeycomb frame.[14]

The actuation method in this paper is a pneumatic system where air pressure inflates internal airbags embedded in a honeycomb elastomer framework. This inflation causes controlled bending or elongation of the soft manipulator. The honeycomb structure provides mechanical strength and limits excessive deformation, enabling a balance between flexibility and load-bearing capacity. The actuation is controlled by regulating the pressure in specific airbags, allowing versatile motion of the manipulator.

2.3.2 Cable-driven mode

The soft manipulator with the cable-driven mode makes the spatial motion by controlling the multicable system. Each cable needs a motor for its retraction and release control. It is necessary to configure corresponding preloading device because the cable can only provide tensile force. In the research of cable-driven mode, a large number of prototypes have been seen in the literatures, as shown in Figure 6 and 7.




Figure 7 Tendon driven soft griper [15]



Figure 6 soft griper grasping object of different shape [15]

The actuation process of the tendon-driven soft–rigid modular gripper presented in the paper relies on the use of tendons (cables) that transmit force to the finger modules, causing them to bend and grasp objects. Each finger is composed of rigid phalanges connected by elastic joints made from interpenetrating phase composites (IPCs), which provide tunable stiffness and compliance. When the actuator pulls on the tendon, tension is applied along the cable routed through the finger structure. This tendon tension causes the elastic joints to deform, resulting in controlled bending of the finger segments.

Because the joints are compliant and their stiffness can be customized via the IPC material design, the tendon-driven actuation enables underactuated motion: a single tendon can control multiple joints simultaneously, allowing the fingers to conform naturally to the shape of the object being grasped. The modular design allows for adjustment of the number of phalanges and their stiffness, which in turn influences the finger's bending trajectory and grasp type (e.g., power grasp or pinch grasp). The tendon actuation thus works synergistically with the soft joints' mechanical properties to produce adaptive, robust grasping motions with relatively simple control inputs.[15]

2.3.4 Electro active polymer (EAP)-driven mode

The soft manipulator with EAP driven mode makes spatial motion by the electrostatic attraction of the conductive layer to drive the multilayer film compress and deform. EAP can be divided into electronic type and ionic type. The dielectric elastomer belongs to a typical electronic type. It requires a high drive voltage and can produce a relatively large force. Ionic type requires a low voltage, but it depends on the liquid environment and produces a small force. The typical design case seen in the literatures is investigated and shown in Figure 8 [16]




Figure 8 Soft Manipulator Driven by Dielectric elastomers [16]

The soft manipulator is actuated by dielectric elastomer actuators (DEAs) integrated into each module of the manipulator. Each module consists of a flexible polyethylene terephthalate (PET) frame wrapped into a spatially closed tubular structure, with prestretched dielectric elastomer films (VHB 4910) adhered to the frame. These DE films are biaxially prestretched (up to 400%) to enhance their electromechanical response.

When a high voltage is applied across the compliant electrodes on the DE films, electrostatic forces cause the elastomer layers to compress in thickness and expand in area. This expansion

generates a radial force on the PET frame, which causes the frame to buckle inward. This buckling induces bending deformation of the tubular module.The bending occurs because the radial force from the contracting DE films deforms the asymmetric PET frame columns inward, causing the module to bend in a controlled direction. The bending angle of each module depends on the magnitude of the applied voltage, the number of DE film layers, and the geometry of the PET frame.By stacking multiple such modules in series, each bending via this DEA-induced buckling mechanism, the entire manipulator achieves large, continuous bending deformations (exceeding 180°). The actuation is purely electrical, relying on the voltage-induced strain of the dielectric elastomer films to generate mechanical bending without any rigid motors or pneumatic components.[16]

2.3.5 Shape memory materials-driven mode

The soft manipulator with shape memory materials driven mode gets the drive force from the shape restore of the materials at a certain temperature. When the temperature reaches a certain level, the shape memory material can restore its initial memorized shape. To make use of the shape restore process, the drive force can be obtained. According to different materials, it is divided into shape memory alloy (SMA) and shape memory polymer (SMP). As reported in the literatures, the SMA is used commonly in the shape memory materials-driven soft manipulator.

2.3.6 Electromagnetic-driven mode

The soft manipulator with electromagnetic-driven mode conducts its motion control based on the interaction effect of the ferromagnetic soft material and the external magnetic field. The difficulty lies in the design of the magnetic soft robot and the development of the stable and controllable strong magnetic field environment. The electromagnetic-driven soft robot is made of the ferromagnetic soft materials by programmable magnetic printing or mixed casting. The external magnetic field is generated by using the electromagnetic coils distributed in a complex way. The typical design case of the electromagnetic-driven soft robot are shown in Figure

2.3.7 Hybrid drive Mode

Hybrid drive mode is a combination of two or more different drive modes to improve the load capacity or the control accuracy of the soft manipulator. For example, one of the typical hybrid drive mode is the combination of the fluid-driven mode and the cable-driven mode. The fluid-driven mode has a good characteristic of pressure bearing, but a weak performance of tensile bearing. The cable-driven mode has a strong tensile resistance, but cannot bear pressure. The

combination of these two driven modes can give the soft manipulator good characteristics of pressure bearing and tensile bearing, thus increases its load capacity and position control accuracy. The hybrid drive mode keeps the complementary advantages of different drive modes. However, it greatly increases the difficulties and technical challenges of the design and development of the control system as well as the control algorithm. [17]

2.4 Modeling and Control

Modeling and control in soft robotics are more complex than in traditional rigid robotics due to the continuous deformation and high compliance of soft materials. Unlike rigid manipulators that use joint-based models and deterministic control, soft robots require nonlinear, distributed, and often data-driven models to describe their motion and interaction with the environment. Accurate modeling is essential for predicting system behavior, designing effective controllers, and enabling reliable task execution.

2.4.1 Kinematic Modeling

Kinematic modeling in soft robotics focuses on describing the motion of the manipulator without considering the forces that cause it. Unlike rigid robots, where links and joints have defined lengths and angles, soft manipulators deform continuously, leading to **infinite degrees of freedom** (DoF). To simplify this, researchers often use approximations like:

- **Piecewise Constant Curvature (PCC)**: Assumes that the soft manipulator bends in constant-radius segments. This reduces the problem to a finite set of curvature parameters and is widely used in continuum robot modeling.
- **Cosserat Rod Theory**: A more advanced approach, treating the manipulator as a flexible rod governed by a system of differential equations. It accounts for bending, twisting, stretching, and shearing.

Kinematic models are essential for motion planning, trajectory generation, and workspace analysis of soft robotic arms.[18]

2.4.2 Dynamic Modeling

Dynamic modeling incorporates forces and torques, describing how the manipulator moves in response to actuation and external forces. Due to the nonlinear and distributed nature of soft materials, classical rigid-body dynamics do not apply directly.

Instead, researchers often use:

- **Euler–Bernoulli beam theory** (for simple deformation under small loads),
- **Cosserat theory** (for large, complex deformations),
- Or **mass-spring-damper systems** as simplified approximations.

These models are useful in simulating the behavior of soft robots under different loading and actuation conditions. However, due to the complexity and material variability, dynamic modeling often requires experimental calibration and validation. [18]

2.4.3 Finite Element Modeling (FEM)

Finite Element Modeling (FEM) is a powerful numerical method used to simulate the deformation and stress distribution in soft robotic structures. FEM is particularly suited to soft robotics because:

- It can handle complex geometries and material nonlinearities.
- It can simulate how actuators deform over time or under external forces.
- It supports multi-material and multi-physics simulations (e.g., coupling fluid actuation with structural deformation).

Commercial software like **ANSYS**, **Abaqus**, or open-source tools like **SOFA** are commonly used to model soft robotic components. FEM also plays a key role in optimizing designs before fabrication and understanding performance limitations.

However, FEM can be computationally expensive and may not be suitable for real-time control unless simplified or reduced-order models are used.[19]

2.4.4. Data-Driven and Machine Learning Models

Given the limitations of analytical models for highly complex, nonlinear behaviors, **machine learning (ML)** and **data-driven approaches** are increasingly popular in soft robotics. These methods rely on experimental data to train models that predict manipulator behavior or generate control inputs.

Common techniques include:

- **Neural networks** for forward/inverse kinematics and force estimation.
- **Reinforcement learning (RL)** for policy optimization and adaptive control.
- **Gaussian processes** or **support vector machines (SVMs)** for regression tasks.

Data-driven models can compensate for modeling inaccuracies and adapt to material wear or environmental changes, making them useful for real-world applications. However, they require extensive training data and may lack physical interpretability.[20]

2.4.5 Control Strategies

Controlling a soft robotic manipulator is challenging due to its infinite DoF, nonlinear elasticity, and hysteresis. As a result, a variety of **control strategies** have been developed, including:

- **Open-loop control**: Simple but limited in accuracy, often used for exploratory or demonstration purposes.
- **Closed-loop control (feedback control)**: Uses sensors (e.g., pressure, strain, vision) to adjust inputs in real time.
- **Model Predictive Control (MPC)**: Optimizes future control actions based on a model of the system, suitable for dynamic tasks.
- **Learning-based control**: Includes neural network controllers, imitation learning, and reinforcement learning approaches that adapt based on performance.
- **Hybrid control**: Combines model-based and data-driven techniques to balance accuracy and robustness.

Soft robot control often requires **sensor fusion** and **real-time estimation** of shape and force due to the lack of rigid encoders or clear joint angles.[21]

2.5 Sensing Technology

Sensing technology is crucial for the effective operation of soft robotic manipulators. These robots, due to their inherent compliance and flexibility, require advanced sensing systems to accurately perceive their environment and their own state. Unlike rigid robots that rely on fixed joint angles and positions, soft robots often require distributed sensors to detect deformation, contact, and environmental factors. These sensors enable feedback mechanisms that support real-time control, adaptive behaviors, and precise interactions.

2.5.1. Tactile Sensing

Tactile sensing refers to the ability of a soft robotic manipulator to detect and respond to physical interactions with objects in its environment, such as touch, pressure, or texture. Tactile sensors are often used for:

- **Object grasping and manipulation**: By detecting the shape, texture, and force of contact with an object, soft robots can adjust their grip to avoid slippage or damage to the object.
- **Human-robot interaction**: In medical and assistive robotics, tactile sensing ensures that robots apply the right amount of force, especially when interacting with sensitive or delicate materials.

Common tactile sensing methods include:

- **Resistive sensors**: Changes in resistance are detected as the sensor is compressed, commonly used in soft robots for force and touch sensing.
- **Capacitive sensors**: Measure changes in capacitance due to deformation, which is useful for determining proximity and contact.
- **Piezoelectric sensors**: Used to detect dynamic pressure changes during manipulation.

Tactile sensing is vital for improving the dexterity and safety of soft robotic systems.

2.5.2. Proprioception

Proprioception refers to the ability of a soft robot to sense its own internal state, such as its position, velocity, and deformation. This feedback is essential for accurate motion control and for understanding how the robot's body is behaving during manipulation tasks.

Soft robots, unlike rigid robots with defined joint angles, use proprioceptive sensors that detect changes in deformation or strain across the robot's body. Proprioception is typically achieved through:

- **Stretchable strain sensors**: These sensors detect the deformation of soft materials and provide feedback on bending, stretching, and compression.
- **Distributed encoders**: Embedded along the robot's body, these can estimate the relative position of different segments or actuators, even in highly deformable systems.

Proprioception helps in tasks requiring precision, like tracking arm posture or maintaining orientation in unstructured environments.

2.5.3. Vision Systems

Vision systems are used in soft robotics to allow the robot to perceive its environment and adjust its actions based on visual input. For soft robots, vision systems play a critical role in:

- **Object recognition**: Allowing robots to identify and interact with objects of varying sizes, shapes, and textures.
- **Localization**: Vision aids in mapping the robot's surroundings or determining its position relative to other objects or targets in a workspace.
- **Dynamic interaction**: Combining vision with tactile feedback enables real-time decision-making when performing tasks like object manipulation.

Soft robots often integrate **camera-based vision systems**, **depth cameras**, or **stereo vision**, which help to gather visual information for autonomous decision-making. Advanced image processing and machine learning algorithms are then used to analyze the visual data.

2.5.4. Force and Pressure Sensing

Force and pressure sensing is essential for detecting the forces applied during interaction, ensuring the robot's actions are safe and effective. These sensors are widely used for applications like gripping, pushing, or lifting delicate objects.

Common methods for force and pressure sensing include:

- **Pneumatic sensors**: In pneumatic actuators, pressure sensors can detect the internal pressure in actuators to infer the force being applied by the robot.

- **Piezoelectric sensors**: These sensors detect force changes based on the deformation of materials under pressure, offering both dynamic and static force measurements.
- **Capacitive force sensors**: Detect pressure variations based on changes in the capacitance between electrodes as the soft material compresses.

By monitoring forces during manipulation, soft robots can adjust their movements, preventing damage to both themselves and the objects they handle.

2.5.5. Strain and Deformation Sensing

Since soft robots often undergo large deformations, **strain and deformation sensing** is a critical component of their control and feedback systems. These sensors measure the stretching, compressing, or bending of the robot's body as it deforms during actuation or interaction with the environment.

- **Stretchable sensors**: These sensors, often made from conductive polymers or elastomers, detect elongation or compression and provide continuous feedback about the robot's deformation.
- **Fiber-optic sensors**: Fiber-optic sensors use light transmission to detect strain in soft robots, enabling high-resolution, accurate deformation monitoring over long distances.
- **Conductive materials**: Soft robots often incorporate conductive fabrics or inks that change resistance as the robot deforms, offering an inexpensive and flexible method for strain sensing.

Strain sensors are key for monitoring how much a soft manipulator is bending, stretching, or twisting, which aids in proprioception and helps to adjust movement and force during operation.

2.5.6. Environmental Sensing

Environmental sensing enables the robot to perceive external conditions, such as temperature, humidity, or the presence of obstacles. These sensors allow the robot to adapt to changing environments and ensure safety in unpredictable conditions.

- **Thermal sensors**: Detect changes in temperature, which is useful for tasks that require thermal management or for robots working in varying environmental conditions.
- **Humidity sensors**: Measure environmental moisture levels, which may influence the performance of soft robots, particularly in bio-inspired or biological applications.
- **Proximity sensors**: Non-contact sensors, such as ultrasonic or infrared, help soft robots detect nearby objects, ensuring safe navigation and collision avoidance.

Environmental sensing is essential for soft robots operating in unstructured environments, as it helps them understand the conditions they are working in and adjust accordingly.

2.5.7. Sensor Integration and Fusion

Sensor integration and fusion refers to the combination of data from multiple sensors to provide a more complete and accurate understanding of the robot's environment and internal state. This process enables more sophisticated behaviors and decision-making, especially when using different types of sensors such as tactile, proprioceptive, and vision-based sensors.

- **Sensor fusion algorithms**: These combine information from various sensors to improve accuracy, reduce noise, and provide reliable feedback for control systems.
- **Multi-modal sensing**: Soft robots can integrate multiple sensing modalities (e.g., tactile, force, and vision) to provide a richer set of data. This enables more nuanced interaction with the environment and better task execution.
- **Real-time feedback**: Sensor fusion allows for real-time feedback and dynamic adjustment of the robot's actions, improving task efficiency and safety.

Effective sensor fusion is crucial for the reliable operation of soft robots, especially in complex or unstructured environments.[22]

2.6 Challenges and Limitations in Soft Robotic Manipulators

While soft robotic manipulators hold great promise in a variety of applications due to their inherent flexibility, compliance, and adaptability, they also face significant challenges and limitations that hinder their widespread adoption and performance. These challenges range from material constraints and actuation issues to complex control and sensing requirements. Understanding these limitations is crucial for advancing the field and designing more efficient and reliable soft robotic systems.

2.6.1 Material Limitations

The performance of soft robotic manipulators heavily relies on the materials used in their construction. While soft materials offer flexibility, they also present several challenges:

- **Material fatigue**: Soft materials, such as elastomers or silicones, are prone to wear and tear over time, especially under repeated deformation. This results in **material fatigue**, which can lead to performance degradation and eventual failure.
- **Limited durability**: Soft materials may not withstand harsh environments or long-term use. For instance, exposure to extreme temperatures, UV radiation, or chemical agents can cause degradation of the material properties, impacting the robot's reliability.
- **Limited strength-to-weight ratio**: While soft materials are lightweight and flexible, they often lack the strength-to-weight ratios found in traditional rigid materials. This makes them unsuitable for tasks that require significant force or load-bearing capacity.
- **Limited variety of materials**: The variety of soft materials available with desired mechanical properties (e.g., high elasticity, low viscosity, high fatigue resistance) is still limited, and integrating multiple materials with different properties in one system remains challenging.

Overcoming these material limitations requires the development of new, advanced soft materials that combine high strength, durability, and flexibility, ideally tailored for specific robotic tasks.[23]

2.6.2 Actuation Challenges

Actuation is one of the most critical aspects of soft robotics, but it also presents several challenges:

- **Limited precision and control**: Soft actuators, such as pneumatic, hydraulic, or elastic actuators, often lack the fine control and precision that rigid actuators (e.g., motors or servos) offer. This makes it difficult to achieve accurate positioning and high precision in tasks that demand fine manipulation.
- **Slow response time**: Many soft actuators, particularly those that rely on fluidic systems (e.g., pneumatics and hydraulics), have slower response times compared to traditional electric actuators. This can limit their use in real-time, high-speed applications.
- **Complex actuation mechanisms**: Soft actuators often require more complex systems for control, including valves, pumps, or pressure regulation systems. These can add to the system's complexity, making it harder to design, maintain, and troubleshoot.
- **Limited force output**: While soft actuators are highly adaptable and flexible, they typically generate less force compared to rigid actuators. This limits their use in tasks that require significant lifting or manipulation forces, such as heavy industrial tasks.

To address these challenges, researchers are developing more advanced actuation techniques, such as soft robots with embedded actuators, hybrid actuation systems, and actuation based on new principles like shape memory alloys (SMAs) or electroactive polymers (EAPs).

2.6.3 Control Complexity

The control of soft robotic manipulators is inherently more complex than rigid robots due to the continuous deformation of soft materials and the infinite degrees of freedom (DoF) associated with them:

- **Nonlinear behavior**: Soft robots exhibit highly nonlinear behavior, which makes it difficult to model and control their movements accurately. The deformation of soft materials is dependent on multiple factors, including material properties, shape, and the nature of external forces.
- **High-dimensional control**: Since soft robots often have many degrees of freedom, controlling their motion requires handling a large number of variables simultaneously, making the system harder to control. Standard control methods, such as inverse kinematics, are often insufficient for soft robots due to their continuous, deformable nature.
- **Limited control algorithms**: While various algorithms, such as model-based control, machine learning, and reinforcement learning, have been applied to soft robots, many of these methods still require further refinement for real-time applications. Moreover,

real-time control in soft robots demands a fast feedback loop, which can be computationally intensive and challenging to implement in practice.
- **Stability issues**: Ensuring stable operation during manipulation tasks can be difficult due to the high sensitivity of soft robots to small changes in the environment or internal conditions. This is particularly problematic when the robot needs to operate autonomously or interact with unknown or dynamic environments.

Advancements in adaptive control, machine learning, and sensor integration are required to make soft robot control more reliable and practical for complex tasks.[25]

2.6.4 Sensing Challenges

Effective sensing is crucial for soft robots to interact with their environment and perform tasks safely and efficiently. However, soft robots face several sensing challenges:

- **Distributed and continuous sensing**: Since soft robots deform continuously, it is challenging to implement accurate and distributed sensing systems that can monitor changes across the entire structure. This often requires specialized sensors, such as strain gauges, stretchable tactile sensors, or fiber-optic sensors, which may not always be reliable or accurate.
- **Sensor integration**: Integrating sensors into soft robotic systems is a challenge due to the deformable nature of the materials. The sensors must be flexible and capable of withstanding large deformations without losing functionality. Moreover, embedding sensors without affecting the robot's flexibility is a complex design challenge.
- **Feedback accuracy**: The accuracy of sensory feedback in soft robots can be compromised by the inherent material deformations and environmental noise. As a result, obtaining high-quality, real-time feedback for closed-loop control is challenging.

Improving soft robot sensors involves developing more resilient and precise sensing technologies and integrating multiple sensor types to provide comprehensive, real-time environmental and proprioceptive feedback.[26]

2.6.5 Durability and Longevity

Soft robots are generally less durable than rigid robots, especially when subjected to repeated stress or use in harsh environments. Their longevity is limited by:

- **Deformation-induced wear**: Soft robots are subjected to constant deformation, which can lead to material fatigue, tearing, or degradation over time, particularly in applications where repetitive motions are involved.
- **Environmental factors**: Soft robots may not perform well in extreme environmental conditions such as high humidity, extreme temperatures, or corrosive environments. Many soft materials used in soft robotics are susceptible to environmental damage, such as cracking or degradation from UV exposure.

- **Maintenance challenges**: Given the complex actuation and sensing systems, as well as the material degradation over time, maintaining and repairing soft robots is often more challenging than with rigid robots.

Ensuring the longevity and durability of soft robots requires ongoing research into new materials, more robust actuation mechanisms, and advanced wear-resistant coatings or protective layers.[27]

2.6.6 Cost and Scalability

Soft robotics technologies, particularly those that involve novel materials, advanced actuators, and integrated sensing systems, can be expensive to design and produce. Some of the challenges related to cost and scalability include:

- **High material costs**: Soft materials with desired properties (e.g., high elasticity, durability, and strength) may be more expensive than traditional materials, making the production of soft robots costly.
- **Complex fabrication processes**: The fabrication of soft robots often involves intricate processes, such as 3D printing or mold-based techniques, which can be time-consuming and require specialized equipment.
- **Scaling production**: While prototypes and small-scale production are possible, scaling soft robotics technologies for mass production while keeping costs low remains a significant challenge.[28]

Efforts to reduce costs will require innovations in manufacturing techniques, the use of more cost-effective materials, and the development of scalable fabrication methods.

2.7 Future Directions in Soft Robotic Manipulators

Soft robotics, with its unique capabilities, is rapidly advancing toward becoming a significant technological paradigm for various industries. The future of soft robotic manipulators is poised to be shaped by breakthroughs in material science, actuation methods, sensing technologies, control strategies, and integration with artificial intelligence (AI) and machine learning (ML). While soft robotics have already demonstrated promising capabilities, the field still faces several challenges that need to be addressed to unlock their full potential. Below are the key future directions for soft robotic manipulators:

2.7.1 Advanced Materials Development

The development of novel materials with improved properties is one of the most critical aspects of advancing soft robotic manipulators. Future materials for soft robotics need to combine

flexibility, strength, durability, and adaptability, while also being lightweight and cost-effective. Potential areas of focus include:

- **Self-healing materials**: These materials can repair themselves after being damaged, which would significantly enhance the durability and longevity of soft robots. Self-healing polymers and elastomers could extend the operational lifetime of soft manipulators, especially in harsh environments or in applications where repair and maintenance are difficult.
- **Responsive materials**: Materials that can change their properties (e.g., shape, stiffness, or conductivity) in response to environmental stimuli like temperature, light, or electric fields are likely to play a central role in the future. Examples include **electroactive polymers (EAPs)** and **shape memory alloys (SMAs)**, which can be triggered to change shape or mechanical properties in response to external signals.
- **Multi-functional materials**: Combining multiple functions in a single material, such as integrated actuation and sensing, would make soft robots more efficient and versatile. For example, materials that can both sense deformation and change shape in response to stimuli would streamline the integration of actuation and feedback systems.[29]

By advancing material science, soft robots will become more reliable, adaptable, and capable of performing a broader range of tasks.

2.7.2 Actuation Innovation

Actuation is central to the operation of soft robots, and future research will focus on enhancing actuation methods to improve performance and expand their application range. Potential areas for innovation include:

- **High-performance soft actuators**: Developing actuators that offer better precision, faster response times, and higher force output will enable soft robots to handle more demanding tasks. Research into **pneumatic artificial muscles (PAMs)**, **hydraulic actuators**, and **synthetic muscle fibers** is expected to result in more powerful and responsive soft actuators.
- **Autonomous actuation systems**: The integration of actuators with autonomous control mechanisms will allow soft robots to perform tasks without requiring external intervention. **Distributed actuation networks**, where each segment of a soft robot is controlled independently, will enhance adaptability and precision in complex environments.
- **Miniaturization**: As actuators become smaller and more efficient, soft robots can be deployed in micro and nanoscale applications, such as medical surgery, inspection tasks, and delicate material handling, where conventional rigid robots would be impractical.[30]

Improving actuation systems will expand the range of applications for soft robotic manipulators, from precision manipulation to complex, large-scale industrial tasks.

2.7.3. Integration with Artificial Intelligence (AI) and Machine Learning (ML)

The incorporation of AI and ML techniques into soft robotics will significantly enhance their capabilities, particularly in tasks involving decision-making, adaptation, and real-time optimization. Future directions in AI integration include:

- **Adaptive control systems**: Soft robots are highly sensitive to environmental changes. AI algorithms, such as **reinforcement learning (RL)**, can be used to develop adaptive control systems that allow soft robots to learn from their interactions and improve their performance over time. These systems will enable robots to perform tasks more efficiently and autonomously in dynamic environments.
- **Sensor fusion with AI**: Combining data from multiple sensors (e.g., tactile, vision, force) using AI will improve the robot's understanding of its environment and its own state. **Deep learning** and **neural networks** will enable better interpretation of complex data, such as recognizing objects, predicting deformations, and understanding complex tactile feedback.
- **Autonomous task planning**: AI can enable soft robots to autonomously plan and execute tasks, making them suitable for high-level decision-making scenarios, such as autonomous assembly, inspection, and even collaborative human-robot interaction.

AI and ML technologies are essential for enabling soft robots to operate autonomously, improve over time, and handle more complex, unpredictable environments.[31]

2.7.4. Bio inspired Designs

Bioinspired designs, often referred to as **biomimicry**, will continue to drive innovations in soft robotics. By studying and replicating the structure, movement, and behavior of biological organisms, soft robots can achieve higher efficiency, adaptability, and resilience. Some future bioinspired directions include:

- **Soft actuators inspired by biological muscles**: Emulating the structure and function of muscles, tendons, and other soft biological tissues will result in soft robots with smoother, more coordinated movements. Advances in **biomimetic actuators**, like those based on muscle-like materials, will lead to robots that can perform delicate tasks, such as surgery or handling fragile objects.
- **Adaptive and self-healing robots**: Inspired by biological organisms that can self-repair or adapt to changing conditions, future soft robots may incorporate self-healing materials and adaptive behaviors to prolong their operational lifespan and improve reliability.
- **Locomotion based on animal movement**: Soft robots could be designed to mimic the locomotion patterns of animals, such as the flexibility of octopus arms or the undulation of worms. These movements can be applied to soft robots for navigating complex and unstructured environments, including underwater or tight spaces.[32]

Bioinspired designs will lead to soft robots that can perform a wider range of tasks with greater versatility and resilience, pushing the boundaries of what robots can do.

2.7.5 Hybrid Soft-Rigid Robots

While soft robots are highly versatile, they are limited by their relatively low strength and precision. Hybrid robots, which combine both soft and rigid components, are expected to emerge as an important direction for soft robotics. These hybrid robots could take advantage of the flexibility and compliance of soft robots, while maintaining the precision and force generation capabilities of rigid structures. Potential benefits include:

- **Enhanced load-bearing capacity**: By incorporating rigid structures into soft robots, hybrid systems can perform tasks that require higher load-bearing capacity while still maintaining flexibility for delicate interactions.
- **Increased versatility**: Combining soft and rigid components enables the design of robots that can change their stiffness or shape, depending on the task at hand. This would allow soft robots to perform both fine manipulation tasks and more robust tasks requiring higher precision and force.
- **Improved dexterity and control**: Hybrid robots could utilize rigid components for precise control in key parts of their structure (e.g., actuators), while using soft materials for flexibility and compliance in other areas (e.g., end effectors).

The development of hybrid robots will open up new opportunities in fields such as manufacturing, medical robotics, and disaster response, where versatility and adaptability are critical.[33]

2.7.6 Integration into Industry and Medicine

The future of soft robotic manipulators is closely tied to their integration into real-world applications, particularly in industries like manufacturing, healthcare, and service robotics. Some key future trends include:

- **Collaborative robots (cobots)**: Soft robots will play an essential role in collaborative environments, where they work alongside humans to perform tasks like assembly, packaging, or testing. Their flexibility and compliance make them ideal for working safely with humans in shared spaces.
- **Medical robots**: In medicine, soft robots are expected to revolutionize surgery, rehabilitation, and assistive technologies. For example, soft robotic endoscopes, surgical instruments, and prosthetics could lead to minimally invasive procedures, better patient outcomes, and improved accessibility for patients with disabilities.
- **Agriculture and exploration**: Soft robots could be used for tasks such as delicate harvesting, plant care, and exploration of inaccessible environments like caves, underwater habitats, or space.

The continuous development of soft robotics technologies will lead to their increased integration across these sectors, enabling more efficient, safe, and adaptable solutions.

Chapter 3

3.1 Conclusion

Soft robotic manipulators are changing the way we think about robots. Unlike traditional rigid robots, they are flexible, safe, and can adapt to different environments. Inspired by nature, they can perform delicate and complex tasks with great care, making them ideal for use in fields like healthcare, farming, manufacturing, and space exploration. While there are still challenges—like material limits, control difficulties, and durability—these are being improved through new materials, better actuators, and smarter control systems. Using artificial intelligence and machine learning, soft robots are becoming more autonomous and responsive to their surroundings.

Looking ahead, we can expect advances like self-healing materials, better sensors, and robots that combine soft and rigid parts. These improvements will make soft robots even more useful in surgery, precise manufacturing, wearable tech, and more.In short, the future for soft robotic manipulators is very promising. With ongoing research and innovation, they are set to play a major role in many industries, helping humans work more safely and efficiently.

3.2 Further Work

This seminar has provided a foundational understanding of soft robotic manipulators—their materials, actuation methods, sensing strategies, and design considerations. The current research has focused on studying the fundamental principles of soft manipulators, including their compliant behavior, control challenges, and potential for safe interaction in dynamic environments.

Building upon this foundation, the next phase of research will explore the integration of these manipulators into **automated electric vehicle (EV) charging stations**. This future work aims to design a soft robotic arm that can autonomously identify the charging port of a vehicle, align precisely, and insert the charging connector without damaging vehicle surfaces or requiring human intervention.This research will not only contribute to advancements in soft robotics but also address the growing demand for scalable, user-friendly, and autonomous EV charging infrastructure. The outcome is expected to enhance sustainability, reduce reliance on manual operations, and accelerate the adoption of electric vehicles.

References

[1] Chen, X., Zhang, X., Huang, Y., Cao, L., & Liu, J. (2022). A review of soft manipulator research, applications, and opportunities. *Journal of Field Robotics*, *39*(3), 281-311.

[2] Khalil TA, Habib S, Seadby SG, Maged SA. A structural optimization analysis of cable-driven soft manipulator. International Journal of Advanced Robotic Systems. 2024;21(2). doi:10.1177/17298806241246886

[3] Kheirikhah, Mohammad & Rabiee, Samaneh & Edalat, Mohammad. (2010). A Review of Shape Memory Alloy Actuators in Robotics. 206-217. 10.1007/978-3-642-20217-9_18.

[4] Kim, Sangbae & Laschi, Cecilia & Trimmer, Barry. (2013). Soft robotics: A bioinspired evolution in robotics. Trends in biotechnology. 31. 10.1016/j.tibtech.2013.03.002.

[5] Kim, Sangbae & Laschi, Cecilia & Trimmer, Barry. (2013). Soft robotics: A bioinspired evolution in robotics. Trends in biotechnology. 31. 10.1016/j.tibtech.2013.03.002.

[6] [Online]. Available: https://www.tudelft.nl/en/ide/research/technology/soft-robotics.

[7] R.F. Shepherd, F. Ilievski, W. Choi, S.A. Morin, A.A. Stokes, A.D. Mazzeo, X. Chen, M. Wang, & G.M. Whitesides, Multigait soft robot, Proc. Natl. Acad. Sci. U.S.A. 108 (51) 20400-20403, https://doi.org/10.1073/pnas.1116564108 (2011).

[8] R.F. Shepherd, F. Ilievski, W. Choi, S.A. Morin, A.A. Stokes, A.D. Mazzeo, X. Chen, M. Wang, & G.M. Whitesides, Multigait soft robot, Proc. Natl. Acad. Sci. U.S.A. 108 (51) 20400-20403, https://doi.org/10.1073/pnas.1116564108 (2011).

[9] Rolf Pfeifer, Max Lungarella, and Fumiya Iida. 2012. The challenges ahead for bio-inspired 'soft' robotics. Commun. ACM 55, 11 (November 2012), 76–87. https://doi.org/10.1145/2366316.2366335

[10] Dong, Hui & Weng, Tao & Zheng, Kexin & Sun, Hao & Chen, Bingxing. (2024). Review: Application of 3D Printing Technology in Soft Robots. 3D Printing and Additive Manufacturing. 11. 10.1089/3dp.2023.0127.

[11] Y. Lee, W.J. Song, J.-Y. Sun,Hydrogel soft robotics,Materials Today Physics,Volume 15,2020,

[12] Yap, Y. L., Sing, S. L., & Yeong, W. Y. (2020). A review of 3D printing processes and materials for soft robotics. Rapid Prototyping Journal, 26(8), 1345-1361.

[13] Marchese, Andrew D. Katzschmann, Robert K. Rus, Daniela, A Recipe for Soft Fluidic Elastomer Robots

[14] Hao, Jiang & Liu, Xinghua & Chen, Xiaotong & Wang, Zhanchi & Jin, Yusong & Chen, Xiaoping. (2016). Design and simulation analysis of a soft manipulator based on honeycomb pneumatic networks. 350-356. 10.1109/ROBIO.2016.7866347.

[15] Hussain, Irfan Al-Ketan, Oraib Design and prototyping soft–rigid tendon-driven modular grippers using interpenetrating phase composites materials,2020

[16] Xing, Zhiguang & Zhang, Junming & McCoul, David & Cui, Yanzhen & Sun, Lining & Zhao, Jianwen. (2020). A Super-Lightweight and Soft Manipulator Driven by Dielectric Elastomers. Soft Robotics. 7. 10.1089/soro.2018.0134.

[17] Chen, Xiaoqian & Zhang, Xiang & Huang, Yiyong & Cao, Lu & Liu, Jinguo. (2021). A review of soft manipulator research, applications, and opportunities. Journal of Field Robotics. 39. 10.1002/rob.22051.

[18] Till J, Aloi V, Rucker C. Real-time dynamics of soft and continuum robots based on Cosserat rod models. The International Journal of Robotics Research. 2019;38(6):723-746. doi:10.1177/0278364919842269

[19] Xavier, Matheus & Fleming, Andrew & Yong, Yuen Kuan. (2020). Finite Element Modeling of Soft Fluidic Actuators: Overview and Recent Developments. Advanced Intelligent Systems. 3. 10.1002/aisy.202000187.

[20] Chen, Zixi and Renda, Federico and Le Gall,Data-Driven Methods Applied to Soft Robot Modeling and Control: A Review

[21] Bruder, D., Gillespie, B., Remy, C. D., & Vasudevan, R. (2019). Modeling and control of soft robots using the koopman operator and model predictive control. *arXiv preprint arXiv:1902.02827*.

[22] Hegde C, Su J, Tan JMR, He K, Chen X, Magdassi S. Sensing in Soft Robotics. ACS Nano. 2023 Aug 22;17(16):15277-15307. doi: 10.1021/acsnano.3c04089. Epub 2023 Aug 2. PMID: 37530475; PMCID: PMC10448757.

[23] H. Tian, X. Xiang, K. He, C. Liu, S. Hou, S. Wang, Y. Huang, X. Wu, W. Wen, Automatically Adaptive Ventilated Metamaterial Absorber for Environment with Varying Noises. *Adv. Mater. Technol.* 2021, 6, 2100668.

[24] J. Shintake, V. Cacucciolo, D. Floreano, H. Shea, *Adv. Mater.* 2018, 30, 1707035. **https://doi.org/10.1002/adma.201707035**

[25] R.F. Shepherd, F. Ilievski, W. Choi, S.A. Morin, A.A. Stokes, A.D. Mazzeo, X. Chen, M. Wang, & G.M. Whitesides, Multigait soft robot, Proc. Natl. Acad. Sci. U.S.A. 108 (51) 20400-20403, https://doi.org/10.1073/pnas.1116564108 (2011).

[26] C. Larson *et al.* Highly stretchable electroluminescent skin for optical signaling and tactile sensing.*Science***351**,1071-1074(2016).DOI:10.1126/science.aac5082

[27] R.F. Shepherd, F. Ilievski, W. Choi, S.A. Morin, A.A. Stokes, A.D. Mazzeo, X. Chen, M. Wang, & G.M. Whitesides, Multigait soft robot, Proc. Natl. Acad. Sci. U.S.A. 108 (51) 20400-20403, https://doi.org/10.1073/pnas.1116564108 (2011).

[28] Wehner, M., Truby, R., Fitzgerald, D. *et al.* An integrated design and fabrication strategy for entirely soft, autonomous robots. *Nature* **536**, 451–455 (2016). https://doi.org/10.1038/nature19100

[29] H. Tian, X. Xiang, K. He, C. Liu, S. Hou, S. Wang, Y. Huang, X. Wu, W. Wen, Automatically Adaptive Ventilated Metamaterial Absorber for Environment with Varying Noises. *Adv. Mater. Technol.* 2021, 6, 2100668. **https://doi.org/10.1002/admt.202100668**

[30] Robert K. Katzschmann *et al*Exploration of underwater life with an acoustically controlled soft robotic fish.*Sci. Robot.***3**,eaar3449(2018).DOI:10.1126/scirobotics.aar3449

[31] R.F. Shepherd, F. Ilievski, W. Choi, S.A. Morin, A.A. Stokes, A.D. Mazzeo, X. Chen, M. Wang, & G.M. Whitesides, Multigait soft robot, Proc. Natl. Acad. Sci. U.S.A. 108 (51) 20400-20403, https://doi.org/10.1073/pnas.1116564108 (2011).

[32] Sangbae Kim, Cecilia Laschi, Barry Trimmer,Soft robotics: a bioinspired evolution in robotics,Trends in Biotechnology,Volume 31, Issue 5,2013,

[33] Wehner, M., Truby, R., Fitzgerald, D. *et al.* An integrated design and fabrication strategy for entirely soft, autonomous robots. *Nature* **536**, 451–455 (2016). https://doi.org/10.1038/nature19100

[34] Cecilia Laschi, 1* Barbara Mazzolai, 2 Matteo Cianchetti 1 Soft robotics: Technologies and systems pushing theboundaries of robot abilities