

The akshar package

Vu Van Dung

Version 0.1 — 2020/05/17

Abstract

This package provides tools to deal with special characters in a Devanagari string.

Contents

1	Introduction	1
2	User manual	1
2.1	$\LaTeX 2_{\epsilon}$ macros	1
2.2	expl3 functions	2
3	Implementation	2
3.1	Variable declarations	2
3.2	Utilities	3
3.3	The <code>\akshar_convert</code> function	3
3.4	Front-end $\LaTeX 2_{\epsilon}$ macros	4
	Index	4

1 Introduction

When dealing with processing strings in the Devanagari script, normal \LaTeX commands usually find some difficulties in distinguishing “normal” characters, like क, and “special” characters, for example ् or ी. Let’s consider this example code:

```
1 \ExplSyntaxOn
2 \tl_set:Nn \l_tmpa_tl { की}
3 \tl_count:N \l_tmpa_tl \c_space_token tokens.
4 \ExplSyntaxOff
```

2 tokens.

The output is 2, but the number of characters in it is only one! The reason is quite simple: the compiler treats की as a normal character, and it shouldn’t do so.

To tackle that, this package provides expl3 functions to “convert” a given string, written in the Devanagari script, to a sequence of token lists. Each of these token lists is a “true” Devanagari character. You can now do anything you want with this sequence; and this package does provide some front-end macros for some simple actions on the input string.

2 User manual

2.1 $\LaTeX 2_{\epsilon}$ macros

`\aksharStrLen` `\aksharStrLen {<token list>}`

Return the number of Devanagari characters in the `<token list>`.

There are 4 characters in नमस्कार.
expl3 returns 7, which is wrong.

\aksharStrChar

Return the n -th character of the token list.

```

1 3rd character of नमस्कार is \aksharStrChar{ नमस्कार}{3}.\par
2 \ExplSyntaxOn
3 It is not ~\tl_item:nn { नमस्कार } {3}.
4 \ExplSyntaxOff

```

2.2 expl3 functions

```
\akshar_convert:Nn
```

```
\akshar_convert:(cn|Nx|cx)
```

न, म, स्का, and र

3 Implementation

Declare the package. By loading fontspec, xparse, and in turn, expl3, are also loaded.

3.1 Variable declarations

These variables store the special characters we need to take into account:

```
6 \tl_const:Nn \c__akshar_joining_tl { }
```

8 {

(End definition for \c_akshar_joining_tl and \c_akshar_diacritics_tl.)

`\l__akshar_prev_joining_bool` When we get to a normal character, we need to know whether it is joined, i.e. whether the previous character is the joining character. This boolean variable takes care of that.

```
13 \bool_new:N \l__akshar_prev_joining_bool
```

(End definition for `\l__akshar_prev_joining_bool`.)

`\l__akshar_char_seq` This local sequence stores the output of the converter.

```
14 \seq_new:N \l__akshar_char_seq
```

(End definition for `\l__akshar_char_seq`.)

`\l__akshar_tmp_tl` Some temporary variables.

`\l__akshar_tmp_seq`

```
15 \tl_new:N \l__akshar_tmp_tl
```

```
16 \seq_new:N \l__akshar_tmp_seq
```

(End definition for `\l__akshar_tmp_tl` and `\l__akshar_tmp_seq`.)

3.2 Utilities

`\tl_if_in:NoTF` When we get to a character which is not the joining one, we need to know if it is a diacritic. The current character is stored in a variable, so an expanded variant is needed. We only need it to expand only once.

```
17 \prg_generate_conditional_variant:Nnn \tl_if_in:Nn { No } { TF }
```

(End definition for `\tl_if_in:NoTF`.)

3.3 The `\akshar_convert` function

`\akshar_convert:Nn` This converts #2 to a sequence of true Devanagari characters. The sequence is set to #1, which should be a sequence variable. The assignment is local.

`\akshar_convert:cn`

`\akshar_convert:Nx`

`\akshar_convert:cx`

```
18 \cs_new:Npn \akshar_convert:Nn #1 #2
```

```
19 {
```

Clear anything stored in advance. We don't want different calls of the function to conflict with each other.

```
20 \seq_clear:N \l__akshar_char_seq
```

```
21 \bool_set_false:N \l__akshar_prev_joining_bool
```

Loop through every token of the input.

```
22 \tl_map_variable:NNn {#2} \l__akshar_map_tl
```

```
23 {
```

```
24 \tl_if_in:NoTF \c__akshar_diacritics_tl {\l__akshar_map_tl}
```

```
25 {
```

It is a diacritic. We append the current diacritic to the last item of the sequence instead of pushing the diacritic to a new sequence item.

```
26 \seq_pop_right:NN \l__akshar_char_seq \l__akshar_tmp_tl
```

```
27 \seq_put_right:Nx \l__akshar_char_seq
```

```
28 { \l__akshar_tmp_tl \l__akshar_map_tl }
```

```
29 }
```

```
30 {
```

```
31 \tl_if_eq:NNTF \l__akshar_map_tl \c__akshar_joining_tl
```

```
32 {
```

In this case, the character is the joining character, ङ. What we do is similar to the above case, but `\l__akshar_prev_joining_bool` is set to true so that the next character is also appended to this item.

```
33 \seq_pop_right:NN \l__akshar_char_seq \l__akshar_tmp_tl
```

```
34 \seq_put_right:Nx \l__akshar_char_seq
```

```
35 { \l__akshar_tmp_tl \l__akshar_map_tl }
```

```

36         \bool_set_true:N \l__akshar_prev_joining_bool
37     }
38     {

```

Now the character is normal. We see if we can push to a new item or not. It depends on the boolean variable.

```

39         \bool_if:NTF \l__akshar_prev_joining_bool
40     {
41         \seq_pop_right:NN \l__akshar_char_seq \l__akshar_tmp_tl
42         \seq_put_right:Nx \l__akshar_char_seq
43             { \l__akshar_tmp_tl \l__akshar_map_tl }
44         \bool_set_false:N \l__akshar_prev_joining_bool
45     }
46     {
47         \seq_put_right:Nx \l__akshar_char_seq { \l__akshar_map_tl }
48     }
49     }
50 }
51 }

```

Set #1 to `\l__akshar_char_seq`. The assignment is local, and I have not found a way to automatically pick `\seq_set_eq` or `\seq_gset_eq` based on the name of the sequence variable.

```

52     \seq_set_eq:NN #1 \l__akshar_char_seq
53 }

```

Generate variants that might be helpful for some.

```

54 \cs_generate_variant:Nn \akshar_convert:Nn { cn, Nx, cx }

```

(End definition for `\tl_if_in:NoTF` and `\akshar_convert:Nn`. These functions are documented on page ??.)

3.4 Front-end $\text{\LaTeX}2_{\epsilon}$ macros

`\aksharStrLen` Expands to the length of the string.

```

55 \NewExpandableDocumentCommand \aksharStrLen {m}
56 {
57     \akshar_convert:Nn \l__akshar_tmp_seq {#1}
58     \seq_count:N \l__akshar_tmp_seq
59 }

```

(End definition for `\aksharStrLen`. This function is documented on page 1.)

`\aksharStrChar` Returns the n -th character of the string.

```

60 \NewExpandableDocumentCommand \aksharStrChar {mm}
61 {
62     \akshar_convert:Nn \l__akshar_tmp_seq {#1}
63     \seq_item:Nn \l__akshar_tmp_seq {#2}
64 }

```

(End definition for `\aksharStrChar`. This function is documented on page 2.)

```

65 \endpackage

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A	<code>\akshar_convert:Nn</code> ... 2, <u>18</u> , 57, 62
akshar commands:	
<code>\akshar_convert</code>	1, 3

akshar internal commands:

`\l__akshar_char_seq` 4, 14, 20, 26, 27, 33, 34, 41, 42, 47, 52
`\c__akshar_diacritics_tl` .. 2, 6, 24
`\c__akshar_joining_tl` 2, 6, 31
`\l__akshar_map_tl`
..... 22, 24, 28, 31, 35, 43, 47
`\l__akshar_prev_joining_bool` ..
..... 3, 13, 21, 36, 39, 44
`\l__akshar_tmp_seq` 15, 57, 58, 62, 63
`\l__akshar_tmp_tl`
..... 15, 26, 28, 33, 35, 41, 43
`\aksharStrChar` 2, 60
`\aksharStrLen` 1, 55

B

bool commands:

`\bool_if:NTF` 39
`\bool_new:N` 13
`\bool_set_false:N` 21, 44
`\bool_set_true:N` 36

C

cs commands:

`\cs_generate_variant:Nn` 54
`\cs_new:Npn` 18

N

`\NewExpandableDocumentCommand` . 55, 60

P

prg commands:

`\prg_generate_conditional_variant:Nnn` 17
`\ProvidesExplPackage` 4

R

`\RequirePackage` 3

S

seq commands:

`\seq_clear:N` 20
`\seq_count:N` 58
`\seq_gset_eq` 4
`\seq_item:Nn` 63
`\seq_new:N` 14, 16
`\seq_pop_right:NN` 26, 33, 41
`\seq_put_right:Nn` ... 27, 34, 42, 47
`\seq_set_eq` 4
`\seq_set_eq:NN` 52

T

tl commands:

`\tl_const:Nn` 6, 7
`\tl_if_eq:NNTF` 31
`\tl_if_in:Nn` 17
`\tl_if_in:NnTF` 17, 24
`\tl_map_variable:NNn` 22
`\tl_new:N` 15