

[Dashb...](#) / [My cou...](#) / [CS23331-DAA-20...](#) / [Competitive Progra...](#) / [6-Pair with Difference -O\(n\) Time Complexity,O\(1\) Spac...](#)

Started on	Wednesday, 20 November 2024, 8:38 PM
State	Finished
Completed on	Wednesday, 20 November 2024, 8:39 PM
Time taken	1 min 10 secs
Marks	1.00/1.00
Grade	4.00 out of 4.00 (100%)

Question **1**

Correct

Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int findPair(int A[], int n, int k) {
4      int i = 0, j = 1;
5
6      while (j < n) {
7          int diff = A[j] - A[i];
8
9          if (diff == k) {
10             return 1;
11         }
12         if (diff < k) {
13             j++;
14         } else {
15             i++;
16             if (i == j) {
17                 j++;
18             }
19         }
20     }
21     return 0;
22 }
23
24 int main() {
25     int n;
26     scanf("%d", &n);
27
28     int A[n];
29     for (int i = 0; i < n; i++) {
30         scanf("%d", &A[i]);
31     }
32
33     int k;
34     scanf("%d", &k);

```

```
35 |
36 |     int result = findPair(A, n, k);
37 |     printf("%d\n", result);
38 |
39 |     return 0;
40 | }
41 |
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 5-Pair with Difference-O(n^2)Time Complexity,O(1) Space Complexity



Jump to...