

[Dashboard](#) / [My courses](#) / [PSPP/PUP](#) / [Functions: Built-in functions, User-defined functions, Recursive functions](#) / [Week9 Coding](#)

Started on	Friday, 24 May 2024, 9:26 AM
State	Finished
Completed on	Friday, 24 May 2024, 9:51 AM
Time taken	25 mins 16 secs
Marks	5.00/5.00
Grade	100.00 out of 100.00

Question 1

Correct

Mark 1.00 out of 1.00

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10^6$

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12

Answer: (penalty regime: 0 %)

Reset answer

```

1 def is_prime(n):
2     if n < 2:
3         return False
4     for i in range(2, int(n**0.5) + 1):
5         if n % i == 0:
6             return False
7     return True
8
9 def christmasDiscount(orderValue):
10     prime_digits = [2, 3, 5, 7] # List of prime digits
11     total_discount = 0
12
13     for digit in str(orderValue):
14         if int(digit) in prime_digits:
15             total_discount += int(digit)
16
17     return total_discount
18
19

```

	Test	Expected	Got	
✓	print(christmasDiscount(578))	12	12	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of 1.00

Write a code to check whether product of digits at even places is divisible by sum of digits at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False

Answer: (penalty regime: 0 %)

Reset answer

```
1 def productDigits(n):
2     num_str = str(n)
3     even_product = 1
4     odd_sum = 0
5     for i in range(len(num_str)):
6         digit = int(num_str[i])
7         if i % 2 != 0: # Even index
8             even_product *= digit
9         else: # Odd index
10            odd_sum += digit
11    return even_product % odd_sum == 0
```

	Test	Expected	Got	
✓	print(productDigits(1256))	True	True	✓
✓	print(productDigits(1595))	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of 1.00

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly

Answer: (penalty regime: 0 %)

Reset answer

```

1 def checkUgly(n):
2     if n <= 0:
3         raise ValueError("Input number must be a positive integer.")
4     for prime in [2, 3, 5]:
5         while n % prime == 0:
6             n /= prime
7     if n == 1:
8         return "ugly"
9     else:
10        return "not ugly"
11
12

```

	Test	Expected	Got	
✓	print(checkUgly(6))	ugly	ugly	✓
✓	print(checkUgly(21))	not ugly	not ugly	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of 1.00

An automorphic number is a number whose square ends with the number itself.

For example, 5 is an automorphic number because $5 \times 5 = 25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

Input Format:

Take a Integer from Stdin Output Format: Print Automorphic if given number is Automorphic number,otherwise Not Automorphic Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example input: 7 Output: Not Automorphic

For example:

Test	Result
print(automorphic(5))	Automorphic

Answer: (penalty regime: 0 %)

Reset answer

```

1 def automorphic(n):
2     if not isinstance(n, int) or n < 0:
3         return "Invalid input"
4
5     # Calculate the square of the number
6     square = n ** 2
7
8     # Convert the number and its square to strings
9     n_str = str(n)
10    square_str = str(square)
11
12    # Check if the square ends with the number
13    if square_str.endswith(n_str):
14        return "Automorphic"
15    else:
16        return "Not Automorphic"
17

```

	Test	Expected	Got	
✓	print(automorphic(5))	Automorphic	Automorphic	✓
✓	print(automorphic(7))	Not Automorphic	Not Automorphic	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of 1.00

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1 def coinChange(target):  
2     """  
3     Finds the minimum number of coins required to meet the given target amount.  
4     """  
5     # Create a list to store the minimum number of coins for each amount from 0 to target  
6     coins = [float('inf')] * (target + 1)  
7     coins[0] = 0 # 0 coins are needed to make 0 amount  
8  
9     # Iterate over each amount from 1 to target  
10    for amount in range(1, target + 1):  
11        # Iterate over each available coin denomination  
12        for coin in [1, 2, 3, 4]:  
13            # If the coin is not more than the current amount  
14            if coin <= amount:  
15                # Update the minimum number of coins for the current amount  
16                coins[amount] = min(coins[amount], coins[amount - coin] + 1)  
17  
18    # If it's not possible to make the target amount, return -1  
19    if coins[target] == float('inf'):  
20        return -1  
21    else:  
22        return coins[target]
```


	Test	Expected	Got	
✓	print(coinChange(16))	4	4	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[◀ Week9_MCQ](#)

Jump to...



Searching ▶