CHAPTER 1

SUPPORT EQUIPMENT FOR CONCURRENT REFUELING OPERATIONS

The following support equipment is required to follow the procedures set forth in this checklist.

- Electrical Generator Unit, if required.
- Aviation Hydrant Servicers (with passengers on board) or R5/R9/R11 refuelers with deadman controls and non-collapsible fuel servicing hose. Ground and Bonding Wires (as required).
- Ground and Bonding Wires (as required).
- Intercom Headsets, Contractor Supplied - A minimum of three (except B-757/767/777 aircraft which requires only two) for Air Force use with passengers on board (one 100-foot and two 50-foot or longer cords) and one for the contractor fuel control panel operator (four total). A minimum of two for Air Force use on non-passenger aircraft (one 100-foot and one 50-foot or longer cords) and one for the contractor fuel control panel operator (three total). If don't have access to commercial communication cords and headsets, hand held intrinsically safe radios should be used.
- Air Conditioner (if required).
- Fire Extinguisher, 150-pounds Halon, or equivalent.
- Vest with Chief Servicing Supervisor (CSS) Lettering.
- Aircraft Rescue and Fire Fighting (ARFF) Vehicle (required only when servicing with JP-4 or Jet B fuel and passengers are on board).
- Passenger Handling Equipment.
- Ramp and Stairs (as required).
- Baggage Handling Equipment (as required).
- Fleet Servicing and Catering Equipment (as required).
- Maintenance Stands.
- Cargo Handling Equipment.

1.1 PERSONNEL AND PERSONNEL LOCATIONS.

*CSS	Stationed at nose of aircraft. Moves as required. Monitor wing fuel vents on the opposite side of the aircraft from the Single Point Receptacle (SPR).