CHAPTER 3A
C-130 HOT CONCURRENT SERVICING OPERATION (HCSO)

INTRODUCTION.

This chapter is a step-by-step guide for use as a reference by 2F0X1 fuels specialists (Refueling Equipment Operator (REO)) who is certified to conduct hot refuel operations and Concurrent Servicing Operations (CSO) in accordance with Technical Order (TO) 00-25-172 and Major Command (MAJCOM) directives. This checklist is intended to prevent the omission of a sequential task in the accomplishment of authorized hot refueling with CSO but does not provide detailed technical instruction. These procedures are to be used in conjunction with the general and emergency aircraft refueling procedures outlined in Chapter 1 and Chapter 2 of this checklist.

a. This procedure will be utilized to conduct hot refueling with simultaneous cargo or passenger loading/unloading, performance of minor maintenance, or fleet servicing.

b. Ensure all equipped and installed hoses on fuel servicing vehicle meets the requirements listed in TO 37A-1-101.

c. Fuel servicing equipment when equipped with servicing controls are authorized for use in hot concurrent servicing operations.

d. Perform a pressurized serviceability check of the fuel servicing equipment once every 24 hours or when returned to service after maintenance.

REFUELING SITE SET UP.

a. Preposition equipment for fuel servicing operation at designated hot refueling pad allowing for maximum separation between refueling vehicle and aircraft. Wind direction should be a consideration for this portion. Setup truck downwind of the aircraft parking location, if possible.