



**ALLIED
MEDICAL**

Meditec M777

Multi-Parameter Patient Monitors



Features

- 15" LED touch screen display
- Pre-configured, light weight and sturdy design
- Flexible parameter configuration for different clinical environment
- Rechargeable Li-ion battery (up to 4 hours)
- Graphical and tabular trends of 168 Hrs.
- Defibrillation Interface & Cautery Protection

Optional Features

- 12 Lead ECG Monitoring & Analysis
- Dual IBP
- EtCO₂
- Anaesthetic Gas Monitoring
- Cardiac Output
- Depth of Anaesthesia / BIS
- EEG
- In-built Thermal Printer
- Wall Mount
- Mobile Trolley
- Bed Rail Mount
- Connectivity with Central Monitoring System - Wired/Wireless

**ALLIED
MEDICAL**



Technical Specifications

Display

General Parameters	Suitable Bedside monitors for Adult/Paediatric & neonatal patients User selectable priority alarms - Red, Yellow, Orange color coded
Sweep Speed	6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s
Various working interface selectable	Standard Monitoring Display, Large Font Intensive Care Display, Trend Graph/ Monitoring Co-Display, Bed to Bed view Display, OxyCRG Dynamic View Display, Drug Dose Calculation Interface
Trends	Tabular & Graphical trends
Events	ECG, SpO ₂ , NIBP with waveform & review

ECG

Lead Mode	3 Leads (I, II, III), 5 Leads (I, II, III, aVR, aVL, aVF, V) 12 Leads ((I, II, III, aVR, aVL, aVF, V1-V6)
Waveform	Up to 12 waveforms display on screen
4 selectable plus	0.25, 0.5, 1, 2 cm/mV
PACE Detection	Automatic
Defibrillation energy distributary	
Input voltage range	±8mV, polarized voltage: ±500mV
CMRR Diagnosis	> 100 dB (no 50Hz/60Hz software wave trap)
Monitor	> 110 dB (has 50Hz/60Hz software wave trap)
Surgery	> 100dB (50Hz/60Hz software wave trap)
System noise	< 30µV p-p (RTI)

HR Measuring and Alarm Range

Adult/Paed	15 bpm – 300bpm
Neo	15 bpm – 350bpm
Accuracy	± 1% or ± 1bpm, which great
Resolution	1 bpm
Sensitivity	> 200 µV P-P
Differential Input Impedance	5 M
Electrode offset potential	300mVd.c. – 600mVd.c.
Patient leakage current	< 10 uA
ECG Signal Range	6 mV (Vp-p).
ST Segment Monitoring Range	
Measure and Alarm	-2.0 – +2.0 mV

SpO₂

Method	Self / Masimo
Measuring Range	1–100%
Alarm Range	1–100%
Resolution	1 %
Accuracy	
Adult / Paediatric	± 1 digit (70%–100% SpO ₂)
Adult / Paediatric with Low-perfusion	Undefined (0–70% SpO ₂)
Neonate	± 1 digit (70%–100% SpO ₂)
Neonate with Low-perfusion	Undefined (0–70% SpO ₂)
Pulse Rate Measuring and Alarm Range	20–300bpm

NIBP

Method	Oscillometric
Mode	Manual, Auto, Continuous
Measuring Interval in AUTO mode	1/2/3/4/5/10/15/30/60/90/120/240/480 Min
Continuous	5min, interval 5s
Measuring Type	Systolic Pressure, Diastolic Pressure, Mean Pressure
Cuff Pressure measuring Range	0–300 mmHg
Pressure Resolution	1 mmHg
Mean error	3 mmHg
Maximum Standard deviation	3 mmHg
Over pressure protection	Dual Over pressure protection
Measured unit	mmHg/kPa selectable
Measurement types	Systolic, Diastolic, Mean Systolic : 40–300 mmHg Diastolic : 10–150 mmHg Mean : 20–235 mmHg
Pressure range for Paediatrics	Systolic : 20–235 mmHg Diastolic : 10–150 mmHg Mean : 20–165 mmHg
Pressure range for Neonates	Systolic : 10–235 mmHg Diastolic : 10–100 mmHg Mean : 20–110 mmHg

Respiration

Method	Impedance between R-F (RA-LL), R-L (RA-LA)		
Respiration Rate Measuring and Alarm Range:			
Adult	0 rpm – 120 rpm	Neo/Ped	0 rpm – 180 rpm
Resolution	1 rpm	Accuracy	2 rpm
Gain Selection	0.25, 0.5, 1, 2, 3, 4, 5		
Apnea	10 – 60 Sec.		

Temp

Channel	1 (Std.) / 2 (Optional)	Measuring Range	0–50°C
Sensor type	YSI (B Series) OR CF-FI	Resolution	0.1°C
Accuracy	0.1°C (25°C–45°C), 0.2°C (0–25°C, 45° – 50°C)		

Power Supply

Input Voltage	AC 100V–240V
Input Frequency	50/60Hz

Environmental Conditions

Storage	Temp (-) 10°C – 40°C
	Humidity 15%–80%
Operational	Temp 0°C – 40°C
	Humidity 15%–80%
Atmospheric Pressure	700kPa–1060kPa



Manufactured in India by
Allied Medical Limited
 76-77, Udyog Vihar, Phase IV,
 Gurugram - 122 015, Haryana, INDIA
 Phone : +91 124 4111444
 Mobile : +91 9811184252
 Toll Free : 1800 102 7879
 E-mail : sales@alliedmed.co.in
 Website : www.alliedmed.co.in

Design & Technology Partner



Meditec International England Limited

E-mail : sales@meditecengland.co.uk
 Website : www.meditecengland.co.uk

*In view of continued product improvement Allied Medical Limited reserves the right to make changes in the equipment which may affect the information contained in this leaflet without giving any prior notice. Pictures are representative, accessories are optional and may vary at the time of supply. Meditec England is the registered trademark of Meditec International England Limited.