

```
MySQL 8.0 Command Line Cli  x  +  v
-> INSERT INTO AuditLog (Action, EmpID, ActionDate)
-> VALUES ('INSERT', NEW.EmpID, NOW());
-> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> -- Reset Delimiter
mysql> DELIMITER ;
mysql>
mysql> -- Insert Data into Employee Table
mysql> INSERT INTO Employee (EmpName, Salary)
-> VALUES ('John', 25000);
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> INSERT INTO Employee (EmpName, Salary)
-> VALUES ('Alice', 30000);
Query OK, 1 row affected (0.00 sec)

mysql>
mysql> -- View Employee Table
mysql> SELECT * FROM Employee;
+-----+-----+-----+
| EmpID | EmpName | Salary |
+-----+-----+-----+
| 1 | John | 25000 |
| 2 | Alice | 30000 |
+-----+-----+-----+
2 rows in set (0.00 sec)

mysql>
mysql> -- View Audit Log Table
mysql> SELECT * FROM AuditLog;
+-----+-----+-----+-----+
| LogID | Action | EmpID | ActionDate |
+-----+-----+-----+-----+
| 1 | INSERT | 1 | 2026-02-13 22:02:32 |
| 2 | INSERT | 2 | 2026-02-13 22:02:32 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```