

PVsyst - Simulation report

Grid-Connected System

Project: EC9180_PVsyst_Lab2.

Variant: New simulation variant

Sheds, single array

System power: 105 kWp

Kilinochchi - Sri Lanka

**PVsyst V8.1.5**

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

Project summary**Geographical Site****Kilinochchi**

Sri Lanka

Situation

Latitude 9.3840 °(N)

Longitude 80.4087 °(E)

Altitude 29 m

Time zone UTC+5.5

Project settings

Albedo 0.20

Weather data

Kilinochchi

Meteonorm 9.0 dll, Sat=100% - Synthetic

System summary**Grid-Connected System****Orientation #1****Fixed plane**

Tilt/Azimuth 9.5 / 0 °

System information**PV Array**

Nb. of modules

190 units

Pnom total

105 kWp

Sheds, single array**Near Shadings**

According to strings : Fast (table)

Electrical effect 100 %

User's needs

Unlimited load (grid)

Inverters

Nb. of units

1 unit

Total power

100 kWac

Pnom ratio

1.05

Results summary

Simulation step Hourly

Produced Energy 101896 kWh/year Specific production 975 kWh/kWp/year Perf. Ratio PR 50.72 %

Table of contents

Project and results summary	2
General parameters, PV Array Characteristics, System losses	3
Near shading definition - Iso-shadings diagram	4
Main results	5
Loss diagram	6
Predef. graphs	7
Single-line diagram	8



PVsyst V8.1.5

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

General parameters

Grid-Connected System

Sheds, single array

Simulation step

Hourly

Orientation #1

Fixed plane

Tilt/Azimuth 9.5 / 0 °

Sheds configuration

Nb. of sheds 5 units

Single array

Shading limit angle

Limit profile angle 90 °

Sizes

Sheds spacing 2.50 m

Sensitive width 4.58 m

GCR Shading 183.8 %

Top inactive band 0.02 m

Bottom inactive band 0.02 m

Models used

Transposition Perez
Diffuse Perez, Meteonorm
Circumsolar separate

Horizon

Free Horizon

Near Shadings

According to strings : Fast (table)

Electrical effect 100 %

User's needs

Unlimited load (grid)

PV Array Characteristics

PV module

Manufacturer Generic

Model Mono 550 Wp Twin half-cells bifacial
(Original PVsyst database)

Unit Nom. Power 550 Wp
Number of PV modules 190 units
Nominal (STC) 105 kWp
Modules 10 units x 19 In series

At operating cond. (50°C)

Pmpp 95.9 kWp
U mpp 718 V
I mpp 134 A

Total PV power

Nominal (STC) 105 kWp
Total 190 modules
Module area 491 m²
Cell area 453 m²

Inverter

Manufacturer Generic

Model 100 kWac inverter
(Original PVsyst database)

Unit Nom. Power 100 kWac
Number of inverters 2 * MPPT 50% 1 unit
Total power 100 kWac
Operating voltage 180-1000 V
Pnom ratio (DC:AC) 1.05
No power sharing between MPPTs

Total inverter power

Total power 100 kWac
Number of inverters 1 unit
Pnom ratio 1.05

Array losses

Thermal Loss factor

Module temperature according to irradiance
Uc (const) 20.0 W/m²K
Uv (wind) 0.0 W/m²K/m/s

DC wiring losses

Global array res. 88 mΩ
Loss Fraction 1.50 % at STC

Module Quality Loss

Loss Fraction -0.38 %

Module mismatch losses

Loss Fraction 2.00 % at MPP

Strings Mismatch loss

Loss Fraction 0.10 %

IAM loss factor

Incidence effect (IAM): Fresnel, AR coating, n(glass)=1.526, n(AR)=1.290

0°	30°	50°	60°	70°	75°	80°	85°	90°
1.000	0.999	0.987	0.963	0.892	0.814	0.679	0.438	0.000




PVsyst V8.1.5

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

Near shadings parameter


Perspective of the PV-field and surrounding shading scene



Iso-shadings diagram

Orientation #1 - Fixed plane, Tilts/azimuths: 9.5°/ 0°

Beam shading factor (according to strings) : Iso-shadings curves





PVsyst V8.1.5

VC0, Simulation date:

14/08/26 16:14

with V8.1.5

Main results

Simulation step

Hourly

System Production

Produced Energy

101896 kWh/year


Specific production

975 kWh/kWp/year


Perf. Ratio PR

50.72 %

Normalized productions (per installed kWp)



Performance Ratio PR



Balances and main results

	GlobHor	DiffHor	T_Amb	GlobInc	GlobEff	EArray	E_Grid	PR
	kWh/m²	kWh/m²	°C	kWh/m²	kWh/m²	kWh	kWh	ratio
January	138.4	67.23	25.56	149.0	88.3	7260	7083	0.455
February	146.2	60.86	26.51	154.0	93.0	8306	8134	0.506
March	184.8	78.57	28.57	188.6	116.2	10447	10247	0.520
April	171.9	81.15	30.10	168.9	106.3	9376	9188	0.521
May	182.2	89.05	30.32	174.9	111.8	9816	9622	0.527
June	176.0	80.75	30.28	166.5	107.3	9337	9139	0.525
July	176.3	86.42	29.86	167.9	107.7	9444	9239	0.526
August	177.9	83.32	29.34	173.4	109.8	9689	9487	0.524
September	173.1	77.08	28.88	174.4	108.3	9706	9518	0.522
October	147.7	71.46	27.95	153.2	93.2	8398	8211	0.513
November	117.8	67.10	26.72	124.8	74.5	6364	6196	0.475
December	118.1	64.60	25.79	126.9	75.0	6002	5830	0.440
Year	1910.5	907.58	28.33	1922.5	1191.5	104145	101896	0.507

Legends

GlobHor Global horizontal irradiation

DiffHor Horizontal diffuse irradiation

T_Amb Ambient Temperature

GlobInc Global incident in coll. plane

GlobEff Effective Global, corr. for IAM and shadings

EArray Effective energy at the output of the array

E_Grid Energy injected into grid


PR Performance Ratio



PVsyst V8.1.5

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

Loss diagram







PVsyst V8.1.5

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

Predef. graphs
Daily Input/Output diagram



System Output Power Distribution






PVsyst V8.1.5

VC0, Simulation date:
14/08/26 16:14
with V8.1.5

Single-line diagram



PV module	Mono 550 Wp Twin half-cells bifacial
Inverter	100 kWac inverter
String	19 x Mono 550 Wp Twin half-cells bifacial

EC9180_PVsyst_Lab2

VC0 : New simulation variant

14/08/26