

Institute of Computer Technology  
B. Tech Computer Science and Engineering

Sub: Identity and Access Management (2CSE507)

Name - Nisarg Prajapati

Branch - Cyber Security

Enrollment no. – 23162171019

Semester - 5

Class - A


Batch – 52

**PRACTICAL NO:- 7**


**Aim :** Demonstration of SSO in Keycloak

**Starting the Container:**

- Open your Docker Desktop.
- In the containers tab, click the start button of the container you want to start.



- Now open your browser and go to '<http://localhost:8080/>'.



**Code:**

- App1:

❖ index.js

```
import express from "express";
import session from "express-session";
import { client, code_verifier, code_challenge } from
"./auth.js";

const PORT = 3001;
const app = express();

app.use(
  session({
    secret: "app1_secret",
    resave: false,
    saveUninitialized: true,
  })
);

// Home route
app.get("/", async (req, res) => {
  if (!req.session.tokenSet) {
    return res.send(`<a href="/login">Login with
Keycloak</a>`);
  }
  res.send(`
    <h2>Welcome to App1!</h2>
    <p>User: ${req.session.user?.preferred_username}</p>
    <a href="/logout">Logout</a>
    <br><a href="http://localhost:3002/">Go to App2</a>
  `);
});

// Login route
app.get("/login", (req, res) => {
  req.session.code_verifier = code_verifier;
```

```

    const authUrl = client.authorizationUrl({
      scope: "openid profile email",
      code_challenge,
      code_challenge_method: "S256",
    });
    res.redirect(authUrl);
  });

  // Callback route
  app.get("/callback", async (req, res) => {
    try {
      const params = client.callbackParams(req);
      const tokenSet = await client.callback(
        "http://localhost:3001/callback",
        params,
        { code_verifier: req.session.code_verifier }
      );
      req.session.tokenSet = tokenSet;

      const userinfo = await
client.userinfo(tokenSet.access_token);
      req.session.user = userinfo;

      res.redirect("/");
    } catch (err) {
      console.error(err);
      res.status(500).send("Login failed");
    }
  });

  // Logout route
  app.get("/logout", (req, res) => {
    const idToken = req.session.tokenSet?.id_token;
    req.session.destroy(() => {
      let logoutUrl =
`http://localhost:8080/realms/demo-realm/protocol/openid-conne
ct/logout`;
      if (idToken) {
        logoutUrl +=
`?id_token_hint=${idToken}&post_logout_redirect_uri=http://loc

```

```
localhost:3001/`;
    }
    res.redirect(logoutUrl);
  });
});

app.listen(PORT, () =>
  console.log(` App1 running on http://localhost:${PORT}`)
);
```

- auth.js

```
import { createClient } from "../oidc_config/oidc-config.js";

export const { client, code_verifier, code_challenge } =
createClient(
  "app-a",
  "http://localhost:3001/callback"
);
```

- App2

- ❖ index.js

```
import express from "express";
import session from "express-session";
import { client, code_verifier, code_challenge } from
"./auth.js";
import axios from "axios";

const PORT = 3002;
const app = express();

app.use(
  session({
    secret: "app2_secret",
    resave: false,
    saveUninitialized: true,
  })
);

// Home route
app.get("/", async (req, res) => {
  if (!req.session.tokenSet) {
    // Attempt SSO: check if user is logged in Keycloak using
    iframe-like request
    return res.send(`<a href="/login">Login with
Keycloak</a>`);
  }
  res.send(`
    <h2>Welcome to App2!</h2>
    <p>User: ${req.session.user?.preferred_username}</p>
    <a href="/logout">Logout</a>
    <br><a href="http://localhost:3001/">Go to App1</a>
  `);
});

// Login route
app.get("/login", (req, res) => {
```

```

req.session.code_verifier = code_verifier;
const authUrl = client.authorizationUrl({
  scope: "openid profile email",
  code_challenge,
  code_challenge_method: "S256",
});
res.redirect(authUrl);
});

// Callback route
app.get("/callback", async (req, res) => {
  try {
    const params = client.callbackParams(req);
    const tokenSet = await client.callback(
      "http://localhost:3002/callback",
      params,
      { code_verifier: req.session.code_verifier }
    );
    req.session.tokenSet = tokenSet;

    const userinfo = await
client.userinfo(tokenSet.access_token);
    req.session.user = userinfo;

    res.redirect("/");
  } catch (err) {
    console.error(err);
    res.status(500).send("Login failed");
  }
});

// Logout route
app.get("/logout", (req, res) => {
  const idToken = req.session.tokenSet?.id_token;
  req.session.destroy(() => {
    let logoutUrl =
`http://localhost:8080/realms/demo-realm/protocol/openid-conne
ct/logout`;
    if (idToken) {
      logoutUrl +=

```

```

    `?id_token_hint=${idToken}&post_logout_redirect_uri=http://localhost:3002/`;
  }
  res.redirect(logoutUrl);
});
});

app.listen(PORT, () =>
  console.log(` App2 running on http://localhost:${PORT}`)
);

```

### ❖ auth.js

```

import { createClient } from "../oidc_config/oidc-config.js";

export const { client, code_verifier, code_challenge } =
createClient(
  "app-b",
  "http://localhost:3002/callback"
);

```

### ● my-realm.json

```

{
  "realm": "demo-realm",
  "enabled": true,
  "clients": [
    {
      "clientId": "app-a",
      "publicClient": true,
      "protocol": "openid-connect",
      "redirectUris": ["http://localhost:3000/callback"],
      "webOrigins": ["http://localhost:3000"],
      "standardFlowEnabled": true,
      "implicitFlowEnabled": false,
      "directAccessGrantsEnabled": true
    }
  ]
}


```




```
},
{
  "clientId": "app-b",
  "publicClient": true,
  "protocol": "openid-connect",
  "redirectUris": ["http://localhost:3001/callback"],
  "webOrigins": ["http://localhost:3001"],
  "standardFlowEnabled": true,
  "implicitFlowEnabled": false,
  "directAccessGrantsEnabled": true
}
],
"users": [
  {
    "username": "testuser",
    "enabled": true,
    "emailVerified": true,
    "firstName": "Test",
    "lastName": "User",
    "email": "testuser@example.com",
    "credentials": [
      {
        "type": "password",
        "value": "Test@123",
        "temporary": false
      }
    ]
  }
]
}
```

## Creating a new Realm:



- Login as admin.





- Go to the 'Manage Realm' tab and click on 'Create realm'.




- Enter the realm name, select the 'my-realm.json' in 'Resource file' and create the realm.




- To change between realms, in ‘Manage Realm’ tab, click on the realm name.



- Check the created user in ‘Users’ tab



- Check the created clients in ‘Clients’ tab



## Starting the login apps:

- Run the index.js files from both app1 and app2.

The screenshot shows a VS Code editor with a project named 'keycloak\_sso\_demo'. The file explorer on the left shows the project structure, including 'app\_1' and 'app\_2' folders. The main editor displays the code for 'app\_1/index.js'. The code imports 'express' and 'express-session', sets a secret, and defines a home route. The console at the bottom shows 'App1 running on http://localhost:3001'.

```

1 import express from "express";
2 import session from "express-session";
3 import { client, code_verifier, code_challenge } from "../auth.js";
4
5 const PORT = 3001;
6 const app = express();
7
8 app.use(
9   session({
10     secret: "app1_secret",
11     resave: false,
12     saveUninitialized: true,
13   })
14 );
15
16 // Home route
17 app.get("/", async (req, res) => {
18   if (!req.session.tokenSet) {
19     // Redirect to login
20   }
21 });

```

The screenshot shows the same VS Code editor with the project 'keycloak\_sso\_demo'. The file explorer shows the project structure. The main editor displays the code for 'app\_2/index.js'. The code imports 'express' and 'express-session', sets a secret, and defines a home route. The console at the bottom shows 'App2 running on http://localhost:3002'.


```

1 import express from "express";
2 import session from "express-session";
3 import { client, code_verifier, code_challenge } from "../auth.js";
4
5 const PORT = 3002;
6 const app = express();
7
8 app.use(
9   session({
10     secret: "app2_secret",
11     resave: false,
12     saveUninitialized: true,
13   })
14 );
15
16 // Home route
17 app.get("/", async (req, res) => {
18   if (!req.session.tokenSet) {
19     // Attempt SSO: check if user is logged in Keycloak using iframe-like request
20     return res.send(
21       `<iframe src="${client.baseUrl}/login" style="width: 100%; height: 100%; border: none;"></iframe>`
22     );
23   }
24 });


```

## Checking SSO:



- Open '<http://localhost:3001/>' in the browser.



- Click on 'Login with Keycloak'.




- Enter username and password and click on ‘Sign in’.





- Click on ‘Go to App2’.



- Click on ‘Login with Keyclock’.

