

# Rotation Matrices



Reading: Modern Robotics 3.1 – 3.2

EBERHARD KARLS  
UNIVERSITÄT  
TÜBINGEN



FACULTY OF SCIENCE  
COMPUTER SCIENCE DEPARTMENT  
COGNITIVE SYSTEMS - PROF. DR. A. ZELL



andro

andro


andro Roller

# This Lecture




---

- Why do we use rotation matrices?




Given the stop sign in frame  $\{b\}$ ,  
what is the position in frame  $\{a\}$ ?



Given the stop sign in frame  $\{b\}$ ,  
what is the position in frame  $\{a\}$ ?


$$p_a = R_{ab}p_b$$



Given the stop sign in frame  $\{b\}$ ,  
what is the position in frame  $\{a\}$ ?

$$p_a = R_{ab} p_b$$


$$R_{ab} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}$$



Given the stop sign in frame  $\{b\}$ ,  
what is the position in frame  $\{a\}$ ?

$$p_a = R_{ab} p_b$$

$$R_{ab} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \quad p_b = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$







Given the stop sign in frame  $\{b\}$ ,  
what is the position in frame  $\{a\}$ ?

$$p_a = R_{ab} p_b$$

$$R_{ab} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \quad p_b = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$p_a = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} = \begin{bmatrix} \cos \theta \\ \sin \theta \end{bmatrix}$$





We can use rotation  
matrices to **change** the  
frame of reference.

# Changing Perspectives


When we multiply rotation matrices, if the subscripts *cancel* then we **change** the frame of reference (i.e., the perspective)

$$p_a = R_{ab}p_b$$

$$R_{ac} = R_{ab}R_{bc}$$

$$p_a = R_{ab}R_{bc}p_c$$

We can also use rotation matrices to rotate a vector.



# Rotating Objects


We can use rotation matrices as a mathematical operator to **rotate** an object in a single, fixed coordinate frame

$$Rot(x, \theta) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \theta & -\sin \theta \\ 0 & \sin \theta & \cos \theta \end{bmatrix}$$

$$Rot(y, \theta) = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix}$$

$$Rot(z, \theta) = \begin{bmatrix} \cos \theta & -\sin \theta & 0 \\ \sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$


If we **rotate the base** of this prosthetic leg about  $y$ , where does the foot end up?





If we **rotate the base** of this prosthetic leg about  $y$ , where does the foot end up?


$$p' = Rp$$



If we **rotate the base** of this prosthetic leg about  $y$ , where does the foot end up?

$$p' = Rp$$

$$p' = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix} \begin{bmatrix} 0 \\ 0 \\ -2 \end{bmatrix}$$






If we **rotate the base** of this prosthetic leg about  $y$ , where does the foot end up?

$$p' = Rp$$

$$p' = \begin{bmatrix} -2 \sin \theta \\ 0 \\ 2 \cos \theta \end{bmatrix}$$



# Takeaways

Multiplying by rotation matrices can:

1. Change our frame of reference
2. Rotate a vector or frame

# Next Lecture



---

- How do we describe angular velocity?
- What are some other ways to represent rotation?