



Graphic Era
HILL UNIVERSITY

Established by an Act of the State Legislature of Uttarakhand (Adhiniyam Sankhya 12 of 2011)

Term Work

On

Java Programming Language

(PCS 408)

Submitted to:

Dr. Prateek Srivastava
Associate Professor
GEHU, D. Dun

Submitted by:

Nishant Kumar
University Roll. No.: 2018527
Class Roll No./Section: 37/A

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

GRAPHIC ERA HILL UNIVERSITY, DEHRADUN



Graphic Era
HILL UNIVERSITY
Established by an Act of the State Legislature of Uttarakhand (Adhiniyam Sankhya 12 of 2011)

Table of Contents

Program No.	Program Name	Page No.
1		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		

16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		



Graphic Era

HILL UNIVERSITY

Established by an Act of the State Legislature of Uttarakhand (Adhiniyam Sankhya 12 of 2011)

DEPARTMENT OF CSE STUDENT LAB REPORT SHEET

Name of Student Mob. No
 Address Permanent
 Father's Name Occupation Mob. No
 Mother's Name Occupation Mob. No
 Section Branch Semester Class Roll No Grade A B C
 Local Address Email Marks 5 3
 1

Photograph
Passport Size

S.N o.	Practical	D.O.P.	Date of Submission	Grade (Viva)	Grade (Report File)	Total Marks (out of 10)	Student's Signature	Teacher's Signature
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								

11								
12								
13								
14								
15								
16								
17								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								

PRACTICAL 1

Question:

Create a class "Student" having following instance variables and methods. Instance variables: ID, Name, Branch and university Method: setDetails() and showDetails(). The setDetails() method sets the values of ID, Name, Branch and University. And showDetails() method shows the value of each field.

Source Code:

```
import java.util.Scanner;
public class Student {
    String name;
    int id;
    String branch;
    String university;
    public void getDetails (String stName, int stId, String stBranch, String stUniversity) {
        name = stName;
        id = stId;
        branch = stBranch;
        university = stUniversity;
    }
    public void showDetails (String stName, int stId, String stBranch, String stUniversity) {
        System.out.println("Name : " +stName);
        System.out.println("Student Id. : " +stId);
        System.out.println("Branch Name : " +stBranch);
        System.out.println("University Name : " +stUniversity);
    }
    public static void main (String[] args) {
        Scanner Sc = new Scanner(System.in);
        Student St = new Student();
        System.out.print("Enter the Student Name : ");
        String stName = Sc.nextLine();
        System.out.print("Enter the Student Id : ");
        int stId = Sc.nextInt();
        Sc.nextLine();
        System.out.print("Enter the Student Branch : ");
        String stBranch = Sc.nextLine();
        System.out.print("Enter the University Name: ");
        String stUniversity = Sc.nextLine();
        St.getDetails(stName, stId, stBranch, stUniversity);
        St.showDetails(stName, stId, stBranch, stUniversity);
    }
}
```

OUTPUT:

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Student.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Student
Enter the Student Name : Nishant
Enter the Student Id : 2011940
Enter the Student Branch : CSE
Enter the University Name: GEHU
Name : Nishant
Student Id. : 2011940
Branch Name : CSE
University Name : GEHU

C:\Users\nk534\Documents\Java\Practical File Of Java>
```

PRACTICAL- 2

Question:

Write a Java Program to demonstrate the working of a banking-system

Instance variables: name, account_no, amount

Instance methods: deposit(), withdraw(), checkBalance(), insert() and display().

Here we can deposit and withdraw amount from our account using deposit() and withdraw() methods respectively. The insert() method is to initialize state and display() method is to display state values.

Source Code:

```
import java.util.Scanner;

public class BankSystem {
    String bankName, accountNo;
    double amount;

    public void insert(String name, String accountNumber, double balance) {
        bankName = name;
        accountNo = accountNumber;
        amount = balance;
    }

    public double deposit(double depositAmount) {
        amount = amount + depositAmount;
        return amount;
    }

    public void withdraw(double withdrawalAmount) {
        amount = amount - withdrawalAmount;
    }

    public void display() {
        System.out.println();
        System.out.println("Bank Name : " + bankName);
        System.out.println("Account Number : " + accountNo);
        System.out.println("Current Amount : " + amount);
    }

    public static void main(String[] args) {
        Scanner Sc = new Scanner(System.in);
```



```
BankSystem Bs = new BankSystem();
System.out.print("Bank Name : ");
String name = Sc.nextLine();
System.out.print("Account Number : ");
String accountNumber = Sc.nextLine();
System.out.print("Original Amount : ");
double balance = Sc.nextDouble();

Bs.insert(name, accountNumber, balance);
Bs.display();
System.out.println();

System.out.print("Enter the amount for Deposit : ");
double depositAmount = Sc.nextDouble();
double ans = Bs.deposit(depositAmount);
Bs.display();
System.out.println();

System.out.print("Enter the amount for withdrawal : ");
double withdrawalAmount = Sc.nextDouble();
if (withdrawalAmount < ans) {
    System.out.println("Money Available for withdrawal");
    Bs.withdraw(withdrawalAmount);
    Bs.display();
    System.out.println();
}
else {
    System.out.println("Insufficient Balance...");
}
}
```

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac BankSystem.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java BankSystem
Bank Name : SBI
Account Number : 4868846
Original Amount : 2500

Bank Name : SBI
Account Number : 4868846
Current Amount : 2500.0

Enter the amount for Deposit : 500

Bank Name : SBI
Account Number : 4868846
Current Amount : 3000.0

Enter the amount for withdrawal : 2000
Money Available for withdrawal

Bank Name : SBI
Account Number : 4868846
Current Amount : 1000.0

C:\Users\nk534\Documents\Java\Practical File Of Java>
```

PRACTICAL 3


Question:

Write a program to sum two numbers. Here inputs are provided through command line argument.

Source Code:

```
public class sumCommand {  
  
    public static void main(String[] args) {  
  
        int a = Integer.parseInt(args[0]);  
        int b = Integer.parseInt(args[1]);  
  
        int sum = a + b;  
  
        System.out.println("Sum of Two number by Command Line : " +sum);  
    }  
}
```

OUTPUT:



```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac sumCommand.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java sumCommand 4 6
Sum of Two number by Command Line : 10

C:\Users\nk534\Documents\Java\Practical File Of Java>
```

PRACTICAL 4

Question:

Create class Employee with following attributes and methods ID, name, department, and salary. The setDetails() method sets the values of ID, name, department and salary. And showDetails() method shows the value of each field.

Note: (i) Values must be entered through Scanner class.


(ii) Use proper constructor

(iii) Use “this” reference variable to avoid ambiguity.

Source Code:

```
import java.util.Scanner;
public class Employee {
    int id, salary;
    String name, department;
    public void getDetails(int Id, String employeeName, String dep, int sal) {
        id = Id;
        name = employeeName;
        department = dep;
        salary = sal;
    }
    public void showDetails() {
        System.out.println();
        System.out.println("Id : " +id);
        System.out.println("Name : " +name);
        System.out.println("Department : " +department);
        System.out.println("Salary : " +salary);
    }
    public static void main(String[] args) {
        Scanner Sc = new Scanner(System.in);
        Employee Em = new Employee();
        System.out.print("Enter the Employee Id : ");
        int Id = Sc.nextInt();
        Sc.nextLine();
        System.out.print("Enter the Employee name : ");
        String employeeName = Sc.nextLine();
        System.out.print("Enter the Employee Department : ");
        String dep = Sc.nextLine();
        System.out.print("Enter the Employee Salary : ");
        int sal = Sc.nextInt();
        Em.getDetails(Id, employeeName, dep, sal);
        Em.showDetails();
    }
}
```

OUTPUT:



```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Employee.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Employee
Enter the Employee Id : 25
Enter the Employee name : Nishant
Enter the Employee Department : CSE
Enter the Employee Salary : 25000

Id : 25
Name : Nishant
Department : CSE
Salary : 25000

C:\Users\nk534\Documents\Java\Practical File Of Java>
```

PRACTICAL 5

Question:


Re-write program 1 with better memory management approach.

Source Code:

```
import java.util.Scanner;

public class StudentInfo {
    String name;
    int id;
    String branch;
    static String university = "GEHU";
    public void getDetails (String name, int id, String branch) {
        this.name = name;
        this.id = id;
        this.branch = branch;
    }
    public void showDetails (String name, int id, String branch, String university) {
        System.out.println();
        System.out.println("Name : " +name);
        System.out.println("Student Id. : " +id);
        System.out.println("Branch Name : " +branch);
        System.out.println("University Name : " +university);
    }
    public static void main (String[] args) {
        Scanner Sc = new Scanner(System.in);
        StudentInfo St = new StudentInfo();
        System.out.print("Enter the Student Name : ");
        String name = Sc.nextLine();
        System.out.print("Enter the Student Id : ");
        int id = Sc.nextInt();
        Sc.nextLine();
        System.out.print("Enter the Student Branch : ");
        String branch = Sc.nextLine();
        St.getDetails(name, id, branch);
        St.showDetails(name, id, branch, university);
    }
}
```

OUTPUT:



```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac StudentInfo.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java StudentInfo
Enter the Student Name : Nishant
Enter the Student Id : 2011940
Enter the Student Branch : CSE

Name : Nishant
Student Id. : 2011940
Branch Name : CSE
University Name : GEHU

C:\Users\nk534\Documents\Java\Practical File Of Java>
```


PRACTICAL 6

Question:

Apply following functions on the String "Java".

- (i) Try to concat "Welcome" and write down your observation.
- (ii) Find character at index 1
- (iii) Find index of first 'a'.
- (iv) Find index of second 'a'
- (v) Compare "Java" to "JAVA"
- (vi) Compare "Java" to "JAVA" ignoring the case
- (vii) Find the index of first 'a' from last

Source Code:

```
public class JavaFun {  
    public static void main(String[] args) {  
        String s = "Java";  
        System.out.println("String after the Concatentation : "  
+s.concat("Welcome "));  
        System.out.println("Character at First Index : " +s.charAt(1));  
        System.out.println("Index of First 'a' : " +s.indexOf('a'));  
        System.out.println("Index of Second 'a' : " +s.indexOf('a', s.indexOf('a')  
+ 1));  
        System.out.println("Compare 'Java' to 'JAVA' : "  
+s.compareTo("JAVA"));  
        System.out.println("Compare 'Java' to 'JAVA' ignoring Case : "  
+s.equalsIgnoreCase("JAVA"));  
        System.out.println("Index of First 'a' from last : " +s.lastIndexOf('a'));  
    }  
}
```

OUTPUT:

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac JavaFun.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java JavaFun
String after the Concatentation : JavaWelcome
Character at First Index : a
Index of First 'a' : 1
Index of Second 'a' : 3
Compare 'Java' to 'JAVA' : 32
Compare 'Java' to 'JAVA' ignoring Case : true
Index of First 'a' from last : 3

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

PRACTICAL 7


Question:

Apply following functions on StringBuffer object "HELLO"

- (i) Append "Java"
- (ii) Insert "Java" at index 1
- (iii) Replace with "Java" with characters between index 1 to 2
- (iv) Delete characters between index 1 and 2
- (v) Reverse the string "HELLO"

Source Code:

```
class Append {
    public void app() {
        StringBuffer Sb = new StringBuffer("Hello");
        Sb.append("Java"); System.out.println(Sb);
    }
}
class Insert {
    public void ins() {
        StringBuffer Sb = new StringBuffer("Hello");
        Sb.insert(1, "JAVA"); System.out.println(Sb);
    }
}
class Replace {
    public void rep() {
        StringBuffer Sb = new StringBuffer("Hello");
        Sb.replace(1, 3, "JAVA"); System.out.println(Sb);
    }
}
class Delete {
    public void del() {
        StringBuffer Sb = new StringBuffer("Hello");
        Sb.delete(1, 3); System.out.println(Sb);
    }
}
class Reverse {
    public void rev() {
        StringBuffer Sb = new StringBuffer("Hello");
        Sb.reverse(); System.out.println(Sb);
    }
}
public class Main {
    public static void main (String [] args) {
        Append Ap = new Append (); Ap.app();
        Insert In = new Insert (); In.ins();
        Replace Rp = new Replace (); Rp.rep();
        Delete De = new Delete (); De.del();
        Reverse Re = new Reverse (); Re.rev();
    }
}
```



```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Main.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Main
HelloJava
HJAVAAello
HJAVAlO
Hlo
olleH

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

PRACTICAL - 8


Question:

Create a class “Student” having following instance variables and methods.
Instance variables: ID, Name, Branch, city and university While creating constructors with one, two, three, four and five arguments reuse the constructors by construction chaining.

Source Code:

```
public class ConstructorChain {
    int ID;
    String name, city, branch, university;
    ConstructorChain(int Id) {
        ID = Id;
    }
    ConstructorChain(int Id, String nm) {
        this(Id);
        name = nm;
    }
    ConstructorChain(int Id, String nm, String bran) {
        this(Id, nm);
        branch = bran;
    }
    ConstructorChain(int Id, String nm, String bran, String City) {
        this(Id, nm, bran);
        city = City;
    }
    ConstructorChain(int Id, String nm, String bran, String City, String University) {
        this(Id, nm, bran, City);
        university = University;
    }
    public void Display() {
        System.out.println("ID : " + ID);
        System.out.println("Name : " + name);
        System.out.println("Branch : " + branch);
        System.out.println("City : " + city);
        System.out.println("University : " + university);
    }
    public static void main(String[] args) {
        ConstructorChain ConC = new ConstructorChain(20011940, "Nishan
Kumar", "CSE", "Dehradun", "GEHU");
        ConC.Display();
    }
}
```

OUTPUT:



```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac ConstructorChain.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java ConstructorChain
ID : 20011940
Name : Nishan Kumar
Branch : CSE
City : Dehradun
University : GEHU

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

PRACTICAL - 9

Question:

Create two-dimensional integer array and insert, search, and traverse this array.

Note: Use Scanner class to insert data.

Source Code:

```
import java.util.Scanner;
public class Arrays {
    public static void main(String[] args) {
        Scanner Sc = new Scanner(System.in);
        System.out.print("Enter the Number of Rows : ");
        int row = Sc.nextInt();
        System.out.print("Enter the number of Column : ");
        int column = Sc.nextInt();
        int arr[][] = new int[row][column];
        for (int I = 0; I < row; ++i) {
            for (int j = 0; j < column; ++j) {
                System.out.print("Enter the element : ");
                int val = Sc.nextInt();
                arr[i][j] = val;
            }
        }
        System.out.println("After Enter the element in Array : ");
        for (int I = 0; I < row; ++i) {
            for (int j = 0; j < column; ++j) {
                System.out.print(arr[i][j] + " ");
            }
            System.out.println("");
        }
        System.out.print("Enter the element to be Search : ");
        int num = Sc.nextInt();
        for (int I = 0; I < row; ++i) {
            for (int j = 0; j < column; ++j) {
                if (arr[i][j] == num) {
                    System.out.println("Element Found : " + num);
                    break;
                }
            }
        }
    }
}
```

OUTPUT:

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Arrays.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Arrays
Enter the Number of Rows : 3
Enter the number of Column : 3
Enter the element : 1
Enter the element : 2
Enter the element : 3
Enter the element : 4
Enter the element : 5
Enter the element : 6
Enter the element : 7
Enter the element : 8
Enter the element : 9
After Enter the element in Array :
1 2 3
4 5 6
7 8 9
Enter the element to be Search : 5
Element Found : 5

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```


PRACTICAL - 10

Question:

Create a jagged array having three rows. Where 1st row contains 3 columns, 2nd row contains 4 columns and 3rd row contains 2 columns. Insert and traverse it.

Source Code:

```
import java.util.Scanner;

public class Jagged {
    public static void main(String[] args) {
        Scanner Sc = new Scanner(System.in);
        int arr[][] = new int[3][];
        arr[0] = new int[3];
        arr[1] = new int[5];
        arr[2] = new int[6];

        for (int i = 0; i < arr.length; ++i) {
            for (int j = 0; j < arr[i].length; ++j) {
                System.out.print("Enter the Value : ");
                int val = Sc.nextInt();
                arr[i][j] = val;
            }
        }

        System.out.println("Jagged Array : ");
        for (int i = 0; i < arr.length; ++i) {
            for (int j = 0; j < arr[i].length; ++j) {
                System.out.print(arr[i][j] + " ");
            }
            System.out.println(" ");
        }
    }
}
```

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Jagged.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Jagged
Enter the Value : 2
Enter the Value : 3
Enter the Value : 4
Enter the Value : 6
Enter the Value : 5
Enter the Value : 7
Enter the Value : 8
Enter the Value : 9
Enter the Value : 1
Enter the Value : 6
Enter the Value : 6
Enter the Value : 6
Enter the Value : 4
Enter the Value : 4
Jagged Array :
2 3 4
6 5 7 8 9
1 6 6 6 4 4

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

PRACTICAL – 11

Question:

Create a class “Shape” having area () method to calculate area. Overload the area () method for shapes like triangle, rectangle, and circle.

Source Code:

```
import java.util.Scanner;
public class Shape {
    int length, breadth, side;
    double radius;
    public void Area(int length, int breadth) {
        this.length = length;
        this.breadth = breadth;
        int area = (this.length) * (this.breadth);
        System.out.println("The area of Rectangle : " +area);
        System.out.println(" ");
    }
    public void Area(int side) {
        this.side = side;
        int area = (this.side) * (this.side);
        System.out.println("The area of Square : " +area);
        System.out.println(" ");
    }
    public void Area(double radius) {
        this.radius = radius;
        double area = (3.14 * (this.radius) * (this.radius));
        System.out.println("The area of Circle : " +area);
    }
    public static void main(String[] args) {
        Scanner Sc = new Scanner(System.in);
        Shape Sp = new Shape();
        System.out.print("Enter the length of Rectangle : ");
        int length = Sc.nextInt();
        System.out.print("Enter the breadth of Rectangle : ");
        int breadth = Sc.nextInt();
        Sp.Area(length, breadth);
        System.out.print("Enter the Side Of Square : ");
        int side = Sc.nextInt();
        Sp.Area(side);
        System.out.print("Enter the radius of Circle : ");
        double radius = Sc.nextDouble();
        Sp.Area(radius);
    }
}
```

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Shape.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Shape
Enter the length of Rectangle : 4
Enter the breadth of Rectangle : 5
The area of Rectangle : 20

Enter the Side Of Square : 5
The area of Square : 25

Enter the radius of Circle : 3
The area of Circle : 28.259999999999998

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

PRACTICAL - 12

Question:

Create a class “Bank” having method `getRateOfInterest()`. Create child classes as HDFC, SBI and PNB and override `getRateOfInterest()` and return interest rates as 4.0, 4.5 and 5% correspondingly. Use concept of Upcasting to implement this scenario.

Source Code:

```
class Bank {
    double getRateOfInterest() {
        double rateOfInterest = 2.0;
        return rateOfInterest;
    }
}
class Hdfc extends Bank {
    double getRateOfInterest() {
        double rateOfInterest = 4.0;
        return rateOfInterest;
    }
}
class Sbi extends Bank {
    double getRateOfInterest() {
        double rateOfInterest = 4.5;
        return rateOfInterest;
    }
}
class Pnb extends Bank {
    double getRateOfInterest() {
        double rateOfInterest = 5.0;
        return rateOfInterest;
    }
}
class Interests {
    public static void main(String[] args) {
        // Upcasting
        Bank Bn = new Hdfc();
        System.out.print("Rate Of Interest Of HDFC Bank : "
+Bn.getRateOfInterest());
        System.out.println();
        Bn = new Sbi();
        System.out.print("Rate Of Interest Of SBI Bank : " +Bn.getRateOfInterest());
        System.out.println();
        Bn = new Pnb();
        System.out.print("Rate Of Interest Of PNB Bank : " +Bn.getRateOfInterest());
        System.out.println();
    }
}
```

```
C:\WINDOWS\system32\cmd.exe

C:\Users\nk534\Documents\Java\Practical File Of Java>javac Interests.java

C:\Users\nk534\Documents\Java\Practical File Of Java>java Interests
Rate Of Interest Of HDFC Bank : 4.0
Rate Of Interest Of SBI Bank : 4.5
Rate Of Interest Of PNB Bank : 5.0

C:\Users\nk534\Documents\Java\Practical File Of Java>_
```

Practical – 13

Question:


Create a package pack1 having one class C1 and one interface I1. Class C1 has two methods int sum (int, int) and int sub (int, int). The I1 has one method int division (int, int). Create another package pack2 having class C2. Reuse C1 and I1 in C2 and show the results.

Note: Use appropriate Access Modifiers as required.

Source Code:

```
package p1;
public class C1 {
    public int sum(int x,int y) {
        return(x+y);
    }
    public int sub(int a, int b) {
        return(a-b);
    }
}
package p1;
public interface I1 {
    int div(int a ,int b);
}
package p2;
import p1.*;
import java.util.*;
public class C2 implements I1 {
    public int div(int a ,int b) {
        if(b!=0) {
            Name- Nishant Kumar Roll Number: 2018861 Section-A V
        } else {}
    }
    return(a/b);
    return(-1);
    public static void main(String args[]) {
        Scanner in=new Scanner(System.in);
        C1 d=new C1();
        C2 f=new C2();
        System.out.println("Enter 2 numbers");
        int a=in.nextInt();
        int b=in.nextInt();
        System.out.println("Sum of a and b:"+d.sum(a,b));
        System.out.println("Subtraction of a and b:"+d.sub(a,b));
        System.out.println("Division of a and b:"+f.div(a,b));
    }
}
```

OUTPUT



```
C:\Windows\System32\cmd.exe

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac -d . C1.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac -d . I1.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac -d . C2.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java p2.C2
Enter 2 numbers
6 2
Sum of a and b:8
Subtraction of a and b:4
Division of a and b:3
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```



Practical - 14**QUESTION:**

Write a program to divide two numbers with proper exception handlers.

Source Code:

```
import java.util.*;
class Xyz
{
    public static void main(String args[])
    {
        Scanner sc= new Scanner(System.in);
        System.out.println("Enter 2 numbers:");
        int a=sc.nextInt();
        int b=sc.nextInt();
        try{
            System.out.println("Dividing a and b: "+(a/b));
        }
        catch(ArithmeticException e)
        {
            System.out.println("Don't divide by 0!!\n"+e);
        }
    }
}
```

OUTPUT



```
C:\Windows\System32\cmd.exe
Microsoft Windows [Version 10.0.19044.1706]
(c) Microsoft Corporation. All rights reserved.

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p14.java

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Xyz
Enter 2 numbers:
8 0
Don?t divide by 0!!
java.lang.ArithmeticException: / by zero

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p14.java

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Xyz
Enter 2 numbers:
8 4
Dividing a and b: 2

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```

Practical - 15

Question:


Create LowBalanceException that occurs when user tries to withdraw some amount that is greater than his current bank balance. To withdraw you have to write a **void withdrawal (int amount)** method.

Source Code:

```
import java.util.*;
class LowBalanceException extends RuntimeException
{
    LowBalanceException(String s)
    {
        super(s);
    }
}
class Acc
{
    int bal=10000;
    void withdraw(int amt)
    {
        if(amt>bal)
            throw new LowBalanceException("Insufficient balance\n");
        else
            bal-=amt;
    }

    public static void main(String args[])
    {
        Acc d=new Acc();
        Scanner in= new Scanner(System.in); System.out.println("Enter the amount
        to be withdrawn: "); int amt=in.nextInt();
        d.withdraw(amt); System.out.println("Balance:
        "+d.bal);
    }
}
```

OUTPUT



```
C:\Windows\System32\cmd.exe

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac P15.java

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Acc
Enter the amount to be withdrawn:
5000
Balance: 5000

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac P15.java

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Acc
Enter the amount to be withdrawn:
12000
Exception in thread "main" LowBal: Insufficient balance

    at Acc.withdraw(P15.java:15)
    at Acc.main(P15.java:25)

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```


Practical - 16**QUESTION:**

Write a program that reads from a text file byte by byte and writes in some another file. Write this program in an efficient way.

Source Code:

```
import java.io.*;
class Abc
{
    public static void main(String args[])throws IOException
    {
        FileInputStream fis=new FileInputStream("file1.txt");
        BufferedInputStream bis=new BufferedInputStream(fis);
        FileOutputStream fos=new FileOutputStream("file2.txt");
        BufferedOutputStream bos=new BufferedOutputStream(fos);
        int i=0;
        while((i=bis.read())!=-1)
        {
            bos.write(i);
        }
        System.out.println();
        fis.close();
        bis.close();
        fos.close();
        bos.close();
    }
}
```

OUTPUT



The screenshot displays an IDE interface with several tabs: p14.java, P15.java, p16.java, File1.txt, and File2.txt. The p16.java tab is active, showing two lines of code:

```
1 Hey there...how's your day going so far
2
```

Overlaid on the IDE is a Windows command prompt window titled "C:\Windows\System32\cmd.exe". It shows the following commands and their outputs:

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p16.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Abc
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```


Practical - 17**QUESTION:**

Write a program that reads from a text file char by char and writes in some another file. Write this program in an efficient way.

Source Code:

```
import java.io.*;
class Abc
{
    public static void main(String args[])throws IOException
    {
        FileReader fr=new FileReader("file1.txt");
        BufferedReader br=new BufferedReader(fr);
        FileWriter fw=new FileWriter("file2.txt");
        BufferedWriter bw=new BufferedWriter(fw);
        int i=0;
        while((i=br.read())!=-1)
        {
            bw.write((char)i);
        }
        System.out.println();
        fr.close();
        br.close();
        fw.close();
        bw.close();
    }
}
```

OUTPUT



The screenshot displays an IDE with several tabs: p14.java, P15.java, p17.java, File1.txt, and File2.txt. The p17.java tab is active, showing two lines of code: `1 This file reads text char by char` and `2`. Overlaid on the IDE is a Windows command prompt window titled `C:\Windows\System32\cmd.exe`. The command prompt shows the following commands and their outputs:

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p17.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Abc
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```



Practical - 18**QUESTION:**

Write a program that reads from a text file line by line and writes on console.

Source Code:

```
import java.io.*;
class Abc
{
    public static void main(String args[])throws IOException
    {
        FileReader fr=new FileReader("file1.txt");
        BufferedReader br=new BufferedReader(fr);
        String i;
        while((i=br.readLine())!=null)
        {
            System.out.println(i);
        }
        System.out.println();
        fr.close();
        br.close();
    }
}
```

OUTPUT



A screenshot of a Windows command prompt window. The title bar shows 'C:\Windows\System32\cmd.exe'. The command prompt is open in the directory 'C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder'. The user has entered the command 'javac p18.java', followed by 'java Abc'. The output of the program is displayed as 'This program reads from a text file line by line and writes on console'. The prompt is currently waiting for input after the last command.

```
C:\Windows\System32\cmd.exe
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p18.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Abc
This program reads from a text file line by line and writes on console
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>_
```

Practical -19**QUESTION:**

Write a program that take your name from keyboard and writes in some text file.

Source Code:


```
import java.io.*;
class Name
{
    public static void main(String args[])throws IOException
    {
        InputStreamReader isr=new InputStreamReader(System.in);
        BufferedReader br=new BufferedReader(isr);

        FileOutputStream fos=new FileOutputStream("File1.txt");
        BufferedOutputStream bos=new BufferedOutputStream(fos);

        System.out.println("Enter a String:");
        String str=br.readLine();
        byte b[]=str.getBytes();

        bos.write(b);
        bos.close();
        fos.close();
        br.close();
        isr.close();
    }
}
```

OUTPUT



```
Select C:\Windows\System32\cmd.exe

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p19.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Name
Enter a String:
Bhavya Shastri
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>
```

Practical - 20**QUESTION:**

Write a multithreaded program where three threads are there and printing the numbers from 1 to 10 concurrently.

Source Code:

```

class A extends Thread{
    public void run(){
        for(int i=1;i<=10;i++){ System.out.print("From A:
            "+i+" ");
        }
    }
}
class B extends Thread{
    public void run(){
        for(int j=1;j<=10;j++){ System.out.println("From B:
            "+j+" ");
        }
    }
}
class C extends Thread {
    public void run(){
        for(int k=1;k<=10;k++){ System.out.println("From C:
            "+k+" ");
        }
    }
}
class XYZ{
    public static void main(String args[]){ A a=new
        A();
        B b=new B(); C
        c=new C();
        a.start();
        b.start();
        c.start();
    }
}

```

OUTPUT

```
C:\Windows\System32\cmd.exe
Microsoft Windows [Version 10.0.19044.1706]
(c) Microsoft Corporation. All rights reserved.

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p20.java

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java XYZ
From A: 1 From A: 2 From A: 3 From C: 1
From C: 2
From B: 1
From C: 3
From A: 4 From A: 5 From A: 6 From A: 7 From A: 8 From A: 9 From A: 10 From C: 4
From C: 5
From B: 2
From C: 6
From B: 3
From C: 7
From C: 8
From B: 4
From B: 5
From C: 9
From B: 6
From B: 7
From C: 10
From B: 8
From B: 9
From B: 10

C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>_
```

Practical - 21**QUESTION:**

Write a program to set and get the name of threads also set and get the priority of threads.

Source Code:

```

class A extends Thread {
    public void run() {
        for(int i=1;i<=10;i++) { System.out.print("From A: "+i+" "); }
    }
}
class B extends Thread {
    public void run() {
        for(int j=1;j<=10;j++){System.out.println("FromB: "+j+" ");}
    }
}
class C extends Thread {
    public void run() {
        for(int k=1;k<=10;k++){System.out.println("From C: "+k+" "); }
    }
}
class Test {
    public static void main(String args[]) {
        A a=new A();B b=new B(); C c=new C();
        System.out.println("Getting Thread A Name: "+a.getName());
        System.out.println("Getting Thread B Name: "+b.getName());
        System.out.println("Getting Thread C Name: "+c.getName());
        a.setName("Thread_1"); b.setName("Thread_2"); c.setName("Thread_3");
        System.out.println("Getting Thread A Name after setting: "+a.getName());
        System.out.println("Getting Thread B Name after setting: "+b.getName());
        System.out.println("Getting Thread C Name after setting: "+c.getName());
        System.out.println("Getting Thread A Priority: "+a.getPriority());
        System.out.println("Getting Thread B Priority: "+b.getPriority());
        System.out.println("Getting Thread C Priority: "+c.getPriority());
        a.setPriority(1); b.setPriority(9); c.setPriority(7);
        System.out.println("Getting Thread A Priority after setting: "+a.getPriority());
        System.out.println("Getting Thread B Priority after setting: "+b.getPriority());
        System.out.println("Getting Thread C Priority after setting: "+c.getPriority());
    }
}

```

OUTPUT

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p20.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Test
Getting Thread A Name: Thread-0
Getting Thread B Name: Thread-1
Getting Thread C Name: Thread-2
Getting Thread A Name after setting: Thread_1
Getting Thread B Name after setting: Thread_2
Getting Thread C Name after setting: Thread_3
Getting Thread A Priority: 5
Getting Thread B Priority: 5
Getting Thread C Priority: 5
Getting Thread A Priority after setting: 1
Getting Thread B Priority after setting: 9
Getting Thread C Priority after setting: 7
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>_
```


Practical – 22

QUESTION:

Write a class Display having void wish (String name) methods that wishes hello to given string name. Between printing hello and provided string name apply delay of 500 milliseconds. Suppose multiple threads are there and they are trying to access this wish () method concurrently on **same object** then irregular output will be there. Write this application in such a way so that output becomes regular.

Source Code:

```
class Display {
    public synchronized void wish(String s) {
        for(int i=1;i<=5;i++) {
            System.out.println(s); try {
                Thread.sleep(500);
            }
            catch(Exception e) {
                System.out.println(e);
            }
        }
    }
}

class MyThread extends Thread {
    Display d; String
    name;
    MyThread(Display d,String name) {
        this.d=d;
        this.name=name;
    }
    public void run(){
        d.wish(name);
    }
}

class Demo
{
    public static void main(String args[])
    {
        Display d= new Display();
        MyThread t1=new MyThread(d,"Bhavya"); t1.start();
        MyThread t2=new MyThread(d,"Shastri"); t2.start();
    }
}
```

OUTPUT

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p22.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Demo
Bhavya
Bhavya
Bhavya
Bhavya
Bhavya
Shastri
Shastri
Shastri
Shastri
Shastri
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>■
```

Practical - 23

QUESTION:

Write a class Display having **synchronized void wish(String)** methods that wishes hello to given string name. Between printing hello and provided string name apply delay of 500 milliseconds. Suppose multiple threads are there and they are trying to access this wish() method concurrently on **different objects** then irregular output will be there. Write this application in such a way so that output becomes regular.

Source Code:

```
class Display {
    public static synchronized void wish(String s) {
        for (int i=1;i<=5;i++) {
            System.out.println(s); try {
                Thread.sleep(500);
            }
            Catch (Exception e) {
                System.out.println(e);
            }
        }
    }
}

class MyThread extends Thread {
    Display d; String
    name;
    MyThread(Display d,String name) {
        this.d=d; this.name=name;
    }
    public void run() {
        d.wish(name);
    }
}

class Demo {
    public static void main(String args[]) {
        Display d1= new Display(); Display
        d2= new Display();
        MyThread t1=new MyThread(d1,"Bhavya"); t1.start();
        MyThread t2=new MyThread(d2,"Shastri"); t2.start();
    }
}
```

OUTPUT

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p22.java
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Demo
Bhavya
Bhavya
Bhavya
Bhavya
Bhavya
Shastri
Shastri
Shastri
Shastri
Shastri
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>_
```

Practical - 24

QUESTION:

Write a class Customer having **balance** as a property and **void withdrawal (int amount)**, and **void deposit (int amount)** as instance methods. There are two threads, the first thread wants to withdrawal some amount and second thread wants to deposit some amount. Apply inter thread communication where, if withdrawal amount is higher than current balance then first thread will wait for second thread to deposit then resume the withdrawal.

Source Code:

```
class Customer {
    int bal=1000;
    public synchronized void withdrawl(int amt) {
        System.out.println("Going to withdraw. .. ");
        if(this.bal < amt) { System.out.println("Less Balance...Kindly wait. ");
            try { wait (); }
            catch (Exception e) { System.out.println(e); }
        } this.bal=this.bal - amt;
    }
    public synchronized void deposit(int amt) {
        System.out.println("Going to deposit... "); this.bal=this.bal + amt;
        System.out.println("Deposited:...And total balance is: "+bal); notify();
    }
}

class MyThread1 extends Thread { Customer c; MyThread1(Customer c) {
    this.c=c;
}
    public void run() { c.withdrawl(1500); }
}

class MyThread2 extends Thread {
    Customer c; MyThread2(Customer c){
        this.c=c;
    }
    public void run() {
        c.deposit(1000);
    }
}

class Demo {
    public static void main(String args[]) {
        Customer c= new Customer();
        MyThread1 t1=new MyThread1(c); t1.start();
        MyThread2 t2=new MyThread2(c); t2.start();
    }
}
```

OUTPUT

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p24.java  
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java Demo  
Going to withdraw....  
Less Balance...Kindly wait...  
Going to deposit....  
Deposited:...And total balance is: 2000  
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>_
```


Practical - 25**QUESTION:**

Create a GUI for student's information system. A GUI that asks all the relevant information's related to a student.

Source Code:

```
import javax.swing.*; import
java.awt.*;          import
java.awt.event.*;
class A extends JFrame {
    JLabel l1,l2,l3; JTextField
    t1,t2,t3;
    A() {
        l1=new JLabel("Name");
        l2=new JLabel("RollNo");
        l3=new JLabel("Student ID");
        t1=new JTextField(10);
        t2=new JTextField(10);
        t3=new JTextField(10);
        JRadioButton rb1=new JRadioButton("Other");
        JRadioButton rb2=new JRadioButton("Female",true);
        JRadioButton rb3=new JRadioButton("Male");
        JRadioButton rb4=new JRadioButton("Sec: A");
        JRadioButton rb5=new JRadioButton("Sec: B");
        JRadioButton rb6=new JRadioButton("Sec: C");
        JCheckBox cb1=new JCheckBox();
        JCheckBox cb2=new JCheckBox("CSE",true);
        JCheckBox cb3=new JCheckBox("ESE");
        JCheckBox cb4=new JCheckBox("ME");
        JButton b1=new JButton("Submit");
        setLayout(new FlowLayout()); add(l1);
        add(t1); add(l2); add(t2); add(rb4); add(rb5); add(rb6); add(cb1); add(cb2); add(cb3);
        add(cb4); add(l3); add(t3); add(rb1); add(rb2); add(rb3); add(b1);
    }
    public static void main(String args[]) {
        A d=new A();
        d.setSize(400,400);
        d.setVisible(true);
    }
}
```

OUTPUT




Practical - 26**QUESTION:**

Create a canvas having smiley face.

Source Code:

```
import java.awt.*;
import javax.swing.*;
class Xyz extends Canvas {
    public void paint(Graphics g) {
        g.drawOval(140,120,200,200);
        g.setColor(Color.yellow);
        g.fillOval(140,120,200,200);
        g.setColor(Color.black);
        g.drawOval(180,170,40,40);
        g.setColor(Color.white);
        g.fillOval(180,170,40,40);
        g.setColor(Color.black);
        g.drawOval(260,170,40,40);
        g.setColor(Color.white);
        g.fillOval(260,170,40,40);
        g.setColor(Color.black);
        g.drawLine(240,210,240,230);
        g.drawArc(220,230,40,40,0,-180);
    }
    public static void main(String args[]) {
        Xyz d=new Xyz(); JFrame
        f=new JFrame();
        f.setSize(500,400);
        f.setVisible(true);
        f.add(d);
    }
}
```

OUTPUT



Practical – 27**QUESTION:**

Write a JFrame having three textfields. The first two textfields refers to two numbers on which sum, or subtraction will happen. The third textfield will show the result. There are two buttons “SUM” and “SUBTRACTION”. Once user will click on sum or subtraction buttons then the corresponding result will be displayed in result field.

Source Code:

```
import javax.swing.*;
import java.awt.*; import
java.awt.event.*;
class A extends JFrame implements ActionListener {
    JLabel l1; JTextField t1; JLabel l2; JTextField t2; JButton b1; JButton b2; JLabel l3; JTextField t3;
    A () {
        setLayout(new FlowLayout());
        l1=new JLabel("Enter the first no.: "); t1=new JTextField(20);
        l2=new JLabel("Enter the second no.: "); t2=new JTextField(20);
        b1=new JButton("SUM"); b2=new JButton("SUB");
        l3=new JLabel("Enter the result: "); t3=new JTextField(20);
        setLayout(new FlowLayout());
        add(l1); add(t1); add(l2); add(t2); add(b1); add(b2); add(l3); add(t3);
        b1.addActionListener(this); b2.addActionListener(this);
        setVisible(true);
    }
    public void actionPerformed(ActionEvent e) {
        String s=e.getActionCommand(); int result=0;
        if(s.equals("SUM")) {
            result=Integer.parseInt(t1.getText())+Integer.parseInt(t2.getText());
        } if(s.equals("SUB")) {
            result=Integer.parseInt(t1.getText())-Integer.parseInt(t2.getText());
        }
        t3.setText(Integer.toString(result));
    }
    public static void main(String args[]) {
        A d=new A(); d.setSize(300,400); d.setVisible(true);
    }
}
```

OUTPUT

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>javac p27.java
```

```
C:\Users\ASUS\OneDrive - Graphic Era University\Desktop\New folder>java A
```

Enter the first no.:
612

Enter the second no.:
2009

SUB SUM

Enter the result:
2621